

November 2010

For the most current product/pricing information on Anvil products, please visit our website at www.anvilintl.com.



Pipe Fittings & Steel Nipples

Forged Steel • Cast Iron • Malleable

B U I L D I N G C O N N E C T I O N S T H A T L A S T

BUILDING CONNECTIONS THAT LAST



For over 150 years, Anvil has worked diligently to build a strong, vibrant tradition of making connections — pipe to pipe and people to people.

We pride ourselves in providing the finest quality pipe products and services with integrity and dedication to superior customer service at all levels.



We provide expertise and product solutions for a wide range of applications, from plumbing, mechanical, HVAC, industrial and fire protection to mining, oil and gas. Our comprehensive line of products includes: grooved pipe couplings, grooved and plain-end fittings, valves, cast and malleable iron fittings, forged steel fittings, steel pipe nipples and couplings, pipe hangers and supports, channel and strut fittings, mining and oil field fittings, along with much more.

As an additional benefit to our customers, Anvil offers a complete and comprehensive Design Services Analysis for mechanical equipment rooms, to help you determine the most effective and cost-efficient piping solutions.



Anvil is a proud member of the United States Green Building Council (USGBC). Go to the Anvil website to obtain manufacturer recycled certificates and other Green information.

At Anvil, we believe that responsive and accessible customer support is what makes the difference between simply delivering products — and delivering solutions.



Pipe Fittings

History

For over 150 years, Anvil has been a trusted name in piping solutions by consistently providing quality products, service, and support to the PVF industry. Our ability to provide cost-efficient piping packages that are tailored to individual markets is unmatched in the industry. From plumbing, mechanical, and fire protection, to mining, oil and gas, our innovative responses are designed to meet your specific demands.

Products

Our manufacturing facilities produce an unrivaled package of piping products, while setting a world-wide industry standard for quality and dependability. Our ISO certified facilities use recycled materials in the manufacturing of our product as well as being a proud member of the USGBC.

Distribution Channel

The wholesaler has always been the key to Anvil's business. Our dedication to the wholesale trade is the driving force for our services and these relationships remain a primary focus of Anvil's innovation. Our value-added services including a proprietary suite of inventory management tools signifies a strong commitment to our customers needs.

Customer Service

Having major distribution centers located throughout North America, you can count on getting the product you need - when you need it. Customer satisfaction has always been Anvil's #1 objective. Our experienced Sales and Customer Service Teams are knowledgeable and eager to serve our customers, validating our company's motto "Building Connections that Last."

Pipe Fitting Product Line

- Malleable Iron Pipe Fittings
Threaded Fittings
Class 150 (Standard)
Class 300 (XS/XH)
- Cast Iron Pipe Fittings
Threaded Fittings
Class 125 (Standard)
Class 250 (Extra Heavy)
Flanged Fittings
Class 125 (Standard)
Class 250 (Extra Heavy)
Drainage Fittings
- Small Steel Fittings
Merchant Steel
- Pipe Nipples
Seamless and Welded
- Pipe Couplings
- Forged Steel Pipe Fittings
Threaded Fittings
Class 2000
Class 3000
Class 6000
Socket Weld Fittings
Class 3000
Class 6000
- Anvilets
- Catawissa Products
- J.B. Smith Products

TABLE OF CONTENTS

Malleable Iron through Forged Steel

Malleable Iron

Technical Data	17
CLASS 150 (STANDARD)	
Fig. 1101 90° Elbow	18
Fig. 1101R Reducing Elbow	18
Fig. 1102 45° Elbow	19
Fig. 1103 (Straight) & Fig. 1103R (Reducing) 90° Street Elbow	19
Fig. 1104 45° Street Elbow	20
Fig. 1105 Straight Tee	20
Fig. 1105R Reducing Tee	21 - 23
Fig. 1106 (Straight) & Fig. 1106R (Reducing) Street or Service Tee	24
Fig. 1107 Cross	24
Fig. 1108 45° Y-Branch or Lateral	24
Fig. 1119 Return Bend Open Pattern, R.H.	25
Fig. 1121 Coupling Right Hand	25
Fig. 1124 Cap	25
Fig. 1125 Reducer	26
Fig. 1134 Hex Locknut	27
Fig. 1190 Floor Flange (Ductile Iron)	27
Fig. 1133 Waste Nut	27
Fig. 1138 Extension Piece	27
CLASS 300 (XS/XH)	
Fig. 1161 90° Elbow Straight	28
Fig. 1161R 90° Reducing Elbow	28
Fig. 1160 45° Street Elbow	28
Fig. 1162 45° Elbow	29
Fig. 1170 90° Street Elbow	29
Fig. 1164 Straight Tee	29
Fig. 1164R Reducing Tee	30
Fig. 1165 Cross	30
Fig. 1166 Coupling	31
Fig. 1167 Reducer	31
Fig. 1163 Cap	32
Fig. 390 Square Countersunk Plug	32
ALL IRON UNIONS	
Fig. J-3300 All Iron Union Class 300	32
MALLEABLE IRON UNIONS – CLASS 150; 250; 300	
Fig. 463 Class 150 Union	33
Fig. 554 Class 250 Union	33
Fig. 459 Class 300 Union	33
Fig. 551 Class 300 Union male & female	33
Fig. 552 Class 300 90° Female Union	34
Fig. 832 Dart Union Bronze Seat to Bronze Seat Union	34
MALLEABLE HEX AND FACE BUSHING	
Fig. 383 Hex Bushing	35
Fig. 385 Face Bushing	35

Cast Iron

Technical Data	37
THREADED FITTINGS – CLASS 125 (STANDARD)	
Fig. 351 90° Elbow	38
Fig. 371 90° Elbow, Flange & Screw	38
Fig. 356 (Straight) & Fig. 356R (Reducing) 45° Elbow	39
Fig. 356A 22½° Elbow	39
Fig. 352 90° Elbow, Reducing	40
Fig. 358 Tee	41
Fig. 359 Tee, Reducing	41 - 45
Fig. 360 Cross	46

Cast Iron (continued)

Fig. 361 Cross, Reducing	46
Fig. 366 Screwed Hex Coupling	47
Fig. 487 Flanged Union Gasket Type	47
Fig. 367 Concentric Reducer	48
Fig. 368 Eccentric Reducer	49
Fig. 383 Hex Bushing	50 - 51
Fig. 385 Face Bushing	51
Fig. 387 Square Head Plug, Cored	52
Fig. 388 Square Head Plug, Solid	52
Fig. 389 Bar Plug, Cored	52
Fig. 380 Bar Plug, Solid	52
Fig. 390 Countersunk Plug	52
Fig. 381 Cap	52
Fig. 370 Locknut	53
THREADED FITTINGS – CLASS 250 (EXTRA HEAVY)	
Fig. 421 90° Elbow	53
Fig. 424 45° Elbow	53
Fig. 425 Tee	54
Fig. 426 Reducing Tee	54
DRAINAGE FITTINGS	
Technical Data	55, 58
Fig. 701 90° Short Turn Elbow	56
Fig. 701R 90° Reducing Short Turn Elbow	56
Fig. 702 90° Long Turn Elbow	56
Fig. 702A 90° Extra Long Turn Elbow	56
Fig. 703 60° Short Turn Elbow	56
Fig. 705 45° Short Turn Elbow	57
Fig. 706 45° Long Turn Elbow	57
Fig. 707 22½° Elbow	57
Fig. 708 11¼° Elbow	57
Fig. 718 90° Street Elbow	59
Fig. 719 45° Street Elbow	59
Fig. 722 Tee	59
Fig. 723 Reducing Tee	59
Fig. 726 90° Short Turn Y-Branch Tee Pattern	60
Fig. 727 90° Reducing Short Turn Y-Branch Tee Pattern	60
Fig. 729 Reducing Double Short Turn Tee	60
Fig. 730 90° Long Turn Y-Branch Tee Pattern	60
Fig. 731 90° Reducing Long Turn Y-Branch Tee Pattern	61
Fig. 734 45° Y-Branch	61
Fig. 735 45° Reducing Y-Branch	61
Fig. 736 45° Double Y-Branch	61
Fig. 753 Coupling	62
Fig. 744 Tucker Connection	62
Fig. 752 P-Trap	62
Fig. 754 Bath P-Trap	62
FLANGED FITTINGS – CLASS 125 (STANDARD)	
Technical Data	63, 78
Fig. 801 90° Flanged Elbow	64
Fig. 802 45° Flanged Elbow	64
Fig. 803 90° Reducing Flanged Elbow	65
Fig. 804 90° Long Radius Flanged Elbow	65
Fig. 804R 90° Long Radius Reducing Flanged Elbow	65
Fig. 805 90° Flanged Base Elbow	66
Fig. 808 90° Flanged Side Outlet Elbow	66
Fig. 811 Flanged Tee	67
Fig. 812 Flanged Reducing Tee	68
Fig. 821 Flanged Cross	69

Cast Iron (continued)

Fig. 823 Flanged Lateral	69
Fig. 825 Flanged Concentric Reducer	70
Fig. 826 Flanged Eccentric Reducer	70
FLANGED FITTINGS – CLASS 250 (EXTRA HEAVY)	
Technical Data	71, 79
Fig. 831 90° Flanged Elbow	72
Fig. 841 Flanged Tee	72
Fig. 842 Flanged Reducing Tee	72
Fig. 855 Flanged Concentric Reducer	73
IRON FLANGES – CLASS 125 (STANDARD)	
Fig. 1011 Companion Flange	73
Fig. 1016 Reducing Flange	74
Fig. 1018 Blind Flange	75
IRON FLANGES – CLASS 250 (EXTRA HEAVY)	
Fig. 1025 Companion Flange	75
Fig. 1030 Reducing Flange	76
Fig. 1021 Blind Flange	76
HIGH HUB FLANGES FOR C.I. PIPE	
Fig. 1010T Cast Iron Flange for Cast Iron Pipe	76
THREADED FITTING - SAFETY VALVE DISCHARGE ELBOW	
Fig. 1538 Screwed Cast Iron	77

Small Steel Fittings

MERCHANT STEEL	
Hex Bushings	81
Countersunk Plugs (Square and Hex Socket)	81
Flush Bushings	82
Caps	82
Solid Square Head Plugs	82

Pipe Nipples and Pipe Couplings

Technical Data	83, 89
Seamless Pipe Nipples	84
Welded Pipe Nipples	85 - 88
Fig. 336 Standard, Full & Half Couplings	90
Fig. 337 Extra Strong (XS), Full & Half Couplings	91
Fig. 346 Standard, Right & Left Couplings	92
Fig. 347 Extra Strong (XS), Right & Left Couplings	92
Fig. 348 API Line Pipe Coupling	93
Fig. 379 Shallow Well Coupling	94
Fig. 380 Water Well Reamed & Drifted Coupling	94
Fig. 381 #9 Drive Coupling	94

Forged Steel

Technical Data	95
THREADED – CLASS 2000	
Fig. 2101 90° Elbow	96
Fig. 2102 45° Elbow	96
Fig. 2103 Tee	97
Fig. 2104 Cross	97
THREADED – CLASS 3000	
Fig. 2111 90° Elbow	98
Fig. 2112 45° Elbow	98
Fig. 2114 Tee	98
Fig. 2115 Cross	99
Fig. 2113 90° Street Elbow	99
Fig. 2116 Lateral	99
Fig. 2117 Coupling	100
Fig. 2119 Half Coupling	100

Forged Steel through Technical Data

Forged Steel (continued)

Fig. 2118 Reducing Coupling.....	101
Fig. 2120 Pipe Cap.....	101

THREADED – CLASS 6000

Fig. 2131 90° Elbow.....	102
Fig. 2132 45° Elbow.....	102
Fig. 2134 Tee.....	102
Fig. 2135 Cross.....	103
Fig. 2133 90° Street Elbow.....	103
Fig. 2136 Lateral.....	103
Fig. 2137 Coupling.....	104
Fig. 2141 Half Coupling.....	104
Fig. 2138 Reducing Coupling.....	105
Fig. 2143 Pipe Cap.....	105

SOCKET WELD – CLASS 3000

Fig. 2150 90° Elbow.....	106
Fig. 2151 45° Elbow.....	106
Fig. 2152 Tee.....	107
Fig. 2153 Cross.....	107
Fig. 2158 Lateral.....	108
Fig. 2154 Coupling.....	108
Fig. 2155 Half Coupling.....	109
Fig. 2156 Reducing Coupling.....	109
Fig. 2157 Pipe Cap.....	110

SOCKET WELD – CLASS 6000

Fig. 2170 90° Elbow.....	111
Fig. 2171 45° Elbow.....	111
Fig. 2172 Tee.....	112
Fig. 2173 Cross.....	112
Fig. 2178 Lateral.....	112
Fig. 2174 Coupling.....	113
Fig. 2175 Half Coupling.....	113
Fig. 2176 Reducing Coupling.....	114
Fig. 2177 Pipe Cap.....	114

HIGH PRESSURE PLUGS & BUSHINGS

Fig. 2122 Square Head Plug.....	115
Fig. 2142 Hex Head Plug.....	115
Fig. 2121 Round Head Plug.....	115
Fig. 2139 Hex Head Bushing.....	116
Fig. 2140 Flush Bushing.....	116

SOCKET-WELD REDUCER INSERTS

Class 3000.....	117
Class 6000.....	118

FORGED STEEL UNIONS

Fig. 2125 Class 3000 Threaded Union.....	119
Fig. 2126 Class 3000 Socket-Weld Union.....	119
Fig. 2127 Class 6000 Threaded Union.....	120
Fig. 2128 Class 6000 Socket-Weld Union.....	120

Anvilets

Technical Data.....	121, 126
Universal Forged Steel Butt Weld Anvilets.....	122 - 123
Universal Forged Steel Threaded Anvilets.....	124
Universal Forged Steel Socket-Weld Anvilets.....	125
Universal Elbowlet.....	127
Lateral Anvilet.....	128
Flat Anvilet.....	129

Catawissa

Technical Data.....	131
Fig. 100 Wing Union.....	132

Catawissa (continued)

Fig. 100C Wing Union.....	132
Fig. 200 Wing Union.....	133
Fig. 200 Wing Union (Butt Weld Ends).....	134
Fig. 200C Wing Union.....	134
Fig. 206 Wing Union.....	135
Fig. 206 Wing Union (Butt Weld Ends).....	136
Fig. 202 Blanking Cap Only with O-Ring.....	136
Fig. 211 Insulating Union.....	137
Fig. 300 Flat-Face Union.....	137
Fig. 301 Steam Service Union.....	138
Fig. 400 Wing Union.....	138
Fig. 400 Wing Union (Butt Weld Ends).....	139
Fig. 600 Wing Union.....	139
Fig. 602 Wing Union.....	140
Fig. 602 Wing Union (Butt Weld Ends).....	141
Fig. 607 Well Service Union.....	141
Fig. 1002 Wing Union.....	142
Fig. 1002 Wing Union (Butt Weld Ends-Sch. 160).....	143
Fig. 1002 Wing Union (Butt Weld Ends-Sch. XXH).....	143
Fig. 1502 Wing Union.....	144
Fig. 1502 Wing Union (Butt Weld Ends-Sch. 160).....	144
Fig. 1502 Wing Union (Butt Weld Ends-Sch. XXH).....	144
Fig. S1A High Speed Union.....	145
Fig. 3L S1A Tri-Lug High Speed Union.....	145
Catawissa Quick Reference Chart.....	146

J.B. Smith Products

Technical Data.....	147, 148, 155
Concentric Swage Nipples.....	149 & 150
Eccentric Swage Nipple.....	151
Stainless & Alloy Steel Swage Nipple.....	152
Carbon Steel Bull Plug.....	153
Solid Refinery Plug.....	153
Adapter Nipples.....	154

OIL COUNTRY FITTINGS

Large End Upset Reduced to Regular Swage Nipple.....	156
Large End Non-Upset Reduced to Upset Swage Nipple.....	156
Swage Nipple Oil Country Tubing & Casing non EUE ends.....	157
Tubing Bull Plug.....	158
Casing Bull Plug.....	158
API Bull Plug Female.....	158
Bell Nipple.....	159
Tubing Nipple (Standard Weight).....	159
Tubing Nipple (Extra Heavy Weight).....	159
Oil Country Casing Nipple.....	160
API Casing Coupling (Short Thread).....	161
API Casing Coupling (Long Thread).....	161
Combination Coupling J-55.....	161
Sub Tubing Couplings J-55.....	162
API Tubing Coupling.....	162
Special Clearance Tubing Coupling.....	162
Chambers/Pressure Vessels.....	163
Coated Products.....	164

Cartons

Malleable Iron Class 150 (Standard).....	165 - 171
Malleable Iron Class 300 (XS/XH).....	172 - 174
All Iron Unions.....	175

Cartons (continued)

Malleable Iron Unions.....	175 - 176
Malleable Hex and Face Bushing.....	176
Cast Iron Threaded Class 125 (Standard).....	177 - 179
Cast Iron Drainage Fittings.....	180
Cast Iron Flanged Fittings.....	180
Iron Flanges.....	181
High Hub Flanges for C.I. Pipe.....	181
Steel Pipe Bushings, Plugs & Caps.....	181 - 182
Steel Pipe Plugs & Hose Fittings.....	182
Steel Pipe Couplings.....	183 - 185
Forged Steel Class 2000 Threaded.....	186
Forged Steel Class 3000 Threaded.....	187 - 189
Forged Steel Class 6000 Threaded.....	190
Forged Steel Class 3000 Socket-Weld.....	191 - 192
Forged Steel Class 6000 Socket-Weld.....	193
Forged Steel High Pressure Plugs & Bushings.....	194 - 195
Forged Steel Socket-Weld Reducer Insert.....	196
Forged Steel Unions.....	196 - 197
Catawissa Wing Unions.....	197 - 199

Technical Data

Standards & Specifications.....	200
Conditions and Terms of Sale.....	201
General Assembly of Threaded Fittings.....	202
Engineering Information.....	203
Figure Number Index.....	204

Anvil reserves the right to make specification changes without notice. While every effort has been made to assure the accuracy of information contained in this catalog at the time of publication, we cannot accept responsibility for inaccuracies resulting from undetected errors or omissions.

PICTORIAL TABLE OF CONTENTS

Malleable Iron

MALLEABLE IRON FITTINGS – CLASS 150 (STANDARD)

 Fig. 1101 90° Elbow Size Range: 1/8" thru 6" Page 18	 Fig. 1101R 90° Reducing Elbow Size Range: 1/4" x 1/8" thru 4" x 3" Page 18	 Fig. 1102 45° Elbow Size Range: 1/8" thru 6" Page 19	 Fig. 1103 & 1103R 90° Street Elbow (Straight & Reducing) Size Range: 1/8" thru 4" (Straight) 1/2" x 3/8" thru 2" x 1 1/2" (Reducing) Page 19	 Fig. 1104 45° Street Elbow Size Range: 1/8" thru 2" Page 20
 Fig. 1105 Straight Tee Size Range: 1/8" thru 6" Page 20	 Fig. 1105R Reducing Tee Size Range: 1/8" x 1/8" x 1/4" thru 4" x 4" x 3" Page 21 - 23	 Fig. 1106 & 1106R Street or Service Tee (Straight & Reducing) Size Range: 1/4" thru 2" (Straight) 1 1/4" x 1" x 1 1/4" (Reducing) Page 24	 Fig. 1107 Cross Size Range: 1/8" thru 4" Page 24	 Fig. 1108 45° Y-Branch or Lateral Size Range: 3/8" thru 4" Page 24
 Fig. 1119 Return Bend - Open Pattern, R.H. Size Range: 1/2" thru 2" Page 25	 Fig. 1121 Coupling Right Hand Size Range: 1/8" thru 4" Page 25	 Fig. 1124 Cap Size Range: 1/2" thru 6" Page 25	 Fig. 1125 Reducer Size Range: 1/4" x 1/8" thru 6" x 4" Page 26	 Fig. 1134 Hex Locknut Size Range: 1/8" thru 2" Page 27
 Fig. 1190 Floor Flange (Ductile Iron) Size Range: 1/4" thru 2" Page 27	 Fig. 1133 Waste Nut Size Range: 1/2" & 3/4" Page 27	 Fig. 1138 Extension Piece Size Range: 1/2" thru 1" Page 27		

MALLEABLE HEX AND FACE BUSHING

 Fig. 383 Hex Bushing Size Range: 3/4" x 1/8" thru 2 1/2" x 2" Page 35	 Fig. 385 Hex Bushing Size Range: 3/4" x 3/8" thru 3" x 2 1/2" Page 35
---	---

Malleable Iron *(Continued)*

MALLEABLE IRON FITTINGS – CLASS 300 (XS/XH)

 Fig. 1161 90° Elbow Size Range: 1/4" thru 4" Page 28	 Fig. 1161R 90° Reducing Elbow Size Range: 3/8" x 1/4" thru 2" x 1 1/2" Page 28	 Fig. 1160 45° Street Elbow Size Range: 1/2" thru 2" Page 28	 Fig. 1162 45° Elbow Size Range: 1/4" thru 4" Page 29	 Fig. 1170 90° Street Elbow Size Range: 1/4" thru 3" Page 29
 Fig. 1164 Straight Tee Size Range: 1/4" thru 4" Page 29	 Fig. 1164R Reducing Tee Size Range: 3/8" x 3/8" x 1/4" thru 3" x 3" x 2" Page 30	 Fig. 1165 Cross Size Range: 1/4" thru 2" Page 30	 Fig. 1166 Coupling Size Range: 1/4" thru 3" Page 31	 Fig. 1167 Reducer Size Range: 3/8" thru 4" Page 31
 Fig. 1163 Cap Size Range: 1/4" thru 3" Page 32	 Fig. 390 Square Countersunk Plugs Size Range: 1/2" & 3/4" Page 32			

MALLEABLE IRON UNIONS (CLASS 150; 250, 300)

 Fig. 463 Class 150 Union Size Range: 1/8" thru 2" Page 33	 Fig. 554 Class 250 Union Size Range: 1/8" thru 4" Page 33	 Fig. 459 Class 300 Union Size Range: 1/8" thru 4" Page 33
 Fig. 551 Class 300 Union Male & Female Size Range: 1/2" thru 2" Page 33	 Fig. 552 Class 300 90° Elbow Female Union Size Range: 3/8" thru 1" Page 34	 Fig. 832 Dart Union Bronze to Bronze Seat Union Size Range: 3/8" thru 2" Page 34


ALL IRON UNION

 Fig. J-3300 All Iron Union Class 300 Size Range: 1/4" thru 3" Page 32

PICTORIAL TABLE OF CONTENTS

Cast Iron

CAST IRON THREADED FITTINGS – CLASS 125 (STANDARD)

 Fig. 351 90° Elbow Size Range: 1/4" thru 8" Page 38	 Fig. 371 90° Elbow - Flange & Screw Size Range: 2 1/2" thru 6" Page 38	 Fig. 356 & 356R 45° Elbow (Straight & Reducing) Size Range: 1/4" thru 8" (Straight) 1" x 1/2" (Reducing) Page 39	 Fig. 356A 22 1/2° Street Elbow Size Range: 3/4" thru 2 1/2" Page 39	 Fig. 352 90° Reducing Elbow Size Range: 1/2" x 1/4" thru 6" x 5" Page 40
 Fig. 358 Tee Size Range: 1/4" thru 8" Page 41	 Fig. 359 Reducing Tee Size Range: 1/2" x 1/2" x 1/4" thru 6" x 6" x 5" Page 41 - 45	 Fig. 360 Cross Size Range: 1/2" thru 6" Page 46	 Fig. 361 Cross Reducing Size Range: 1" x 1" x 3/4" x 3/4" thru 4" x 4" x 2" x 2" Page 46	 Fig. 366 Screwed Hex Coupling Size: 1" Page 47
 Fig. 487 Flanged Union Gasket Type Size Range: 1/2" thru 8" Page 47	 Fig. 367 Concentric Reducer Size Range: 3/4" x 1/2" thru 8" x 6" Page 48	 Fig. 368 Eccentric Reducer Size Range: 3/4" x 1/2" thru 6" x 4" Page 49	 Fig. 383 Hex Bushing Size Range: 1 1/2" x 1/4" thru 10" x 8" Page 50 - 51	 Fig. 385 Face Bushing Size Range: 3" x 2" thru 4" x 3" Page 51
 Fig. 387 Square Head Plugs, Cored Size Range: 3/4" thru 4" Page 52	 Fig. 388 Square Head Plugs, Solid Size Range: 1/2" thru 3 1/2" Page 52	 Fig. 389 Bar Plugs, Cored Size Range: 4" thru 8" Page 52	 Fig. 380 Bar Plugs, Solid Size Range: 4" thru 8" Page 52	 Fig. 390 Countersunk Plugs Size Range: 1" thru 4" Page 52
 Fig. 381 Cap Size Range: 2 1/2" thru 8" Page 52	 Fig. 370 Locknut Size Range: 2 1/2" thru 4" Page 53			

CAST IRON THREADED FITTINGS – CLASS 250 (EXTRA HEAVY)

 Fig. 421 90° Elbow Size Range: 1/4" thru 3" Page 53	 Fig. 424 45° Elbow Size Range: 1/2" thru 2 1/2" Page 53	 Fig. 425 Tee Size Range: 1/4" thru 4" Page 54	 Fig. 426 Reducing Tee Size Range: 3/4" x 3/4" x 1/2" thru 2" x 2" x 1 1/2" Page 54
---	---	--	--

Cast Iron *(Continued)*

CAST IRON DRAINAGE FITTINGS

 Fig. 701 90° Short Turn Elbow Size Range: 1½" thru 4" Page 56	 Fig. 701R 90° Reducing Short Turn Elbow Sizes: 1½" & 2" Page 56	 Fig. 702 90° Long Turn Elbow Size Range: 1½" thru 4" Page 56	Fig. 702A 90° Extra Long Turn Elbow Sizes: 1½" & 2" Page 56	 Fig. 703 60° Short Turn Elbow Size: 1½" Page 56
 Fig. 705 45° Short Turn Elbow Size Range: 1½" thru 4" Page 57	 Fig. 706 45° Long Turn Elbow Size: 1½" Page 57	 Fig. 707 22½° Elbow Sizes: 1½" & 2" Page 57	 Fig. 708 11¼° Elbow Sizes: 1½" & 2" Page 57	 Fig. 718 90° Street Elbow Sizes: 1½" & 2" Page 59
 Fig. 719 45° Street Elbow Sizes: 1½" & 2" Page 59	 Fig. 722 Tee Sizes: 1½" & 2" Page 59	 Fig. 723 Reducing Tee Size: 2" x 2" x 1½" Page 59	 Fig. 726 90° Short Turn Y-Branch Tee Pattern Size Range: 1½" thru 4" Page 60	 Fig. 727 90° Reducing Short Turn Y-Branch Tee Pattern Sizes: 2" x 2" x 1½" & 2" x 1½" x 1½" Page 60
 Fig. 729 Reducing Double Short Turn Tee Size: 2" x 1½" Page 60	 Fig. 730 90° Long Turn Y-Branch Tee Pattern Sizes: 1½" & 2" Page 60	 Fig. 731 90° Reducing Long Turn Y-Branch Tee Pattern Size: 2" x 2" x 1½" Page 61	 Fig. 734 45° Y-Branch Size Range: 1½" thru 4" Page 61	 Fig. 735 45° Reducing Y-Branch Sizes: 2" x 2" x 1½" & 4" x 4" x 3" Page 61
 Fig. 736 45° Double Y-Branch Size: 1½" Page 61	 Fig. 753 Coupling Size: 1½" Page 62	 Fig. 744 Tucker Connection Size Range: 1½" thru 4" Page 62	 Fig. 752 P-Trap Size Range: 1½" thru 3" Page 62	 Fig. 754 Bath P-Trap Sizes: 1½" & 2" Page 62

PICTORIAL TABLE OF CONTENTS

Cast Iron *(Continued)*

CAST IRON FLANGED FITTINGS – CLASS 125 (STANDARD)

 Fig. 801 90° Flanged Elbow Size Range: 1½" thru 12" Page 64	 Fig. 802 45° Flanged Elbow Size Range: 1½" thru 12" Page 64	 Fig. 803 90° Reducing Flanged Elbow Size Range: 2½" x 2" thru 12" x 10" Page 65	 Fig. 804 90° Long Radius Flanged Elbow Size Range: 2" thru 12" Page 65	 Fig. 804R 90° Long Radius Reducing Flanged Elbow Size Range: 4" x 3" thru 10" x 8" Page 65
 Fig. 805 90° Flanged Base Elbow Size Range: 3" thru 12" Page 66	 Fig. 808 90° Flanged Side Outlet Elbow Size Range: 4" thru 8" Page 66	 Fig. 811 Flanged Tee Size Range: 1½" thru 12" Page 67	 Fig. 812 Flanged Reducing Tee Size Range: 3" x 2" x 3" thru 12" x 12" x 10" Page 68	 Fig. 821 Flanged Cross Sizes: 2" thru 10" Page 69
 Fig. 823 Flanged Lateral Size Range: 2" thru 8" Page 69	 Fig. 825 Flanged Concentric Reducer Size Range: 2" x 1½" thru 12" x 10" Page 70	 Fig. 826 Flanged Eccentric Reducer Size Range: 3" x 2" thru 12" x 10" Page 70		

CAST IRON FLANGED FITTINGS – CLASS 250 (EXTRA HEAVY)

 Fig. 831 90° Flanged Elbow Size Range: 2" thru 8" Page 72	 Fig. 841 Flanged Tee Size Range: 2½" thru 8" Page 72	 Fig. 842 Flanged Reducing Tee Sizes: 6" x 6" x 4 & 8" x 8" x 6" Page 72	 Fig. 855 Flanged Concentric Reducer Size Range: 3" x 2" thru 10" x 8" Page 73
---	--	--	---

Cast Iron *(Continued)* – Pipe Nipples

IRON FLANGES – CLASS 125 (STANDARD)



Fig. 1011
Companion Flange
Size Range: 3/4" thru 12"
Page 73



Fig. 1016
Reducing Flange
Size Range: 1" thru 8"
Page 74



Fig. 1018
Blind Flange
Size Range: 1" thru 12"
Page 75

HIGH HUB FLANGES FOR C.I. PIPE



Fig. 1010T
Cast Iron Flanges for Cast Iron Pipe
Size Range: 3" thru 12"
Page 76

IRON FLANGES – CLASS 250 (EXTRA HEAVY)



Fig. 1025
Companion Flange
Size Range: 1 1/4" thru 8"
Page 75



Fig. 1030
Reducing Flange
Size Range: 2" thru 4"
Page 76

Fig. 1021
Blind Flange
Size Range: 1" thru 12"
Page 76

CAST IRON THREADED FITTING



Safety Valve Discharge Elbow – Fig. 1538
Screwed Cast Iron
Size Range: 2 1/2" thru 6"
Page 77

MERCHANT STEEL BUSHINGS, CAPS & PLUGS



Hex Bushing
Size Range: 1/4" x 1/8" thru 1" x 3/4"
Page 81



Countersunk Plugs
(Square and Hex Socket)
Size Range: 1/8" thru 2"
Page 81



Flush Bushings
Size Range: 1/4" x 1/8" thru 1/2" x 3/8"
Page 82



Caps
Size Range: 1/8" thru 3/4"
Page 82



Solid Square Head Plugs
Size Range: 1/8" thru 2"
Page 82

PIPE NIPPLES – BLACK & GALVANIZED



Seamless Pipe Nipples
Std. Sch. 40, XH Sch. 80, Sch. 160, XXH
Size Range: 1/8" thru 6"
Page 84



Welded Pipe Nipples
Std. Sch. 40, XH Sch. 80
Size Range: 1/8" thru 6"
Page 85 - 88

PICTORIAL TABLE OF CONTENTS

Steel Pipe Couplings – Forged Steel

STEEL PIPE COUPLINGS

 Fig. 336 Standard, Full & Half Size Range: 1/8" thru 6" Page 90	 Fig. 337 Extra Strong (XS), Full & Half Size Range: 1/8" thru 3" Page 91	 Fig. 346 Standard, Right & Left Size Range: 1/2" thru 2" Page 92	 Fig. 347 Extra Strong (XS), Right & Left Size Range: 1/2" thru 2" Page 92
 Fig. 348 API Line Pipe Coupling Size Range: 1/8" thru 12" Page 93	 Fig. 379 Shallow Well Coupling Size Range: 1/4" thru 2" Page 94	 Fig. 380 Water Well Reamed & Drifted Coupling Size Range: 1/4" thru 12" Page 94	 Fig. 381 #9 Drive Coupling Size Range: 1/4" thru 2" Page 94

FORGED STEEL FITTINGS – CLASS 2000 THREADED

 Fig. 2101 90° Elbow Size Range: 1/4" thru 4" Page 96	 Fig. 2102 45° Elbow Size Range: 1/4" thru 3" Page 96	 Fig. 2103 Tee Size Range: 1/4" thru 4" Page 97	 Fig. 2104 Cross Size Range: 1/4" thru 3" Page 97
---	---	--	---

FORGED STEEL FITTINGS – CLASS 3000 THREADED

 Fig. 2111 90° Elbow Size Range: 1/8" thru 4" Page 98	 Fig. 2112 45° Elbow Size Range: 1/8" thru 4" Page 98	 Fig. 2114 Tee Size Range: 1/8" thru 4" Page 98	 Fig. 2115 Cross Size Range: 1/8" thru 4" Page 99	 Fig. 2113 90° Street Elbow Size Range: 1/8" thru 2" Page 99
 Fig. 2116 Lateral Size Range: 1/2" thru 2" Page 99	 Fig. 2117 Coupling Size Range: 1/8" thru 4" Page 100	 Fig. 2119 Half Coupling Size Range: 1/8" thru 4" Page 100	 Fig. 2118 Reducing Coupling Size Range: 1/4" x 1/8" thru 4" x 1 1/2" Page 101	 Fig. 2120 Pipe Cap Size Range: 1/8" thru 4" Page 101

Forged Steel_(Continued)

FORGED STEEL FITTINGS – CLASS 6000 THREADED

 Fig. 2131 90° Elbow Size Range: 1/8" thru 4" Page 102	 Fig. 2132 45° Elbow Size Range: 1/8" thru 4" Page 102	 Fig. 2134 Tee Size Range: 1/8" thru 4" Page 102	 Fig. 2135 Cross Size Range: 1/8" thru 4" Page 103	 Fig. 2133 90° Street Elbow Size Range: 1/8" thru 1 1/2" Page 103
 Fig. 2136 Lateral Size Range: 1/2" thru 1 1/2" Page 103	 Fig. 2137 Coupling Size Range: 1/8" thru 4" Page 104	 Fig. 2141 Half Coupling Size Range: 1/8" thru 4" Page 104	 Fig. 2138 Reducing Coupling Size Range: 1/4" x 1/8" thru 4" x 2" Page 105	 Fig. 2143 Pipe Cap Size Range: 1/8" thru 4" Page 105

FORGED STEEL FITTINGS CLASS 3000 SOCKET WELD

 Fig. 2150 90° Elbow Size Range: 1/8" thru 4" Page 106	 Fig. 2151 45° Elbow Size Range: 1/8" thru 4" Page 106	 Fig. 2152 Tee Size Range: 1/8" thru 4" Page 107
 Fig. 2153 Cross Size Range: 1/8" thru 4" Page 107	 Fig. 2158 Lateral Size Range: 1/2" thru 2" Page 108	 Fig. 2154 Coupling Size Range: 1/8" thru 4" Page 108
 Fig. 2155 Half Coupling Size Range: 1/8" thru 4" Page 109	 Fig. 2156 Reducing Coupling Size Range: 1/4" x 1/8" thru 4" x 2" Page 109	 Fig. 2157 Pipe Cap Size Range: 1/8" thru 4" Page 110

FORGED STEEL FITTINGS CLASS 6000 SOCKET WELD

 Fig. 2170 90° Elbow Size Range: 1/2" thru 4" Page 111	 Fig. 2171 45° Elbow Size Range: 1/2" thru 4" Page 111	 Fig. 2172 Tee Size Range: 1/2" thru 4" Page 112
 Fig. 2173 Cross Size Range: 1/2" thru 2" Page 112	 Fig. 2178 Lateral Size Range: 1/2" thru 1 1/2" Page 112	 Fig. 2174 Coupling Size Range: 1/2" thru 4" Page 113
 Fig. 2175 Half Coupling Size Range: 1/2" thru 4" Page 113	 Fig. 2176 Reducing Coupling Size Range: 1/2" x 1/4" thru 4" x 2" Page 114	 Fig. 2177 Pipe Cap Size Range: 1/2" thru 4" Page 114

PICTORIAL TABLE OF CONTENTS

Forged Steel^(Continued) – Anvilets

FORGED STEEL FITTINGS – HIGH PRESSURE PLUGS & BUSHINGS



Fig. 2122
Square Head Plug
Size Range: 1/8" thru 4"
Page 115



Fig. 2142
Hex Head Plug
Size Range: 1/8" thru 4"
Page 115



Fig. 2121
Round Head Plug
Size Range: 1/8" thru 4"
Page 115



Fig. 2139
Hex Head Bushing
Size Range: 1/4" x 1/8" thru 4" x 1 1/2"
Page 116



Fig. 2140
Flush Bushing
Size Range: 1/4" x 1/8" thru 2" x 1/4"
Page 116

FORGED STEEL FITTINGS SOCKET WELD REDUCER INSERTS

Class 3000

For use with Sch. 40 & 80 Pipe
Size Range: 1/2" x 1/4" thru 3" x 2 1/2"
Page 117

Class 6000

For use with Sch. 160 Pipe
Size Range: 3/4" x 1/4" thru 2" x 1 1/4"
Page 118

FORGED STEEL UNIONS

Class 3000

Fig. 2125 – Threaded Union
Fig. 2126 – Socket Weld Union
Size Range: 1/4" thru 3"
Page 119

Class 6000

Fig. 2127 – Threaded Union
Fig. 2128 – Socket Weld Union
Size Range: 1/4" thru 2"
Page 120

UNIVERSAL ELBOWLET



Class 3000 & 6000 – Butt weld, Threaded & Socket-Weld

Class 3000 Threaded & Socket-Weld/Standard & XS/XH Butt weld
Size Range: 1/2" thru 2"

Class 6000 Threaded & Socket-Weld
Size Range: 1/2" thru 1 1/2"
Page 127

UNIVERSAL FORGED STEEL ANVILETS

Butt weld



Standard
Size Range: 1/8" thru 24"
Page 122



Extra Strong
Size Range: 1/8" thru 24"
Page 122



XXS, Sch. 160
Size Range: 1/2" thru 4"
Page 123

Threaded



Class 3000
Size Range: 1/8" thru 4"
Page 124



Class 6000
Size Range: 1/2" thru 2"
Page 124

Socket-Weld



Class 3000
Size Range: 1/8" thru 4"
Page 125



Class 6000
Size Range: 1/2" thru 2"
Page 125

LATERAL ANVILET



Class 3000 Butt weld & Threaded

Class 3000 Standard/XS Butt Weld
Size Range: 1/2" thru 2"

Class 3000 Threaded/Standard
Size Range: 1/2" thru 2"
Page 128


FLAT ANVILET

Class 3000 Threaded, Butt weld & Socket-Weld

Size Range: 1/4" thru 3"
Page 129

Catawissa

CATAWISSA WING UNIONS

 Fig. 100 Threaded Ends 1,000 psi cwp - 1,500 psi test Size Range: 2" thru 8" Page 132	 Fig. 100C Threaded Ends - Lug Union 1,000 psi cwp - 1,500 psi test Size: 2" Page 132	 Fig. 200 Threaded Ends 2,000 psi cwp - 3,000 psi test Size Range: 1" thru 6" Page 133	 Fig. 200 Butt Weld Ends - Sch. 40 2,000 psi cwp - 3,000 psi test Size Range: 1" thru 6" Page 134	 Fig. 200C Threaded Ends - Lug Union 2,000 psi cwp - 3,000 psi test Size Range: 1" thru 2" Page 134	 Fig. 206 Threaded Ends 2,000 psi cwp - 3,000 psi test Size Range: 1" thru 6" Page 135
 Fig. 206 Butt Weld Ends - Sch. 40 2,000 psi cwp - 3,000 psi test Size Range: 2" thru 6" Page 136	 Fig. 202 Blanking Cap Only with O-Ring Size: 4" Page 136	 Fig. 211 Threaded Ends Insulating Union 2,000 psi cwp - 3,000 psi test Sizes: 1" & 2" Page 137	 Fig. 300 Flat-Face Union 2,000 psi cwp - 3,000 psi test Size Range: 1" thru 4" Page 137	 Fig. 301 Steam Service Union 3,000 psi cwp - 4,500 psi test Size Range: 1" thru 3" Page 138	 Fig. 400 Threaded Ends 4,000 psi cwp - 6,000 psi test Size Range: 2" thru 4" Page 138
 Fig. 400 Butt Weld Ends - Sch. 80 4,000 psi cwp - 6,000 psi test Size: 2" Page 139	 Fig. 600 Threaded Ends 6,000 psi cwp - 9,000 psi test Size Range: 1" thru 4" Page 139	 Fig. 602 Threaded Ends 6,000 psi cwp - 9,000 psi test Size Range: 1" thru 4" Page 140	 Fig. 602 Butt Weld Ends - Sch. 80 6,000 psi cwp - 9,000 psi test Size Range: 2" thru 4" Page 141	 Fig. 607 Threaded Ends Well Service Union 2,000 psi cwp - 3,000 psi test Sizes: 1 1/2" & 2" Page 141	 Fig. 1002 Threaded Ends 10,000 psi cwp - 15,000 psi test Size Range: 1" thru 4" Page 142
 Fig. 1002 Butt Weld Ends - Sch. 160 10,000 psi cwp - 15,000 psi test Size Range: 2" thru 4" Page 143	 Fig. 1002 Butt Weld Ends - Sch. XXH 10,000 psi cwp - 15,000 psi test Size Range: 2" thru 4" Page 143	 Fig. 1502 Threaded Ends 15,000 psi cwp - 22,500 psi test Sizes: 2" & 3" Page 144	 Fig. 1502 Butt Weld Ends - Sch. 160 15,000 psi cwp - 22,500 psi test Sizes: 2" & 3" Page 144	 Fig. S1A High Speed Union 3,000 psi cwp - 4,500 psi test Size Range: 1" thru 3" Page 145	 Fig. 3L S1A Tri-Lug High Speed Union 3,000 psi cwp - 4,500 psi test Size Range: 1" thru 2" Page 145

PICTORIAL TABLE OF CONTENTS

J.B. Smith Oil Country Products

SWAGE NIPPLES, BULL PLUGS, OIL COUNTRY FITTINGS, COUPLINGS & STAINLESS SWAGES

 Concentric Swage Nipple Size Range: 1/4" x 1/8" thru 1" x 3/4" Page 149	 Concentric Swage Nipple Size Range: 1 1/4" x 1/4" thru 8" x 6" Page 150	 Eccentric Swage Nipple Size Range: 1/4" x 1/8" thru 4" x 3 1/2" Page 151	 Stainless & Alloy Steel Swage Nipple Size Range: 1/4" x 1/8" thru 4" x 3 1/2" Page 152	 Carbon Steel Bull Plug Size Range: 1/8" thru 8" Page 153	 Solid Refinery Plug Black (non-plated) Carbon Steel Size Range: 1/8" thru 2" Page 153
 Adapter Nipples Size Range: 3/4" thru 12" Page 154	 Swage Nipple (Oil Country Sizes) Large End Upset Reduced to Regular or Upset Size Range: 1" x 3/4" thru 4" x 3 1/2" Page 156	 Swage Nipple (Oil Country Sizes) Large End Non-Upset Reduced to Upset Size Range: 1" x 3/4" thru 4" x 3" Page 156	 Swage Nipple Oil Country Tubing & Casing non EUE ends Page 157	 Tubing Bull Plugs Size Range: 3/4" EUE thru 3" EUE Page 158	 Casing Bull Plugs Size Range: 4 1/2" thru 10 3/4" Page 158
 API Bull Plug Female Size Range: 3/4" thru 4" EUE Page 158	 Bell Nipple Size Range: 4 1/2" thru 8 5/8" Page 159	 Tubing Nipple Standard Weight Size Range: 1" thru 4" Page 159	 Tubing Nipple Extra Heavy Weight Size Range: 1" thru 4" Page 159	 Oil Country Casing Nipple Size Range: 4 1/2" thru 16" Page 160	 API Casing Coupling Short Thread Size Range: 4 1/2" thru 20" Page 161
 API Casing Coupling Long Thread Size Range: 4 1/2" thru 13 3/8" Page 161	 Combination Coupling J-55 Size Range: 2" thru 4" Page 161	 Sub Tubing Coupling J-55 Size Range: 2" EUE x 2" Reg thru 4" EUE x 4" Reg Page 162	 API Tubing Coupling Size Range: 2" thru 4" Page 162	 Special Clearance Tubing Coupling Size Range: 2" thru 3" Page 162	 Chambers/Pressure Vessels Size Range: 2" thru 8" Page 163



Malleable Iron

Cast Iron

Small Steel Fittings

Pipe Nipples & Pipe Couplings

Forged Steel Fittings & Unions

Anvils

Catawissa

J.B. Smith Products

Carton Information

**Malleable Iron Threaded Pipe Unions
Pressure - Temperature Ratings**

Temperature	Pressure					
	Class 150		Class 250		Class 300	
	(°F)	(°C)	psi	bar	psi	bar
-20° to 150°	-28.9° to 65.6°		300	20.7	500	34.5
200°	93.3°		265	18.3	455	31.4
250°	121.1°		225	15.5	405	27.9
300°	148.9°		185	12.8	360	24.8
350°	176.7°		150	10.3	315	21.7
400°	204.4°		110	7.6	270	18.6
450°	232.2°		75	5.2	225	15.5
500°	260.0°		—	—	180	12.4
550°	287.8°		—	—	130	9.0

Note: Unions with Copper or Copper Alloy seats are not intended for use where temperature exceeds 450°F



For Listings/Approval Details and Limitations, visit our website @ www.anvilintl.com or contact an Anvil/AnvilStar Sales Representative.

**Malleable Iron Threaded Fittings
Pressure - Temperature Ratings**

Temperature	Pressure							
	Class 150		Class 300					
	(°F)	(°C)	psi		psi		psi	
-20° to 150°	-28.9° to 65.6°		300	20.7	2,000	137.9	1,500	103.4
200°	93.3°		265	18.3	1,785	123.1	1,350	93.1
250°	121.1°		225	15.5	1,575	108.6	1,200	82.7
300°	148.9°		185	12.8	1,360	93.8	1,050	72.4
350°	176.7°		150	10.3	1,150	79.3	900	62.1
400°	204.4°		—	—	935	64.5	750	51.7
450°	232.2°		—	—	725	50.0	600	41.4
500°	260.0°		—	—	510	35.2	450	31.0
550°	287.8°		—	—	300	20.7	300	20.7

Anvil Class 150/300 Malleable Iron Fittings conform to ASME B16.3 and Unions conform to ASME B16.39.

ALL ELBOWS & TEES 3/8" (10 DN) and LARGER ARE 100% GAS TESTED AT A MINIMUM OF 100 PSI. (6.9 bar)



www.anvilintl.com

MALLEABLE IRON

Malleable Iron Class 150 (Standard)



FIGURE 1101 90° Elbow	Size		A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1/8	6	11/16	17	0.06	0.03	0.06	0.03
	1/4	8	13/16	22	0.11	0.05	0.11	0.05
	3/8	10	15/16	24	0.17	0.08	0.17	0.08
	1/2	15	1 1/8	29	0.30	0.14	0.30	0.14
	3/4	20	1 5/16	33	0.45	0.20	0.45	0.20
	1	25	1 1/2	38	0.73	0.33	0.73	0.33
	1 1/4	32	1 3/4	44	0.97	0.44	0.97	0.44
	1 1/2	40	1 15/16	49	1.30	0.59	1.30	0.59
	2	50	2 1/4	57	2.06	0.93	2.06	0.93
	2 1/2	65	2 11/16	68	3.55	1.61	3.55	1.61
	3	80	3 1/16	78	5.46	2.48	5.46	2.48
	3 1/2	90	3 7/16	87	7.10	3.22	7.10	3.22
	4	100	3 13/16	98	8.95	4.06	8.95	4.06
	5	125	4 1/2	114	13.90	6.30	13.90	6.30
	6	150	5 1/8	130	23.00	10.43	23.00	10.43

FIGURE 1101R Reducing Elbow	Size				X		Z			Unit Weight			
										Black		Galv.	
	NPS	DN	NPS	DN	in	mm	in	mm		lbs	kg	lbs	kg
	1/4	8	1/8	6	3/4	19	3/4	19		0.10	0.05	0.10	0.05
	3/8	10	1/8	6	13/16	22	7/8	22		0.12	0.05	0.12	0.05
			1/4	8	7/8	22	15/16	24		0.14	0.06	0.14	0.06
	1/2	15	1/4	8	1	25	1	25		0.19	0.09	0.19	0.09
			3/8	10	1 1/16	27	1 1/16	27		0.22	0.10	0.22	0.10
	3/4	20	1/4	8	1 1/8	29	1 1/8	29		0.26	0.12	0.26	0.12
			3/8	10	1 1/8	29	1 1/8	29		0.29	0.13	0.29	0.13
			1/2	15	1 3/16	30	1 1/4	32		0.38	0.17	0.38	0.17
	1	25	3/8	10	1 3/16	30	1 1/4	32		0.41	0.19	0.41	0.19
			1/2	15	1 1/4	32	1 3/8	35		0.46	0.21	0.46	0.21
			3/4	20	1 3/8	35	1 7/16	37		0.56	0.25	0.56	0.25
	1 1/4	32	1/2	15	1 3/8	35	1 9/16	40		0.61	0.28	0.61	0.28
			3/4	20	1 7/16	37	1 5/8	41		0.71	0.32	0.71	0.32
			1	25	1 9/16	40	1 11/16	43		0.87	0.39	0.87	0.39
	1 1/2	40	3/4	20	1 1/2	38	1 3/4	44		0.83	0.38	0.83	0.38
			1	25	1 5/8	41	1 13/16	47		1.02	0.46	1.02	0.46
			1 1/4	32	1 13/16	47	1 7/8	48		1.17	0.53	1.17	0.53
	2	50	3/4	20	1 5/8	41	2	51		1.30	0.59	1.30	0.59
			1	25	1 3/4	44	2	51		1.35	0.61	1.35	0.61
			1 1/4	32	1 7/8	48	2 1/8	54		1.53	0.69	1.53	0.69
			1 1/2	40	2	51	2 1/8	54		1.75	0.79	1.75	0.79
	2 1/2	65	1 1/2	40	2 3/16	56	2 1/2	64		2.50	1.13	2.50	1.13
			2	50	2 7/16	62	2 5/8	67		2.98	1.35	2.98	1.35
	3	80	2	50	2 9/16	65	2 15/16	75		3.75	1.70	3.75	1.70
			2 1/2	65	2 13/16	73	3	76		4.30	1.95	4.30	1.95
	4	100	3	80	3 5/16	84	3 5/8	92		7.87	3.57	7.87	3.57

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

Malleable Iron Class 150 (Standard)



FIGURE 1102 45° Elbow	Size		C		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
 	1/8	6	11/16	17	0.07	0.03	0.07	0.03
	1/4	8	3/4	19	0.11	0.05	0.11	0.05
	3/8	10	13/16	22	0.16	0.07	0.16	0.07
	1/2	15	7/8	22	0.22	0.10	0.22	0.10
	3/4	20	1	25	0.37	0.17	0.37	0.17
	1	25	1 1/8	29	0.54	0.24	0.54	0.24
	1 1/4	32	1 5/16	33	0.86	0.39	0.86	0.39
	1 1/2	40	1 7/16	37	1.13	0.51	1.13	0.51
	2	50	1 11/16	43	1.79	0.81	1.79	0.81
	2 1/2	65	1 15/16	49	3.60	1.63	3.60	1.63
	3	80	2 3/16	56	4.48	2.03	4.48	2.03
	4	100	2 5/8	67	7.40	3.36	7.40	3.36
	5	125	3 1/16	78	11.46	5.20	11.46	5.20
	6	150	3 7/16	87	19.93	9.04	19.93	9.04

FIGURE 1103 (Straight) FIGURE 1103R (Reducing) 90° Street Elbow	Size		A		J		Unit Weight			
							Black		Galv.	
	NPS	DN	in	mm	in	mm	lbs	kg	lbs	kg
 	1/8	6	11/16	17	1	25	0.06	0.03	0.06	0.03
	1/4	8	13/16	22	1 3/16	30	0.10	0.05	0.10	0.05
	3/8	10	15/16	24	1 7/16	37	0.17	0.08	0.17	0.08
	1/2	15	1 1/8	29	1 5/8	41	0.28	0.13	0.28	0.13
	3/4	20	1 5/16	33	1 7/8	48	0.41	0.19	0.41	0.19
	1	25	1 1/2	38	2 1/8	54	0.62	0.28	0.62	0.28
	1 1/4	32	1 3/4	44	2 7/16	62	1.09	0.49	1.09	0.49
	1 1/2	40	1 15/16	49	2 11/16	68	1.44	0.65	1.44	0.65
	2	50	2 1/4	57	3 1/4	83	2.85	1.29	2.85	1.29
	2 1/2	65	2 11/16	68	3 7/8	98	4.00	1.81	4.00	1.81
	3	80	3 1/16	78	4 1/2	114	6.06	2.75	6.06	2.75
	4	100	3 13/16	98	5 11/16	144	10.53	4.78	10.53	4.78
	1/2 x 3/8	15 x 10	1 1/16	27	1 9/16	40	0.23	0.10	0.23	0.10
	3/4 x 1/2	20 x 15	1 3/16	30	1 3/4	44	0.32	0.15	0.32	0.15
	1 x 3/4	25 x 20	1 3/8	35	2 1/16	52	0.54	0.24	0.54	0.24
	1 1/4 x 1	32 x 25	1 9/16	40	2 5/16	59	0.86	0.39	0.86	0.39
	1 1/4 x 3/4	32 x 20	1 7/16	37	2 1/4	57	0.75	0.34	0.75	0.34
	1 1/2 x 1 1/4	40 x 32	1 13/16	47	2 9/16	65	1.18	0.54	1.18	0.54
	1 1/2 x 1	40 x 25	1 5/8	41	2 1/2	64	1.08	0.49	1.08	0.49
	2 x 1 1/2	50 x 40	2	51	2 15/16	75	1.85	0.84	1.85	0.84

First size denotes female end.

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

MALLEABLE IRON

Malleable Iron

Class 150 (Standard)



FIGURE 1104 45° Street Elbow	Size		C		K		Unit Weight			
							Black		Galv.	
	NPS	DN	in	mm	in	mm	lbs	kg	lbs	kg
	1/8	6	11/16	17	7/8	22	0.06	0.03	0.06	0.03
	1/4	8	3/4	19	15/16	24	0.10	0.05	0.10	0.05
	3/8	10	13/16	22	1	25	0.14	0.06	0.14	0.06
	1/2	15	7/8	22	1 1/8	29	0.20	0.09	0.20	0.09
	3/4	20	1	25	1 5/16	33	0.33	0.15	0.33	0.15
	1	25	1 1/8	29	1 7/16	37	0.52	0.24	0.52	0.24
	1 1/4	32	1 5/16	33	1 11/16	43	0.85	0.39	0.85	0.39
	1 1/2	40	1 7/16	37	1 7/8	48	1.22	0.55	1.22	0.55
	2	50	1 11/16	43	2 1/4	57	1.92	0.87	1.92	0.87


FIGURE 1105 Straight Tee	Size		A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1/8	6	11/16	17	0.09	0.04	0.09	0.04
	1/4	8	13/16	22	0.15	0.07	0.15	0.07
	3/8	10	15/16	24	0.23	0.10	0.23	0.10
	1/2	15	1 1/8	29	0.41	0.19	0.41	0.19
	3/4	20	1 5/16	33	0.60	0.27	0.60	0.27
	1	25	1 1/2	38	0.90	0.41	0.90	0.41
	1 1/4	32	1 3/4	44	1.31	0.59	1.31	0.59
	1 1/2	40	1 15/16	49	1.73	0.78	1.73	0.78
	2	50	2 1/4	57	2.52	1.14	2.52	1.14
	2 1/2	65	2 11/16	68	4.90	2.22	4.90	2.22
	3	80	3 1/16	78	7.13	3.23	7.13	3.23
	3 1/2	90	3 7/16	87	9.00	4.08	9.00	4.08
	4	100	3 13/16	98	11.32	5.13	11.32	5.13
	5	125	4 1/2	114	19.42	8.81	19.42	8.81
	6	150	5 1/8	130	25.50	11.56	25.50	11.56

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
 All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

Malleable Iron

Class 150 (Standard)

FIGURE 1105R
Reducing Tee



Size						X		Y		Z		Unit Weight			
												Black		Galv.	
NPS	DN	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
1/8	6	1/8	6	1/4	8	3/4	19	3/4	19	3/4	19	0.12	0.05	0.12	0.05
1/4	8	1/4	8	1/8	6	3/4	19	3/4	19	3/4	19	0.13	0.06	0.13	0.06
				3/8	10	15/16	24	15/16	24	7/8	22	0.19	0.09	0.19	0.09
3/8	10	1/4	8	1/4	8	7/8	22	13/16	22	15/16	24	0.19	0.09	0.19	0.09
				3/8	10	15/16	24	15/16	24	15/16	24	0.21	0.10	0.21	0.10
		3/8	10	1/4	8	7/8	22	7/8	22	15/16	24	0.21	0.10	0.21	0.10
				1/2	15	1 1/16	27	1 1/16	27	1 1/16	27	0.27	0.12	0.27	0.12
1/2	15	1/4	8	1/2	15	1 1/8	29	1 5/16	24	1 1/8	29	0.29	0.13	0.29	0.13
				3/8	10	1 1/16	27	1	25	1 1/16	27	0.28	0.13	0.28	0.13
		1/2	15	1/2	15	1 1/8	29	1 1/16	27	1 1/8	29	0.33	0.15	0.33	0.15
				1/4	8	1	25	1	25	1	25	0.27	0.12	0.27	0.12
				3/8	10	1 1/16	27	1 1/16	27	1 1/16	27	0.30	0.14	0.30	0.14
				3/4	20	1 1/4	32	1 1/4	32	1 3/16	30	0.45	0.20	0.45	0.20
3/4	20	1/4	8	1	25	1 3/8	35	1 3/8	35	1 1/4	32	0.55	0.25	0.55	0.25
				1 1/4	32	1 5/8	41	1 5/8	41	1 7/16	37	0.90	0.41	0.90	0.41
		3/8	10	3/4	20	1 5/16	33	1 1/8	29	1 5/16	33	0.45	0.20	0.45	0.20
				1 1/2	15	1 3/16	30	1 1/8	29	1 1/4	32	0.36	0.16	—	—
		1/2	15	1/2	15	1 3/16	30	1 1/8	29	1 1/4	32	0.46	0.21	0.46	0.21
				3/4	20	1 5/16	33	1 1/4	32	1 5/16	33	0.43	0.20	0.43	0.20
		3/4	20	1/4	8	1 1/16	27	1 1/16	27	1 1/8	29	0.51	0.23	0.51	0.23
				3/8	10	1 1/8	29	1 1/8	29	1 1/8	29	0.38	0.17	0.38	0.17
				1/2	15	1 3/16	22	1 3/16	30	1 1/4	32	0.42	0.19	0.42	0.19
				1	25	1 7/16	37	1 7/16	37	1 3/8	35	0.47	0.21	0.47	0.21
1	25	1/4	8	1	25	1 1/2	38	1 5/16	33	1 1/2	38	0.62	0.28	0.62	0.28
				1 1/4	32	1 5/8	41	1 5/8	41	1 7/16	37	0.90	0.41	0.90	0.41
		1/2	15	1/2	15	1 1/4	32	1 1/8	29	1 3/8	35	0.69	0.31	0.69	0.31
				3/4	20	1 3/8	35	1 1/4	32	1 7/16	37	0.70	0.32	0.70	0.32
		1	25	1	25	1 1/2	38	1 3/8	35	1 1/2	38	0.56	0.25	0.56	0.25
				1 1/2	15	1 3/16	30	1 3/16	30	1 3/8	35	0.76	0.34	0.76	0.34
		3/4	20	1/2	15	1 1/4	32	1 3/16	30	1 3/8	35	0.59	0.27	0.59	0.27
				3/4	20	1 3/8	35	1 5/16	33	1 7/16	37	0.74	0.34	0.74	0.34
		1	25	1	25	1 1/2	38	1 7/16	37	1 1/2	38	0.78	0.35	0.78	0.35
				1/4	8	1 1/8	29	1 1/8	29	1 1/4	32	0.53	0.24	0.53	0.24
				3/8	10	1 3/16	30	1 3/16	30	1 1/4	32	0.60	0.27	0.60	0.27
				1/2	15	1 1/4	32	1 1/4	32	1 3/8	35	0.70	0.32	0.70	0.32
				3/4	20	1 3/8	35	1 3/8	35	1 7/16	37	0.82	0.37	0.82	0.37
				1 1/4	32	1 11/16	43	1 11/16	43	1 9/16	40	0.92	0.42	0.92	0.42
				1 1/2	40	1 13/16	47	1 13/16	46	1 5/8	41	1.19	0.54	1.19	0.54
				2	50	2	51	2	51	1 3/4	44	1.63	0.74	1.63	0.74

See additional sizes on following page.


Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.

All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

Malleable Iron

Class 150 (Standard)

FIGURE 1105R
Reducing Tee (Cont'd.)



Size						X		Y		Z		Unit Weight						
												Black		Galv.				
NPS	DN	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	lbs	kg	lbs	kg			
1¼	32	½	15	1	25	1⅞	40	1⅜	35	1⅞	43	0.87	0.39	0.87	0.39			
				1¼	32	1¾	44	1⅞	40	1¾	44	1.04	0.47	1.04	0.47			
	¾	20	¾	20	1⅞	37	1⅝	33	1⅝	41	0.86	0.39	0.86	0.39				
			1	25	1⅞	40	1⅞	37	1⅞	43	0.91	0.41	0.91	0.41				
			1¼	32	1¾	44	1⅝	41	1¾	44	1.04	0.47	1.04	0.47				
			1	25	½	15	1⅜	35	1¼	32	1⅞	40	0.76	0.34	0.76	0.34		
	¾	20			1⅞	37	1⅜	35	1⅝	41	0.87	0.39	0.87	0.39				
	1	25			1⅞	40	1½	38	1⅞	43	1.11	0.50	1.11	0.50				
	1¼	32			1¾	44	1⅞	43	1¾	44	1.13	0.51	1.13	0.51				
	1¼	32	¾	10	1¼	32	1¼	32	1⅞	37	0.86	0.39	0.86	0.39				
			½	15	1⅜	35	1⅜	35	1⅞	40	0.98	0.44	0.98	0.44				
			¾	20	1⅞	37	1⅞	37	1⅝	41	1.07	0.49	1.07	0.49				
			1	25	1⅞	40	1⅞	40	1⅞	43	1.18	0.54	1.18	0.54				
			1½	40	1⅞	48	1⅞	48	1⅞	47	1.45	0.66	1.45	0.66				
			2	50	2⅞	54	2⅞	54	1⅞	48	1.70	0.77	1.70	0.77				
			1½	40	½	15	1½	40	1⅞	49	1⅞	43	1⅝	49	1.33	0.60	1.33	0.60
					¾	20	¾	20	1½	38	1⅝	33	1¾	44	1.00	0.45	1.00	0.45
	1½	40			1½	40	1⅞	49	1¾	44	1⅝	49	1.41	0.64	1.41	0.64		
	1	25			1	25	1⅝	41	1½	38	1⅞	47	1.14	0.52	1.14	0.52		
					1¼	32	1⅞	47	1⅞	43	1⅞	48	1.30	0.59	1.30	0.59		
1½					40	1⅞	49	1⅞	47	1⅝	49	1.50	0.68	1.50	0.68			
1¼					32	½	15	1⅞	37	1⅝	35	1⅞	43	1.05	0.48	1.05	0.48	
	¾	20				1½	38	1⅞	37	1¾	44	1.08	0.49	1.08	0.49			
	1	25	1⅝	41		1⅞	40	1⅞	47	1.26	0.57	1.26	0.57					
	1¼	32	1⅞	47		1¾	44	1⅞	48	1.52	0.69	1.52	0.69					
1½	40	1½	40	1⅞	49	1⅞	48	1⅝	49	1.50	0.68	1.50	0.68					
		½	15	1⅞	37	1⅞	37	1⅞	43	1.19	0.54	1.19	0.54					
		¾	20	1½	38	1½	38	1¾	44	1.60	0.73	1.60	0.73					
		1	25	1⅝	41	1⅝	41	1⅞	47	1.45	0.66	1.45	0.66					
1¼	40	1¼	32	1⅞	47	1⅞	47	1⅞	48	1.45	0.66	1.45	0.66					
		2	50	2⅞	56	2⅞	56	2	51	1.86	0.84	1.86	0.84					


See additional sizes on previous and following page.

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

Malleable Iron

Class 150 (Standard)

FIGURE 1105R
Reducing Tee (Cont'd.)



Size					X		Y		Z		Unit Weight				
												Black		Galv.	
NPS	DN	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
2	50	1/2	15	2	50	2 1/4	57	1 7/8	48	2 1/4	57	2.15	0.98	2.15	0.98
		3/4	20	2	50	2 1/4	57	1 15/16	49	2 1/4	57	2.00	0.91	2.00	0.91
		1	25	2	50	2 1/4	57	2	51	2 1/4	57	2.14	0.97	2.14	0.97
		1 1/4	32	1 1/4	32	1 7/8	48	1 3/4	44	2 1/8	54	1.72	0.78	1.72	0.78
				1 1/2	40	2	51	1 7/8	48	2 3/16	56	1.85	0.84	1.85	0.84
				2	50	2 1/4	57	2 1/8	54	2 1/4	57	2.20	1.00	2.20	1.00
		1 1/2	40	1	25	1 3/4	44	1 5/8	41	2	51	1.57	0.71	1.57	0.71
				1 1/4	32	1 7/8	48	1 13/16	47	2 1/8	54	1.76	0.80	1.76	0.80
				1 1/2	40	2	51	1 15/16	49	2 3/16	56	1.95	0.88	1.95	0.88
				2	50	2 1/4	57	2 3/16	56	2 1/4	57	2.24	1.02	2.24	1.02
		2	50	1/2	15	1 1/2	38	1 1/2	38	1 7/8	48	1.65	0.75	1.65	0.75
				3/4	20	1 5/8	41	1 5/8	41	2	51	1.87	0.85	1.87	0.85
				1	25	1 3/4	44	1 3/4	44	2	51	1.76	0.80	1.76	0.80
				1 1/4	32	1 7/8	48	1 7/8	48	2 1/8	54	2.35	1.07	2.35	1.07
				1 1/2	40	2	51	2	51	2 3/16	56	2.55	1.16	2.55	1.16
				2 1/2	65	2 5/8	67	2 5/8	67	2 3/8	60	3.50	1.59	3.50	1.59
2 1/2	65	1 1/2	40	2	50	2 3/8	60	2 3/16	56	2 5/8	67	3.43	1.56	3.43	1.56
				2 1/2	65	2 1 1/16	68	2 1/2	64	2 1 1/16	68	3.80	1.72	3.80	1.72
		2	50	2	50	2 3/8	60	2 1/4	57	2 5/8	67	3.28	1.49	3.28	1.49
				2 1/2	65	2 1 1/16	68	2 5/8	67	2 1 1/16	68	4.10	1.86	4.10	1.86
		2 1/2	65	3/4	20	1 3/4	44	1 3/4	44	2 3/16	59	2.72	1.23	2.72	1.23
				1	25	1 7/8	48	1 7/8	48	2 3/8	60	2.85	1.29	2.85	1.29
				1 1/4	32	2 1/16	52	2 1/16	52	2 7/16	62	3.36	1.52	3.36	1.52
				1 1/2	40	2 3/16	56	2 3/16	56	2 1/2	64	3.46	1.57	3.46	1.57
				2	50	2 3/8	60	2 3/8	60	2 5/8	67	3.65	1.66	3.65	1.66
				3	80	3	76	3	76	2 13/16	73	5.82	2.64	5.82	2.64
3	80	2	50	2	50	2 1/2	64	2 1/4	57	2 7/8	73	4.50	2.04	4.50	2.04
				3	80	3 1/8	79	2 7/8	73	3 1/8	79	5.80	2.63	5.80	2.63
		2 1/2	65	2	50	2 1/2	64	2 3/8	60	2 7/8	73	4.80	2.18	4.80	2.18
				2 1/2	65	2 13/16	73	2 1 1/16	68	3	76	5.80	2.63	5.80	2.63
		3	80	3/4	20	1 7/8	48	1 7/8	48	2 5/8	67	4.03	1.83	4.03	1.83
				1	25	2	51	2	51	2 5/8	67	4.13	1.87	4.13	1.87
				1 1/4	32	2 3/16	56	2 3/16	56	2 3/4	70	4.50	2.04	4.50	2.04
				1 1/2	40	2 5/16	59	2 5/16	59	2 13/16	73	5.18	2.35	5.18	2.35
2	50	2 1/2	64	2 1/2	64	2 1/2	64	2 7/8	73	5.70	2.59	5.70	2.59		
		2 1/2	65	2 13/16	73	2 13/16	73	3	76	6.09	2.76	6.09	2.76		
4	100	3	80	4	100	3 13/16	98	3 5/8	92	3 13/16	98	10.40	4.72	10.40	4.72
		4	100	1 1/2	40	2 1/2	65	2 1/2	65	3 5/8	86	7.47	3.39	7.47	3.39
				2	50	2 3/4	70	2 3/4	70	3 7/16	87	8.39	3.80	8.39	3.80
				2 1/2	65	3 1/16	78	3 1/16	78	3 1/2	89	9.60	4.35	9.60	4.35
				3	80	3 5/16	84	3 5/16	84	3 5/8	92	11.02	5.00	11.02	5.00

See additional sizes on previous page.

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.

All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

MALLEABLE IRON

Malleable Iron

Class 150 (Standard)


FIGURE 1106 (Straight) FIGURE 1106R (Reducing) Street or Service Tee	Size		A		J		Unit Weight			
							Black		Galv.	
	NPS	DN	in	mm	in	mm	lbs	kg	lbs	kg
	1/4	8	1 3/16	30	1 3/16	30	0.15	0.07	0.15	0.07
	3/8	10	1 5/16	33	1 7/16	37	0.24	0.11	0.24	0.11
	1/2	15	1 1/8	29	1 5/8	41	0.34	0.15	0.34	0.15
	3/4	20	1 5/16	33	1 7/8	48	0.61	0.28	0.61	0.28
	1	25	1 1/2	38	2 1/8	54	0.96	0.44	0.96	0.44
	1 1/4	32	1 3/4	44	2 1/16	62	1.39	0.63	1.39	0.63
	1 1/2	40	1 15/16	49	2 11/16	68	1.93	0.88	1.93	0.88
	2	50	2 1/4	57	3 1/4	83	3.16	1.43	3.16	1.43
	Size female run x male run x outlet		Run		Outlet		Unit Weight			
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg
	1 1/4 x 1 x 1 1/4	32 x 25 x 32	1 3/4	44	2 5/16	59	1 3/4	44	1.34	0.61



FIGURE 1107 Cross	Size		A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1/8	6	1 1/16	17	0.12	0.05	0.12	0.05
	1/4	8	1 3/16	22	0.18	0.08	0.18	0.08
	3/8	10	1 5/16	24	0.28	0.13	0.28	0.13
	1/2	15	1 1/8	29	0.42	0.19	0.42	0.19
	3/4	20	1 5/16	33	0.69	0.31	0.69	0.31
	1	25	1 1/2	38	1.12	0.51	1.12	0.51
	1 1/4	32	1 3/4	44	1.44	0.65	1.44	0.65
	1 1/2	40	1 15/16	49	1.98	0.90	1.98	0.90
	2	50	2 1/4	57	3.30	1.50	3.30	1.50
	2 1/2	65	2 11/16	68	5.90	2.68	5.90	2.68
	3	80	3 1/16	78	7.94	3.60	7.94	3.60
	4	100	3 13/16	98	13.50	6.12	13.50	6.12


FIGURE 1108 45° Y-Branch or Lateral	Size		T		U		V		Unit Weight			
									Black		Galv.	
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
	3/8	10	1/2	13	1 7/16	37	1 15/16	49	0.27	0.12	0.27	0.12
	1/2	15	5/8	16	1 11/16	43	2 5/16	59	0.37	0.17	0.37	0.17
	3/4	20	3/4	19	2 1/16	52	2 3/16	73	0.62	0.28	0.62	0.28
	1	25	7/8	22	2 1/16	62	3 5/16	84	0.86	0.39	0.86	0.39
	1 1/4	32	1	25	2 15/16	75	3 5/16	100	1.63	0.74	1.63	0.74
	1 1/2	40	1 1/8	29	3 1/4	83	4 3/8	111	2.00	0.91	2.00	0.91
	2	50	1 1/4	32	3 15/16	100	5 3/16	132	3.05	1.38	3.05	1.38
	2 1/2	65	1 1/2	38	4 3/4	121	6 1/4	159	5.86	2.66	5.86	2.66
	3	80	1 11/16	43	5 5/16	141	7 1/4	184	9.18	4.16	9.18	4.16
	4	100	2	51	7	178	9	229	15.70	7.12	15.70	7.12

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

Malleable Iron

Class 150 (Standard)

FIGURE 1119 Return Bends Open Pattern, R.H.	Size		Center to Center		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1/2	15	1 1/2	38	0.36	0.16	—	—
	3/4	20	2	51	0.64	0.29	—	—
	1	25	2 1/2	64	1.10	0.50	1.10	0.50
	1 1/4	32	3	76	1.77	0.80	—	—
	1 1/2	40	3 1/2	90	2.55	1.16	2.55	1.16
	2	50	4	102	4.00	1.81	4.00	1.81

FIGURE 1121 Coupling Right Hand	Size		W		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
 	1/8*	6	15/16	24	0.06	0.03	0.06	0.03
	1/4	8	1 1/16	27	0.09	0.04	0.09	0.04
	3/8	10	1 3/16	30	0.13	0.06	0.13	0.06
	1/2	15	1 5/16	33	0.20	0.09	0.20	0.09
	3/4	20	1 1/2	38	0.30	0.14	0.30	0.14
	1	25	1 11/16	43	0.48	0.22	0.48	0.22
	1 1/4	32	1 15/16	49	0.75	0.34	0.75	0.34
	1 1/2	40	2 1/8	54	1.00	0.45	1.00	0.45
	2	50	2 1/2	64	1.45	0.66	1.45	0.66
	2 1/2	65	2 7/8	73	2.40	1.09	2.40	1.09
	3	80	3 3/16	81	3.30	1.50	3.30	1.50
	4	100	3 11/16	94	5.72	2.59	5.72	2.59


* Offered in steel only.

FIGURE 1124 Cap	Size		Unit Weight			
			Black		Galv.	
	NPS	DN	lbs	kg	lbs	kg
	1/2	15	0.12	0.05	0.12	0.05
	3/4	20	0.22	0.10	0.22	0.10
	1	25	0.38	0.17	0.38	0.17
	1 1/4	32	0.58	0.26	0.58	0.26
	1 1/2	40	0.73	0.33	0.73	0.33
	2	50	1.13	0.51	1.13	0.51
	2 1/2	65	1.75	0.79	1.75	0.79
	3	80	2.62	1.19	2.62	1.19
	3 1/2	90	3.19	1.45	3.19	1.45
	4	100	4.54	2.06	4.54	2.06
	5	125	6.45	2.93	6.45	2.93
	6	150	10.00	4.54	10.00	4.54

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
 All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

MALLEABLE IRON

Malleable Iron Class 150 (Standard)

FIGURE 1125 Reducer	Size				M		Unit Weight			
							Black		Galv.	
	NPS	DN	NPS	DN	in	mm	lbs	kg	lbs	kg
	1/4	8	1/8	6	1	25	0.07	0.03	0.07	0.03
	3/8	10	1/8	6	1 1/8	29	0.11	0.05	0.11	0.05
			1/4	8			0.11	0.05	0.11	0.05
	1/2	15	1/8	6	1 1/4	32	0.14	0.06	0.14	0.06
			1/4	8			0.15	0.07	0.15	0.07
			3/8	10			0.17	0.08	0.17	0.08
	3/4	20	1/8	6	1 7/16	37	0.24	0.11	0.24	0.11
			1/4	8			0.22	0.10	0.22	0.10
			3/8	10			0.25	0.11	0.25	0.11
			1/2	15			0.27	0.12	0.27	0.12
	1	25	1/4	8	1 11/16	43	0.35	0.16	0.35	0.16
			3/8	10			0.35	0.16	0.35	0.16
			1/2	15			0.39	0.18	0.39	0.18
			3/4	20			0.43	0.20	0.43	0.20
	1 1/4	32	1/2	15	2 1/16	52	0.61	0.28	0.61	0.28
			3/4	20			0.64	0.29	0.64	0.29
			1	25			0.68	0.31	0.68	0.31
	1 1/2	40	1/2	15	2 5/16	59	0.78	0.35	0.78	0.35
			3/4	20			0.88	0.40	0.88	0.40
			1	25			0.88	0.40	0.88	0.40
			1 1/4	32			0.90	0.41	0.90	0.41
	2	50	1/2	15	2 13/16	73	1.30	0.59	1.30	0.59
			3/4	20			1.34	0.61	1.34	0.61
			1	25			1.40	0.63	1.40	0.63
			1 1/4	32			1.53	0.69	1.53	0.69
			1 1/2	40			1.55	0.70	1.55	0.70
	2 1/2	65	1	25	3 1/4	83	2.12	0.96	2.12	0.96
			1 1/4	32			2.09	0.95	2.09	0.95
			1 1/2	40			2.09	0.95	2.09	0.95
			2	50			2.51	1.14	2.51	1.14
	3	80	1	25	3 11/16	94	3.16	1.43	3.16	1.43
			1 1/4	32			2.99	1.36	2.99	1.36
			1 1/2	40			3.30	1.50	3.30	1.50
			2	50			3.25	1.47	3.25	1.47
			2 1/2	65			3.31	1.50	3.31	1.50
	3 1/2	90	2	50	4	102	4.32	1.96	4.32	1.96
			2 1/2	65			4.72	2.14	4.72	2.14
			3	80			4.99	2.26	4.99	2.26
	4	100	1 1/2	40	4 3/8	111	4.90	2.22	4.90	2.22
			2	50			5.10	2.31	5.10	2.31
			2 1/2	65			5.93	2.69	5.93	2.69
			3	80			6.55	2.97	6.55	2.97
			3 1/2	90			6.30	2.86	6.30	2.86
	5	125	4	100	4 9/16	116	9.57	4.34	9.57	4.34
	6	150	4	100	4 13/16	124	10.30	4.67	10.30	4.67

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

Malleable Iron Class 150 (Standard)



FIGURE 1134 Hex Locknut	Size		Minimum Dimensions								Unit Weight			
			A		B		C		D		Black		Galv.	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
 For additional sizes larger than 2" (50 DN) see Cast Iron page 53. Not to be used for pressure service.	• 1/8	6	.690	18	.500	13	.190	5	.040	1	0.04	0.02	0.04	0.02
	• 1/4	8	.840	21	.660	17	.250	6	.060	2	0.02	0.01	0.02	0.01
	• 3/8	10	1.000	25	.770	20	.280	7	.060	2	0.04	0.02	0.04	0.02
	• 1/2	15	1.180	30	.970	25	.310	8	.060	2	0.06	0.03	0.06	0.03
	3/4	20	1.430	36	1.230	31	.340	9	.060	2	0.08	0.04	0.08	0.04
	1	25	1.750	44	1.500	38	.380	10	.060	2	0.14	0.06	0.14	0.06
	1 1/4	32	2.100	53	1.860	47	.420	11	.060	2	0.21	0.10	0.21	0.10
	1 1/2	40	2.350	60	2.120	54	.470	12	.060	2	0.24	0.11	0.24	0.11
	2	50	2.880	73	2.630	67	.530	13	.090	2	0.40	0.18	0.40	0.18

FIGURE 1190 Floor Flange (Ductile Iron)	Size		Dia. of Flange		Diameter of Bolt Circle		No. of Holes	Dia. of Holes			Unit Weight			
											Black		Galv.	
	NPS	DN	in	mm	in	mm		in	mm		lbs	kg	lbs	kg
 Structural use only.	1/4	8	2 3/16	56	1 7/8	48	4	1/4	6		0.39	0.18	0.39	0.18
	3/8	10	3	76	2	51	4	1/4	6		0.43	0.20	0.43	0.20
	1/2	15	3 1/2	89	2 1/2	64	4	1/4	6		0.56	0.25	0.56	0.25
	3/4	20	3 1/2	89	2 1/2	64	4	1/4	6		0.60	0.27	0.60	0.27
	1	25	4	102	3	76	4	1/4	6		0.84	0.38	0.84	0.38
	1 1/4	32	4	102	3	76	4	1/4	6		0.90	0.41	0.90	0.41
	1 1/2	40	4 1/2	114	3 1/2	89	4	5/16	8		1.20	0.54	1.20	0.54
	2	50	5 1/2	140	4 1/4	108	4	5/16	8		2.03	0.92	2.03	0.92

FIGURE 1133 Waste Nut	Size		Unit Weight			
			Black		Galv.	
	NPS	DN	lbs	kg	lbs	kg
 Not to be used for pressure service.	1/2	15	0.12	0.05	—	—
	3/4	20	0.15	0.07	0.15	0.07

FIGURE 1138 Extension Piece	Size		A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1/2	15	1 5/8	41	0.19	0.09	0.19	0.09
	3/4	20	1 15/16	49	0.35	0.16	0.35	0.16
	1	25	2 1/16	52	0.48	0.22	0.48	0.22

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

MALLEABLE IRON

Malleable Iron

Class 300 (XS / XH)


FIGURE 1161 90° Elbow Straight	Size		A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1/4	8	1 5/16	24	0.20	0.09	0.20	0.09
	3/8	10	1 1/16	27	0.29	0.13	0.29	0.13
	1/2	15	1 1/4	32	0.47	0.21	0.47	0.21
	3/4	20	1 7/16	37	0.66	0.30	0.66	0.30
	1	25	1 5/8	41	1.15	0.52	1.15	0.52
	1 1/4	32	1 15/16	49	1.88	0.85	1.88	0.85
	1 1/2	40	2 1/8	54	2.47	1.12	2.47	1.12
	2	50	2 1/2	64	3.85	1.75	3.85	1.75
	2 1/2	65	2 15/16	75	5.80	2.63	5.80	2.63
	3	80	3 3/8	86	9.95	4.51	9.95	4.51
	4	100	4 1/2	114	16.00	7.26	16.00	7.26



FIGURE 1161R 90° Reducing Elbow	Size		A		B		Unit Weight			
							Black		Galv.	
	NPS	DN	in	mm	in	mm	lbs	kg	lbs	kg
	3/8 x 1/4	10 x 8	1	25	1	25	0.26	0.12	—	—
	1/2 x 3/8	15 x 10	1 3/16	30	1 3/16	30	0.41	0.19	—	—
	3/4 x 1/2	20 x 15	1 5/16	33	1 3/8	35	0.62	0.28	0.62	0.28
	1 x 1/2	25 x 15	1 7/16	37	1 1/2	38	0.87	0.39	—	—
	1 x 3/4	25 x 20	1 1/2	38	1 9/16	40	1.00	0.45	1.00	.45
	1 1/4 x 3/4	32 x 20	1 5/8	41	1 3/4	44	1.41	0.64	—	—
	1 1/4 x 1	32 x 25	1 3/4	44	1 13/16	47	1.60	0.73	—	—
	1 1/2 x 1	40 x 25	1	25	1 13/16	47	1.89	0.86	—	—
	1 1/2 x 1 1/4	40 x 32	2	51	2 1/16	52	2.15	0.98	—	—
	2 x 1 1/4	50 x 32	2 1/8	54	2 5/16	59	3.12	1.41	3.12	1.41
	2 x 1 1/2	50 x 40	2 1/4	57	2 3/8	60	3.30	1.50	—	—

FIGURE 1160 45° Street Elbow	Size		C		K		Unit Weight	
							Black	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/2	15	1	25	1 3/8	35	0.36	0.16
	3/4	20	1 1/8	29	1 9/16	40	0.54	0.24
	1	25	1 5/16	33	1 13/16	47	0.85	0.39
	1 1/4	32	1 1/2	38	2 1/8	54	1.50	0.68
	1 1/2	40	1 11/16	43	2 5/16	59	2.06	0.93
	2	50	2	51	2 11/16	68	3.34	1.51

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
 All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

Malleable Iron

Class 300 (XS / XH)

Malleable Iron

Cast Iron

Small Steel Fittings

Pipe Nipples & Pipe Couplings

Forged Steel Fittings & Unions

Anvils

Catawissa

J.B. Smith Products

Carton Information


FIGURE 1162 45° Elbow	Size		C		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1/4	8	13/16	22	0.19	0.09	0.19	0.09
	3/8	10	7/8	22	0.28	0.13	0.28	0.13
	1/2	15	1	25	0.43	0.20	0.43	0.20
	3/4	20	1 1/8	29	0.66	0.30	0.66	0.30
	1	25	1 5/16	33	1.00	0.45	1.00	0.45
	1 1/4	32	1 1/2	38	1.67	0.76	1.67	0.76
	1 1/2	40	1 11/16	43	2.15	0.98	2.15	0.98
	2	50	2	51	3.40	1.54	3.40	1.54
	2 1/2	65	2 1/4	57	5.51	2.50	5.51	2.50
	3	80	2 1/2	64	8.10	3.67	8.10	3.67
	4	100	2 13/16	73	13.41	6.08	13.41	6.08



FIGURE 1170 90° Street Elbow	Size		A		J		Unit Weight			
							Black		Galv.	
	NPS	DN	in	mm	in	mm	lbs	kg	lbs	kg
	1/4	8	15/16	24	1 7/16	37	0.17	0.08	0.17	0.08
	3/8	10	1 1/16	27	1 5/8	41	0.26	0.12	0.26	0.12
	1/2	15	1 1/4	32	2	51	0.40	0.18	0.40	0.18
	3/4	20	1 7/16	37	2 3/16	56	0.68	0.31	0.68	0.31
	1	25	1 5/8	41	2 9/16	65	1.04	0.47	1.04	0.47
	1 1/4	32	1 15/16	49	2 7/8	73	1.60	0.73	1.60	0.73
	1 1/2	40	2 1/8	54	3 1/8	79	2.20	1.00	2.20	1.00
	2	50	2 1/2	64	3 11/16	94	3.59	1.63	3.59	1.63
	3	80	3 3/8	86	5 1/8	130	9.55	4.33	—	—

FIGURE 1164 Straight Tee	Size		Center to End A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1/4	8	1 5/16	33	0.27	0.12	0.27	0.12
	3/8	10	1 1/16	27	0.42	0.19	0.42	0.19
	1/2	15	1 1/4	32	0.65	0.29	0.65	0.29
	3/4	20	1 7/16	37	1.07	0.49	1.07	0.49
	1	25	1 5/8	41	1.62	0.73	1.62	0.73
	1 1/4	32	1 15/16	49	2.49	1.13	2.49	1.13
	1 1/2	40	2 1/8	54	3.40	1.54	3.40	1.54
	2	50	2 1/2	64	5.20	2.36	5.20	2.36
	2 1/2	65	2 15/16	75	7.87	3.57	7.87	3.57
	3	80	3 3/8	86	12.46	5.65	12.46	5.65
	4	100	4 1/2	114	24.02	10.89	24.02	10.89

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

MALLEABLE IRON

Malleable Iron

Class 300 (XS / XH)



FIGURE 1164R Reducing Tee		Size						Center to End						Unit Weight				
								A		B		C		Black		Galv.		
		NPS	DN	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	lbs	kg	lbs	kg	
 	3/8	10	3/8	10	1/4	8	1	25	1	25	1	25	0.37	0.17	—	—		
	1/2	15	1/2	15	1/4	8	1 1/16	27	1 1/16	27	1 1/8	29	0.48	0.22	—	—		
					3/8	10	1 3/16	30	1 3/16	30	1 3/16	30	0.61	0.28	—	—		
					3/4	20	1 3/8	35	1 3/8	35	1 5/16	33	0.80	0.36	—	—		
	3/4	20	1/2	15	1 5/16	33	1 1/4	32	1 3/8	35	0.78	0.35	—	—				
					1 7/16	37	1 3/8	35	1 7/16	37	0.93	0.42	—	—				
			3/4	20	1/4	8	1 3/16	30	1 3/16	30	1 1/4	32	0.76	0.34	—	—		
					3/8	10	1 1/4	32	1 1/4	32	1 5/16	33	0.80	0.36	—	—		
					1/2	15	1 5/16	33	1 5/16	33	1 3/8	35	0.90	0.41	0.9	0.41		
	1	25	1/2	15	1	25	1 5/8	41	1 1/2	38	1 5/8	41	1.36	0.62	—	—		
					3/4	20	1 1/2	38	1 7/16	37	1 9/16	40	1.27	0.58	—	—		
			1	25	1	25	1 5/8	41	1 9/16	40	1 5/8	41	1.38	0.63	—	—		
					1/4	8	1 1/4	32	1 1/4	32	1 3/8	35	1.09	0.49	—	—		
					1/2	15	1 7/16	37	1 7/16	37	1 1/2	38	1.26	0.57	1.26	0.57		
					3/4	20	1 1/2	38	1 1/2	38	1 9/16	40	1.33	0.60	1.33	0.60		
	1 1/4	32	1	25	1	25	1 3/4	44	1 5/8	41	1 13/16	47	1.92	0.87	—	—		
					1/2	15	1 1/2	38	1 1/2	38	1 11/16	43	1.70	0.77	1.70	0.77		
			1 1/4	32	3/4	20	1 5/8	41	1 5/8	41	1 3/4	44	1.90	0.86	1.90	0.86		
					1	25	1 3/4	44	1 3/4	44	1 13/16	47	2.10	0.95	2.10	0.95		
					1 1/2	40	1/2	15	1 5/8	41	1 5/8	41	1 13/16	47	2.27	1.03	2.27	1.03
							3/4	20	1 11/16	43	1 11/16	43	1 7/8	48	2.46	1.12	2.46	1.12
	1 1/2	40	1 1/2	40	1	25	1 13/16	47	1 13/16	47	2	51	2.60	1.18	2.60	1.18		
					1 1/4	32	2	51	2	51	2 1/16	52	3.05	1.38	3.05	1.38		
					2	50	1 1/2	40	2 1/2	64	2 3/8	60	2 1/2	64	4.50	2.04	—	—
							1/2	15	1 3/4	44	1 3/4	44	2 1/16	52	3.35	1.52	3.35	1.52
			2	50	3/4	20	1 13/16	47	1 13/16	47	2 1/8	54	3.56	1.61	3.56	1.61		
					1	25	2	51	2	51	2 1/4	57	3.70	1.68	3.70	1.68		
	1 1/4	32			2 1/8	54	2 1/8	54	2 5/16	59	4.22	1.91	4.22	1.91				
	1 1/2	40			2 1/4	57	2 1/4	57	2 3/8	60	4.60	2.09	4.60	2.09				
	2 1/2	65	2 1/2	65	1 1/2	40	2 7/16	62	2 7/16	62	2 5/8	67	6.35	2.88	—	—		
					2	50	2 11/16	68	2 11/16	68	2 3/4	70	7.60	3.45	—	—		
	3	80	3	80	2	50	2 13/16	73	2 13/16	73	3 1/8	79	9.60	4.35	9.60	4.36		

FIGURE 1165 Cross	Size		Center to End A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1/4	8	15/16	24	0.35	0.16	—	—
	3/4	20	1 7/16	37	1.25	0.57	1.25	0.57
	1	25	1 5/8	41	1.90	0.86	—	—
	1 1/4	32	1 15/16	49	3.23	1.46	—	—
	1 1/2	40	2 1/8	54	4.20	1.90	—	—
	2	50	2 1/2	64	6.49	2.94	—	—

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

Malleable Iron

Class 300 (XS / XH)


FIGURE 1166 Coupling	Size		End to End W		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1/4	8	1 3/8	35	0.17	0.08	0.17	0.08
	3/8	10	1 5/8	41	0.26	0.12	0.26	0.12
	1/2	15	1 7/8	48	0.40	0.18	0.40	0.18
	3/4	20	2 1/8	54	0.65	0.29	0.65	0.29
	1	25	2 3/8	60	0.99	0.45	0.99	0.45
	1 1/4	32	2 7/8	73	1.66	0.75	1.66	0.75
	1 1/2	40	2 7/8	73	2.03	0.92	2.03	0.92
	2	50	3 5/8	92	3.24	1.47	3.24	1.47
	2 1/2	65	4 1/8	105	5.45	2.47	5.45	2.47
	3	80	4 1/8	105	7.30	3.31	7.30	3.31

FIGURE 1167 Reducer	Size				End to End M		Unit Weight			
							Black		Galv.	
	NPS	DN	NPS	DN	in	mm	lbs	kg	lbs	kg
	3/8	10	1/4	8	1 7/16	37	0.21	0.10	0.21	0.10
	1/2	15	1/4	8	1 11/16	43	0.31	0.14	0.31	0.14
			3/8	10			0.34	0.15	0.34	0.15
	3/4	20	1/4	8	1 3/4	44	0.46	0.21	—	—
			3/8	10			0.47	0.21	0.47	0.21
			1/2	15			0.50	0.23	0.50	0.23
	1	25	1/4	8	2	51	0.66	0.30	0.66	0.30
			3/8	10			0.71	0.32	0.71	0.32
			1/2	15			0.71	0.32	0.71	0.32
			3/4	20			0.77	0.35	0.77	0.35
	1 1/4	32	1/2	15	2 3/8	60	1.12	0.51	1.12	0.51
			3/4	20			1.16	0.53	1.16	0.53
			1	25			1.27	0.58	1.27	0.58
	1 1/2	40	1/2	15	2 11/16	68	1.51	0.68	1.51	0.68
			3/4	20			1.57	0.71	1.57	0.71
			1	25			1.62	0.73	1.62	0.73
			1 1/4	32			1.78	0.81	1.78	0.81
	2	50	1/2	15	3 3/16	81	2.39	1.08	2.39	1.08
			3/4	20			2.44	1.11	2.44	1.11
			1	25			2.54	1.15	2.54	1.15
			1 1/4	32			2.66	1.21	2.66	1.21
			1 1/2	40			2.72	1.23	2.72	1.23
	2 1/2	65	1 1/2	40	3 11/16	94	4.09	1.85	4.09	1.85
			2	50			4.32	1.96	—	—
	3	80	1 1/2	40	4 1/16	103	5.79	2.63	—	—
			2	50			5.83	2.64	5.83	2.64
			2 1/2	65			6.45	2.93	6.45	2.93
	4	100	2	50	4 3/8	111	9.50	4.31	—	—
			3	80			10.00	4.54	—	—

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

MALLEABLE IRON

Malleable Iron

Class 300 (XS / XH)

FIGURE 1163 Cap	Size		Height L		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1/4	8	25/32	20	0.10	0.05	0.10	0.05
	3/8	10	13/16	22	0.15	0.07	0.15	0.07
	1/2	15	1	25	0.23	0.10	0.23	0.10
	3/4	20	1 1/16	27	0.35	0.16	0.35	0.16
	1	25	1 1/4	32	0.58	0.26	0.58	0.26
	1 1/4	32	1 3/8	35	1.00	0.45	1.00	0.45
	1 1/2	40	1 7/16	37	1.18	0.54	1.18	0.54
	2	50	1 11/16	43	1.94	0.88	1.94	0.88
	2 1/2	65	2 1/16	52	3.32	1.51	3.32	1.51
	3	80	2 3/16	56	4.71	2.14	4.71	2.14

FIGURE 390 Square Countersunk Plugs	Size		Unit Weight			
			Black		Galv.	
	NPS	DN	lbs	kg	lbs	kg
	1/2	15	0.05	0.02	0.05	0.02
	3/4	20	0.11	0.05	0.11	0.05

See page 52 (Cast Iron) for other available sizes.

All Iron Unions

FIGURE J-3300 All Iron Union Class 300	Size		End to End		Unit Weight	
					Black	
	NPS	DN	in	mm	lbs	kg
	1/4	8	1 5/8	41	0.27	0.12
	3/8	10	1 13/16	47	0.37	0.17
	1/2	15	2 1/8	54	0.51	0.23
	3/4	20	2 7/16	62	0.76	0.34
	1	25	2 3/4	70	1.20	0.54
	1 1/4	32	3	76	1.87	0.85
	1 1/2	40	3 3/16	81	2.51	1.14
	2	50	3 1/2	89	4.30	1.95
	2 1/2	65	3 11/16	94	6.02	2.73
	3	80	3 15/16	100	7.96	3.61

Note: See page 17 for pressure-temperature ratings. Galvanized weights may vary. Please contact your Anvil Representative if you need verification.
All Elbows & Tees 3/8" (10 DN) and Larger are 100% Gas Tested at a Minimum of 100 PSI. (6.9 bar)

Malleable Iron Unions

Class 150; 250; 300

BRASS TO IRON								
Unions	Size		End to End		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
FIGURE 463 ■ Class 150 Union 150lb. wsp · 300lb. wog non-shock   (UL Listed Sizes: 1/4" - 2") (FM Approved Sizes: 1/4" - 3") Note: 3/4" x 1/2" size is not UL Listed or FM Approved.	1/8	6	1 5/16	33	0.15	0.07	0.15	0.07
	1/4	8	1 13/16	47	0.48	0.22	0.48	0.22
	3/8	10	1 13/16	47	0.42	0.19	0.42	0.19
	1/2	15	1 15/16	49	0.42	0.19	0.42	0.19
	3/4	20	2 1/16	52	0.60	0.27	0.60	0.27
	3/4 x 1/2	20 x 15	2 1/16	52	0.55	0.25	0.55	0.25
	1	25	2 7/16	62	1.12	0.51	1.12	0.51
	1 1/4	32	2 5/8	67	1.74	0.79	1.74	0.79
	1 1/2	40	2 3/4	70	2.08	0.94	2.08	0.94
	2	50	2 15/16	75	3.00	1.36	3.00	1.36
	2 1/2	65	3 3/8	92	3.60	1.63	3.60	1.63
	3	80	3 3/4	95	4.95	2.24	4.95	2.24
FIGURE 554 ■ Class 250 Union 250 lb. wsp · 500lb. wog non-shock   (UL Listed Sizes: 1/4" - 2") (FM Approved Sizes: 1/4" - 4")	1/8	6	1 5/16	33	0.14	0.06	—	—
	1/4	8	1 13/16	47	0.48	0.22	0.48	0.22
	3/8	10	1 13/16	47	0.42	0.19	0.42	0.19
	1/2	15	2 1/16	52	0.64	0.29	0.64	0.29
	3/4	20	2 1/4	57	1.00	0.45	1.00	0.45
	1	25	2 9/16	65	1.56	0.71	1.56	0.71
	1 1/4	32	2 3/4	70	2.30	1.04	2.30	1.04
	1 1/2	40	3	76	2.74	1.24	2.74	1.24
	2	50	3 3/8	86	4.34	1.97	4.34	1.97
	2 1/2	65	3 7/8	98	5.30	2.40	5.30	2.40
	3	80	4 1/4	108	7.60	3.45	7.60	3.45
	4	100	4 7/8	124	17.50	7.94	17.50	7.94
FIGURE 459 ■ Class 300 Union 300lb. wsp · 600lb. wog non-shock   (UL Listed Sizes: 1/4" - 2") (FM Approved Sizes: 1/4" - 4")	1/8	6	1 5/16	33	0.14	0.06	0.14	0.06
	1/4	8	1 13/16	47	0.48	0.22	0.48	0.22
	3/8	10	1 13/16	47	0.42	0.19	0.42	0.19
	1/2	15	2 1/16	52	0.64	0.29	0.64	0.29
	3/4	20	2 1/4	57	1.00	0.45	1.00	0.45
	1	25	2 9/16	65	1.56	0.71	1.56	0.71
	1 1/4	32	2 3/4	70	2.30	1.04	2.30	1.04
	1 1/2	40	3	76	2.74	1.24	2.74	1.24
	2	50	3 3/8	86	4.34	1.97	4.34	1.97
	2 1/2	65	3 7/8	98	5.05	2.29	5.05	2.29
	3	80	4 1/4	108	7.66	3.47	7.66	3.47
	4	100	4 7/8	124	17.70	8.03	17.70	8.03
FIGURE 551 ■ Class 300 Union male & female 300lb. wsp · 600lb. wog non-shock  	1/2	15	3	76	0.62	0.28	—	—
	3/4	20	3 3/16	81	0.92	0.42	—	—
	1	25	3 5/8	92	1.54	0.70	—	—
	1 1/2	40	4 1/4	108	2.60	1.18	—	—
	2	50	4 5/8	117	4.21	1.91	—	—

■ Pressure & Temperature rates shown on page 17.

- Anvil Malleable Iron Unions conform to ASME B 16.39 and are in compliance with the requirements of the AAR (1994 AAR Manual of standards and Practices).
- Dimensions conform to ASME B 16.39 for Class 150, 250 & 300 Unions.

wsp=working steam pressure

wog=water, oil, gas

Malleable Iron Unions

Class 150; 250; 300



BRASS TO IRON								
FIGURE 552 Class 300 90° Elbow Female Union 300lb. wsp	Size		Center to End				Unit Weight	
			Elbow		Union		Black	
	NPS	DN	in	mm	in	mm	lbs	kg
	$\frac{3}{8}$	10	$1\frac{1}{16}$	27	$2\frac{1}{16}$	52	0.51	0.23
	$\frac{1}{2}$	15	$1\frac{1}{4}$	32	$2\frac{5}{16}$	59	0.79	0.36
	$\frac{3}{4}$	20	$1\frac{7}{16}$	37	$2\frac{3}{4}$	70	1.24	0.56
	1	25	$1\frac{5}{8}$	41	3	76	1.88	0.85

FIGURE 832 Dart Union Bronze to Bronze Seat Union	Size		A		B		C		D		Unit Weight			
											Black		Galv.	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
	$\frac{3}{8}$	10	$1\frac{3}{4}$	44	$1\frac{5}{16}$	24	$1\frac{1}{2}$	38	$1\frac{3}{4}$	44	0.41	0.19	0.43	0.20
	$\frac{1}{2}$	15	$2\frac{1}{8}$	54	$1\frac{1}{8}$	29	$1\frac{3}{16}$	30	2	51	0.58	0.26	0.61	0.28
	$\frac{3}{4}$	20	$2\frac{5}{16}$	59	$1\frac{3}{8}$	35	$2\frac{3}{16}$	56	$2\frac{1}{2}$	64	0.82	0.37	0.86	0.39
	1	25	$2\frac{5}{8}$	67	$1\frac{11}{16}$	43	$2\frac{9}{16}$	65	3	76	1.31	0.59	1.36	0.62
	$1\frac{1}{4}$	32	$2\frac{13}{16}$	73	$2\frac{1}{16}$	52	$3\frac{1}{16}$	78	$3\frac{1}{2}$	89	1.90	0.86	2.00	0.91
	$1\frac{1}{2}$	40	3	76	$2\frac{3}{16}$	56	$3\frac{3}{8}$	86	4	102	2.32	1.05	2.43	1.10
	2	50	$3\frac{5}{8}$	92	$2\frac{7}{8}$	73	$4\frac{1}{16}$	103	$4\frac{5}{8}$	117	4.00	1.81	4.20	1.90

- Meets ASME B16.39 The standard union for most installations
 $\frac{3}{8}$ – 2 NPS (10 – 50 DN) – 300lb (136 kg) steam working pressure at 450°F.
 $\frac{3}{8}$ – 2 NPS (10 – 50 DN) – 600lb (272 kg) cold water, gas, or oil pressure - non-shock.
- Bronze Seat, on both sides of the joint. Resists corrosion.
- True bearing surfaces, unlike ordinary union seats.
- Bodies and nuts are high test air-refined malleable iron - generally superior to mild steel in most services.
- Can be repeatedly installed and removed.
- Straight way through. No cored parts to hold liquid or sediment.
- Extra heavy shoulder on swivel end and in the nut to stand pipe strains, vibration, and wrench abuse.
- Bronze Seat Ball Joint, with extra wide seating surfaces.

Malleable Hex and Face Bushing

FIGURE 383 Hex Bushing	Size					Unit Weight			
						Black		Galv.	
	NPS	DN	Hex	NPS	DN	lbs	kg	lbs	kg
 ● Inside hex See page 50-51 (Cast Iron) for other available sizes.	3/4	10		1/8	6	0.12	0.05	0.12	0.05
				1/4	8	0.14	0.06	0.14	0.06
				3/8	10	0.11	0.05	0.11	0.05
				1/2	15	0.09	0.04	0.09	0.04
	1	25	●	1/8	6	0.24	0.11	0.24	0.11
			●	1/4	8	0.18	0.08	0.18	0.08
			●	3/8	10	0.18	0.08	0.18	0.08
				1/2	15	0.20	0.09	0.20	0.09
				3/4	20	0.16	0.07	0.16	0.07
	1 1/4	32	●	1/4	8	0.33	0.15	0.33	0.15
			●	3/8	10	0.27	0.12	0.27	0.12
			●	1/2	15	0.34	0.15	0.34	0.15
				3/4	20	0.39	0.18	0.39	0.18
				1	25	0.30	0.14	0.30	0.14
	1 1/2	40		1 1/4	32	0.30	0.14	0.30	0.14
	2	50	●	1 1/2	40	0.64	0.29	0.64	0.29
	2 1/2	65		2	50	1.02	0.46	1.02	0.46

FIGURE 385 Face Bushing	Size					Unit Weight			
						Black		Galv.	
	NPS	DN	NPS	DN		lbs	kg	lbs	kg
	3/4	20	3/8	10		0.08	0.04	—	—
			1/2	15		0.06	0.03	0.06	0.03
	1	25	1/2	15		0.16	0.07	0.16	0.07
			3/4	20		0.10	0.05	0.10	0.05
	1 1/4	32	1/2	15		0.30	0.14	—	—
			3/4	20		0.27	0.12	—	—
			1	25		0.19	0.09	0.19	0.09
	1 1/2	40	1/2	15		0.40	0.18	—	—
			3/4	20		0.39	0.18	—	—
			1	25		0.33	0.15	—	—
			1 1/4	32		0.16	0.07	0.16	0.07
	2	50	1	25		0.65	0.29	0.65	0.29
			1 1/4	32		0.53	0.24	0.53	0.24
			1 1/2	40		0.40	0.18	0.40	0.18
	2 1/2	65	1 1/4	32		1.10	0.50	—	—
			1 1/2	40		0.93	0.42	—	—
			2	50		0.40	0.18	0.40	0.18
	3	80	2 1/2	65		0.99	0.45	—	—

Note: Hexagon head or octagon head bushings 2 1/2 NPS (65 DN) and smaller reducing one size may be made of malleable iron, ductile iron or steel. Other sizes may be made of cast iron, ductile iron, malleable iron or steel. Face bushings 2 1/2 NPS (65 DN) and smaller may be made of malleable iron, ductile iron or steel. Face bushings 3NPS (80 DN) and larger reducing two sizes or more may be made of cast or malleable iron, ductile iron, or steel. According to specifications, hex bushings and cored plugs should be used with 150# malleable iron and 125# cast iron. Solid plugs and face bushings are recommended for use with 250# and 300# fittings.



Anvil standard and extra heavy cast iron threaded fittings are manufactured in accordance with ASME-B16.4 (except plugs and bushings, ASME B16.14). Dimensions also conform to Federal Specifications, WW-P-501 (except plugs and bushings WW-P-471).



For Listings/Approval Details and Limitations, visit our website @ www.anvilintl.com or contact an Anvil/AnvilStar Sales Representative.

Cast Iron Threaded Fittings Pressure - Temperature Ratings					
Temperature		Pressure			
		Class 125		Class 250	
(°F)	(°C)	psi	bar	psi	bar
-20° to 150°	-28.9 to 65.6	175	12.1	400	27.6
200°	93.3	165	11.4	370	25.5
250°	121.1	150	10.3	340	23.4
300°	148.9	140	9.7	310	21.4
350°	176.7	125	8.6	300	20.7
400°	204.4	—	—	250	17.2

Cast Iron Threaded Fittings

Class 125 (Standard)



FIGURE 351 90° Elbow	Size		A		B		Unit Weight	
							Black	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/4	8	1/2	13	13/16	22	0.16	0.07
	3/8	10	9/16	14	15/16	24	0.25	0.11
	1/2	15	11/16	17	1 1/8	29	0.40	0.18
	3/4	20	13/16	22	1 15/16	33	0.60	0.27
	1	25	15/16	24	1 1/2	38	0.92	0.42
	1 1/4	32	1 1/8	29	1 3/4	44	1.44	0.65
	1 1/2	40	1 5/16	33	1 15/16	49	1.95	0.88
	2	50	1 9/16	40	2 1/4	57	3.13	1.42
	2 1/2	65	1 13/16	47	2 11/16	68	4.94	2.24
	3	80	2 3/16	56	3 1/8	79	7.21	3.27
	3 1/2	90	2 7/16	62	3 7/16	87	9.67	4.39
	4	100	2 11/16	68	3 13/16	98	12.17	5.52
	5	125	3 5/16	84	4 1/2	114	21.46	9.73
	6	150	3 7/8	98	5 1/8	130	31.33	14.21
	8	200	5 3/16	132	6 9/16	167	64.56	29.28


FIGURE 371 90° Elbow, Flange & Screw	Size		A		B		Unit Weight	
							Black	
	NPS	DN	in	mm	in	mm	lbs	kg
	2 1/2	65	1 13/16	47	2 11/16	68	10.22	4.63
	3	80	2 3/16	56	3 1/8	79	13.25	6.01
	4	100	2 11/16	68	3 13/16	98	21.56	9.78
	6	150	3 7/8	98	5 1/8	130	40.50	18.37
†Nominal Pipe Sizes of 4" (100 DN) and larger have two holes tapped for stud or tap bolts.								

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)

FIGURE 352
90° Elbow, Reducing



Size				A		B		C		D		Unit Weight	
												Black	
NPS	DN	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
1/2	15	1/4	8	5/8	16	3/4	19	1 1/16	27	1 1/16	27	0.40	0.18
		3/8	10	5/8	16	11/16	17	1 1/16	27	1 1/16	27	0.34	0.15
3/4	20	1/2	15	11/16	17	13/16	22	1 1/4	32	1 1/4	32	0.51	0.23
1	25	1/2	15	11/16	17	15/16	24	1 3/8	35	1 3/8	35	0.67	0.30
		3/4	20	13/16	22	15/16	24	1 7/16	37	1 7/16	37	0.76	0.34
1 1/4	32	1/2	15	11/16	17	1 1/16	27	1 1/2	38	1 1/2	38	1.07	0.49
		3/4	20	13/16	22	1 1/8	29	1 5/8	41	1 5/8	41	1.02	0.46
		1	25	15/16	24	1 1/8	29	1 11/16	43	1 11/16	43	1.21	0.55
1 1/2	40	1/2	15	3/4	19	1 1/4	32	1 5/8	41	1 5/8	41	1.53	0.69
		3/4	20	7/8	22	15/16	33	1 13/16	47	1 13/16	47	1.55	0.70
		1	25	1	25	1 1/4	32	1 13/16	47	1 13/16	47	1.44	0.65
		1 1/4	32	1 3/16	30	1 1/4	32	1 7/8	48	1 7/8	48	1.74	0.79
2	50	1/2	15	1 3/16	30	1 7/16	37	1 3/8	35	1 3/8	35	2.22	1.01
		3/4	20	1 5/16	33	1 1/2	38	2	51	2	51	2.20	1.00
		1	25	1 1/16	27	1 7/16	37	2	51	2	51	2.08	0.94
		1 1/4	32	1 3/16	30	1 7/16	37	2 1/16	52	2 1/16	52	2.33	1.06
		1 1/2	40	1 5/16	33	1 1/2	38	2 1/8	54	2 1/8	54	2.59	1.17
2 1/2	65	1	25	1	25	1 3/4	44	2 5/16	59	2 5/16	59	2.93	1.33
		1 1/4	32	1 3/16	30	1 3/4	44	2 3/8	60	2 3/8	60	3.41	1.55
		1 1/2	40	1 5/16	33	1 13/16	47	2 7/16	62	2 7/16	62	3.68	1.67
		2	50	1 9/16	40	1 7/8	48	2 9/16	65	2 9/16	65	4.01	1.82
3	80	1 1/4	32	1 5/8	41	2 5/16	59	2 15/16	75	2 15/16	75	5.98	2.71
		1 1/2	40	1 5/8	41	2 5/16	59	2 15/16	75	2 15/16	75	5.65	2.56
		2	50	1 5/8	41	2 1/4	57	2 15/16	75	2 15/16	75	5.25	2.38
		2 1/2	65	1 7/8	48	2 3/16	56	3 1/16	78	3 1/16	78	6.44	2.92
4	100	2	50	2 3/16	56	2 15/16	75	3 5/8	92	3 5/8	92	11.89	5.39
		2 1/2	65	2 3/16	56	2 3/4	70	3 5/8	92	3 5/8	92	11.27	5.11
		3	80	2 3/16	56	2 11/16	68	3 5/8	92	3 5/8	92	10.63	4.82
5	125	4	100	2 13/16	73	3 5/16	84	4 3/8	111	4 3/8	111	16.47	7.47
6	150	3	80	2 5/16	59	3 13/16	98	4 13/16	124	4 13/16	124	19.43	8.81
		4	100	2 13/16	73	3 7/8	98	4 15/16	125	4 15/16	125	23.53	10.67
		5	125	3 3/8	86	3 13/16	98	5	127	5	127	26.66	12.09

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)



FIGURE 358 Tee	Size		A		B		Unit Weight	
							Black	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/4	8	1/2	13	13/16	22	0.22	0.10
	3/8	10	5/8	16	1	25	0.35	0.16
	1/2	15	11/16	17	1 1/8	29	0.56	0.25
	3/4	20	13/16	22	1 5/16	33	0.84	0.38
	1	25	1 5/16	24	1 1/2	38	1.25	0.57
	1 1/4	32	1 7/8	29	1 3/4	44	2.03	0.92
	1 1/2	40	1 5/16	33	1 15/16	49	2.70	1.22
	2	50	1 9/16	40	2 1/4	57	4.23	1.92
	2 1/2	65	1 13/16	47	2 11/16	68	6.67	3.02
	3	80	2 3/16	56	3 1/8	79	10.00	4.54
	3 1/2	90	2 7/16	62	3 7/16	87	13.29	6.03
	4	100	2 11/16	68	3 3/4	95	16.33	7.41
	5	125	3 5/16	84	4 1/2	114	27.33	12.39
	6	150	3 7/8	98	5 1/8	130	40.85	18.53
	8	200	5 3/16	132	6 9/16	167	79.00	35.83

FIGURE 359 Tee Reducing																			
Size						A		B		C		D		E		F		Unit Weight	
																		Black	
NPS	DN	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
1/2	15	1/2	15	1/4	8	1 1/16	17	1 1/16	17	1 3/16	22	1 1/8	29	1 1/8	29	1 1/8	29	0.57	0.26
				3/8	10	1 1/16	17	1 1/16	17	3/4	19	1 1/8	29	1 1/8	29	0.57	0.26		
				3/4	20	1 3/16	22	1 3/16	22	1 1/4	32	1 1/4	32	1 3/16	22	0.68	0.31		
				1	25	1	25	1 3/16	22	1 7/16	37	1 7/16	37	1 3/8	35	1.00	0.45		
3/4	20	1/2	15	3/4	20	1 3/16	22	1 5/16	24	1 3/16	22	1 5/16	24	1 1/4	32	1 5/16	24	0.79	0.36
				1/2	15	1 1/16	17	1 1/16	17	1 3/16	22	1 3/16	22	1 1/8	29	1 1/4	32	0.64	0.29
				3/4	20	1 3/16	22	1 3/16	22	1 3/16	22	1 5/16	24	1 1/4	32	1 5/16	24	0.75	0.34
				3/4	20	1 3/16	22	1 3/16	22	1 3/16	22	1 3/16	22	1 3/16	22	1 1/4	32	0.62	0.28
		3/8	10	1 1/16	17	1 1/16	17	1 5/16	24	1 3/16	22	1 3/16	22	1 1/4	32	0.75	0.34		
		1/2	15	1 1/16	17	1 1/16	17	1 3/16	22	1 3/16	22	1 3/16	22	1 1/4	32	0.76	0.34		
		1	25	1 5/16	24	1 5/16	24	1 3/16	22	1 7/16	37	1 7/16	37	1 3/8	35	0.99	0.45		
		1/4	8	1	25	1 5/16	24	1 5/16	24	1 5/16	24	1 1/2	38	1 1/4	32	1 1/2	38	1.08	0.49
1	25	1/2	15	1/2	15	1 1/16	17	3/4	19	1 5/16	24	1 1/4	32	1 3/16	22	1 3/8	35	0.90	0.41
				3/4	20	1 3/16	22	1 3/16	22	1 5/16	24	1 3/8	35	1 1/4	32	1 7/16	37	0.91	0.41
				1	25	1 5/16	24	1 5/16	24	1 5/16	24	1 1/2	38	1 3/8	35	1 1/2	38	1.08	0.49
				3/4	20	1 3/16	22	1 3/16	22	1 5/16	24	1 3/8	35	1 5/16	24	1 7/16	37	0.89	0.40
		3/4	20	1 3/16	22	1 3/16	22	1 3/16	22	1 5/16	24	1 3/8	35	1 5/16	24	1 7/16	37	1.00	0.45
		1	25	1 5/16	24	1 5/16	24	1 5/16	24	1 1/2	38	1 7/16	37	1 1/2	38	1.13	0.51		
		1	25	1/4	8	1 1/16	17	1 1/16	17	1 1/8	29	1 1/8	29	1 1/4	32	1 3/8	35	1.01	0.46
				1/2	15	1 1/16	17	1 1/16	17	1 5/16	24	1 1/4	32	1 1/4	32	1 3/8	35	1.01	0.46
				3/4	20	1 3/16	22	1 3/16	22	1 5/16	24	1 3/8	35	1 3/8	35	1 7/16	37	1.11	0.50
				1 1/4	32	1 1/8	29	1 1/8	29	1 5/16	24	1 11/16	43	1 11/16	43	1 9/16	40	1.49	0.68
				1 1/2	40	1 1/4	32	1 1/4	32	1	25	1 13/16	47	1 13/16	47	1 5/8	41	1.84	0.83
				2	50	1 7/16	37	1 7/16	37	1	25	2	50	2	50	1 3/4	44	2.70	1.22


Note: See page 37 for pressure-temperature ratings.

Continued on next page.

Cast Iron Threaded Fittings

Class 125 (Standard)

FIGURE 359
Tee Reducing




Size						A		B		C		D		E		F		Unit Weight	
																		Black	
NPS	DN	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
1 1/4	32	1/2	15	1 1/2	15	1 3/16	22	1 3/16	22	1 1/8	29	1 7/16	37	1 5/16	24	1 5/8	41	1.00	0.45
				1	25	1 5/16	24	1 5/16	24	1 1/8	29	1 9/16	40	1 3/8	35	1 11/16	43	1.38	0.63
				1 1/4	32	1 1/8	29	1 1/8	29	1 1/8	29	1 3/4	44	1 9/16	40	1 3/4	44	1.64	0.74
		3/4	20	3/4	20	1 3/16	22	1 3/16	22	1 1/8	29	1 7/16	37	1 5/16	24	1 5/8	41	1.27	0.58
				1	25	1 5/16	24	1 5/16	24	1 1/8	29	1 9/16	40	1 7/16	37	1 11/16	43	1.43	0.65
				1 1/4	32	1 1/8	29	1 1/8	29	1 1/8	29	1 3/4	44	1 5/8	41	1 3/4	44	1.73	0.78
	32	1	25	1 1/2	15	1 1/16	17	1 1/16	17	1 1/8	29	1 5/16	24	1 1/4	32	1 9/16	40	1.27	0.58
				3/4	20	1 3/16	22	1 3/16	22	1 1/8	29	1 7/16	37	1 3/8	35	1 5/8	41	1.36	0.62
				1	25	1 5/16	24	1 5/16	24	1 1/8	29	1 9/16	40	1 9/16	40	1 11/16	43	1.53	0.69
				1 1/4	32	1 1/8	29	1 1/8	29	1 1/8	29	1 3/4	44	1 11/16	43	1 3/4	44	1.79	0.81
				1 1/2	40	1 1/4	32	1 1/4	32	1 3/16	22	1 7/8	48	1 13/16	47	1 13/16	47	2.07	0.94
				2	50	1 7/16	37	1 7/16	37	1 3/16	22	2 1/16	52	2	50	1 7/8	48	2.66	1.21
		1 1/4	32	1 1/2	15	1 1/16	17	1 1/16	17	1 1/8	29	1 5/16	24	1 5/16	24	1 9/16	40	1.47	0.67
				3/4	20	1 3/16	22	1 3/16	22	1 1/8	29	1 7/16	37	1 7/16	37	1 5/8	41	1.57	0.71
	40	1/2	15	1 1/4	32	1 3/16	22	1 1/8	29	1 1/4	32	1 13/16	47	1 9/16	40	1 7/8	48	1.93	0.88
				1 1/2	40	1 5/16	24	1 1/4	32	1 5/16	24	1 15/16	49	1 11/16	43	1 15/16	49	2.14	0.97
		3/4	20	1 1/2	40	1 5/16	24	1 1/4	32	1 5/16	24	1 15/16	49	1 3/4	44	1 15/16	49	2.18	0.99
				1 1/2	40	1 5/16	24	1 1/4	32	1 5/16	24	1 15/16	49	1 3/4	44	1 15/16	49	2.18	0.99
		1	25	1 1/2	15	1 3/16	22	3/4	19	1 1/4	32	1 7/16	37	1 5/16	24	1 11/16	43	1.75	0.79
				3/4	20	7/8	22	1 3/16	22	1 1/4	32	1 1/2	38	1 3/8	35	1 3/4	44	1.70	0.77
				1	25	1	25	1 5/16	24	1 1/4	32	1 5/8	41	1 1/2	38	1 13/16	47	1.72	0.78
				1 1/4	32	1 3/16	22	1 1/8	29	1 1/4	32	1 13/16	47	1 11/16	43	1 7/8	48	2.08	0.94
				1 1/2	40	1 5/16	24	1 1/4	32	1 5/16	24	1 15/16	49	1 13/16	47	1 15/16	49	2.29	1.04
				2	50	1 1/2	38	1 7/16	37	1 5/16	24	2 1/8	54	2	50	2	51	2.91	1.32
	40	1 1/4	32	1 1/2	15	1 3/16	22	1 1/16	17	1 1/4	32	1 7/16	37	1 5/16	24	1 11/16	43	1.67	0.76
				3/4	20	7/8	22	1 3/16	22	1 1/4	32	1 1/2	38	1 7/16	37	1 3/4	44	1.79	0.81
				1	25	1	25	1 5/16	24	1 1/4	32	1 5/8	41	1 9/16	40	1 13/16	47	1.97	0.89
				1 1/4	32	1 3/16	22	1 1/8	29	1 1/4	32	1 13/16	47	1 3/4	44	1 7/8	48	2.28	1.03
				1 1/2	40	1 5/16	24	1 1/4	32	1 5/16	24	1 15/16	49	1 7/8	48	1 15/16	49	2.50	1.13
				2	50	1 1/2	38	1 7/16	37	1 5/16	24	2 1/8	54	2 1/16	52	2	51	3.07	1.39
		1 1/2	40	1 1/2	15	1 3/16	22	1 3/16	22	1 1/4	32	1 7/16	37	1 7/16	37	1 11/16	43	1.84	0.83
				3/4	20	7/8	22	7/8	22	1 1/4	32	1 1/2	38	1 1/2	38	1 3/4	44	1.95	0.88
				1	25	1	25	1	25	1 1/4	32	1 5/8	41	1 5/8	41	1 13/16	47	2.13	0.97
				1 1/4	32	1 3/16	22	1 3/16	22	1 1/4	32	1 13/16	47	1 13/16	47	1 7/8	48	2.44	1.11
	40	2	50	1 1/2	40	1 1/2	38	1 1/2	38	1 5/16	24	2 1/8	54	2 1/8	54	2	51	3.23	1.46
				2 1/2	65	1 13/16	47	1 13/16	47	1 5/16	24	2 7/16	62	2 7/16	62	2 3/16	56	4.15	1.88

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)

FIGURE 359
Tee Reducing



Size					A		B		C		D		E		F		Unit Weight		
																	Black		
NPS	DN	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
2	50	1/2	15	1 1/2	40	15/16	24	1 3/8	35	1 1/2	38	2	51	1 13/16	47	2 1/8	54	2.95	1.34
				2	50	1 9/16	40	1 7/16	37	1 9/16	40	2 1/4	57	1 7/8	48	2 1/4	57	3.30	1.50
		3/4	20	1 1/4	32	13/16	22	1 1/8	29	1 7/16	37	1 7/8	48	1 3/4	44	2 1/16	52	2.50	1.13
				1 1/2	40	15/16	24	1 5/16	24	1 1/2	38	2	51	1 13/16	47	2 1/8	54	3.40	1.54
				2	50	1 9/16	40	1 7/16	37	1 9/16	40	2 1/4	57	1 15/16	49	2 1/4	57	3.31	1.50
		1	25	1	25	11/16	17	11/16	17	1 7/16	37	1 3/4	44	1 5/8	41	2	51	2.70	1.22
				1 1/4	32	13/16	22	1 1/8	29	1 1/2	38	1 7/8	48	1 3/4	44	2 1/16	52	2.94	1.33
				1 1/2	40	15/16	24	1 1/4	32	1 1/2	38	2	51	1 13/16	47	2 1/8	54	2.85	1.29
				2	50	1 9/16	40	1 7/16	37	1 9/16	40	2 1/4	57	2	51	2 1/4	57	3.46	1.57
				2 1/2	65	1 7/8	48	1 13/16	47	1 9/16	40	2 9/16	65	2 3/8	60	2 7/16	62	4.88	2.21
		1 1/4	32	1/2	15	11/16	17	1	25	1 7/16	37	1 3/4	44	1 5/8	41	2	51	2.48	1.12
				3/4	20	7/8	22	7/8	22	1 7/16	37	1 9/16	40	1 1/2	38	1 15/16	49	2.50	1.13
				1	25	11/16	17	1	25	1 7/16	37	1 3/4	44	1 5/8	41	2	51	2.73	1.24
				1 1/4	32	13/16	22	1 1/8	29	1 7/16	37	1 7/8	48	1 3/4	44	2 1/16	52	2.90	1.32
				1 1/2	40	15/16	24	1 1/4	32	1 1/2	38	2	51	1 7/8	48	2 1/8	54	3.13	1.42
				2	50	1 9/16	40	1 7/16	37	1 9/16	40	2 1/4	57	2 1/16	52	2 1/4	57	3.71	1.68
				2 1/2	65	1 7/8	48	1 3/4	44	1 9/16	40	2 9/16	65	2 3/8	60	2 7/16	62	4.54	2.06
		1 1/2	40	1/2	15	13/16	22	13/16	22	1 7/16	37	1 1/2	38	1 7/16	37	1 7/8	48	2.34	1.06
				3/4	20	7/8	22	7/8	22	1 7/16	37	1 9/16	40	1 1/2	38	1 15/16	49	2.46	1.12
				1	25	11/16	17	1	25	1 7/16	37	1 3/4	44	1 5/8	41	2	51	2.66	1.21
	1 1/4			32	13/16	22	13/16	22	1 7/16	37	1 7/8	48	1 13/16	47	2 1/16	52	2.98	1.35	
	1 1/2			40	15/16	24	15/16	24	1 1/2	38	2	51	1 15/16	49	2 1/8	54	3.24	1.47	
	2			50	1 9/16	40	1 1/2	38	1 9/16	40	2 1/4	57	2 1/8	54	2 1/4	57	3.70	1.68	
	2 1/2			65	1 7/8	48	1 15/16	49	1 9/16	40	2 9/16	65	2 9/16	65	2 7/16	62	5.46	2.48	
	2	50	1/2	15	13/16	22	13/16	22	1 7/16	37	1 1/2	38	1 1/2	38	1 7/8	48	2.74	1.24	
			3/4	20	7/8	22	7/8	22	1 7/16	37	1 9/16	40	1 9/16	40	1 15/16	49	2.86	1.30	
			1	25	11/16	17	11/16	17	1 7/16	37	1 3/4	44	1 3/4	44	2	51	3.05	1.38	
1 1/4			32	13/16	22	13/16	22	1 7/16	37	1 7/8	48	1 7/8	48	2 1/16	52	3.38	1.53		
1 1/2			40	15/16	24	15/16	24	1 1/2	38	2	51	2	51	2 1/8	54	3.59	1.63		
2 1/2			65	1 7/8	48	1 7/8	48	1 9/16	40	2 9/16	65	2 9/16	65	2 7/16	62	5.17	2.34		
3			100	3	76	3	76	2 7/16	62	3 11/16	94	3 11/16	94	3 1/2	89	7.87	3.57		


Continued on next page.

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)

FIGURE 359
Tee Reducing




Size				A		B		C		D		E		F		Unit Weight			
																Black			
NPS	DN	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
2 1/2	65	1/2	15	2 1/2	65	1 13/16	47	1 13/16	47	1 13/16	47	2 11/16	68	2 1/4	57	2 11/16	68	5.20	2.36
		3/4	20	2 1/2	65	1 13/16	47	1 3/4	44	1 13/16	47	2 11/16	68	2 1/4	57	2 11/16	68	5.10	2.31
		1	25	2	50	1 9/16	40	1 9/16	40	1 7/8	48	2 7/16	62	2 1/8	54	2 9/16	65	5.03	2.28
				2 1/2	65	1 13/16	47	1 3/4	44	1 13/16	47	2 11/16	68	2 5/16	59	2 11/16	68	5.36	2.43
		1 1/4	32	2	50	1 9/16	40	1 1/2	38	1 7/8	48	2 7/16	62	2 1/8	54	2 9/16	65	4.96	2.25
				2 1/2	65	1 13/16	47	1 3/4	44	1 13/16	47	2 11/16	68	2 3/8	60	2 11/16	68	5.40	2.45
		1 1/2	40	1 1/2	40	1 5/16	24	1 5/16	22	1 13/16	47	2 3/16	56	1 15/16	49	2 7/16	62	4.23	1.92
				2	50	1 9/16	40	1 1/2	38	1 7/8	48	2 7/16	62	2 1/8	54	2 9/16	65	4.85	2.20
				2 1/2	65	1 13/16	47	1 13/16	47	1 13/16	47	2 11/16	68	2 7/16	62	2 11/16	68	4.85	2.20
		2	50	1/2	15	3/4	19	13/16	22	1 3/4	44	1 11/16	43	1 1/2	38	2 3/16	56	5.82	2.64
				3/4	20	7/8	22	7/8	22	1 3/4	44	1 3/4	44	1 9/16	40	2 1/4	57	3.62	1.64
				1	25	1	25	11/16	17	1 3/4	44	1 15/16	49	1 3/4	44	2 5/16	59	3.92	1.78
				1 1/4	32	13/16	22	13/16	22	1 3/4	44	2 1/16	52	1 7/8	48	2 3/8	60	4.26	1.93
				1 1/2	40	15/16	24	15/16	24	1 13/16	47	2 3/16	56	2	51	2 7/16	62	4.42	2.00
				2	50	1 9/16	40	1 9/16	40	1 7/8	48	2 7/16	62	2 1/4	57	2 9/16	65	5.17	2.34
				2 1/2	65	1 13/16	47	1 7/8	48	1 13/16	47	2 11/16	68	2 9/16	65	2 11/16	68	6.00	2.72
				3	80	2 1/16	52	2 1/8	54	1 7/8	48	3	80	2 7/8	73	2 13/16	73	7.35	3.33
		2 1/2	65	1/2	15	3/4	19	3/4	19	1 3/4	44	1 11/16	43	1 11/16	43	2 3/16	56	4.00	1.81
				3/4	20	7/8	22	7/8	22	1 3/4	44	1 3/4	44	1 3/4	44	2 1/4	57	4.29	1.95
				1	25	1	25	1	25	1 3/4	44	1 15/16	49	1 5/8	49	2 5/16	59	4.48	2.03
				1 1/4	32	13/16	22	13/16	22	1 3/4	44	2 1/16	52	2 1/16	52	2 3/8	60	4.83	2.19
				1 1/2	40	15/16	24	15/16	24	1 13/16	47	2 3/16	56	2 3/16	56	2 7/16	62	5.14	2.33
				2	50	1 9/16	40	1 9/16	40	1 7/8	48	2 7/16	62	2 7/16	62	2 9/16	65	5.88	2.67
				3	80	2 1/16	52	2 1/16	52	1 7/8	48	3	80	3	80	2 13/16	73	8.09	3.67
				4	100	2 3/4	70	2 13/16	73	2 7/16	62	3 11/16	94	3 11/16	94	3 1/2	89	14.03	6.36
3	80	3/4	20	3	80	2 1/8	54	2 1/8	54	2 1/8	54	3 1/8	79	2 11/16	68	3 1/8	79	8.25	3.74
		1	25	3	80	2 1/8	54	2 1/8	54	2 1/8	54	3 1/8	79	2 11/16	68	3 1/8	79	8.30	3.76
		1 1/4	32	3	80	2 1/8	54	2 1/8	54	2 1/8	54	3 1/8	79	2 13/16	73	3 1/8	79	8.46	3.84
		1 1/2	40	3	80	2 1/8	54	2 3/16	56	2 1/8	54	3 1/8	79	2 13/16	73	3 1/8	79	8.13	3.69
		2	50	1 1/2	40	1 3/8	35	1 1/2	38	2 3/16	56	2 5/16	59	2 3/16	56	2 13/16	73	6.83	3.10
				2	50	1 9/16	40	1 9/16	40	2 3/16	56	2 9/16	65	2 1/4	57	2 5/16	75	7.29	3.31
				2 1/2	65	1 7/8	48	1 15/16	49	2 1/8	54	2 13/16	73	2 9/16	65	3 1/16	78	7.10	3.22
				3	80	2 1/8	54	2 3/16	56	2 1/8	54	3 1/8	79	2 15/16	75	3 1/8	79	8.79	3.99
		2 1/2	65	1	25	1	25	15/16	24	2 1/8	54	2 1/16	52	1 15/16	49	2 11/16	68	5.51	2.50
				1 1/4	32	1 1/4	32	13/16	22	2 1/8	54	2 3/16	56	2 1/16	52	2 3/4	70	5.92	2.68
				1 1/2	40	1 3/8	35	15/16	24	2 3/16	56	2 5/16	59	2 3/16	56	2 13/16	73	6.23	2.83
				2	50	1 9/16	40	1 1/2	38	2 3/16	56	2 9/16	65	2 7/16	62	2 15/16	75	6.81	3.09
				2 1/2	65	1 7/8	48	1 13/16	47	2 1/8	54	2 13/16	73	2 11/16	68	3 1/16	78	7.66	3.47
		3	80	3	80	2 1/8	54	2 1/8	54	2 1/8	54	3 1/8	79	3 1/8	78	3 1/8	79	9.13	4.14
				1/2	15	15/16	24	15/16	24	2 3/16	56	1 7/8	48	1 7/8	48	2 5/8	67	6.08	2.76
				3/4	20	15/16	24	15/16	24	2 1/8	54	1 7/8	48	1 7/8	48	2 5/8	67	6.06	2.75
				1	25	1	25	1	25	2 1/8	54	2 1/16	52	2 1/16	52	2 11/16	68	6.27	2.84
				1 1/4	32	1 1/4	32	1 1/4	32	2 1/8	54	2 3/16	56	2 3/16	56	2 3/4	70	6.75	3.06
				1 1/2	40	1 3/8	35	1 3/8	35	2 3/16	56	2 5/16	59	2 5/16	59	2 15/16	75	7.10	3.22
				2	50	1 9/16	40	1 9/16	40	2 3/16	56	2 9/16	65	2 9/16	65	2 7/8	73	7.75	3.51
				2 1/2	65	1 7/8	48	1 7/8	48	2 1/8	54	2 13/16	73	2 13/16	73	3 1/16	78	8.92	4.05
		4	100	2 11/16	68	2 11/16	68	2 7/16	62	3 11/16	94	3 11/16	94	3 1/2	89	12.80	5.80		

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)

FIGURE 359
Tee Reducing



Size						A		B		C		D		E		F		Unit Weight	
																		Black	
NPS	DN	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
3 1/2	90	3 1/2	90	1 1/2	40	1 3/8	35	1 3/8	35	2 7/16	62	2 3/8	60	2 3/8	60	3 1/16	78	8.87	4.02
				2	50	1 5/8	41	1 5/8	41	2 7/16	62	2 5/8	67	2 5/8	67	3 3/16	81	9.94	4.51
4	100	1	25	4	100	2 3/4	70	2 15/16	75	2 3/4	70	3 3/4	95	3 1/2	89	3 3/4	95	13.52	6.13
				1 1/2	40	2 3/4	70	2 7/8	73	2 3/4	70	3 3/4	95	3 1/2	89	3 3/4	95	13.47	6.11
		2	50	2	50	1 11/16	43	1 7/8	48	2 3/4	70	2 11/16	68	2 9/16	65	3 1/2	89	11.34	5.14
				4	100	2 3/4	70	2 3/4	70	2 3/4	70	3 3/4	95	3 1/2	89	3 3/4	95	13.89	6.30
		2 1/2	65	2 1/2	65	1 7/8	48	1 13/16	47	2 5/8	67	2 15/16	75	2 13/16	73	3 9/16	90	11.78	5.34
				4	100	2 3/4	70	2 3/4	70	2 3/4	70	3 3/4	95	3 5/8	92	3 3/4	95	15.75	7.14
		3	80	2	50	1 11/16	43	1 9/16	40	2 3/4	70	2 11/16	68	2 9/16	65	3 1/2	89	10.21	4.63
				2 1/2	65	1 7/8	48	1 7/8	48	2 5/8	67	2 15/16	75	2 13/16	73	3 9/16	90	11.25	5.10
				3	80	2 1/4	57	2 1/8	54	2 11/16	68	3 1/4	83	3 1/8	79	3 5/8	92	12.50	5.67
				4	100	2 3/4	70	2 11/16	68	2 3/4	70	3 3/4	95	3 5/8	92	3 3/4	95	15.04	6.82
		4	100	1	25	1 3/16	22	1 3/16	22	2 3/4	70	2 5/16	59	2 5/16	59	3 5/16	84	10.40	4.72
				1 1/4	32	1 5/16	24	1 5/16	24	2 5/8	67	2 5/16	59	2 5/16	59	3 5/16	84	10.38	4.71
				1 1/2	40	1 7/16	37	1 7/16	37	2 11/16	68	2 7/16	62	2 7/16	62	3 5/16	84	10.75	4.88
				2	50	1 11/16	43	1 11/16	43	2 3/4	70	2 11/16	68	2 11/16	68	3 1/2	89	11.63	5.27
				2 1/2	65	2	51	2	51	2 5/8	67	2 15/16	75	2 15/16	75	3 9/16	90	12.85	5.83
				3	80	2 1/4	57	2 1/4	57	2 11/16	68	3 1/4	83	3 1/4	83	3 5/8	92	14.12	6.40
				5	125	3 3/8	86	3 3/8	86	2 13/16	73	4 3/8	111	4 3/8	111	4	102	20.88	9.47
				6	150	3 7/8	98	3 7/8	98	2 7/8	73	4 15/16	125	4 15/16	125	4 1/16	103	26.36	11.95
5	125	5	125	2	50	1 3/4	44	1 3/4	44	3 7/16	87	2 15/16	75	2 15/16	75	4 1/8	105	17.43	7.90
				3	80	2 5/16	59	2 5/16	59	3 1/4	83	3 1/2	89	3 1/2	89	4 1/4	108	20.00	9.07
				4	100	2 13/16	71	2 13/16	71	3 3/8	86	4	102	4	102	4 3/8	111	23.83	10.81
6	150	6	150	4	100	2 7/8	73	2 13/16	71	3 7/8	98	4 1/16	103	4	102	4 15/16	125	30.00	13.61
				2 1/2	65	2	51	2	51	3 13/16	97	3 1/4	83	3 1/4	83	4 3/4	121	25.67	11.64
				3	80	2 3/8	60	2 3/8	60	3 13/16	97	3 9/16	90	3 9/16	90	4 13/16	122	27.46	12.45
				4	100	2 7/8	73	2 7/8	73	3 7/8	98	4 1/16	103	4 1/16	103	4 15/16	125	32.44	14.71
				5	125	3 3/8	86	3 3/8	86	3 13/16	97	4 5/8	117	4 5/8	117	5	127	37.00	16.78

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)



FIGURE 360 Cross		Size		A		B		Unit Weight	
								Black	
		NPS	DN	in	mm	in	mm	lbs	kg
		1/2	15	13/16	22	9/16	14	2.80	1.27
		3/4	20	15/16	33	13/16	22	1.03	0.47
		1	25	1 1/2	38	15/16	24	1.59	0.72
		1 1/4	32	1 3/4	44	1 1/8	29	2.42	1.10
		1 1/2	40	1 15/16	49	1 5/16	33	3.21	1.46
		2	50	2 1/4	57	1 9/16	40	5.28	2.39
		2 1/2	65	2 11/16	68	1 13/16	47	8.07	3.66
		3	80	3 3/8	79	2 3/16	56	11.84	5.37
		4	100	3 13/16	98	2 3/4	70	19.63	8.90
		6	150	5 1/8	130	3 7/8	98	47.67	21.62

FIGURE 361 Cross Reducing								2 NPS 3 NPS — 2½ NPS 1¼ NPS				50 DN 80 DN — 65 DN 32 DN											
								Read as: 3 x 2½ x 2 x 1¼				Read as: 80 x 65 x 50 x 32											
Size								A		B		C		D		E, F		G, H		Unit Weight			
NPS	DN	NPS	DN	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg		
1	25	1	25	¾	20	¾	20	13/16	22	13/16	22	15/16	24	15/16	24	1⅜	35	17/16	37	1.30	0.59		
1¼	32	1¼	32	1	25	1	25	15/16	24	15/16	24	1⅛	29	1⅛	29	19/16	40	111/16	43	2.04	0.93		
1½	40	1	25	1	25	1	25	1	25	1⅛	29	1¼	32	1¼	32	1⅝	41	113/16	47	2.74	1.24		
		1¼	32	1	25	1	25	1	25	1	25	1¼	32	1¼	32	1⅝	41	113/16	47	2.67	1.21		
		1½	40	1	25	1	25	1	25	1	25	1¼	32	1¼	32	1⅝	41	113/16	47	2.51	1.14		
				1¼	32	1	25	1	25	1⅛	29	1⅛	29	13/16	22	15/16	24	113/16	47	1⅞	48	3.90	1.77
2	50	1½	40	1	25	1	25	1⅛	29	1⅛	29	13/8	35	13/8	35	113/16	47	1⅞	48	3.95	1.79		
				1¼	32	1⅛	29	1⅛	29	13/8	35	13/8	35	113/16	47	1⅞	48	21/8	54	4.25	1.93		
				1¼	32	13/16	22	13/16	22	1½	38	1½	38	1⅞	48	21/16	52	4.18	1.90				
				1	25	1	25	11/16	17	11/16	17	17/16	37	17/16	37	1¾	44	2	51	3.57	1.62		
		2	50	1¼	32	1¼	32	1⅛	29	1⅛	29	17/16	37	17/16	37	1⅞	48	21/8	54	4.00	1.81		
				1½	40	1½	40	1¼	32	1¼	32	17/16	37	17/16	37	2	51	21/8	54	4.08	1.85		
2½	65	2	50	1	25	1	25	1	25	11/16	17	113/16	47	113/16	47	115/16	49	25/16	59	5.11	2.32		
				1½	40	1½	40	1¼	32	15/16	24	17/8	48	17/8	48	23/16	56	27/16	62	6.13	2.78		
				2	50	2	50	1½	38	1¾	44	17/8	48	17/8	48	27/16	62	29/16	65	7.23	3.28		
		2½	65	1¼	32	1	25	13/16	22	13/16	22	1¾	44	113/16	47	113/16	47	27/16	52	23/8	60	5.39	2.44
				1¼	32	1⅛	29	1⅛	29	113/16	47	113/16	47	113/16	47	27/16	52	23/8	60	5.26	2.39		
				1½	40	1½	40	1¼	32	1¼	32	17/8	48	17/8	48	23/16	56	27/16	62	5.68	2.58		
3	80	3	80	2	50	2	50	19/16	40	19/16	40	115/16	49	27/16	62	29/16	65	6.82	3.09				
				1½	40	1½	40	13/8	35	13/8	35	23/16	56	23/16	56	25/16	59	213/16	73	7.91	3.59		
4	100	4	100	2	50	2	50	15/8	41	15/8	41	23/16	56	23/16	56	29/16	65	215/16	75	8.85	4.01		
				2	50	2	50	2	50	211/16	68	211/16	68	2¾	70	37/16	87	12.00	5.44				

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)


FIGURE 366 Screwed Hex Coupling	Size		Across Flats A		B		C		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg
	1	25	1 ¹⁵ / ₁₆	49	1 ¹¹ / ₁₆	43	9/ ₁₆	14	0.82	0.37


FIGURE 487 Flanged Union Gasket Type	Size		Diam. of Flanges		No. of Bolts	Unit Weight			
	NPS	DN	in	mm		Black		Galv.	
						lbs	kg	lbs	kg
Assembled with gaskets 	1/2	15	2 ¹⁵ / ₁₆	75	3	1.75	0.79	1.75	0.79
	3/4	20	3	76	3	2.00	0.91	2.00	0.91
	1	25	3 ¹ / ₄	83	3	2.25	1.02	2.25	1.02
	1 ¹ / ₄	32	4 ³ / ₁₆	106	4	4.75	2.15	4.75	2.15
	1 ¹ / ₂	40	4 ³ / ₈	111	4	5.00	2.27	5.00	2.27
	2	50	5	127	4	6.50	2.95	6.50	2.95
	2 ¹ / ₂	65	5 ⁵ / ₈	143	4	8.50	3.85	8.50	3.85
	3	80	6 ³ / ₈	162	4	11.00	4.99	11.00	4.99
	3 ¹ / ₂	90	6 ⁷ / ₈	175	4	12.75	5.78	—	—
	4	100	7 ¹¹ / ₁₆	195	5	18.00	8.16	18.00	8.16
	5	125	8 ¹⁵ / ₁₆	227	5	22.00	9.98	—	—
	6	150	10 ¹ / ₄	260	6	30.00	13.61	30.00	13.61
	8	200	12 ¹⁵ / ₁₆	329	8	51.00	23.13	51.00	23.13

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)

FIGURE 367
Concentric
Reducer




Size				A		B		Unit Weight	
								Black	
NPS	DN	NPS	DN	in	mm	in	mm	lbs	kg
3/4	20	1/2	15	5/8	16	1 9/16	40	0.40	0.18
1	25	1/2 (Hex)	15	11/16	17	1 11/16	43	0.54	0.24
		3/4 (Hex)	20	7/16	11	1 1/2	38	0.63	0.29
1 1/4	32	1/2	15	9/16	14	1 5/8	41	0.84	0.38
		3/4	20	1	25	2 1/8	54	0.90	0.41
		1	25	1 5/16	24	2 1/8	54	1.07	0.49
1 1/2	40	1/2	15	1/2	13	1 5/8	41	1.00	0.45
		3/4	20	1/2	13	1 5/8	41	1.20	0.54
		1	25	1/2	13	1 3/4	44	1.50	0.68
		1 1/4	32	1	25	2 1/4	57	1.45	0.66
2	50	1/2	15	5/8	16	2	51	2.00	0.91
		3/4	20	3/4	19	2	51	1.90	0.86
		1	25	3/4	19	2	51	1.83	0.83
		1 1/4	32	1 3/16	22	2 1/8	54	1.78	0.81
		1 1/2	40	7/8	22	2 3/16	56	1.98	0.90
2 1/2	65	1 1/2	40	3/4	19	2	51	3.10	1.41
		2	50	1	25	2 9/16	65	2.98	1.35
3	80	3/4	20	1 5/16	24	2 1/2	64	4.31	1.95
		2	50	1 1/16	27	2 3/4	70	3.96	1.80
		2 1/2	65	1 5/16	24	2 13/16	73	4.40	2.00
4	100	2	50	1 3/16	30	2 15/16	75	6.50	2.95
		2 1/2	65	1 3/16	30	3 1/8	79	7.78	3.53
		3	80	1 1/16	27	3 1/8	79	7.01	3.18
5	125	4	100	1 1/16	27	3 5/16	84	10.48	4.75
6	150	4	100	1 1/8	29	3 7/16	87	13.83	6.27
		5	125	1 1/8	29	3 9/16	90	15.53	7.04
8	200	6	150	1 1/4	32	3 7/8	98	29.10	13.20

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)

FIGURE 368 Eccentric Reducer	Size				A		B*			
	NPS	DN	NPS	DN	in	mm	in	mm	lbs	kg
	3/4	20	1/2	15	9/16	14	1 1/2	38	0.45	0.20
	1	25	1/2	15	1/2	13	1 7/16	37	0.57	0.26
			3/4	20	7/16	11	1 1/2	38	0.61	0.28
	1 1/4	32	1/2	15	9/16	14	1 5/8	41	1.00	0.45
			3/4	20	1/2	13	1 5/8	41	0.90	0.41
			1	25	1/2	13	1 11/16	43	1.00	0.45
	1 1/2	40	1/2	15	11/16	17	1 3/4	44	1.11	0.50
			3/4	20	9/16	14	1 11/16	43	1.17	0.53
			1	25	9/16	14	1 3/4	44	1.21	0.55
			1 1/4	32	5/8	16	1 7/8	48	1.26	0.57
	2	50	1/2	15	3/4	19	1 15/16	49	1.80	0.82
			3/4	20	3/4	19	2	51	1.83	0.83
			1	25	11/16	17	2 1/16	52	1.86	0.84
			1 1/4	32	13/16	22	2 1/8	54	1.87	0.85
			1 1/2	40	7/8	22	2 3/16	56	1.93	0.88
	2 1/2	65	1	25	13/16	22	2 1/4	57	2.74	1.24
			1 1/4	32	7/8	22	2 3/8	60	2.80	1.27
			1 1/2	40	7/8	22	2 3/8	60	2.94	1.33
			2	50	1	25	2 9/16	65	2.95	1.34
	3	80	1	25	7/8	22	2 7/16	62	3.95	1.79
			1 1/4	32	15/16	24	2 9/16	65	3.80	1.72
			1 1/2	40	15/16	24	2 9/16	65	4.16	1.89
			2	50	1 1/16	27	2 3/4	70	4.61	2.09
			2 1/2	65	15/16	24	2 13/16	73	4.80	2.18
	4	100	1 1/4	32	1 1/16	27	2 3/4	70	6.58	2.98
			1 1/2	40	1 1/8	29	2 13/16	73	6.61	3.00
			2	50	1 3/16	30	2 15/16	75	6.91	3.13
			2 1/2	65	1 1/8	29	3 1/16	78	7.26	3.29
	5	125	3	80	1 1/16	27	3 1/4	83	7.64	3.46
			4	100	1 1/16	27	3 5/16	84	11.44	5.19
	6	150	3	80	1 1/16	27	3 5/16	84	11.19	5.07
			4	100	1 1/8	29	3 7/16	87	14.66	6.65
									15.36	6.97
* Dimension "B" does not conform to ASME standard.										

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)

FIGURE 383 Hex Bushing		Size					Unit Weight			
							Black		Galv.	
		NPS	DN	Hex	All Cast Iron	NPS	DN	lbs	kg	lbs
	1½	40		C	¼	8	0.47	0.21	0.47	0.21
				C	⅜	10	0.47	0.21	0.47	0.21
				C	½	15	0.42	0.19	0.42	0.19
				C	¾	20	0.47	0.21	0.47	0.21
				C	1	25	0.50	0.23	0.50	0.23
	2	50		C	¼	8	0.75	0.34	0.75	0.34
				C	⅜	10	0.75	0.34	0.75	0.34
				C	½	15	0.70	0.32	0.70	0.32
				C	¾	20	0.71	0.32	0.71	0.32
				C	1	25	0.73	0.33	0.73	0.33
				C	1¼	32	0.81	0.37	0.81	0.37
	2½	65		C	½	15	1.28	0.58	1.28	0.58
				C	¾	20	1.25	0.57	1.25	0.57
				C	1	25	1.16	0.53	1.16	0.53
				C	1¼	32	1.24	0.56	1.24	0.56
				C	1½	40	1.29	0.59	1.29	0.59
	3	80		C	½	15	1.93	0.88	1.93	0.88
				C	¾	20	1.92	0.87	1.92	0.87
				C	1	25	1.90	0.86	1.90	0.86
				C	1¼	32	1.77	0.80	1.77	0.80
				C	1½	40	1.79	0.81	1.79	0.81
				C	2	50	1.90	0.86	1.90	0.86
				C	2½	65	1.63	0.74	1.63	0.74
	3½	80		C	1	25	2.42	1.10	2.42	1.10
				C	1¼	32	2.56	1.16	2.56	1.16
				C	1½	40	2.65	1.20	2.65	1.20
				C	2	50	2.54	1.15	2.54	1.15
				C	2½	65	3.23	1.46	3.23	1.46
				C	3	80	1.96	0.89	1.96	0.89

 Inside hex
See page 35 (Malleable Iron)
for other available sizes.

Continued on next page.

According to specifications, hex bushings and cored plugs should be used with 150# malleable iron and 125# cast iron. Solid plugs and face bushings are recommended for use with 250# and 300# fittings.

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)

Continued from previous page.

FIGURE 383 Hex Bushing	Size						Unit Weight			
							Black		Galv.	
	NPS	DN	Hex	All Cast Iron	NPS	DN	lbs	kg	lbs	kg
  Inside hex See page 35 (Malleable Iron) for other available sizes.	4	100		C	1	25	3.59	1.63	3.59	1.63
				C	1 1/4	32	3.54	1.61	3.54	1.61
				C	1 1/2	40	3.44	1.56	3.44	1.56
				C	2	50	3.11	1.41	3.11	1.41
				C	2 1/2	65	3.29	1.49	3.29	1.49
				C	3	80	3.15	1.43	3.15	1.43
				C	3 1/2	90	2.50	1.13	2.50	1.13
	5	125		C	2	50	5.12	2.32	5.12	2.32
				C	2 1/2	65	4.87	2.21	4.87	2.21
				C	3	80	4.83	2.19	4.83	2.19
				C	3 1/2	90	4.00	1.81	—	—
				C	4	100	3.94	1.79	3.94	1.79
	6	150		C	2	50	8.00	3.63	8.00	3.63
				C	2 1/2	65	7.72	3.50	—	—
				C	3	80	7.75	3.51	7.75	3.51
				C	4	100	6.83	3.10	6.83	3.10
				C	5	125	5.24	2.38	5.24	2.38
	8	200		C	3	80	15.50	7.03	—	—
				C	4	100	13.93	6.32	—	—
				C	5	125	13.65	6.19	—	—
				C	6	150	13.19	5.98	13.19	5.98
	10	250		C	6	150	24.50	11.11	—	—
				C	8	200	22.00	9.98	—	—

FIGURE 385 Face Bushing	Size				Unit Weight	
					Black	
	NPS	DN	NPS	DN	lbs	kg
 See page 35 (Malleable Iron) for other available sizes.	3	80	2	50	13.30	6.03
	4	100	2 1/2	65	2.55	1.16
			3	80	19.20	8.71

According to specifications, hex bushings and cored plugs should be used with 150# malleable iron and 125# cast iron. Solid plugs and face bushings are recommended for use with 250# and 300# fittings.

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)

FIGURE 387 Square Head Plugs, Cored	Size		Unit Weight			
			Black		Galv.	
	NPS	DN	lbs	kg	lbs	kg
	3/4	20	0.13	0.06	0.13	0.06
	1	25	0.25	0.11	0.25	0.11
	1 1/4	32	0.39	0.18	0.39	0.18
	1 1/2	40	0.50	0.23	0.50	0.23
	2	50	0.82	0.37	0.82	0.37
	2 1/2	65	1.32	0.60	1.32	0.60
	3	80	1.87	0.85	1.87	0.85
	3 1/2	90	2.50	1.13	2.50	1.13
	4	100	4.00	1.81	4.00	1.81

FIGURE 388 Square Head Plugs, Solid	Size		Unit Weight			
			Black		Galv.	
	NPS	DN	lbs	kg	lbs	kg
	1/2	15	0.10	0.05	0.10	0.05
	3/4	20	0.17	0.08	0.17	0.08
	1	25	0.32	0.15	0.32	0.15
	1 1/4	32	0.53	0.24	0.53	0.24
	1 1/2	40	0.76	0.34	0.76	0.34
	2	50	1.23	0.56	1.23	0.56
	2 1/2	65	2.00	0.91	2.00	0.91
	3	80	3.18	1.44	3.18	1.44
	3 1/2	90	4.38	1.99	—	—

FIGURE 389 Bar Plugs, Cored	Size		Unit Weight			
			Black		Galv.	
	NPS	DN	lbs	kg	lbs	kg
	4	100	3.82	1.73	3.82	1.73
	5	125	6.50	2.95	6.50	2.95
	6	150	9.94	4.51	9.94	4.51
	8	200	20.26	9.19	20.26	9.19

FIGURE 380 Bar Plugs, Solid	Size		Unit Weight	
			Black	
	NPS	DN	lbs	kg
	4	100	5.68	2.58
	5	125	9.60	4.35
	6	150	14.78	6.70

FIGURE 390 Countersunk Plugs	Size		Unit Weight			
			Black		Galv.	
	NPS	DN	lbs	kg	lbs	kg
	1	25	0.20	0.09	0.20	0.09
	1 1/4	32	0.32	0.15	0.32	0.15
	1 1/2	40	0.47	0.21	0.47	0.21
	2	50	0.84	0.38	0.84	0.38
	2 1/2	65	1.40	0.63	—	—
	3	80	2.25	1.02	—	—
	3 1/2	90	3.02	1.37	—	—
	4	100	3.76	1.71	—	—
	See page 32 (Malleable Iron) for other available sizes.					

FIGURE 381 Cap	Size		Unit Weight			
			Black		Galv.	
	NPS	DN	lbs	kg	lbs	kg
	2 1/2	65	2.55	1.16	—	—
	3	80	4.10	1.86	—	—
	4	100	6.40	2.90	—	—
	5	125	10.70	4.85	—	—
	6	150	14.20	6.44	14.20	6.44
	8	200	27.23	12.35	27.23	12.35

According to specifications, hex bushings and cored plugs should be used with 150# malleable iron and 125# cast iron. Solid plugs and face bushings are recommended for use with 250# and 300# fittings.

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 125 (Standard)

FIGURE 370 Locknut	Size		Minimum Dimensions								Unit Weight	
			A		B		C		D		Black	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
 For nominal sizes smaller than 2½" (65 DN) see Malleable Iron page 27.	2½	65	3.500	89	3.180	81	.590	15	0.90	2	1.13	0.51
	3	80	4.270	108	3.840	98	.670	17	0.90	2	1.60	0.73
	4	100	5.380	137	5.000	127	.800	20	.130	3	1.10	0.50

Cast Iron Threaded Fittings

Class 250 (Extra Heavy)



FIGURE 421 90° Elbow	Size		A		B		Unit Weight	
							Black	
	NPS	DN	in	mm	in	mm	lbs	kg
 	¼	8	⅝	16	15/16	24	0.37	0.17
	½	15	13/16	22	1¼	32	0.75	0.34
	¾	20	15/16	24	17/16	37	1.13	0.51
	1	25	11/16	27	1⅝	41	1.79	0.81
	1¼	32	15/16	33	115/16	49	3.00	1.36
	1½	40	1½	38	2⅛	54	4.05	1.84
	2	50	113/16	47	2½	64	6.76	3.07
	2½	65	2	51	215/16	75	10.56	4.79
	3	80	2⅜	60	3⅜	86	15.25	6.92

FIGURE 424 45° Elbow	Size		A		B		Unit Weight	
							Black	
	NPS	DN	in	mm	in	mm	lbs	kg
 	½	15	9/16	14	1	25	0.66	0.30
	¾	20	⅝	16	1⅛	29	1.04	0.47
	1	25	¾	19	15/16	33	1.56	0.71
	1¼	32	7/8	22	1½	38	2.70	1.22
	1½	40	11/16	27	111/16	43	3.55	1.61
	2	50	15/16	33	2	51	6.07	2.75
	2½	65	15/16	33	2¼	57	9.79	4.44

Note: See page 37 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Class 250 (Extra Heavy)



FIGURE 425 Tee	Size		A		B		Unit Weight	
							Black	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/4	8	5/8	16	15/16	24	0.47	0.21
	3/8	10	11/16	17	1 1/16	27	0.70	0.32
	1/2	15	3/4	19	1 1/4	32	1.20	0.54
	3/4	20	7/8	22	1 7/16	37	1.57	0.71
	1	25	1	25	1 5/8	41	2.43	1.10
	1 1/4	32	1 3/16	30	1 15/16	49	3.94	1.79
	1 1/2	40	1 7/16	37	2 1/8	54	5.31	2.41
	2	50	1 3/4	44	2 1/2	64	9.01	4.09
	2 1/2	65	1 15/16	49	2 15/16	75	14.23	6.45
	3	80	2 5/16	59	3 3/8	86	20.95	9.50
	4	100	2 15/16	75	4 1/8	105	33.98	15.41

FIGURE 426 Reducing Tee  	Size						A, B		C		D, E		F		Unit Weight									
	NPS		DN		NPS		DN		in		mm		in		mm		in		mm		lbs		kg	
	Black																							
	3/4	20	3/4	20	1/2	15	3/4	19	7/8	22	1 5/16	33	1 3/8	35	1.37	0.62								
	1	25	1	25	1/2	15	3/4	19	1	25	1 3/8	35	1 1/2	38	2.03	0.92								
					3/4	20	7/8	22	1	25	1 1/2	38	1 9/16	40	2.19	0.99								
	1 1/4	32	1 1/4	32	3/4	20	15/16	24	1 1/8	29	1 5/8	41	1 11/16	43	3.21	1.46								
					1	25	1 1/16	27	1 3/16	30	1 3/4	44	1 13/16	47	3.49	1.58								
	1 1/2	40	1 1/2	40	3/4	20	1	25	1 1/4	32	1 11/16	43	1 7/8	48	4.02	1.82								
					1	25	1 1/8	29	1 5/16	33	1 13/16	47	1 15/16	49	4.26	1.93								
					1 1/4	32	1 5/16	33	1 3/8	35	2	51	2 1/16	52	4.98	2.26								
	2	50	2	50	3/4	20	1 1/8	29	1 7/16	37	1 7/8	48	2	51	6.24	2.83								
					1	25	1 1/4	32	1 1/2	38	2	51	2 1/8	54	6.57	2.98								
					1 1/4	32	1 3/8	35	1 9/16	40	2 3/16	56	2 1/4	57	7.11	3.22								
					1 1/2	40	1 1/2	38	1 5/8	41	2 5/16	59	2 5/16	59	7.69	3.49								

Note: See page 37 for pressure-temperature ratings.

Cast Iron Drainage Fittings



Anvil drainage fittings have sufficient sweep to allow free unobstructed flow. They are made with a shoulder of the same diameter as the inside of the pipe. Thus, continuous passage is created when the pipe is screwed to the shoulder. There is no place for solid matter to collect and clog in the pipe. Also, Anvil drainage fittings are recessed and threaded for wrought pipe.

Coated drainage fittings are available in hot dipped, galvanized finish (in sizes listed). Coated drainage fittings are made to order.

90° type drainage fittings are normally tapped with pitch of 1/4 inch (6mm) to the foot.

UNPITCHED 90° drainage fittings are POA only.

Malleable Iron

Cast Iron

Small Steel Fittings

Pipe Nipples & Pipe Couplings

Forged Steel Fittings & Unions

Anvilets

Catawissa

J.B. Smith Products

Carton Information

Cast Iron Drainage Fittings


FIGURE 701* 90° Short Turn Elbow	Size		A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1½	40	1 ¹⁵ / ₁₆	49	1.91	0.87	1.91	0.87
	2	50	2 ¹ / ₄	57	3.04	1.38	3.04	1.38
	3	80	3 ¹ / ₁₆	78	7.09	3.22	7.09	3.22
	4	100	3 ¹³ / ₁₆	98	13.69	6.21	13.69	6.21


FIGURE 701R* 90° Reducing Short Turn Elbow	Size				A		B		Unit Weight	
									Black	
	NPS	DN	NPS	DN	in	mm	in	mm	lbs	kg
	1½	40	1¼	32	1 ⁷ / ₈	48	1 ¹¹ / ₁₆	43	1.69	0.77
	2	50	1½	40	2 ¹ / ₈	54	2	51	2.49	1.13


FIGURE 702* 90° Long Turn Elbow	Size		A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1½	40	2½	64	2.24	1.02	2.24	1.02
	2	50	3 ¹ / ₁₆	78	3.61	1.64	3.61	1.64
	3	80	4 ¹ / ₄	108	9.04	4.10	—	—
	4	100	5 ³ / ₁₆	132	16.40	7.44	—	—



FIGURE 702A* 90° Extra Long Turn Elbow	Size		A		Unit Weight	
					Black	
	NPS	DN	in	mm	lbs	kg
	1½	40	3½	90	2.62	1.19
	2	50	4	100	4.54	2.06

FIGURE 703 60° Short Turn Elbow	Size		A		Unit Weight	
					Black	
	NPS	DN	in	mm	lbs	kg
	1½	40	3½	89	2.34	1.06

*Inlets tapped, pitched .25" (6mm) to the foot. Inlets of reducing fittings are always the smallest openings.

Cast Iron Drainage Fittings


FIGURE 705 45° Short Turn Elbow 	Size		A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1½	40	1 ⁷ / ₁₆	37	1.71	0.78	1.71	0.78
	2	50	1 ¹¹ / ₁₆	43	2.79	1.27	2.79	1.27
	3	80	2 ³ / ₁₆	56	6.31	2.86	6.31	2.86
	4	100	2 ⁵ / ₈	67	11.44	5.19	11.44	5.19


FIGURE 706 45° Long Turn Elbow 	Size		A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1½	40	1 ⁷ / ₈	48	2.1	0.97	2.14	0.97




FIGURE 707 22 ½° Elbow 	Size		A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
	1½	40	1 ¹ / ₄	32	1.65	0.75	1.65	0.75
	2	50	1 ⁷ / ₁₆	37	3.08	1.40	3.08	1.40

FIGURE 708 11 ¼° Elbow 	Size		A		Unit Weight	
					Black	
	NPS	DN	in	mm	lbs	kg
	1½	40	1 ¹ / ₄	32	1.81	0.82
	2	50	1 ³ / ₈	35	2.69	1.22

*Inlets tapped, pitched .25" (6mm) to the foot. Inlets of reducing fittings are always the smallest openings.

Cast Iron Drainage Fittings

**SHORTEST OFFSET
AND FACE TO FACE WITH USE
OF CLOSE NIPPLE**



Size		Length Close Nipple		60° Short Figure 703		45° Short Figure 705		45° Long Figure 706	
				A	B	A	B	A	B
NPS	DN	in	mm	in	mm	in	mm	in	mm
1 1/4	32	1 5/8	41	3	76	4 7/8	124	2 3/4	70
1 1/2	40	1 3/4	44	3 1/2	89	5 1/2	140	3	76
2	50	2	51	4 1/8	105	6 1/2	165	3 5/8	92
2 1/2	65	2 1/2	64	4 15/16	125	7 7/8	200	4 3/16	106
3	80	2 5/8	67	5 9/16	141	9	229	4 5/8	117
4	100	2 7/8	73	6 1/2	165	10 1/2	267	5 1/2	140
5	125	3	76	7 1/4	184	11 15/16	303	6 1/4	159
6	150	3 1/8	79	7 7/8	200	13 1/16	332	7 3/8	187
8	200	3 1/2	89	9 3/8	238	16 3/16	411	9	229
10	250	3 7/8	98	—	—	—	—	—	—

Size		Length Close Nipple		22 1/2° Figure 707		11 1/4° Figure 708	
				A	B	A	B
NPS	DN	in	mm	in	mm	in	mm
1 1/4	32	1 5/8	41	1	25	4 11/16	119
1 1/2	40	1 3/4	44	1 1/8	29	5 1/4	133
2	50	2	51	1 3/8	35	6 1/8	156
2 1/2	65	2 1/2	64	1 5/8	41	7 3/8	187
3	80	2 5/8	67	1 13/16	47	8 5/16	211
4	100	2 7/8	73	2 1/16	52	9 9/16	243
5	125	3	76	2 1/4	57	10 11/16	271
6	150	3 1/8	79	2 1/2	64	11 7/8	302
8	200	3 1/2	89	3	76	14 7/16	367
10	250	3 7/8	98	3 7/8	98	17 13/16	452

*Inlets tapped, pitched .25" (6mm) to the foot. Inlets of reducing fittings are always the smallest openings.

Cast Iron Drainage Fittings


FIGURE 718* 90° Street Elbow		Size		A		B		Unit Weight			
								Black		Galv.	
		NPS	DN	in	mm	in	mm	lbs	kg	lbs	kg
		1½	40	3	76	1⅞	48	2.05	0.93	2.05	0.93
		2	50	3¼	83	2⅜	56	3.10	1.41	3.10	1.41


FIGURE 719 45° Street Elbow		Size		A		B		Unit Weight			
								Black		Galv.	
		NPS	DN	in	mm	in	mm	lbs	kg	lbs	kg
		1½	40	2	51	1¼	32	1.64	0.74	1.64	0.74
		2	50	2¼	57	1⅞	43	2.67	1.21	2.67	1.21



FIGURE 722* Tee		Size		A		B		Unit Weight			
								Black		Galv.	
		NPS	DN	in	mm	in	mm	lbs	kg	lbs	kg
		1½	40	3⅞	98	1⅝	49	2.59	1.17	2.59	1.17
		2	50	4½	114	2¼	57	4.66	2.11	4.66	2.11

FIGURE 723* Reducing Tee		Size						A		B		Unit Weight	
		Black											
		NPS	DN	NPS	DN	NPS	DN	in	mm	in	mm	lbs	kg
		2	50	2	50	1½	40	4⅞	103	2⅜	56	3.77	1.71

*Inlets tapped, pitched .25" (6mm) to the foot. Inlets of reducing fittings are always the smallest openings.

Cast Iron Drainage Fittings


FIGURE 726* 90° Short Turn Y-Branch Tee Pattern	Size		A		B		C		Unit Weight			
									Black		Galv.	
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
	1½	40	4¼	108	2½	64	2½	64	3.09	1.40	3.09	1.40
	2	50	5³⁄₁₆	132	3¹⁄₁₆	78	3¹⁄₁₆	78	5.08	2.30	5.08	2.30
	3	80	7¼	184	4¼	108	4¼	108	11.77	5.34	11.77	5.34
	4	100	8¾	222	5³⁄₁₆	132	5³⁄₁₆	132	21.25	9.64	21.25	9.64


FIGURE 727* 90° Reducing Short Turn Y-Branch Tee Pattern 	Size		A		B		C		Unit Weight		
									Black		
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg	
2 x 2 x 1½		50 x 50 x 40		4 ⁵ / ₈	117	2 ¹⁵ / ₁₆	75	2 ¹¹ / ₁₆	68	4.16	1.89
2 x 1½ x 1½		50 x 40 x 40		4 ⁵ / ₈	117	2 ¹⁵ / ₁₆	75	2 ¹¹ / ₁₆	68	4.33	1.96



FIGURE 729* Reducing Double Short Turn Tee	Size		A		B		C		Unit Weight	
									Black	
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg
	2 x 1½	50 x 40	4⁵⁄₈	117	5⁷⁄₈	149	2¹¹⁄₁₆	68	5.82	2.64

FIGURE 730* 90° Long Turn Y-Branch Tee Pattern	Size		A		B		C		Unit Weight			
									Black		Galv.	
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
	1½	40	5³⁄₈	137	4¹⁄₈	105	1¼	32	4.43	2.01	—	—
	2	50	7	178	5¼	133	1¾	44	6.69	3.03	6.69	3.03

*Inlets tapped, pitched .25" (6mm) to the foot. Inlets of reducing fittings are always the smallest openings.

Cast Iron Drainage Fittings


FIGURE 731* 90° Reducing Long Turn Y-Branch Tee Pattern	Size		A		B		C		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg
									Black	
 	2 x 2 x 1½ 50 x 50 x 40		5¾ 146		4¾ 111		1⅝ 24		5.23 2.37	


FIGURE 734 45° Y-Branch	Size		A		B		C		Unit Weight			
	NPS	DN	in	mm	in	mm	in	mm	Black		Galv.	
									lbs	kg	lbs	kg
 	1½	40	5½	140	3⅝	92	3⅝	92	4.03	1.83	4.03	1.83
	2	50	6½	165	4⅜	111	4⅜	111	5.56	2.52	5.56	2.52
	3	80	9	229	6⅜	157	6⅜	157	12.00	5.44	12.00	5.44
	4	100	10⅞	276	7⅞	195	7⅞	195	24.51	11.12	24.51	11.12



FIGURE 735 45° Reducing Y-Branch	Size		A		B		C		Unit Weight			
	NPS	DN	in	mm	in	mm	in	mm	Black		Galv.	
									lbs	kg	lbs	kg
 	2 x 2 x 1½	50 x 50 x 40	5⅞	149	4⅞	105	4⅞	103	4.83	2.19	4.83	2.19
	4 x 4 x 3	100 x 100 x 80	9¼	235	7⅞	183	6⅞	175	20.63	9.36	—	—

FIGURE 736 45° Double Y-Branch	Size		A		B		C		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	Black	
									lbs	kg
 	1½	40	5½	140	3⅝	92	3⅝	92	5.09	2.31

*Inlets tapped, pitched .25" (6mm) to the foot. Inlets of reducing fittings are always the smallest openings.

Cast Iron Drainage Fittings






FIGURE 753 Coupling	Size		A		Unit Weight			
					Black		Galv.	
	NPS	DN	in	mm	lbs	kg	lbs	kg
 	1½	40	3⅜	86	1.75	0.79	1.75	0.79

FIGURE 744 Tucker Connection	Size		A		Unit Weight	
					Black	
	NPS	DN	in	mm	lbs	kg
 	1½	40	4	102	4.04	1.83
	2	50	4½	114	5.40	2.45
	4	100	6⅜	174	20.00	9.07

4" size (100 DN) is only furnished with a loose ring upon request.

FIGURE 752 P-Trap	Size		A		B		C		Clean Out		Water Seal		Unit Weight			
	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
 	1½	40	2⅛	54	2¼	57	7⁄8	22	1	25	2	51	4.69	2.13	4.69	2.13
	2	50	2⁹⁄₁₆	65	2¾	70	7⁄8	22	1	25	2	51	7.18	3.26	7.18	3.26
	3	80	3⅜	86	3¾	95	1⅜	30	1¼	32	2½	64	16.87	7.65	16.87	7.65

Cleanout plug not included. Outlets tapped, pitched .25"/Ft. (21mm/meter).

FIGURE 754 Bath P-Trap	Size		A		B		C		D		Water Seal		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
 	1½	40	2⅛	54	2⅜	60	4⅜	111	4⅝	117	2	51	3.87	1.76
	2	50	2½	64	2⅜	73	5⅝	135	5⅝	135	2	51	6.25	2.83

Outlets tapped, pitched .25"/Ft. (21mm/meter).

*Inlets tapped, pitched .25" (6mm) to the foot. Inlets of reducing fittings are always the smallest openings.

Cast Iron Flanged Fittings

Class 125 (Standard)



For Listings/Approval Details and Limitations, visit our website @ www.anvilintl.com or contact an Anvil/AnvilStar Sales Representative.

Specifications

All standard or "Class 125" Cast Iron Flanged Fittings in sizes listed are made to ASME and are marked 125 for pipe sizes 12 NPS (300 DN) and smaller; and have plain faces. Unless otherwise specified, cast iron flanges and fittings are drilled and faced in accordance with ASME B 16.1.

Coatings

Flanged fittings are available in both black and galvanized. Consult an Anvil Representative for available sizes.

Sizes

Size of all fittings scheduled indicates nominal pipe diameter of ports. Standard reducing elbows carry the same dimensions center-to-face as regular elbows of largest straight size.

Ordering

To order reducing companion flanges, specify threaded or reduced size first, then the outside diameter of flange wanted. For instance, if a reducing flange is required to connect a 5-inch pipe to an 8-inch flanged valve or fitting having a 13 1/2-inch O.D. flange, order: 5 x 13 1/2-inch standard reducing flange.

Dimensions

Bolt holes, for bolts smaller than 1 3/4 inches (44mm) in diameter are drilled 1/8 inch larger than the bolt diameter; 1 3/4 inch (44mm) and

larger, bolt holes are 1/4 inch (6mm) larger than bolt diameter. Bolt holes straddle the center line. Bolt holes are spot faced on order only.

Tolerances

An inspection limit of plus or minus 1/32 inch (1mm) shall be allowed on all center to contact surface dimensions for sizes up to and including 10 NPS (250 DN); plus or minus 1/16 inch (2mm) on sizes larger than 10 NPS (250 DN). Inspection limit of plus or minus 1/16 inch (2mm) shall be allowed on all contact surface to contact surface dimensions for sizes up to and including 10 NPS (250 DN); plus or minus 1/8 inch (3mm) on sizes larger than 10 NPS (250 DN). The largest opening in the fitting governs the tolerance to be applied to all openings.

Cast Iron Flanged Fittings and Cast Iron Flanges											
Temperature		Pressure									
		Class 125						Class 250			
		1"-12"		14"-24"		30"-48"		1"-12"		14"-24"	
(°F)	(°C)	psi	bar	psi	bar	psi	bar	psi	bar	psi	bar
-20° to 150°	-28.9 to 65.6	200	13.8	150	10.3	150	10.3	500	34.5	300	20.7
200°	93.3	190	13.1	135	9.3	115	7.9	460	31.7	280	19.3
225°	107.2	180	12.4	130	9.0	100	6.9	440	30.3	270	18.6
250°	121.1	175	12.1	125	8.6	85	5.9	415	28.6	260	17.9
275°	135.0	170	11.7	120	8.3	65	4.5	395	27.2	250	17.2
300°	148.9	165	11.4	110	7.6	50	3.4	375	25.9	240	16.5
325°	162.8	155	10.7	105	7.2	—	—	355	24.5	230	15.9
350°	178.3	150	10.3	100	6.9	—	—	335	23.1	220	15.2
375°	190.6	145	10.0	—	—	—	—	315	21.7	210	14.5
400°	207.8	140	9.7	—	—	—	—	290	20.0	200	13.8
425°	218.3	130	9.0	—	—	—	—	270	18.6	—	—
450°	232.2	125	8.6	—	—	—	—	250	17.2	—	—

Cast Iron Flanged Fittings

Class 125 (Standard)



FIGURE 801 90° Flanged Elbow	Size		A		Flange Dia.		Thickness				Unit Weight			
							Min. Flange		Wall		Black		Galv.	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
	1½	40	4	102	5	127	9/16	14	5/16	8	9.00	4.08	—	—
	2	50	4½	114	6	152	5/8	16	5/16	8	14.00	6.35	14.00	6.35
	2½	65	5	127	7	178	11/16	17	5/16	8	19.00	8.62	19.00	8.62
	3	80	5½	140	7½	191	¾	19	3/8	10	24.00	10.88	24.00	10.88
	3½	90	6	152	8½	216	13/16	22	7/16	11	31.00	14.06	—	—
	4	100	6½	165	9	229	15/16	24	1/2	13	41.00	18.59	41.00	18.59
	5	125	7½	191	10	254	15/16	24	1/2	13	52.00	23.58	52.00	23.58
	6	150	8	203	11	279	1	25	9/16	14	68.00	30.84	68.00	30.84
	8	200	9	229	13½	343	1 1/8	29	5/8	16	110.00	49.89	110.00	49.89
	10	250	11	279	16	406	1 3/16	30	¾	19	175.00	79.37	175.00	79.37
	12	300	12	305	19	483	1 ¼	32	13/16	23	250.00	113.38	250.00	113.38

FIGURE 802 45° Flanged Elbow	Size		A		Flange Dia.		Thickness				Unit Weight			
							Min. Flange		Wall		Black		Galv.	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
	1½	40	2¼	57	5	127	9/16	14	5/16	8	8.00	3.63	—	—
	2	50	2½	64	6	152	5/8	16	5/16	8	12.00	5.44	—	—
	2½	65	3	76	7	178	11/16	17	5/16	8	17.00	7.71	—	—
	3	80	3	76	7½	191	¾	19	3/8	10	20.00	9.07	20.00	9.07
	4	100	4	102	9	229	15/16	24	1/2	13	36.00	16.33	36.00	16.33
	5	125	4½	114	10	254	15/16	24	1/2	13	45.00	20.41	—	—
	6	150	5	127	11	279	1	25	9/16	14	60.00	27.21	60.00	27.21
	8	200	5½	140	13½	343	1 1/8	29	5/8	16	94.00	42.63	94.00	42.63
	10	250	6½	165	16	406	1 3/16	30	¾	19	145.00	65.76	145.00	65.76
	12	300	7½	191	19	483	1 ¼	32	13/16	23	220.00	99.77	220.00	99.77

Note: See page 63 for pressure-temperature ratings.

Cast Iron Flanged Fittings

Class 125 (Standard)


FIGURE 803 90° Reducing Flanged Elbow	Size				A		Unit Weight	
							Black	
	NPS	DN	NPS	DN	in	mm	lbs	kg
	2½	65	2	50	5	127	18.00	8.16
	3	80	2	50	5½	140	19.00	8.62
			2½	65			22.00	9.98
	4	100	2	50	6½	165	29.00	13.15
			2½	65			31.00	14.06
			3	80			33.00	14.97
	5	125	3	80	7½	191	40.00	18.14
			4	100			48.00	21.77
	6	150	3	80	8	203	47.00	21.32
			4	100			56.00	25.40
			5	125			60.00	27.21
	8	200	4	100	9	229	77.00	34.92
			5	125			82.00	37.19
			6	150			90.00	40.82
	10	250	6	150	11	279	125.00	56.69
			8	200			150.00	68.03
	12	300	6	150	12	305	165.00	74.83
			8	200			190.00	86.17
			10	250			220.00	99.77




FIGURE 804 90° Long Radius Flanged Elbow	Size		B		Flange Diameter		Thickness				Unit Weight	
											Black	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
	2	50	6½	165	6	152	5/8	16	5/16	8	16.00	7.26
	2½	65	7	178	7	178	11/16	17	5/16	8	23.00	10.43
	3	80	7¾	197	7½	191	¾	19	3/8	10	28.00	12.70
	4	100	9	229	9	229	15/16	24	1/2	13	48.00	21.77
	5	125	10¼	260	10	254	15/16	24	1/2	13	62.00	28.12
	6	150	11½	292	11	279	1	25	9/16	14	85.00	38.55
	8	200	14	356	13½	343	1⅛	29	5/8	16	145.00	65.76
	10	250	16½	419	16	406	1⅜	30	¾	19	230.00	104.31
	12	300	19	483	19	483	1¼	32	13/16	22	350.00	158.73

FIGURE 804R 90° Long Radius Reducing Flanged Elbow	Reducing Size		B		Unit Weight	
					Black	
	NPS	DN	in	mm	lbs	kg
	4 x 3	100 x 80	9	229	46.00	20.86
	5 x 4	125 x 100	10¼	260	58.00	26.30
	6 x 4	150 x 100	11½	292	78.00	35.37
	6 x 5	150 x 125	11½	292	81.00	36.73
	8 x 6	200 x 150	14	356	130.00	58.96
	10 x 8	250 x 200	16½	419	205.00	92.97


Note: See page 63 for pressure-temperature ratings.

Cast Iron Flanged Fittings

Class 125 (Standard)

FIGURE 805 90° Flanged Base Elbow	Size		Center to Base R		Dia. of Round Base S		Thickness		Size of Supporting Pipe for Base		Unit Weight	
							Base T	Rubs U				
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
	3	80	4 ⁷ / ₈	124	5	127	⁹ / ₁₆	14	1 ¹ / ₂	13	36.00	16.33
	4	100	5 ¹ / ₂	140	6	152	⁵ / ₈	16	1 ¹ / ₂	13	59.00	26.76
	6	150	7	178	7	178	¹¹ / ₁₆	17	⁵ / ₈	16	110.00	49.89
	8	200	8 ³ / ₈	213	9	229	¹⁵ / ₁₆	24	⁷ / ₈	22	158.00	71.66
	10	250	9 ³ / ₄	248	9	229	¹⁵ / ₁₆	24	⁷ / ₈	22	224.00	101.59
	12	300	11 ¹ / ₄	286	11	279	1	25	1	25	324.00	146.94


Bases, when drilled, should be drilled to the template of the flange of the supporting pipe size. Size of base determined by size of largest opening of fitting. Bases will be furnished not faced and not drilled unless otherwise specified. When ordered faced, dimensions "R" and "T" will be slightly less than shown in table.

FIGURE 808 90° Flanged Side Outlet Elbow	Size		A		Flange Diameter		Thickness		Unit Weight	
							Flange	Wall		
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg
	4	100	6 ¹ / ₂	165	9	229	¹⁵ / ₁₆	24	59.00	26.76
	6	150	8	203	11	279	1	25	96.00	43.54
	8	200	9	229	13 ¹ / ₂	343	1 ¹ / ₈	29	150.00	68.03

Note: See page 63 for pressure-temperature ratings.

Cast Iron Flanged Fittings

Class 125 (Standard)

FIGURE 811 Flanged Tee	Size		A		AA		Flange Diameter		Thickness				Unit Weight			
									Flange		Wall		Black		Galv.	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
	1½	40	4	102	8	203	5	127	9/16	14	5/16	8	15.00	6.80	—	—
	2	50	4½	114	9	229	6	152	5/8	16	5/16	8	21.00	9.52	21.00	9.52
	2½	65	5	127	10	254	7	178	11/16	17	5/16	8	30.00	13.61	30.00	13.61
	3	80	5½	140	11	279	7½	191	¾	19	3/8	10	37.00	16.78	37.00	16.78
	4	100	6½	165	13	330	9	229	15/16	24	1/2	13	64.00	29.02	64.00	29.02
	5	125	7½	191	15	381	10	254	15/16	24	1/2	13	81.00	36.73	—	—
	6	150	8	203	16	406	11	279	1	25	9/16	14	105.00	47.62	105.00	47.62
	8	200	9	229	18	457	13½	343	1 1/8	29	5/8	16	165.00	74.83	165.00	74.83
	10	250	11	279	22	559	16	406	1 3/16	30	¾	19	270.00	122.45	270.00	122.45
	12	300	12	305	24	610	19	483	1 ¼	32	13/16	22	380.00	172.34	380.00	172.34

Note: See page 63 for pressure-temperature ratings.

Cast Iron Flanged Fittings

Class 125 (Standard)

FIGURE 812 Flanged Reducing Tee	Size						Unit Weight			
							Black		Galv.	
	NPS	DN	NPS	DN	NPS	DN	lbs	kg	lbs	kg
 4 NPS (100 DN) 6 NPS (150 DN) — 5 NPS (125 DN) Read as: 6 x 5 x 4 (150 x 125 x 100DN) Dimensions for reducing tees for sizes 16" NPS (400 DN) and smaller have same center to face dimensions as straight size fittings corresponding to the largest opening. Dimensions of sizes not listed furnished on request.	3	80	2	50	3	80	33.00	14.97	—	—
			3	80	1½	40	32.00	14.51	—	—
					2	50	34.00	15.42	—	—
					2½	65	35.00	15.87	—	—
					4	100	56.00	25.40	—	—
	4	100	2	50	4	100	50.00	22.68	—	—
			2½	65	4	100	56.00	25.40	—	—
			3	80	3	80	53.00	24.04	—	—
					4	100	59.00	26.76	—	—
			4	100	2	50	51.00	23.13	—	—
					2½	65	56.00	25.40	—	—
					3	80	57.00	25.85	—	—
	5	125	5	125	6	150	88.00	39.91	—	—
					3	80	71.00	32.20	—	—
					4	100	80.00	36.28	—	—
	6	150	3	80	6	150	91.00	41.27	—	—
					4	100	88.00	39.91	88.00	39.91
					6	150	94.00	42.63	—	—
			6	150	5	125	91.00	41.27	—	—
					2	50	86.00	39.00	—	—
					2½	65	90.00	40.82	—	—
					3	80	92.00	41.72	—	—
					4	100	97.00	43.99	—	—
					5	125	105.00	47.62	—	—
					8	200	142.00	64.40	—	—
	8	200	4	100	6	150	140.00	63.49	—	—
					8	200	146.00	66.21	—	—
			6	150	4	100	125.00	56.69	—	—
					6	150	144.00	65.31	—	—
					8	200	159.00	72.11	—	—
			8	200	3	80	140.00	63.49	—	—
					4	100	143.00	64.85	143.00	64.85
	10	250	8	200	6	150	156.00	70.75	156.00	70.75
					8	200	220.00	99.77	—	—
					10	250	232.00	105.22	—	—
			10	250	4	100	262.00	118.82	—	—
					6	150	225.00	102.04	—	—
					8	200	240.00	108.84	—	—
	12	300	8	200	6	150	262.00	118.82	—	—
					8	200	298.00	135.15	—	—
			12	300	12	300	340.00	154.20	—	—
					6	150	323.00	146.49	—	—
					8	200	330.00	149.66	—	—
			10	250	10	250	362.00	164.17	—	—

Note: See page 63 for pressure-temperature ratings.

Cast Iron Flanged Fittings

Class 125 (Standard)



FIGURE 821 Flanged Cross	Size		A		AA		Flange Diameter		Thickness				Unit Weight	
									Min. Flange		Wall		Black	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
	2	50	4½	114	9	225	6	152	⅝	16	⅝ ₁₆	8	28.00	12.70
	2½	65	5	127	10	250	7	178	11 ₁₆	17	⅝ ₁₆	8	39.00	17.69
	3	80	5½	140	11	275	7½	191	¾	19	¾ ₈	10	48.00	21.77
	4	100	6½	165	13	325	9	229	15 ₁₆	24	½	13	82.00	37.19
	6	150	8	203	16	400	11	279	1	25	9 ₁₆	14	135.00	61.22
	8	200	9	229	18	450	13½	343	1⅛	29	⅝	16	210.00	95.24
	10	250	11	279	22	550	16	406	1⅜ ₁₆	30	¾	19	330.00	149.66

FIGURE 823 Flanged Lateral																					
						Size		Face to Face D		Center to Face E		Center to Face F		Flange Diameter		Thickness				Unit Weight	
																Min. Flange		Wall		Black	
NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg				
2	50	10½	267	8	203	2½	64	6	152	⅝	16	⅝ ₁₆	8	25.00	11.34						
2½	65	12	305	9½	241	2½	64	7	178	11 ₁₆	17	⅝ ₁₆	8	36.00	16.33						
3	80	13	330	10	254	3	76	7½	191	¾	19	¾ ₈	10	44.00	19.95						
4	100	15	381	12	305	3	76	9	229	15 ₁₆	24	½	13	75.00	34.01						
5	125	17	432	13½	343	3½	89	10	254	15 ₁₆	24	½	13	96.00	43.54						
6	150	18	457	14½	368	3½	89	11	279	1	25	9 ₁₆	14	125.00	56.69						
8	200	22	559	17½	445	4½	114	13½	343	1⅛	29	⅝	16	210.00	95.24						

Note: See page 63 for pressure-temperature ratings.

Cast Iron Flanged Fittings

Class 125 (Standard)



FIGURE 825 Flanged Concentric Reducer	Size				F		Unit Weight			
							Black		Galv.	
	NPS	DN	NPS	DN	in	mm	lbs	kg	lbs	kg
	2	50	1½	40	5	127	12.00	5.44	—	—
	2½	65	1½	40	5	127	12.00	5.44	—	—
			2	50			14.00	6.35	—	—
	3	80	1½	40	6	152	14.00	6.35	—	—
			2	50			16.00	7.26	—	—
			2½	65			19.00	8.62	19.00	8.62
	4	100	2	50	7	178	24.00	10.88	24.00	10.88
			2½	65			26.00	11.79	26.00	11.79
			3	80			28.00	12.70	28.00	12.70
	5	125	2½	65	8	203	31.00	14.06	—	—
			3	80			32.00	14.51	—	—
			4	100			39.00	17.69	—	—
	6	150	2	50	9	229	34.00	15.42	—	—
			2½	65			37.00	16.78	—	—
			3	80			39.00	17.69	—	—
			4	100			47.00	21.32	47.00	21.32
			5	125			50.00	22.68	—	—
	8	200	4	100	11	279	66.00	29.93	—	—
			5	125			71.00	32.20	—	—
			6	150			77.00	34.92	77.00	34.92
	10	250	4	100	12	305	85.00	38.55	—	—
			5	125			90.00	40.82	—	—
			6	150			100.00	45.35	—	—
			8	200			120.00	54.42	—	—
	12	300	6	150	14	356	140.00	63.49	—	—
			8	200			155.00	70.29	—	—
			10	250			180.00	81.63	—	—

FIGURE 826 Flanged Eccentric Reducer	Size				F		Unit Weight			
							Black		Galv.	
	NPS	DN	NPS	DN	in	mm	lbs	kg	lbs	kg
	3	80	2	50	6	152	16.00	7.26	—	—
			2½	65			22.00	9.98	—	—
	4	100	2	50	7	178	28.00	12.70	—	—
			2½	65			28.00	12.70	—	—
			3	80			28.00	12.70	—	—
	5	125	4	100	8	203	39.00	17.69	—	—
	6	150	3	80	9	229	47.00	21.32	—	—
			4	100			50.00	22.68	50.00	22.68
			5	125			51.00	23.13	—	—
	8	200	4	100	11	279	71.00	32.20	—	—
			5	125			76.00	34.47	—	—
			6	150			77.00	34.92	—	—
	10	250	6	150	12	305	107.00	48.53	—	—
			8	200			120.00	54.42	—	—
	12	300	8	200	14	356	155.00	70.29	—	—
			10	250			180.00	81.63	—	—

Note: See page 63 for pressure-temperature ratings.

Cast Iron Flanged Fittings Class 250 (Extra Heavy)

Specifications

All Extra Heavy or "Class 250" Cast Iron Flanged Fittings in sizes listed are made to ASME B16.1, and are marked "250". All Class 250 Cast Iron Flange Fittings are faced and drilled to ASME B 16.1, unless otherwise specified.

Anvil Fittings' sizes 1" NPS to 10" NPS (25 to 250 DN) shown in this section are included in the "List of Inspected Fire Protection Equipment and Materials" issued by the Underwriters' Laboratories, Inc.

Coatings

Flanged fittings are available in both black and galvanized. Consult an Anvil Representative for available sizes.

Sizes

To avoid delay in shipment, where other than sizes given are ordered, we carry in stock reducing flanges, the use of which, in connection with straight or reducing fittings carried in stock, enable us to fill orders promptly for reducing sizes where specifications will permit reduction made in this manner. The reducing flanges furnished are the same thickness as the regular companion flange of the corresponding outside diameter and will be drilled to the template corresponding to the outside diameter unless otherwise ordered. For fittings reduced in this manner, please specify "reduce by flanges if necessary."

To order reducing companion flanges, specify threaded or reduced size first and follow with outside diameter. For instance, if

a reducing flange is required to connect a 4-inch (100 DN) pipe to a 6-inch (150 DN) valve or fitting having a 12 1/2" (315 DN) flange, order a 4 NPS x 12 1/2 NPS (100 x 315 DN) reducing flange.

Dimensions

All Extra Heavy or "Class 250" Cast Iron Flanged Fittings have a raised face (for gaskets) 1/16-inch (2mm) high inside of bolt holes. For bolts 1 1/8-inch (29mm) smaller, the bolt hole is drilled 1/8-inch (3mm) larger than the diameter of bolt. Bolt holes straddle the center line and the steel bolts with square heads and hex nuts are recommended.


Reducing elbows have same center to face dimensions as regular elbows of the largest straight size.

Reducing tees NPS 12 (300 DN) and smaller have the same center-to-face and face-to-face dimensions as a straight fitting of the size of the largest opening. Dimensions for larger sizes furnished upon request.

Tolerances

An inspection limit of plus or minus 1/32 inch (1mm) is allowed on all center to contact surface dimensions for sizes up to and including 10 NPS (250 DN) and plus or minus 1/16 inch (2mm) on sizes larger than 10 NPS (250 DN). Inspection limit of plus or minus 1/16 inch (2mm) is allowed on all contact surface to contact surface dimensions for sizes up to and including 10 NPS (250 DN); plus or minus 1/8 inch (3mm) on sizes larger than 10 NPS (250 DN).

Method of designating location of tapped holes for drains when specified Class 125 (standard) and Class 250 (extra heavy)



Note: See page 63 for pressure-temperature ratings.

Cast Iron Flanged Fittings

Class 250 (Extra Heavy)


FIGURE 831 90° Flanged Elbow	Size		A		Flange Diameter		Flange Thickness		Dia. of Raised Face		Wall Thickness of Body		Unit Weight	
													Black	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
	2	50	5	127	6½	165	7⁄8	22	4³⁄₁₆	106	7⁄₁₆	11	20.00	9.07
	2½	65	5½	140	7½	191	1	25	4¹⁵⁄₁₆	125	½	13	30.00	13.61
	3	80	6	152	8¼	210	1⅛	29	5¹¹⁄₁₆	144	9⁄₁₆	14	40.00	18.14
	4	100	7	178	10	254	1¼	32	6¹⁵⁄₁₆	176	5⁄8	16	65.00	29.48
	6	150	8½	216	12½	318	1⅞	37	9¹¹⁄₁₆	246	¾	19	115.00	52.15
	8	200	10	254	15	381	1⅝	41	11¹⁵⁄₁₆	303	1³⁄₁₆	22	185.00	83.90


FIGURE 841 Flanged Tee																	
		Size	Min. Inside Diam. of Flange		J	HH	Flange Diam.		Min. Flange Thickness	Diam. of Raised Face		Min. Wall Thickness of Body	Unit Weight				
													Black				
		NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
	2½	65	2½	64	5½	140	11	279	7½	191	1	25	4 ¹⁵ / ₁₆	125	½	13	46.00 20.86
	3	80	3	76	6	152	12	305	8¼	210	1⅛	29	5 ¹¹ / ₁₆	144	9/ ₁₆	14	58.00 26.30
	4	100	4	102	7	178	14	356	1¼	32	6 ¹⁵ / ₁₆	176	5/ ₈	16	99.00 44.90		
	6	150	6	152	8½	216	17	432	1⅞	37	9 ¹¹ / ₁₆	246	¾	19	180.00 81.63		
	8	200	8	203	10	254	20	508	15	381	1⅝	41	11 ¹⁵ / ₁₆	303	1 ³ / ₁₆	22	280.00 126.98


FIGURE 842 Flanged Reducing Tee	Size Reducing						Unit Weight	
							Black	
	NPS	DN	NPS	DN	NPS	DN	lbs	kg
	6	150	6	150	4	100	160.00	72.56
	8	200	8	200	6	150	257.00	116.55

Dimensions for reducing tees for sizes listed 16 NPS (400 DN) and smaller have same center to face dimension as straight size fittings corresponding to the largest opening. Dimensions of sizes not listed furnished on request.

Note: See page 63 for pressure-temperature ratings.

Cast Iron Flanged Fittings


Class 250 (Extra Heavy)

FIGURE 855 Flanged Concentric Reducer	Size				G		Unit Weight	
							Black	
	NPS	DN	NPS	DN	in	mm	lbs	kg
	3	80	2	50	6	152	25.00	11.34
			2 1/2	65			29.00	13.15
	4	100	2 1/2	65	7	178	40.00	18.14
			3	80			44.00	19.95
	6	150	3	80	9	229	67.00	30.39
			4	100			77.00	34.92
			5	125			85.00	38.55
	8	200	4	100	11	279	105.00	47.62
			6	150			130.00	58.96
	10	250	6	150	12	305	170.00	77.10
			8	200			190.00	86.17

Iron Flanges

Class 125 (Standard)

Class 125 (Standard) Iron Flanges are manufactured to American National Standard ASME B16.1.


FIGURE 1011 Companion Flange	Pipe Size		Diam. of Flange O		Min. Flange Thickness Q		Min. Diam. of Hub X		Min. Length Through Hub Y		Unit Weight			
											Black		Galv.	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
 When ordering companion flanges, always give outside diameter as well as nominal pipe size.	3/4	20	3 7/8	98	7/16	11	1 3/4	44	5/8	16	1.50	0.68	1.50	0.68
	1	25	4 1/4	108	7/16	11	1 15/16	49	11/16	17	1.75	0.79	1.75	0.79
	1 1/4	32	4 5/8	117	1/2	13	2 5/16	59	13/16	22	2.00	0.91	2.00	0.91
	1 1/2	40	5	127	9/16	14	2 9/16	65	7/8	22	2.25	1.02	2.25	1.02
	2	50	6	152	5/8	16	3 1/16	78	1	25	4.00	1.81	4.00	1.81
	2 1/2	65	7	178	11/16	17	3 9/16	90	1 1/8	29	6.00	2.72	6.00	2.72
	3	80	7 1/2	191	3/4	19	4 1/4	108	1 3/16	30	7.63	3.46	7.63	3.46
	3 1/2	90	8 1/2	216	13/16	22	4 13/16	124	1 1/4	32	9.00	4.08	—	—
	4	100	9	229	15/16	24	5 5/16	135	1 5/16	33	11.75	5.33	11.75	5.33
	5	125	10	254	15/16	24	6 7/16	164	1 7/16	37	14.00	6.35	14.00	6.35
	6	150	11	279	1	25	7 9/16	192	1 9/16	40	16.50	7.48	16.50	7.48
	8	200	13 1/2	343	1 1/8	29	9 11/16	246	1 3/4	44	26.00	11.79	26.00	11.79
	10	250	16	406	1 3/16	30	11 15/16	303	1 15/16	49	37.75	17.12	37.75	17.12
	12	300	19	483	1 1/4	32	14 1/16	357	2 3/16	56	50.50	22.90	50.50	22.90

Note: See page 63 for pressure-temperature ratings.

Iron Flanges

Class 125 (Standard)

Class 125 (Standard) Iron Flanges are manufactured to American National Standard ASME B16.1.

FIGURE 1016 Reducing Flange	Pipe Size		Diam. of Flange O		Min. Flange Thickness Q		Min. Diam. of Hub X		Min. Length Thru Hub Y		Unit Weight			
											Black		Galv.	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
	1	25	5	127	9/16	14	1 15/16	49	1 1/16	17	2.75	1.25	—	—
	1 1/4	32					2 5/16	59	1 3/16	22	2.50	1.13	—	—
	1	25	6	152	5/8	16	1 15/16	49	1 1/16	17	5.00	2.27	—	—
	1 1/4	32					2 5/16	59	1 3/16	22	4.75	2.15	—	—
	1 1/2	40					2 9/16	65	7/8	22	4.50	2.04	4.50	2.04
	1 1/2	40	7	178	1 1/16	27	2 9/16	65	7/8	22	7.00	3.17	7.00	3.17
	2	50					3 1/16	78	1	25	6.75	3.06	6.75	3.06
	1	25	7 1/2	191	3/4	19	1 15/16	49	1 3/16	22	9.00	4.08	—	—
	1 1/2	40					2 9/16	65	7/8	22	8.75	3.97	8.75	3.97
	2	50					3 1/16	78	1	25	8.50	3.85	8.50	3.85
	2 1/2	65					3 9/16	90	1 1/8	29	8.00	3.63	8.00	3.63
	3	80	8 1/2	203	1 3/16	30	4 1/4	108	1 3/16	30	10.00	4.54	—	—
	1 1/2	40	9	229	1 5/16	33	2 9/16	65	1	25	14.00	6.35	14.00	6.35
	2	50					3 1/16	78	1	25	14.00	6.35	14.00	6.35
	2 1/2	65					3 9/16	90	1 1/8	29	13.50	6.12	13.50	6.12
	3	80					4 1/4	108	1 3/16	30	12.75	5.78	12.75	5.78
	3 1/2	90					4 13/16	124	1 1/4	32	12.00	5.44	—	—
	3	80	10	254	1 5/16	33	4 1/4	108	1 3/16	30	17.00	7.71	17.00	7.71
	4	100					5 5/16	135	1 5/16	33	16.00	7.26	16.00	7.26
	1 1/2	40	11	279	1	25	2 9/16	65	1 1/16	27	27.00	12.24	—	—
	2	50					3 1/16	78	1 1/16	27	26.00	11.79	26.00	11.79
	2 1/2	65					3 9/16	90	1 1/8	29	25.00	11.34	25.00	11.34
	3	80					4 1/4	108	1 3/16	30	23.00	10.43	23.00	10.43
	4	100					5 5/16	135	1 5/16	33	21.00	9.52	21.00	9.52
	5	125	13 1/2	343	1 1/8	29	6 7/16	164	1 7/16	37	19.00	8.62	19.00	8.62
	2	50					3 1/16	78	1 3/16	30	44.00	19.95	—	—
	3	80					4 1/4	108	1 3/16	30	40.00	18.14	40.00	18.14
	4	100					5 5/16	135	1 5/16	33	37.00	16.78	37.00	16.78
	5	125					6 7/16	164	1 7/16	37	34.00	15.42	—	—
	6	150					7 9/16	192	1 9/16	40	31.00	14.06	31.00	14.06
	6	150	16	406	1 3/16	30	7 9/16	192	1 9/16	40	53.00	24.04	—	—
	8	200					9 11/16	246	1 3/4	44	50.00	22.68	—	—
	6	150	19	483	1 1/4	32	7 9/16	192	1 9/16	40	88.00	39.91	—	—
	8	200					9 11/16	246	1 3/4	44	81.00	36.73	—	—



To order reducing companion flanges, specify threaded or reduced size first, then the outside diameter of desired flange. For instance, if a reducing flange is required to connect a 5 NPS (125 DN) pipe to an 8 NPS (200 DN) valve or fitting having a 13 1/2 inch (338 DN) OD flange, order 5 NPS x 13 1/2 inch (125 x 338 DN) reducing flange.

Note: See page 63 for pressure-temperature ratings.

Iron Flanges

Class 125 (Standard)


Class 125 (Standard) Iron Flanges are manufactured to American National Standard ASME B16.1.

FIGURE 1018 Blind Flange	Pipe Size I		Diam. of Flange O		Min. Flange Thickness Q		Wall Thickness V		Unit Weight			
	NPS	DN	in	mm	in	mm	in	mm	Black		Galv.	
 10 x 16 (NPS) and smaller	1	25	4 1/4	108	7/16	11	3/8	10	2.00	0.91	2.00	0.91
	1 1/4	32	4 5/8	117	1/2	13	7/16	11	2.25	1.02	2.25	1.02
	1 1/2	40	5	127	9/16	14	1/2	13	3.75	1.70	—	—
	2	50	6	152	5/8	16	9/16	14	4.00	1.81	4.00	1.81
	2 1/2	65	7	178	11/16	17	5/8	16	6.75	3.06	—	—
	3	80	7 1/2	191	3/4	19	11/16	17	8.00	3.63	8.00	3.63
 12 x 19 (NPS) and larger	3 1/2	90	8 1/2	216	13/16	22	3/4	19	11.00	4.99	—	—
	4	100	9	229	15/16	24	7/8	22	14.00	6.35	14.00	6.35
	5	125	10	254	15/16	24	7/8	22	18.00	8.16	18.00	8.16
	6	150	11	279	1	25	15/16	24	23.00	10.43	23.00	10.43
	8	200	13 1/2	343	1 1/8	29	1 1/16	27	40.00	18.14	40.00	18.14
	10	250	16	406	1 3/16	30	1 1/8	29	59.00	26.76	—	—
	12	300	19	483	1 1/4	32	1 3/16	22	88.00	39.91	—	—

All Class 125 cast iron standard flanges have a flat face. Blind Flange 12 x 19 NPS supplied dished with inside radius to the pipe diameter. When ordering blind flanges, always give the outside diameters.

Iron Flanges

Class 250 (Extra Heavy)

FIGURE 1025 Companion Flange											
Pipe Size		Diam. of Flange O	Min. Flange Thickness Q	Min. Hub Diameter X	Min. Length Thru Hub Y	Min. Length of Threads T	Diam. of Raised Face W	Unit Weight			
								Black	Galv.		
NPS	DN	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
1¼	32	5¼	133	¾	19	2½	64	3.75	1.70	—	—
1½	40	6⅛	156	13⁄16	22	2¾	70	5.75	2.61	—	—
2	50	6½	165	7⁄8	22	3⅝	84	6.50	2.95	6.50	2.95
2½	65	7½	191	1	25	3⅝	100	9.50	4.31	9.50	4.31
3	80	8¼	210	1⅛	29	4⅝	117	12.33	5.59	12.33	5.59
4	100	10	254	1¼	32	5¾	146	20.00	9.07	20.00	9.07
5	125	11	279	1⅜	35	7	178	—	—	—	—
6	150	12½	318	1⅞	37	8⅞	206	32.00	14.51	—	—
8	200	15	381	1⅝	41	10¼	260	51.00	23.13	—	—

Note: See page 63 for pressure-temperature ratings.

Iron Flanges

Class 250 (Extra Heavy)



FIGURE 1030 Reducing Flange	Pipe Size		Diam. of Flange O		Min. Flange Thickness Q		Min. Length Thru Hub Y		Min. Length of Threads T		Diam. of Raised Face W		Unit Weight	
													Black	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
	2	50	8 ¹ / ₄	210	1 ¹ / ₈	29	1 ¹ / ₄	32	1.00	25	5 ¹¹ / ₁₆	144	14.25	6.46
	2 ¹ / ₂	65	8 ¹ / ₄	210	1 ¹ / ₈	29	1 ⁷ / ₁₆	37	1.14	29	5 ¹¹ / ₁₆	144	13.50	6.12
	3	80	10	254	1 ¹ / ₄	32	1 ⁹ / ₁₆	40	1.20	30	6 ¹⁵ / ₁₆	176	22.75	10.32
	4	100	11	279	1 ³ / ₈	35	1 ³ / ₄	44	1.30	33	8 ⁵ / ₁₆	211	30.00	13.61

FIGURE 1021 Blind Flange	Pipe Size		Diam. of Flange O		Diam. of Port I		Min. Flange Thickness Q		Min. Metal Thickness V		Unit Weight	
											Black	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
	1 ¹ / ₂	40	6 ¹ / ₈	156	1 ¹ / ₂	38	1 ³ / ₁₆	22	—	—	5.30	2.40
	2	50	6 ¹ / ₂	165	2	51	7 ⁷ / ₈	22	—	—	7.00	3.17
	2 ¹ / ₂	65	7 ¹ / ₂	191	2 ¹ / ₂	64	1	25	—	—	11.00	4.99
	3	80	8 ¹ / ₄	210	3	76	1 ¹ / ₈	29	—	—	14.00	6.35
	4	100	10	254	4	102	1 ¹ / ₄	32	—	—	23.00	10.43
	5	125	11	279	5	127	1 ³ / ₈	35	—	—	31.00	14.06
	6	150	12 ¹ / ₂	318	6	152	1 ⁷ / ₁₆	37	—	—	42.00	19.05
	8	200	15	381	8	203	1 ⁵ / ₈	41	—	—	70.00	31.75

High Hub Flanges for C.I. Pipe

FIGURE 1010T Cast Iron Flanges for Cast Iron Pipe	Size		Flange OD		C.I. Pipe O.D.		Flange Thickness		Length thru hub		Unit Weight	
											Black	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
	3	80	7 ¹ / ₂	191	3.96	101	3 ³ / ₄	19	1 ³ / ₄	44	7.50	3.40
	4	100	9	229	4.80	122	1 ⁵ / ₁₆	24	1 ¹⁵ / ₁₆	49	13.00	5.90
	6	150	11	279	6.90	175	1	25	2 ³ / ₁₆	56	17.20	7.80
	8	200	13 ¹ / ₂	343	9.05	230	1 ¹ / ₈	29	2 ⁷ / ₁₆	62	29.00	13.15
	10	250	16	406	11.10	282	1 ³ / ₁₆	30	2 ¹ / ₂	64	42.00	19.05
	12	300	19	483	13.20	335	1 ¹ / ₄	32	2 ¹³ / ₁₆	73	60.00	27.21

Flanges drilled to ASME B16.1. Class 125 Flanges furnished threaded, drilled and faced.

Note: See page 63 for pressure-temperature ratings.

Cast Iron Threaded Fittings

Safety Valve Discharge Elbows

Malleable Iron

Cast Iron

Small Steel Fittings

Pipe Nipples & Pipe Couplings

Forged Steel Fittings & Unions


Anvilets

Catawissa

J.B. Smith Products

Carton Information

FIGURE 1538
Screwed
Cast Iron




Elbow Pipe Size		Riser Pipe Size A		B		C		D		E		F		G		H		J		K		L		Unit Weight	
																								Black	
NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
2½	65	3½	89	2⅞	89	4⅝	110	8½	216	1⅝	41	1⅞	49	2⅛	54	2¾	70	¾	19	—	—	—	—	12.00	5.44
3	80	4	102	3⅛	79	4⅞	124	9½	241	1⅝	41	2⅝	59	2⅞	65	3⅛	79	¾	19	—	—	—	—	15.00	6.80
4	100	5	127	3¾	95	5¾	146	11	279	1¾	44	2⅝	75	3⅛	81	3¾	95	¾	19	—	—	—	—	27.00	12.24
6	150	8	203	5⅛	130	7⅝	194	13¾	349	2	51	4⅝	106	4⅞	116	5	127	¾	19	—	—	—	—	53.00	24.04

Following are the advantages of Anvil safety valve discharge elbow for piping connections to safety valves when attached to boilers, etc.:

- Drip pan for removing condensate and rain water casts integral with elbow.
- Strains on safety valve minimized.
- Pipe tap J is standard.

With multiple pop safety valve, leakage of vapor at any discharge elbow indicates valve in operation.

Street elbows and flanged elbows furnished on order.



Note: See page 37 for pressure-temperature ratings.

Bolt Template

For Drilling Flanged Fittings

Bolt Template for Drilling Flanged Fittings																		
Pipe Size		Flange Dia.		Min. Flange Thickness		Bolt Circle Dia.		No of bolts	Bolt Hole Dia.		Dia. of Bolt		Length of Bolt		Ring Gasket I.D.		Ring Gasket O.D.	
NPS	DN	in	mm	in	mm	in	mm		in	mm	in	mm	in	mm	in	mm	in	mm
¾	20	3⅞	98	⅞	11	2¾	70	4	⅝	16	½	13	1¾	44	1⅞	27	2¼	57
1	25	4¼	108	⅞	11	3⅞	79	4	⅝	16	½	13	1¾	44	1⅞	33	2⅞	67
1¼	32	4⅝	117	½	13	3½	89	4	⅝	16	½	13	2	51	1⅞	42	3	76
1½	40	5	127	⅞	14	3⅞	98	4	⅝	16	½	13	2	51	1⅞	48	3⅞	86
2	50	6	152	⅝	16	4¾	121	4	¾	19	⅝	16	2¼	57	2⅞	60	4⅞	105
2½	65	7	178	1⅞	17	5½	140	4	¾	19	⅝	16	2½	64	2⅞	73	4⅞	124
3	80	7½	191	¾	19	6	152	4	¾	19	⅝	16	2½	64	3½	89	5⅞	137
3½	90	8½	216	1⅞	22	7	178	8	¾	19	⅝	16	2¾	70	4	102	6⅞	162
4	100	9	229	1⅞	24	7½	191	8	¾	19	⅝	16	3	76	4½	114	6⅞	175
5	125	10	254	1⅞	24	8½	216	8	⅞	22	¾	19	3	76	5⅞	141	7¾	197
6	150	11	279	1	25	9½	241	8	⅞	22	¾	19	3¼	83	6⅞	168	8¾	222
8	200	13½	343	1⅞	29	11¾	298	8	⅞	22	¾	19	3½	89	8⅞	219	11	279
10	250	16	406	1⅞	30	14¼	362	12	1	25	⅞	22	3¾	95	10¾	273	13⅞	340
12	300	19	483	1¼	32	17	432	12	1	25	⅞	22	3¾	95	12¾	324	16⅞	410
14 O.D.	350 O.D.	21	533	1⅞	35	18¾	476	12	1⅞	29	1	25	4¼	108	14	356	17¾	451
16 O.D.	400 O.D.	23½	597	1⅞	37	21¼	540	16	1⅞	29	1	25	4½	114	16	406	20¼	514
18 O.D.	450 O.D.	25	635	1⅞	40	22¾	578	16	1¼	32	1⅞	29	4¾	121	18	457	21⅞	549
20 O.D.	500 O.D.	27½	699	1⅞	43	25	635	20	1¼	32	1⅞	29	5	127	20	508	23⅞	606
24 O.D.	600 O.D.	32	813	1⅞	48	29½	749	20	1⅞	35	1¼	32	5½	140	24	610	28¼	718

Drilling templates are in multiples of four, so that fittings may be made to face in any quarter. Bolt holes straddle the center line.

Note: See page 37 for pressure-temperature ratings.

Bolt Template

For Drilling Extra Heavy Flanged Fittings

Bolt Template for Drilling Extra Heavy Flanged Fittings																				
Pipe Size		Flange Dia.		Min. Flange Thickness		Dia. of Raised Face		Bolt Circle Dia.		No of bolts	Dia. of Bolt Holes		Bolt Dia.		Bolt Length		Gasket I.D.		Ring Gasket O.D.	
NPS	DN	in	mm	in	mm	in	mm	in	mm		in	mm	in	mm	in	mm	in	mm	in	mm
1	25	4⅞	124	1⅛	17	2⅛	68	3½	89	4	¾	19	⅝	16	2½	64	1⅝	33	2⅞	51
1¼	32	5¼	133	¾	19	3⅛	78	3⅞	98	4	¾	19	⅝	16	2½	64	1⅔	42	¾	83
1½	40	6⅞	156	1⅜	22	3⅞	90	4½	114	4	⅞	22	¾	19	2¾	70	1⅔	48	¾	95
2	50	6½	165	⅞	22	4⅜	106	5	127	8	¾	19	⅝	16	2¾	70	2⅞	60	4⅞	111
2½	65	7½	191	1	25	4⅝	125	5⅞	149	8	⅞	22	¾	19	¾	83	2⅞	73	5⅞	130
3	80	8¼	210	1⅞	29	5⅛	144	6⅞	168	8	⅞	22	¾	19	3½	89	3½	89	5⅞	149
3½	90	9	229	1⅜	30	6⅝	160	7¼	184	8	⅞	22	¾	19	3½	89	4	102	6½	165
4	100	10	254	1¼	32	6⅝	176	7⅞	200	8	⅞	22	¾	19	¾	95	4½	114	7⅞	181
5	125	11	279	1⅜	35	8⅝	211	9¼	235	8	⅞	22	¾	19	4	102	5⅞	141	8½	216
6	150	12½	318	1⅞	37	9⅛	246	10⅝	270	12	⅞	22	¾	19	4	102	6⅞	168	9⅞	251
8	200	15	381	1⅞	41	11⅝	303	13	330	12	1	25	⅞	22	4½	114	8⅞	219	12⅞	308
10	250	17½	445	1⅞	48	14⅛	357	15¼	387	16	1⅞	29	1	25	5¼	133	10¾	273	14¼	362
12	300	20½	521	2	51	16⅞	418	17¾	451	16	1¼	32	1⅞	29	5½	140	12¾	324	16⅞	422

Drilling templates are in multiples of four, so that fittings may be made to face in any quarter. Bolt holes straddle the center line.

Note: See page 37 for pressure-temperature ratings.

Steel Pipe Bushings & Plugs

Merchant Steel Bushings & Plugs

HEX BUSHINGS 	Nominal Pipe Size		Overall Length		Width Across Flats		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
Canvil Product	1/4 x 1/8	8 x 6	0.625	16	0.625	16	0.02	0.01
	3/8 x 1/8	10 x 6	0.750	19	0.687	17	0.05	0.02
	3/8 x 1/4	10 x 8	0.750	19	0.687	17	0.03	0.01
	1/2 x 1/8	15 x 6	0.875	22	0.875	22	0.11	0.05
	1/2 x 1/4	15 x 8	0.875	22	0.875	22	0.05	0.02
	1/2 x 3/8	15 x 10	0.875	22	0.875	22	0.06	0.03
	3/4 x 1/8	20 x 6	1.000	25	1.062	27	0.21	0.10
	3/4 x 1/4	20 x 8	1.000	25	1.062	27	0.18	0.08
	3/4 x 3/8	20 x 10	1.000	25	1.062	27	0.15	0.07
	3/4 x 1/2	20 x 15	1.000	25	1.062	27	0.10	0.05
	1 x 1/8	25 x 6	1.062	27	1.375	35	0.19	0.09
	1 x 1/4	25 x 8	1.062	27	1.375	35	0.19	0.09
	1 x 3/8	25 x 10	1.062	27	1.375	35	0.19	0.09
	1 x 1/2	25 x 15	1.062	27	1.375	35	0.19	0.09
	1 x 3/4	25 x 20	1.062	27	1.375	35	0.19	0.09

All sizes taper tapped 3/4" per foot (62.5mm per meter) on diameter.

Finish or Coating:

- Black, dipped in rust resistant;
- Galvanized, zinc plated (inside and out). For sizes 1 1/4 (32 DN) and larger, see page 35, 50 and 51 for Malleable and Cast Iron and page 116 for Forged Steel.

COUNTERSUNK PLUGS (Square and Hex Socket)



Nominal Pipe Size		Min. Thread Length		Min. Size of Socket				Metal Thickness Bottom Countersunk		Threads		Unit Weight			
				Square		Hex						Square		Hex	
NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
⅛	6	0.37	9	—	—	⅜ ₁₆	5	0.06	0.06	27	686	0.02	0.01	0.02	0.01
¼	8	0.44	11	¼	6	¼	6	0.09	0.09	18	457	0.04	0.02	0.04	0.02
⅜	10	0.48	12	⅝ ₁₆	8	⅝ ₁₆	8	0.13	0.13	18	457	0.06	0.03	0.06	0.03
½	15	0.56	14	⅜	10	⅜	10	0.16	0.16	14	356	0.12	0.05	0.12	0.05
¾	20	0.63	16	½	8	⅞ ₁₆	14	0.18	0.18	14	356	0.19	0.09	0.19	0.09
1	25	0.75	19	½	8	⅝ ₈	16	0.20	0.20	11½	292	0.22	0.10	0.21	0.10
1¼	32	0.80	20	¾	19	¾	19	0.22	0.22	11½	292	0.37	0.17	0.38	0.17
1½	40	0.83	21	¾	19	1	25	0.24	0.24	11½	292	0.47	0.21	0.44	0.20
2	50	0.88	22	⅞ ₈	22	1	25	0.26	0.26	11½	292	0.84	0.38	0.85	0.39

- All sizes taper tapped — 3/4" per foot (62.5mm per meter) on diameter.

Finish or Coating:

- Black, dipped in rust resistant;
- Galvanized, zinc-plated (inside and out).

SMALL STEEL FITTINGS

Steel Pipe Bushings, Caps & Plugs

Merchant Steel Bushings, Caps & Plugs

FLUSH BUSHINGS	Nominal Pipe Size		Length of External Thread, Min.		Length of Internal Thread, Min.		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/4 x 1/8	8 x 6	0.440	11	0.260	7	0.01	0.00
	3/8 x 1/8	10 x 6	0.480	12	0.250	6	0.03	0.01
	3/8 x 1/4	10 x 8	0.480	12	0.400	10	0.02	0.01
	1/2 x 1/4	15 x 8	0.560	14	0.320	8	0.05	0.02
	1/2 x 3/8	15 x 10	0.560	14	0.410	11	0.03	0.01

CAPS	Nominal Pipe Size		Cap Length		Nominal Width Across Flats		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/8	6	0.563	14	0.560	14	0.02	0.01
	1/4	8	0.844	22	0.625	16	0.03	0.01
	3/8	10	0.813	21	0.870	22	0.06	0.03
	1/2	15	1.063	27	1.062	27	0.11	0.05
	3/4	20	1.114	28	1.183	30	0.14	0.06

SOLID SQUARE HEAD PLUGS	Nominal Pipe Size		Minimum Overall Plug Length		Nominal Width Across Flats		Threads		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg
	1/8	6	0.625	16	9/32	7	27	686	0.02	0.01
	1/4	8	0.687	17	3/8	10	18	457	0.04	0.02
	3/8	10	0.812	21	7/16	11	18	457	0.06	0.03
	1/2	15	0.937	24	9/16	14	14	356	0.12	0.05
	3/4	20	1.062	27	5/8	16	14	356	0.19	0.09
	1	25	1.125	29	13/16	22	11 1/2	292	0.34	0.15
	1 1/4	32	1.360	35	1 5/16	24	11 1/2	292	0.55	0.25
	1 1/2	40	1.450	37	1 1/8	29	11 1/2	292	0.82	0.37
	2	50	1.560	40	1 5/16	34	11 1/2	292	1.35	0.61



Specification

Unless otherwise specified welded nipples ASTM A 53 are furnished on orders for steel nipples in standard and extra strong sizes $\frac{1}{8}$ " – 8" NPS (6 – 200 DN).

Welded steel nipples (A 53 Type F or Type E) are available in standard and extra strong sizes $\frac{1}{8}$ " – 8" NPS (6 – 200 DN), right hand threads, black or galvanized.

Seamless nipples manufactured for the U.S. and International markets are not phosphate coated. Seamless nipples manufactured for Canada are phosphate coated.

Seamless steel pressure tube nipples (ASTM A 106 Grade B) are available in standard and extra strong sizes $\frac{1}{8}$ " – 8" NPS (6 – 200 DN) with right hand threads, black only.

Right and left steel nipples are available in standard and extra heavy weight sizes $\frac{1}{8}$ " – 4" NPS (8 – 50 DN), in 4" (102mm) and 6" (152mm) lengths.

Nipples are available from stock in $\frac{1}{8}$ " – 8" NPS (6 – 200 DN) diameter, close to 12 NPS (300 DN) in length. Sizes 13" – 24" NPS (325 – 600 DN). (Prices on application.)

Steel pipe nipples meet ASTM A733.

Identification

Where possible, each seamless pipe nipple is identified with the following:

- A trade mark
- Seamless designation "SMLS"
- Pipe schedule STD, XS/XH, SCH 160 and XXS/XXH
- Material designation A106 B
- Heat number for traceability

PIPE NIPPLES

Seamless Pipe Nipples

Black & Galvanized, Std. Sch. 40, XH Sch. 80, Sch. 160, XXH



FIG. 320:
Standard
Black Sch. 40

FIG. 325:
Extra Heavy
Black Sch. 80

FIG. 326:
160
Black Sch. 160

FIG. 327:
XXH
Black

FIG. 330:
Standard
Galv. Sch. 40

FIG. 335:
Extra Heavy
Galv. Sch. 80

FIG. 333:
160
Galv. Sch. 160

FIG. 329:
XXH
Galvanized

Material

ASTM A106 Grade B Seamless Pipe

ASTM A333 Grade 6 Seamless Pipe (For Canada only)


Note: Galvanized nipples from Longview Texas plant are electroplated. Galvanized nipples from Beck plant are hot dipped.

Applicable Specification

ASTM A733

(Refer to the chart below for specific pipe dimensions.)

Note: Minimum wall thickness at any point to be not more than 10% over and 3 1/2% under nominal wall thickness specified for that size pipe.



Pipe Size	Pipe O.D.	Length Close	Pipe Nipple Lengths															
in	in	in	1 1/2	2	2 1/2	3	3 1/2	4	4 1/2	5	5 1/2	6	7	8	9	10	11	12
1/8	0.405	3/4																
1/4	0.540	7/8																
3/8	0.675	1																
1/2	0.840	1 1/8																
3/4	1.050	1 3/8																
1	1.315	1 1/2																
1 1/4	1.660	1 7/8																
1 1/2	1.900	1 3/4																
2	2.375	2																
2 1/2	2.875	2 1/2																
3	3.500	2 5/8																
4	4.500	2 7/8																
5	5.563	3																
6	6.625	3 1/8																

Note: Other lengths available.

8" Pipe Size available as POA - contact your Anvil Representative for details.

Welded Pipe Nipples

Black & Galvanized, Std. Sch. 40, XH Sch. 80



Malleable Iron

Cast Iron

Small Steel Fittings

Pipe Nipples & Pipe Couplings

Forged Steel Fittings & Unions

Anvils

Catawissa

J.B. Smith Products

Carton Information



FIG. 339:
Standard
Black Schedule 40

FIG. 338:
Extra Heavy
Black Schedule 80

FIG. 343:
Standard
Galv. Schedule 40

FIG. 342:
Extra Heavy
Galv. Schedule 80

Material

ASTM A53 Standard Specification for Pipe Steel, Black, Galvanized, Hot-Dipped, Zinc Coated, Welded.


Applicable specification

ASTM A733

(Refer to the chart below for specific pipe dimensions.)

Note: Minimum wall thickness at any point to be not more than $\pm 10\%$ nominal wall thickness specified for that size pipe.

Standard and Extra Heavy right and left nipples available in $\frac{1}{8}$ - 4" diameter and 4" and 6" lengths.



Pipe Size	Pipe O.D.	Length Close	Pipe Nipple Lengths															
in	in	in																
⅛	0.405	¾	1½	2	2½	3	3½	4	4½	5	5½	6	7	8	9	10	11	12
¼	0.540	⅞	1½	2	2½	3	3½	4	4½	5	5½	6	7	8	9	10	11	12
⅜	0.675	1	1½	2	2½	3	3½	4	4½	5	5½	6	7	8	9	10	11	12
½	0.840	1⅛	1½	2	2½	3	3½	4	4½	5	5½	6	7	8	9	10	11	12
¾	1.050	1⅜	1½	2	2½	3	3½	4	4½	5	5½	6	7	8	9	10	11	12
1	1.315	1½		2	2½	3	3½	4	4½	5	5½	6	7	8	9	10	11	12
1¼	1.660	1⅞		2	2½	3	3½	4	4½	5	5½	6	7	8	9	10	11	12
1½	1.900	1¾		2	2½	3	3½	4	4½	5	5½	6	7	8	9	10	11	12
2	2.375	2			2½	3	3½	4	4½	5	5½	6	7	8	9	10	11	12
2½	2.875	2½				3	3½	4	4½	5	5½	6	7	8	9	10	11	12
3	3.500	2⅝				3	3½	4	4½	5	5½	6	7	8	9	10	11	12
4	4.500	2⅞						4	4½	5	5½	6	7	8	9	10	11	12
5	5.563	3							4½	5	5½	6	7	8	9	10	11	12
6	6.625	3⅞							4½	5	5½	6	7	8	9	10	11	12

Note: Other lengths available.

8" Pipe Size available as POA - contact your Anvil Representative for details.



PIPE NIPPLES

Steel Pipe Nipples

Welded – Ready Cut Pipe Standard — Schedule 40



“A” ASSORTMENTS

Mixed Cartons (Black — Figure 339 & Galvanized — Figure 343)

Nom. Pipe Size	Close	1½"	2"	2½"	3"	3½"	4"	4½"	5"	5½"	6"	No. of Pieces	Approx. Wt. Lbs.
½	4	3	3	3	2	2	2	1	2	1	2	25	5.00
½	20	10	15	10	10	5	10	5	5	5	5	100	18.00
¾	4	3	3	3	2	2	2	1	2	1	2	25	7.00
¾	20	10	15	10	10	5	10	5	5	5	5	100	24.00
1	15	-	15	10	12	5	5	4	3	3	3	75	24.00
1	5	-	5	3	2	2	2	1	2	1	2	25	10.00
1¼	5	-	5	3	2	2	2	1	2	1	2	25	12.00
1½	5	-	5	3	2	2	2	1	2	1	2	25	15.00
2	6	-	-	3	3	2	3	1	3	1	3	25	22.00

All items ship in bulk quantities.

“66” PACKS OR ASSORTED 6 CARTONS

Black — Figure 339 & Galvanized — Figure 343

Nom. Pipe Size	Close	1½"	2"	2½"	3"	3½"	4"	4½"	5"	5½"	6"	No. of Pieces	Approx. Wt. Lbs.
⅛	6	6	6	6	6	6	6	6	6	6	6	66	6.00
¼	6	6	6	6	6	6	6	6	6	6	6	66	9.00
⅜	6	6	6	6	6	6	6	6	6	6	6	66	12.00
½	6	6	6	6	6	6	6	6	6	6	6	66	14.00
¾	6	6	6	6	6	6	6	6	6	6	6	66	19.00
1	6	-	6	6	6	6	6	6	6	6	6	60	26.00
1¼	6	-	6	6	6	6	6	6	6	6	6	60	33.00
1½	6	-	6	6	6	6	6	6	6	6	6	60	41.00
2	6	-	-	6	6	6	6	6	6	6	6	54	53.00

All items ship in bulk quantities.

HANDY PACK ASSORTMENTS

Mixed Cartons (Black — Figure 339 & Galvanized — Figure 343)

Nom. Pipe Size	Close	1½"	2"	2½"	3"	3½"	4"	4½"	5"	5½"	6"	No. of Pieces	Approx. Wt. Lbs.
⅛	6	6	6	6	6	6	6	6	6	6	6	66	6.00
¼	6	6	6	6	6	6	6	6	6	6	6	66	9.00
⅜	6	6	6	6	6	6	6	6	6	6	6	66	12.00
½	6	6	6	6	6	6	6	6	6	6	6	66	14.00
¾	6	6	6	6	6	6	6	6	6	6	6	66	19.00
1	6	-	6	6	6	6	6	6	6	6	6	60	26.00
1¼	3	-	-	3	3	3	3	3	3	3	3	27	19.00
1½	3	-	-	3	3	3	3	3	3	3	3	27	23.00
2	3	-	-	3	3	3	3	3	3	3	3	27	30.00

All items ship in bulk quantities.

Steel Pipe Nipples

Welded – Ready Cut Pipe Standard — Schedule 40, XH Sch. 80



READY CUT PIPE

Black Extra Long— Figure 339 & Galvanized — Figure 343

Nom. Pipe Size	18"	24"	30"	36"	42"	48"	54"	60"	66"	72"
1/8	5	5	5	5	5	5	5	5	5	5
1/4	5	5	5	5	5	5	5	5	5	5
3/8	5	5	5	5	5	5	5	5	5	5
1/2	5	5	5	5	5	5	5	5	5	5
3/4	5	5	5	5	5	5	5	5	5	5
1	3	3	3	3	3	3	3	3	3	3
1 1/4	3	3	3	3	3	3	3	3	3	3
1 1/2	3	3	3	3	3	3	3	3	3	3
2	2	2	2	2	2	2	2	2	2	2

SINGLE RUN PACKS

Black — Figure 339 & Galvanized — Figure 343

Nom. Pipe Size	Close	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	4 1/2"	5"	5 1/2"	6"	No. of Pieces	Approx. Wt. Lbs.
1/8	1	1	1	1	1	1	1	1	1	1	1	11	1.00
1/4	1	1	1	1	1	1	1	1	1	1	1	11	1.50
3/8	1	1	1	1	1	1	1	1	1	1	1	11	2.00
1/2	1	1	1	1	1	1	1	1	1	1	1	11	2.50
3/4	1	1	1	1	1	1	1	1	1	1	1	11	3.50
1	1	-	1	1	1	1	1	1	1	1	1	10	5.00
1 1/4	1	-	1	1	1	1	1	1	1	1	1	10	7.00
1 1/2	1	-	1	1	1	1	1	1	1	1	1	10	8.00
2	1	-	-	1	1	1	1	1	1	1	1	9	10.00
2 1/2	1	-	-	-	1	1	1	1	1	1	1	8	13.30
3	1	-	-	-	1	1	1	1	1	1	1	8	15.80

All items ship in bulk quantities.

SINGLE RUN PACKS

Black Only Extra Heavy — Figure 338

Nom. Pipe Size	Close	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	4 1/2"	5"	5 1/2"	6"	No. of Pieces	Approx. Wt. Lbs.
1/2	1	1	1	1	1	1	1	1	1	1	1	11	3.20
3/4	1	1	1	1	1	1	1	1	1	1	1	11	4.30
1	1	-	1	1	1	1	1	1	1	1	1	10	6.10
1 1/4	1	-	1	1	1	1	1	1	1	1	1	10	8.40
1 1/2	1	-	1	1	1	1	1	1	1	1	1	10	10.30
2	1	-	-	1	1	1	1	1	1	1	1	9	13.90

All items ship in bulk quantities.

TRAVEL TRAYS (Black & Galvanized)

Nom. Pipe Size	Close	1 1/2"	2"	2 1/2"	3"	3 1/2"	4"	4 1/2"	5"	5 1/2"	6"	No. of Pieces	Approx. Wt. Lbs.
1/2	6	6	6	6	6	6	6	6	6	6	6	66	15.00
3/4	6	6	6	6	6	6	6	6	6	6	6	66	20.00
1	5	-	5	5	5	5	5	5	5	5	5	50	22.00

All items ship in bulk quantities.



Steel Pipe Nipples – Welded



TANK NIPPLES

Black — Figure 339 & Galvanized — Figure 343

Nom. Pipe Size	Length	Weight	Quantity
1/8	6	0.13	-
1/4	6	0.20	-
3/8	6	0.28	-
1/2	6	0.40	-
3/4	6	0.53	-
1	6	0.76	-
1 1/4	6	1.04	-
1 1/2	6	1.28	-
2	6	1.56	-

Tank nipples are recommended for use as tank legs. One end has the standard tapered pipe thread and the other end has a straight running thread 4" long. All Tank Nipples ship in quantities of 25.

BUTT NIPPLES

Black — Figure 339 & Galvanized — Fig. 343

Nom. Pipe Size	Weight	Quantity
1/8 x 1/2	0.02	-
1/4 x 3/4	0.03	-
3/8 x 3/4	0.04	-
1/2 x 3/4	0.04	-
3/4 x 1	0.06	-
1 x 1	0.10	-
1 1/4 x 1	0.16	-
1 1/2 x 1 1/4	0.17	-
2 x 1 1/4	0.28	-
2 1/2 x 2	0.87	-
3 x 2	1.28	-
4 x 2 1/4	1.11	-

RIGHT & LEFT NIPPLES

Black — Figure 339 & Galvanized — Figure 343

Nom. Pipe Size	Length	Weight	Quantity
1/8	4" or 6"	0.09	-
1/4	4" or 6"	0.13	-
3/8	4" or 6"	0.18	25
1/2	4" or 6"	0.25	25
3/4	4" or 6"	0.35	25
1	4" or 6"	0.51	25
1 1/4	4" or 6"	0.68	25
1 1/2	4" or 6"	0.80	25
2	4" or 6"	1.09	25
2 1/2	4" or 6"	1.50	-
3	4" or 6"	2.00	-
3 1/2	4" or 6"	2.80	-
4	4" or 6"	3.24	-

Specialty Fabrication



Malleable Iron

Cast Iron

Small Steel Fittings

Pipe Nipples & Pipe Couplings

Forged Steel Fittings & Unions

Anvils

Catawissa

J.B. Smith Products

Carton Information

1. STEEL NIPPLES

- a. NPT (TOE) x Plain end
- b. NPT (TOE) x Plain end square cut
- c. NPT (TOE) x Plain end square cut and deburred (Bevel, Ream?)
- d. NPT (TOE) x Ream other end(ROE)
- e. Plain end x Plain end (cut blank)(roller cut)(square cut) (B&O cut)
- f. ROE x ROE (Ream x Ream)
- g. NPT (TOE) x Bevel (Specify Bevel, ex. Weld Bevel, 45 degree bevel, etc.)
- h. Bevel x Bevel (Specify Bevel)
- i. NPT (TOE) x Straight Thd (Specify NPSL or NPSM) (depends on nipple length)(Straight thread length can be longer than normal thread length if necessary)
- j. Straight Thd x Straight Thd (Specify NPSL or NPSM) (nipple length restrictions)
- k. Straight Thread x British Standard Pipe Thread
- l. NPT (TOE) x BPST
- m. BSPT x BSPT
- n. BSPT x Plain end square cut
- o. BSPT x Plain end square cut and deburred
- p. BSPT x ROE
- q. BSPT x Groove
- r. BSPT X Left Hand Thread
- s. Right Hand Thread x Left Hand Thread
- t. Left Hand Thread x Left Hand Thread
- u. Left Hand x Plain end
- v. LH x Plain end square cut
- w. LH x Plain end square cut and deburred
- x. LH x ROE
- y. LH x Straight Thd (Specify NPSL or NPSM)
- z. LH x Groove
- aa. Grooving of nipples (grooving is outsourced)
- bb. Sandblasting of nipples (length restrictions)
- cc. Phosphate finish for nipples
- dd. Vibra-Seal coated threads for nipples
- ee. Yellow Di-chromate plating of nipples (length restrictions)
- ff. Galvanized plating of threads for nipples (length restrictions)
- gg. Chrome plating of Brass nipples (length restrictions)
- hh. Any length of nipple from close to 120" in increments of 1/16 of an inch
- ii. Nipple w/NPT tapped hole on the side.
- jj. Flat ream.
- kk. Stamping.
- ll. Stainless Steel Specification ASTM A312 Grade 316 & 304 (Sch. 40 & 80)
- mm. Tank Nipples
- nn. Butt Nipples
- oo. Stainless Steel
- pp. Individually Bar Coded product also available.

NPT National Pipe Thread

NPSL Straight Thread – Locknut

NPSM Straight Thread – Mechanical

BPST British Standard Thread

2. STEEL COUPLINGS

- a. Phosphating
- b. Special Lengths

Steel Pipe Couplings

Merchant Couplings



FIGURE 336
Standard, Full & Half



Size		Outside Diameter (Coupling)		Length				Threads		Unit Weight							
				Full		Half				Full				Half			
										Straight Tapped		Taper Tapped		Straight Tapped		Taper Tapped	
NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg	lbs	kg	lbs	kg	lbs	kg
⅛	6	0.563	14	1⅜	22	1⅛	9	27	686	0.03	0.01	0.03	0.01	0.01	0.00	0.01	0.00
¼	8	0.719	18	1⅜	30	1⅞	13	18	457	0.07	0.03	0.07	0.03	0.03	0.01	0.03	0.01
⅜	10	0.875	22	1⅜	30	1⅞	13	18	457	0.10	0.05	0.10	0.05	0.05	0.02	0.05	0.02
½	15	1.063	27	1⅞	40	2⅜	18	14	356	0.18	0.08	0.18	0.08	0.08	0.04	0.08	0.04
¾	20	1.313	33	1⅝	41	¾	19	14	356	0.26	0.12	0.26	0.12	0.12	0.05	0.12	0.05
1	25	1.576	40	2	51	1⅝	24	11½	292	0.42	0.19	0.42	0.19	0.18	0.08	0.18	0.08
1¼	32	1.900	48	2⅞	52	3⅞	25	11½	292	0.50	0.23	0.50	0.23	0.23	0.10	0.23	0.10
1½	40	2.200	56	2⅞	52	3⅞	25	11½	292	0.67	0.30	0.67	0.30	0.32	0.15	0.32	0.15
2	50	2.750	70	2⅞	54	1	25	11½	292	1.03	0.47	1.03	0.47	0.47	0.21	0.47	0.21
2½	65	3.250	83	3⅞	79	1½	38	8	203	2.09	0.95	2.15	0.98	0.96	0.44	0.96	0.44
3	80	4.000	102	3¼	83	1⅞	40	8	203	3.36	1.52	3.46	1.57	1.60	0.73	1.60	0.73
3½	90	4.625	117	3⅞	86	1⅝	41	8	203	4.82	2.19	5.18	2.35	2.22	1.01	2.22	1.01
4	100	5.000	127	3½	89	1⅞	43	8	203	4.80	2.18	4.87	2.21	2.11	0.96	2.11	0.96
5	125	6.296	160	3¾	95	1⅞	46	8	203	8.31	3.77	8.75	3.97	3.80	1.72	3.80	1.72
6	150	7.390	188	4	102	1⅞	46	8	203	11.18	5.07	11.88	5.39	5.28	2.39	5.28	2.39

- Manufactured in accordance with ASTM specification A865 and A589.
- Merchant couplings in sizes 1/8" NPS (6 DN) through 2" NPS (50 DN) are normally supplied straight tapped. Sizes 2 1/2" NPS (65 DN) and larger are taper tapped.
- Taper tapped standard merchant couplings in sizes 1/8" NPS (6 DN) through 2" NPS (50 DN) are available upon request.
- API line pipe couplings are used in all sizes over 6" NPS (150 DN).
- Couplings from 1/8" NPS (6 DN) through 6" NPS (150 DN) are dipped in rust preventative.
- Galvanized full couplings are also available.

Note

- Half couplings are chamfered on one end and squared on the other.

Steel Pipe Couplings

Merchant Couplings



FIGURE 337
Extra Strong (XS), Full & Half



Size		Outside Diameter (Coupling)		Length				Unit Weight			
				Full		Half		Non-Recessed			
								Full		Half	
NPS	DN	in	mm	in	mm	in	mm	lbs	kg	lbs	kg
1/8	6	0.563	14	1 1/16	27	15/32	12	0.04	0.02	0.02	0.01
1/4	8	0.719	18	1 3/8	41	3/4	19	0.09	0.04	0.04	0.02
3/8	10	0.875	22	1 3/8	41	3/4	19	0.14	0.06	0.06	0.03
1/2	15	1.063	27	2 1/8	54	1	25	0.25	0.11	0.11	0.05
3/4	20	1.313	33	2 1/8	54	1	25	0.36	0.16	0.17	0.08
1	25	1.576	40	2 5/8	67	1 1/4	32	0.56	0.25	0.26	0.12
1 1/4	32	2.054	52	2 3/4	70	1 5/16	33	1.08	0.49	0.51	0.23
1 1/2	40	2.200	56	2 3/4	70	1 5/16	33	0.98	0.44	0.61	0.28
2	50	2.875	73	2 7/8	73	1 3/8	35	2.01	0.91	0.92	0.42
2 1/2	65	3.375	86	4 1/8	105	2	51	3.53	1.60	1.72	0.78
3	80	4.000	102	4 1/4	108	2 1/16	52	4.61	2.09	2.12	0.96

- Manufactured in accordance with ASTM Specification A865.
- All sizes are taper tapped.
- Non-recessed couplings will be supplied for sizes under 6" NPS unless otherwise specified.
- Extra strong half couplings can be supplied in sizes under 6" NPS (150 DN).
- Couplings 1/8" – 6" NPS (6 – 150 DN) are dipped in rust preventative.
- Galvanized full couplings are also available.

Note

- Half couplings are chamfered on one end and squared on the other.

Steel Pipe Couplings

Merchant Couplings



FIGURE 346 Standard, Right & Left	Size		Outside Diameter (Coupling)		Length		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	½	15	1.063	27	1⅞	40	0.17	0.08
	¾	20	1.313	33	1⅝	41	0.28	0.13
	1	25	1.576	40	2	51	0.43	0.20
	1¼	32	1.900	48	2⅞	52	0.54	0.24
	1½	40	2.200	56	2⅞	52	0.73	0.33
	2	50	2.750	70	2⅝	54	1.11	0.50



Note

- The left hand threaded end of all right and left couplings is knurled for identification. All sizes of right and left couplings are taper tapped ¾" per foot (62.5mm per meter) on the diameter and all are dipped in rust preventative.

FIGURE 347 Extra Strong (XS), Right & Left	Size		Outside Diameter (Coupling)		Length		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	½	15	1.063	27	2⅞	54	0.25	0.11
	¾	20	1.313	33	2⅞	54	0.36	0.16
	1	25	1.576	40	2⅞	67	0.74	0.34
	1¼	32	2.054	52	2¾	70	1.08	0.49
	1½	40	2.200	56	2¾	70	0.95	0.43
	2	50	2.875	73	2⅞	73	2.01	0.91



- The left hand threaded end of all right and left couplings is knurled for identification, and all are dipped in rust preventative.
- Extra strong right and left couplings are available on request.

Steel Pipe Couplings



FIGURE 348
API Line Pipe Couplings



Size		Outside Diameter (Coupling)		Length		Unit Weight	
NPS	DN	in	mm	in	mm	lbs	kg
1/8	6	0.563	14	1 1/16	27	0.04	0.02
1/4	8	0.719	18	1 5/8	41	0.10	0.05
3/8	10	0.875	22	1 5/8	41	0.13	0.06
1/2	15	1.063	27	2 1/8	54	0.24	0.11
3/4	20	1.313	33	2 1/8	54	0.35	0.16
1	25	1.576	40	2 5/8	67	0.52	0.24
1 1/4	32	2.054	52	2 3/4	70	1.00	0.45
1 1/2	40	2.200	56	2 3/4	70	0.88	0.40
2	50	2.875	73	2 7/8	73	1.83	0.83
2 1/2	65	3.375	86	4 1/8	105	3.28	1.49
3	80	4.000	102	4 1/4	108	4.09	1.85
3 1/2	90	4.625	117	4 3/8	111	5.92	2.68
4	100	5.200	132	4 1/2	114	7.59	3.44
5	125	6.296	160	4 5/8	117	10.00	4.54
6	150	7.390	188	4 7/8	124	12.92	5.86
8	200	9.625	244	5 1/4	133	23.18	10.51
10	250	11.750	298	5 3/4	146	31.55	14.31
12	300	14.000	356	6 1/8	156	49.27	22.34

- These couplings are manufactured in accordance with American Petroleum Institute Specification 5L.
- All sizes are taper tapped 3/4" per foot (62.5mm per meter) on the diameter.
- All couplings are phosphated unless galvanized.

Steel Pipe Couplings



FIGURE 379 Shallow Well Couplings	Size		Outside Diameter (Coupling)		Length		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	1¼	32	2.054	52	2¾	70	1.03	0.47
	1½	40	2.200	56	2¾	70	0.90	0.41
	2	50	2.875	73	2⅞	73	1.86	0.84

- The 1¼" are Straight Tapped and recessed.
- The 1½" and 2" are Taper Tapped ¾" per foot on diameter and recessed.
- The 2" threads are electroplated.

FIGURE 380 Water Well Reamed & Drifted Couplings	Size		Outside Diameter (Coupling)		Length		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	1¼	32	1.900	48	2¾	70	0.60	0.27
	1½	40	2.200	56	2¾	70	0.84	0.38
	2	50	2.750	70	3⅞	86	1.58	0.72
	2½	65	3.250	83	3⅞	100	2.32	1.05
	3	80	4.000	102	4⅞	103	3.80	1.72
	3½	90	4.625	117	4⅞	106	5.53	2.51
	4	100	5.200	132	4⅞	110	7.14	3.24
	5	125	6.296	160	4½	114	9.57	4.34
	6	150	7.390	188	4⅞	119	12.32	5.59
	8	200	9.625	244	5⅞	129	22.35	10.14
	10	250	11.750	298	5⅞	141	30.60	13.88
	12	300	14.000	356	5⅞	151	48.00	21.77

- Manufactured in accordance with ASTM specification A589.
- All sizes are recessed Taper Tapped ¾" per foot on diameter.
- Sizes over 2" have threads phosphated and outside painted light blue.
The Galvanized have a light blue band around the center of the coupling.

FIGURE 381 #9 Drive Couplings	Size		Outside Diameter (Coupling)		Length		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	1¼	32	2.054	52	2¾	70	1.00	0.45
	1½	40	2.200	56	2¾	70	0.84	0.38
	2	50	2.875	73	3⅞	86	2.14	0.97

- All sizes are Taper Tapped ¾" per foot on diameter.



Materials

The steel for Anvil Forged Carbon Steel Fittings consists of forging, bars, seamless pipe or tubes which conform to the requirements for melting process, chemical composition and mechanical properties of ASTM A105.

Design Basis

ASME B16.11 - Forged fittings, socket-weld and threaded

Dimensions

ASME B16.11, unless otherwise noted

Threads

ANSI/ASME B1.20.1 NPT Threads

Forged Steel Fittings

In accordance with ASME standard B16.11 - "Forged Fittings, Socket-Welding and Threaded" this table shows the schedule of pipe corresponding to each class of fitting for rating purposes.


PRESSURE RATINGS		
Class	Schedule	
	N.P.T.	S.W.
2000	80	—
3000	160	80
6000	XXS/XXH	160

ASME B16.11 provides that the maximum allowable pressure of a fitting be computed in accordance with the applicable piping code or regulation for straight seamless pipe or for material of equivalent composition and mechanical properties to the fitting. Any corrosion or mechanical allowances and any reduction in allowable stress due to temperature or other service conditions must be applied to the pipe and fitting alike.

Reducing Fittings

Reducing elbows, tees and crosses are available in both threaded and socket-welding.

On reducing tees and crosses give the size of the largest run opening; then give the opposite opening. On a tee give the branch size last. On a cross give the largest side outlet third and the opposite opening last.



Forged Steel Fittings

Class 2000 Threaded


FIGURE 2101 90° Elbows	Size		A		H		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	¼	8	0.81	21	0.88	22	0.18	0.08
	⅜	10	0.97	25	1.00	25	0.28	0.13
	½	15	1.12	28	1.31	33	0.55	0.25
	¾	20	1.31	33	1.50	38	0.72	0.33
	1	25	1.50	38	1.81	46	1.22	0.55
	1¼	32	1.75	44	2.19	56	1.65	0.75
	1½	40	2.00	51	2.44	62	2.12	0.96
	2	50	2.38	60	2.97	75	3.78	1.71
	2½	65	3.00	76	3.62	92	6.50	2.95
	3	80	3.38	86	4.31	109	11.10	5.03
	4	100	4.19	106	5.75	146	22.30	10.11

FIGURE 2102 45° Elbows	Size		C		H		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	¼	8	0.69	17	0.88	22	0.16	0.07
	⅜	10	0.75	19	1.00	25	0.25	0.11
	½	15	0.88	22	1.31	33	0.48	0.22
	¾	20	1.00	25	1.50	38	0.57	0.26
	1	25	1.12	28	1.81	46	0.88	0.40
	1¼	32	1.31	33	2.19	56	1.32	0.60
	1½	40	1.38	35	2.44	62	1.62	0.73
	2	50	1.69	43	2.97	75	2.83	1.28
	2½	65	2.06	52	3.62	92	7.70	3.49
	3	80	2.50	64	4.31	109	12.00	5.44

Forged Steel Fittings

Class 2000 Threaded





FIGURE 2103 Tees	Size		A		H		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/4	8	0.81	21	0.88	22	0.25	0.11
	3/8	10	0.97	25	1.00	25	0.37	0.17
	1/2	15	1.12	28	1.31	33	0.62	0.28
	3/4	20	1.31	33	1.50	38	0.43	0.20
	1	25	1.50	38	1.81	46	1.33	0.60
	1 1/4	32	1.75	44	2.19	56	2.10	0.95
	1 1/2	40	2.00	51	2.44	62	2.80	1.27
	2	50	2.38	60	2.97	75	4.50	2.04
	2 1/2	65	3.00	76	3.62	92	9.10	4.13
	3	80	3.38	86	4.31	109	13.50	6.12
	4	100	4.19	106	5.75	146	32.00	14.51


FIGURE 2104 Crosses	Size		A		H		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/4	8	0.81	21	0.88	22	0.50	0.23
	3/8	10	0.97	25	1.00	25	0.40	0.18
	1/2	15	1.12	28	1.31	33	0.85	0.39
	3/4	20	1.31	33	1.50	38	1.10	0.50
	1	25	1.50	38	1.81	46	1.70	0.77
	1 1/4	32	1.75	44	2.19	56	2.40	1.09
	1 1/2	40	2.00	51	2.44	62	3.20	1.45
	2	50	2.38	60	2.97	75	5.20	2.36
	2 1/2	65	3.00	76	3.62	92	16.50	7.48
	3	80	3.38	86	4.31	109	20.00	9.07

Forged Steel Fittings

Class 3000 Threaded


FIGURE 2111 90° Elbows		Size		A		H		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg	
	1/8	6	0.81	21	0.88	22	0.23	0.10	
	1/4	8	0.97	25	1.00	25	0.35	0.16	
	3/8	10	1.12	28	1.31	33	0.66	0.30	
	1/2	15	1.31	33	1.50	38	0.93	0.42	
	3/4	20	1.50	38	1.81	46	1.48	0.67	
	1	25	1.75	44	2.19	56	2.30	1.04	
	1 1/4	32	2.00	51	2.44	62	2.68	1.22	
	1 1/2	40	2.38	60	2.97	75	5.30	2.40	
	2	50	2.50	64	3.31	84	5.85	2.65	
	2 1/2	65	3.25	83	4.00	102	10.00	4.54	
	3	80	3.75	95	4.75	121	17.20	7.80	
	4	100	4.50	114	6.00	152	29.30	13.29	

 	FIGURE 2112 45° Elbows		Size		C		H		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg		
	1/8	6	0.69	17	0.88	22	0.18	0.08		
	1/4	8	0.75	19	1.00	25	0.25	0.11		
	3/8	10	0.88	22	1.31	33	0.53	0.24		
	1/2	15	1.00	25	1.50	38	0.78	0.35		
	3/4	20	1.12	28	1.81	46	1.20	0.54		
	1	25	1.31	33	2.19	56	1.90	0.86		
	1 1/4	32	1.38	35	2.44	62	2.30	1.04		
	1 1/2	40	1.69	43	2.97	75	4.16	1.89		
	2	50	1.72	44	3.31	84	5.12	2.32		
	2 1/2	65	2.06	52	4.00	102	7.70	3.49		
	3	80	2.50	64	4.75	121	12.00	5.44		
4	100	3.12	79	6.00	152	19.70	8.93			

	FIGURE 2114 Tees		Size		A		H		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg
	1/8	6	0.81	21	0.88	22	0.31	0.14		
	1/4	8	0.97	25	1.00	25	0.42	0.19		
	3/8	10	1.12	28	1.31	33	0.93	0.42		
	1/2	15	1.31	33	1.50	38	1.20	0.54		
	3/4	20	1.50	38	1.81	46	1.84	0.83		
	1	25	1.75	44	2.19	56	3.05	1.38		
	1 1/4	32	2.00	51	2.44	62	3.62	1.64		
	1 1/2	40	2.38	60	2.97	75	6.65	3.02		
	2	50	2.50	64	3.31	84	7.15	3.24		
	2 1/2	65	3.25	83	4.00	102	13.70	6.21		
	3	80	3.75	95	4.75	121	21.00	9.52		
4	100	4.50	114	6.00	152	38.00	17.23			

Forged Steel Fittings

Class 3000 Threaded

FIGURE 2115 Crosses		Size		A		H		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg	
	1/8	6	0.81	21	0.88	22	—	—	
	1/4	8	0.97	25	1.00	25	—	—	
	3/8	10	1.12	28	1.31	33	—	—	
	1/2	15	1.31	33	1.50	38	1.40	0.63	
	3/4	20	1.50	38	1.81	46	2.10	0.95	
	1	25	1.75	44	2.19	56	3.50	1.59	
	1 1/4	32	2.00	51	2.44	62	4.30	1.95	
	1 1/2	40	2.38	60	2.97	75	8.20	3.72	
	2	50	2.50	64	3.31	84	8.40	3.81	
	2 1/2	65	3.25	83	4.00	102	17.10	7.76	
	3	80	3.75	95	4.75	121	20.00	9.07	
	4	100	4.50	114	6.00	152	32.00	14.51	



		Size		A		G		H		Unit Weight	
		NPS	DN	in	mm	in	mm	in	mm	lbs	kg
		1/8	6	0.75	19	1.00	25	0.75	19	—	—
		1/4	8	0.88	22	1.25	32	1.00	25	0.23	0.10
		3/8	10	1.00	25	1.50	38	1.25	32	0.38	0.17
		1/2	15	1.12	28	1.62	41	1.50	38	0.53	0.24
		3/4	20	1.38	35	1.88	48	1.75	44	0.88	0.40
		1	25	1.75	44	2.25	57	2.00	51	1.40	0.63
		1 1/4	32	2.00	51	2.62	66	2.44	62	2.40	1.09
		1 1/2	40	2.12	54	2.81	71	2.75	70	2.90	1.32
2	50	2.50	64	3.31	84	3.31	84	5.00	2.27		

FIGURE 2116 Laterals		Size		B		K		L		Unit Weight	
		NPS	DN	in	mm	in	mm	in	mm	lbs	kg
		½	15	1.56	39.62	2.56	65.02	3.56	90.42	1.75	0.79
		¾	20	1.84	46.74	3.00	76.20	4.13	104.90	2.75	1.24
		1	25	2.22	56.39	3.50	88.90	4.81	122.17	4.65	2.09
		1¼	32	2.50	63.50	3.94	100.08	5.38	136.65	5.50	2.48
		1½	40	3.03	79.96	4.75	120.65	6.44	163.58	10.831	4.87
		2	50	3.34	84.84	5.00	127.00	6.63	168.40	9.50	4.28

FORGED STEEL FITTINGS

Forged Steel Fittings

Class 3000 Threaded



FIGURE 2117 Couplings	Size		D		W		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/8	6	0.62	16	1.25	32	0.14	0.06
	1/4	8	0.75	19	1.38	35	0.10	0.05
	3/8	10	0.88	22	1.50	38	0.13	0.06
	1/2	15	1.12	28	1.88	48	0.28	0.13
	3/4	20	1.38	35	2.00	51	0.44	0.20
	1	25	1.75	44	2.38	60	1.08	0.49
	1 1/4	32	2.25	57	2.62	67	1.68	0.76
	1 1/2	40	2.50	64	3.12	79	2.17	0.98
	2	50	3.00	76	3.38	86	3.20	1.45
	2 1/2	65	3.62	92	3.62	92	4.70	2.13
	3	80	4.25	108	4.25	108	6.80	3.08
	4	100	5.50	140	4.75	121	12.30	5.58

FIGURE 2119 Half Couplings	Size		D		W/2		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/8	6	0.62	16	1.25	32	0.05	0.02
	1/4	8	0.75	19	1.38	35	0.04	0.02
	3/8	10	0.88	22	1.50	38	0.06	0.03
	1/2	15	1.12	28	1.88	48	0.12	0.05
	3/4	20	1.38	35	2.00	51	0.21	0.10
	1	25	1.75	44	2.38	60	0.43	0.20
	1 1/4	32	2.25	57	2.62	67	0.76	0.34
	1 1/2	40	2.50	64	3.12	79	1.14	0.52
	2	50	3.00	76	3.38	86	1.50	0.68
	2 1/2	65	3.62	92	3.62	92	2.40	1.09
	3	80	4.25	108	4.25	108	3.25	1.47
	4	100	5.50	140	4.75	121	6.25	2.83

Forged Steel Fittings

Class 3000 Threaded



FIGURE 2118 Reducing Couplings	Size				D		W		Unit Weight	
	NPS	DN	NPS	DN	in	mm	in	mm	lbs	kg
 	1/4	8	1/8	6	0.75	19	1.38	35	0.10	0.05
	3/8	10	1/8	6	0.88	22	1.50	38	0.15	0.07
	1/2	15	1/8	6	1.12	28	1.88	48	0.35	0.16
	3/4	20	1/8	6	1.38	35	2.00	51	0.52	0.24
	1	25	1/8	6	1.75	44	2.38	60	1.10	0.50
	1 1/4	32	1/4	8	2.25	57	2.62	67	2.08	0.94
	1 1/2	40	1/4	8	2.50	64	3.12	79	2.93	1.33
	2	50	1/4	8	3.00	76	3.38	86	4.40	2.00
	2 1/2	65	3/4	20	3.62	92	3.62	92	7.50	3.40
	3	80	3/4	20	4.25	108	4.25	108	11.00	4.99
	4	100	1 1/2	40	5.50	140	4.75	121	20.50	9.30

FIGURE 2120 Pipe Caps	Size		D		P		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
 	1/8	6	0.62	16	0.75	19	0.07	0.03
	1/4	8	0.75	19	1.00	25	0.08	0.04
	3/8	10	0.88	22	1.00	25	0.11	0.05
	1/2	15	1.12	28	1.25	32	0.23	0.10
	3/4	20	1.38	35	1.44	37	0.40	0.18
	1	25	1.75	44	1.62	41	0.79	0.36
	1 1/4	32	2.25	57	1.75	44	1.21	0.55
	1 1/2	40	2.50	64	1.75	44	1.75	0.79
	2	50	3.00	76	1.88	48	2.46	1.12
	2 1/2	65	3.62	92	2.38	60	4.37	1.98
	3	80	4.25	108	2.56	65	6.50	2.95
	4	100	5.50	140	2.69	68	11.30	5.12

Forged Steel Fittings

Class 6000 Threaded

FIGURE 2131 90° Elbows		Size		A		H		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg	
	1/8	6	0.97	25	1.00	25	—	—	
	1/4	8	1.12	28	1.31	33	—	—	
	3/8	10	1.31	33	1.50	38	—	—	
	1/2	15	1.50	38	1.81	46	1.50	0.68	
	3/4	20	1.75	44	2.19	56	2.60	1.18	
	1	25	2.00	51	2.44	62	3.50	1.59	
	1 1/4	32	2.38	60	2.97	75	6.00	2.72	
	1 1/2	40	2.50	64	3.31	84	8.00	3.63	
	2	50	3.25	83	4.00	102	13.00	5.90	
	2 1/2	65	3.75	95	4.75	121	22.30	10.11	
	3	80	4.19	106	5.75	146	36.00	16.33	
	4	100	4.50	114	6.00	152	—	—	




FIGURE 2132 45° Elbows		Size		C		H		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg	
	1/8	6	0.75	19	1.00	25	—	—	
	1/4	8	0.88	22	1.31	33	—	—	
	3/8	10	1.00	25	1.50	38	—	—	
	1/2	15	1.12	28	1.81	46	2.25	1.02	
	3/4	20	1.31	33	2.19	56	2.30	1.04	
	1	25	1.38	35	2.44	62	2.69	1.22	
	1 1/4	32	1.69	43	2.97	75	4.69	2.13	
	1 1/2	40	1.72	44	3.31	84	5.60	2.54	
	2	50	2.06	52	4.00	102	9.50	4.31	
	2 1/2	65	2.50	64	4.75	121	15.50	7.03	
	3	80	3.12	79	5.75	146	31.00	14.06	
	4	100	3.12	79	6.00	152	—	—	


FIGURE 2134 Tees		Size		A		H		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg	
	1/8	6	0.97	25	1.00	25	—	—	
	1/4	8	1.12	28	1.31	33	—	—	
	3/8	10	1.31	33	1.50	38	—	—	
	1/2	15	1.50	38	1.81	46	2.25	1.02	
	3/4	20	1.75	44	2.19	56	2.30	1.04	
	1	25	2.00	51	2.44	62	2.69	1.22	
	1 1/4	32	2.38	60	2.97	75	4.69	2.13	
	1 1/2	40	2.50	64	3.31	84	5.60	2.54	
	2	50	3.25	83	4.00	102	9.50	4.31	
	2 1/2	65	3.75	95	4.75	121	15.50	7.03	
	3	80	4.19	106	5.75	146	31.00	14.06	
	4	100	4.50	114	6.00	152	—	—	

Forged Steel Fittings

Class 6000 Threaded

FIGURE 2135 Crosses		Size		A		H		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg	
	1/8	6	0.97	25	1.00	25	0.56	0.25	
	1/4	8	1.12	28	1.31	33	1.19	0.54	
	3/8	10	1.31	33	1.50	38	1.50	0.68	
	1/2	15	1.50	38	1.81	46	2.60	1.18	
	3/4	20	1.75	44	2.19	56	4.30	1.95	
	1	25	2.00	51	2.44	62	5.70	2.59	
	1 1/4	32	2.38	60	2.97	75	9.60	4.35	
	1 1/2	40	2.50	64	3.31	84	11.40	5.17	
	2	50	3.25	83	4.00	102	21.40	9.71	
	2 1/2	65	3.75	95	4.75	121	28.30	12.83	
	3	80	4.19	106	5.75	146	59.00	26.76	
	4	100	4.50	114	6.00	152	43.50	19.73	

		Size		A		G		H		Unit Weight	
		NPS	DN	in	mm	in	mm	in	mm	lbs	kg
		1/8	6	0.88	22	1.25	32	1.00	25	—	—
		1/4	8	1.00	25	1.50	38	1.25	32	0.38	0.17
		3/8	10	1.12	28	1.62	41	1.50	38	0.44	0.20
		1/2	15	1.38	35	1.88	48	1.75	44	1.10	0.50
		3/4	20	1.75	44	2.25	57	2.00	51	1.62	0.73
		1	25	2.00	51	2.62	66	2.44	62	2.80	1.27
		1 1/4	32	2.12	54	2.81	71	2.75	70	3.80	1.72
		1 1/2	40	2.50	64	3.31	84	3.31	84	7.20	3.27

FIGURE 2136 Laterals		Size		B		K		L		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg	
	½	15	1.84	46.74	3.00	76.20	4.13	104.90	3.25	1.46	
	¾	20	2.22	56.39	3.50	88.90	4.81	122.17	5.44	2.45	
	1	25	2.50	63.5	3.94	100.08	5.38	136.65	7.19	3.23	
	1¼	32	3.03	76.96	4.75	120.65	6.44	163.58	12.31	5.54	
	1½	40	3.34	84.84	5.00	127.00	6.63	168.40	—	—	

Forged Steel Fittings

Class 6000 Threaded



FIGURE 2137 Couplings	Size		D		W		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
 	1/8	6	0.88	22	1.25	32	0.17	0.08
	1/4	8	1.00	25	1.38	35	0.30	0.14
	3/8	10	1.25	32	1.50	38	0.45	0.20
	1/2	15	1.50	38	1.88	48	0.70	0.32
	3/4	20	1.75	44	2.00	51	1.15	0.52
	1	25	2.25	57	2.38	60	1.83	0.83
	1 1/4	32	2.50	64	2.62	67	2.08	0.94
	1 1/2	40	3.00	76	3.12	79	3.95	1.79
	2	50	3.62	92	3.38	86	6.50	2.95
	2 1/2	65	4.25	108	3.62	92	—	—
	3	80	5.00	127	4.25	108	—	—
	4	100	6.25	159	4.75	121	—	—

FIGURE 2141 Half Couplings	Size		D		W/2		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
 	1/8	6	0.88	22	1.25	32	0.08	0.04
	1/4	8	1.00	25	1.38	35	0.13	0.06
	3/8	10	1.25	32	1.50	38	0.22	0.10
	1/2	15	1.50	38	1.88	48	0.35	0.16
	3/4	20	1.75	44	2.00	51	0.46	0.21
	1	25	2.25	57	2.38	60	0.95	0.43
	1 1/4	32	2.50	64	2.62	67	1.10	0.50
	1 1/2	40	3.00	76	3.12	79	2.12	0.96
	2	50	3.62	92	3.38	86	3.00	1.36
	2 1/2	65	4.25	108	3.62	92	—	—
	3	80	5.00	127	4.25	108	—	—
	4	100	6.25	159	4.75	121	—	—

Forged Steel Fittings

Class 6000 Threaded



FIGURE 2138 Reducing Couplings	Size				D		W		Unit Weight	
	NPS	DN	NPS	DN	in	mm	in	mm	lbs	kg
	1/4	8	1/8	6	1.00	25	1.38	35	—	—
	3/8	10	1/8	6	1.25	32	1.50	38	—	—
	1/2	15	1/8	6	1.50	38	1.88	48	0.78	0.35
	3/4	20	1/4	8	1.75	44	2.00	51	1.16	0.53
	1	25	1/4	8	2.25	57	2.38	60	2.03	0.92
	1 1/4	32	1/2	15	2.50	64	2.62	67	2.73	1.24
	1 1/2	40	3/4	20	3.00	76	3.12	79	4.70	2.13
	2	50	3/4	20	3.62	92	3.38	86	7.50	3.40
	2 1/2	65	1 1/4	32	4.25	108	3.62	92	—	—
	3	80	1 1/2	40	5.00	127	4.25	108	—	—
	4	100	2	50	6.25	159	4.75	121	—	—

FIGURE 2143 Pipe Caps	Size		D		P		Unit Weight	
	NPS	DN	in	mm	in	mm	lbs	kg
	1/8	6	0.88	22	1.00	25	0.01	0.00
	1/4	8	1.00	25	1.06	27	0.01	0.00
	3/8	10	1.25	32	1.06	27	0.01	0.00
	1/2	15	1.50	38	1.31	33	0.41	0.19
	3/4	20	1.75	44	1.50	38	0.57	0.26
	1	25	2.25	57	1.69	43	1.17	0.53
	1 1/4	32	2.50	64	1.81	46	1.42	0.64
	1 1/2	40	3.00	76	1.88	48	2.17	0.98
	2	50	3.62	92	2.00	51	3.66	1.66
	2 1/2	65	4.25	108	2.50	64	4.94	2.24
	3	80	5.00	127	2.69	68	7.66	3.47
	4	100	6.25	159	2.94	75	14.53	6.59

FORGED STEEL FITTINGS

Forged Steel Fittings

Class 3000 Socket Weld



FIGURE 2150 90° Elbows		Size		A <i>Nominal</i>		B <i>Socket Dia.</i>		C <i>Minimum</i>		D <i>Bore Dia.</i>		J <i>Socket Depth Minimum</i>		Unit Weight	
		NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
		1/8	6	0.44	11.0	.440 .420	11.2 10.8	0.125	3.18	.299 .239	7.6 6.1	0.38	9.5	0.25	0.11
		1/4	8	0.44	11.0	.575 .555	14.6 14.2	0.130	3.30	.394 .334	10.0 8.5	0.38	9.5	0.31	0.14
		3/8	10	0.53	13.5	.710 .690	18.0 17.6	0.138	3.50	.523 .463	13.3 11.8	0.38	9.5	0.31	0.14
		1/2	15	0.62	15.5	.875 .855	22.2 21.8	0.161	4.09	.652 .592	16.6 15.0	0.38	9.5	0.53	0.24
		3/4	20	0.75	19.0	1.085 1.065	27.6 27.2	0.168	4.27	.854 .794	21.7 20.2	0.50	12.5	0.64	0.29
		1	25	0.88	22.5	1.350 1.330	34.3 33.9	0.196	4.98	1.079 1.019	27.4 25.9	0.50	12.5	0.95	0.43
		1 1/4	32	1.06	27.0	1.695 1.675	43.1 42.7	0.208	5.28	1.410 1.350	35.8 34.3	0.50	12.5	1.60	0.73
		1 1/2	40	1.25	32.0	1.935 1.915	49.2 48.8	0.218	5.54	1.640 1.580	41.6 40.1	0.50	12.5	2.12	0.96
		2	50	1.50	38.0	2.426 2.406	61.7 61.2	0.238	6.04	2.097 2.037	53.3 51.7	0.62	16.0	3.66	1.66
		2 1/2	65	1.62	41.0	2.931 2.906	74.4 73.9	0.302	7.67	2.529 2.409	64.2 61.2	0.62	16.0	6.10	2.77
		3	80	2.25	57.0	3.560 3.535	90.3 89.8	0.327	8.30	3.128 3.008	79.4 76.4	0.62	16.0	9.70	4.40
		4	100	2.62	66.5	4.570 4.545	115.7 115.2	0.368	9.35	4.086 3.966	103.8 100.7	0.75	19.0	23.00	10.43

FIGURE 2151 45° Elbows		Size		A <i>Nominal</i>		B <i>Socket Dia.</i>		C <i>Minimum</i>		D <i>Bore Dia.</i>		J <i>Socket Depth Minimum</i>		Unit Weight	
		NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
		1/8	6	0.31	8.0	.440 .420	11.2 10.8	0.125	3.18	.299 .239	7.6 6.1	0.38	9.5	0.18	0.08
		1/4	8	0.31	8.0	.575 .555	14.6 14.2	0.130	3.30	.394 .334	10.0 8.5	0.38	9.5	0.16	0.07
		3/8	10	0.31	8.0	.710 .690	18.0 17.6	0.138	3.50	.523 .463	13.3 11.8	0.38	9.5	0.18	0.08
		1/2	15	0.44	11.0	.875 .855	22.2 21.8	0.161	4.09	.652 .592	16.6 15.0	0.38	9.5	0.43	0.20
		3/4	20	0.50	13.0	1.085 1.065	27.6 27.2	0.168	4.27	.854 .794	21.7 20.2	0.50	12.5	0.58	0.26
		1	25	0.56	14.0	1.350 1.330	34.3 33.9	0.196	4.98	1.079 1.019	27.4 25.9	0.50	12.5	0.90	0.41
		1 1/4	32	0.69	17.5	1.695 1.675	43.1 42.7	0.208	5.28	1.410 1.350	35.8 34.3	0.50	12.5	1.30	0.59
		1 1/2	40	0.81	20.5	1.935 1.915	49.2 48.8	0.218	5.54	1.640 1.580	41.6 40.1	0.50	12.5	1.57	0.71
		2	50	1.00	25.5	2.426 2.406	61.7 61.2	0.238	6.04	2.097 2.037	53.3 51.7	0.62	16.0	2.73	1.24
		2 1/2	65	1.12	28.5	2.931 2.906	74.4 73.9	0.302	7.67	2.529 2.409	64.2 61.2	0.62	16.0	7.50	3.40
		3	80	1.25	32.0	3.560 3.535	90.3 89.8	0.327	8.30	3.128 3.008	79.4 76.4	0.62	16.0	10.40	4.72
		4	100	1.62	41.0	4.570 4.545	115.7 115.2	0.368	9.35	4.086 3.966	103.8 100.7	0.75	19.0	19.80	8.98

Note: When the pipe is seated against the bottom of the socket prior to welding, to prevent possible cracking of the fillet welds, it is recommended that the pipe be withdrawn approximately 1/16 in (1.6mm) away from contact with the bottom of the socket before starting the weld.

Average of socket wall thickness around periphery shall be no less than listed values. The minimum values are permitted in localized areas.

Forged Steel Fittings

Class 3000 Socket Weld

FIGURE 2152 Tees		Size		A Nominal		B Socket Dia.		C Minimum		D Bore Dia.		J Socket Depth Minimum		Unit Weight	
NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
1/8	6	0.44	11.0	.440 .420	11.2 10.8	0.125	3.18	.299 .239	7.6 6.1	0.38	9.5	0.28	0.13		
1/4	8	0.44	11.0	.575 .555	14.6 14.2	0.130	3.30	.394 .334	10.0 8.5	0.38	9.5	0.24	0.11		
3/8	10	0.53	13.5	.710 .690	18.0 17.6	0.138	3.50	.523 .463	13.3 11.8	0.38	9.5	0.38	0.17		
1/2	15	0.62	15.5	.875 .855	22.2 21.8	0.161	4.09	.652 .592	16.6 15.0	0.38	9.5	0.65	0.29		
3/4	20	0.75	19.0	1.085 1.065	27.6 27.2	0.168	4.27	.854 .794	21.7 20.2	0.50	12.5	0.86	0.39		
1	25	0.88	22.5	1.350 1.330	34.3 33.9	0.196	4.98	1.079 1.019	27.4 25.9	0.50	12.5	1.37	0.62		
1 1/4	32	1.06	27.0	1.695 1.675	43.1 42.7	0.208	5.28	1.410 1.350	35.8 34.3	0.50	12.5	2.00	0.91		
1 1/2	40	1.25	32.0	1.935 1.915	49.2 48.8	0.218	5.54	1.640 1.580	41.6 40.1	0.50	12.5	2.80	1.27		
2	50	1.50	38.0	2.426 2.406	61.7 61.2	0.238	6.04	2.097 2.037	53.3 51.7	0.62	16.0	3.85	1.75		
2 1/2	65	1.62	41.0	2.931 2.906	74.4 73.9	0.302	7.67	2.529 2.409	64.2 61.2	0.62	16.0	8.20	3.72		
3	80	2.25	57.0	3.560 3.535	90.3 89.8	0.327	8.30	3.128 3.008	79.4 76.4	0.62	16.0	12.00	5.44		
4	100	2.62	66.5	4.570 4.545	115.7 115.2	0.368	9.35	4.086 3.966	103.8 100.7	0.75	19.0	29.00	13.15		





FIGURE 2153 Crosses		Size		A Nominal		B Socket Dia.		C Minimum		D Bore Dia.		J Socket Depth Minimum		Unit Weight	
NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
1/8	6	0.44	11.0	.440 .420	11.2 10.8	0.125	3.18	.299 .239	7.6 6.1	0.38	9.5	0.45	0.20		
1/4	8	0.44	11.0	.575 .555	14.6 14.2	0.130	3.30	.394 .334	10.0 8.5	0.38	9.5	0.38	0.17		
3/8	10	0.53	13.5	.710 .690	18.0 17.6	0.138	3.50	.523 .463	13.3 11.8	0.38	9.5	0.32	0.15		
1/2	15	0.62	15.5	.875 .855	22.2 21.8	0.161	4.09	.652 .592	16.6 15.0	0.38	9.5	0.81	0.37		
3/4	20	0.75	19.0	1.085 1.065	27.6 27.2	0.168	4.27	.854 .794	21.7 20.2	0.50	12.5	1.10	0.50		
1	25	0.88	22.5	1.350 1.330	34.3 33.9	0.196	4.98	1.079 1.019	27.4 25.9	0.50	12.5	1.56	0.71		
1 1/4	32	1.06	27.0	1.695 1.675	43.1 42.7	0.208	5.28	1.410 1.350	35.8 34.3	0.50	12.5	2.44	1.11		
1 1/2	40	1.25	32.0	1.935 1.915	49.2 48.8	0.218	5.54	1.640 1.580	41.6 40.1	0.50	12.5	3.25	1.47		
2	50	1.50	38.0	2.426 2.406	61.7 61.2	0.238	6.04	2.097 2.037	53.3 51.7	0.62	16.0	5.20	2.36		
2 1/2	65	1.62	41.0	2.931 2.906	74.4 73.9	0.302	7.67	2.529 2.409	64.2 61.2	0.62	16.0	13.40	6.08		
3	80	2.25	57.0	3.560 3.535	90.3 89.8	0.327	8.30	3.128 3.008	79.4 76.4	0.62	16.0	20.00	9.07		
4	100	2.62	66.5	4.570 4.545	115.7 115.2	0.368	9.35	4.086 3.966	103.8 100.7	0.75	19.0	—	—		



Note: When the pipe is seated against the bottom of the socket prior to welding, to prevent possible cracking of the fillet welds, it is recommended that the pipe be withdrawn approximately 1/16 in (1.6mm) away from contact with the bottom of the socket before starting the weld.
Average of socket wall thickness around periphery shall be no less than listed values. The minimum values are permitted in localized areas.

FORGED STEEL FITTINGS

Forged Steel Fittings

Class 3000 Socket Weld



FIGURE 2158 Laterals	Size		B		C		D		K		L		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
	1/2	15	1.31	33.27	0.855	21.72	0.375	8.89	2.125	54.66	3.000	76.20	1.00	0.45
	3/4	20	1.56	39.62	1.065	27.05	0.500	12.70	2.563	65.10	3.563	90.50	1.50	0.68
	1	25	1.84	46.74	1.330	33.78	0.500	12.70	3.000	76.2	4.125	104.78	2.38	1.07
	1 1/4	32	2.22	56.39	1.675	41.91	0.500	12.70	3.500	88.90	4.810	122.17	3.75	1.69
	1 1/2	40	2.50	63.50	1.915	49.53	0.500	12.70	3.940	100.08	5.375	135.89	4.13	1.91
	2	50	3.03	79.96	2.406	61.11	0.625	16.51	4.750	120.65	6.440	163.58	6.29	2.83

FIGURE 2154 Couplings	Size		B Socket Dia.		C Minimum		D Bore Dia.		E		J Socket Depth Minimum		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
	1/8	6	.440 .420	11.2 10.8	0.125	3.18	.299 .239	7.6 6.1	0.25	6.5	0.38	9.5	0.08	0.04
	1/4	8	.575 .555	14.6 14.2	0.130	3.30	.394 .334	10.0 8.5	0.25	6.5	0.38	9.5	0.10	0.05
	3/8	10	.710 .690	18.0 17.6	0.138	3.50	.523 .463	13.3 11.8	0.25	6.5	0.38	9.5	0.16	0.07
	1/2	15	.875 .855	22.2 21.8	0.161	4.09	.652 .592	16.6 15.0	0.38	9.5	0.38	9.5	0.21	0.10
	3/4	20	1.085 1.065	27.6 27.2	0.168	4.27	.854 .794	21.7 20.2	0.38	9.5	0.50	12.5	0.40	0.18
	1	25	1.350 1.330	34.3 33.9	0.196	4.98	1.079 1.019	27.4 25.9	0.50	12.5	0.50	12.5	0.55	0.25
	1 1/4	32	1.695 1.675	43.1 42.7	0.208	5.28	1.410 1.350	35.8 34.3	0.50	12.5	0.50	12.5	0.75	0.34
	1 1/2	40	1.935 1.915	49.2 48.8	0.218	5.54	1.640 1.580	41.6 40.1	0.50	12.5	0.50	12.5	1.10	0.50
	2	50	2.426 2.406	61.7 61.2	0.238	6.04	2.097 2.037	53.3 51.7	0.75	19.0	0.62	16.0	1.65	0.75
	2 1/2	65	2.931 2.906	74.4 73.9	0.302	7.67	2.529 2.409	64.2 61.2	0.75	19.0	0.62	16.0	3.25	1.47
	3	80	3.560 3.535	90.3 89.8	0.327	8.30	3.128 3.008	79.4 76.4	0.75	19.0	0.62	16.0	5.10	2.31
	4	100	4.570 4.545	115.7 115.2	0.368	9.35	4.086 3.966	103.8 100.7	0.75	19.0	0.75	19.0	7.50	3.40

Note: When the pipe is seated against the bottom of the socket prior to welding, to prevent possible cracking of the fillet welds, it is recommended that the pipe be withdrawn approximately 1/8 in (1.6mm) away from contact with the bottom of the socket before starting the weld.

Average of socket wall thickness around periphery shall be no less than listed values. The minimum values are permitted in localized areas.

Forged Steel Fittings

Class 3000 Socket Weld



FIGURE 2155 Half Couplings	Size		B Socket Dia.		D Bore Dia.		F		J Socket Depth Minimum		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
	1/8	6	.440 .420	11.2 10.8	.299 .239	7.6 6.1	0.62	16.0	0.38	9.5	0.09	0.04
	1/4	8	.575 .555	14.6 14.2	.394 .334	10.0 8.5	0.62	16.0	0.38	9.5	0.12	0.05
	3/8	10	.710 .690	18.0 17.6	.523 .463	13.3 11.8	0.69	17.5	0.38	9.5	0.23	0.10
	1/2	15	.875 .855	22.2 21.8	.652 .592	16.6 15.0	0.88	22.5	0.38	9.5	0.28	0.13
	3/4	20	1.085 1.065	27.6 27.2	.854 .794	21.7 20.2	0.94	24.0	0.50	12.5	0.43	0.20
	1	25	1.350 1.330	34.3 33.9	1.079 1.019	27.4 25.9	1.12	28.5	0.50	12.5	0.66	0.30
	1 1/4	32	1.695 1.675	43.1 42.7	1.410 1.350	35.8 34.3	1.19	30.0	0.50	12.5	1.10	0.50
	1 1/2	40	1.935 1.915	49.2 48.8	1.640 1.580	41.6 40.1	1.25	32.0	0.50	12.5	1.06	0.48
	2	50	2.426 2.406	61.7 61.2	2.097 2.037	53.3 51.7	1.62	41.0	0.62	16.0	2.15	0.98
	2 1/2	65	2.931 2.906	74.4 73.9	2.529 2.409	64.2 61.2	1.69	43.0	0.62	16.0	3.70	1.68
	3	80	3.560 3.535	90.3 89.8	3.128 3.008	79.4 76.4	1.75	44.5	0.62	16.0	6.00	2.72
	4	100	4.570 4.545	115.7 115.2	4.086 3.966	103.8 100.7	1.88	48.0	0.75	19.0	8.00	3.63

FIGURE 2156 Reducing Couplings	Size				B Socket Dia.	D Bore Dia.	E	J Socket Depth Minimum	Unit Weight					
	Lowest Reduction													
	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	lbs	kg		
	¼	8	⅛	6	.575 .555	14.6 14.2	0.130	3.30	.394 .334	10.0 8.5	0.25	6.5	0.38	9.5
	⅜	10	⅛	6	.710 .690	18.0 17.6	0.138	3.50	.523 .463	13.3 11.8	0.25	6.5	0.38	9.5
	½	15	⅛	6	.875 .855	22.2 21.8	0.161	4.09	.652 .592	16.6 15.0	0.38	9.5	0.38	9.5
	¾	20	⅛	6	1.085 1.065	27.6 27.2	0.168	4.27	.854 .794	21.7 20.2	0.38	9.5	0.50	12.5
	1	25	⅛	6	1.350 1.330	34.3 33.9	0.196	4.98	1.079 1.019	27.4 25.9	0.50	12.5	0.50	12.5
	1¼	32	¼	8	1.695 1.675	43.1 42.7	0.208	5.28	1.410 1.350	35.8 34.3	0.50	12.5	0.50	12.5
	1½	40	¼	8	1.935 1.915	49.2 48.8	0.218	5.54	1.640 1.580	41.6 40.1	0.50	12.5	0.50	12.5
	2	50	½	15	2.426 2.406	61.7 61.2	0.238	6.04	2.097 2.037	53.3 51.7	0.75	19.0	0.62	16.0
	2½	65	½	15	2.931 2.906	74.4 73.9	0.302	7.67	2.529 2.409	64.2 61.2	0.75	19.0	0.62	16.0
	3	80	1½	40	3.560 3.535	90.3 89.8	0.327	8.30	3.128 3.008	79.4 76.4	0.75	19.0	0.62	16.0
	4	100	2	50	4.570 4.545	115.7 115.2	0.368	9.35	4.086 3.966	103.8 100.7	0.75	19.0	0.75	19.0

Note: When the pipe is seated against the bottom of the socket prior to welding, to prevent possible cracking of the fillet welds, it is recommended that the pipe be withdrawn approximately 1/16 in (1.6mm) away from contact with the bottom of the socket before starting the weld.

Average of socket wall thickness around periphery shall be no less than listed values. The minimum values are permitted in localized areas.

Forged Steel Fittings

Class 3000 Socket Weld

FIGURE 2157 Pipe Caps	Size		B <i>Socket Dia.</i>		C <i>Minimum</i>		J <i>Socket Depth</i> <i>Minimum</i>		K		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
	1/8	6	.440 .420	11.2 10.8	0.125	3.18	0.38	9.5	0.19	4.8	0.07	0.03
	1/4	8	.575 .555	14.6 14.2	0.130	3.30	0.38	9.5	0.19	4.8	0.09	0.04
	3/8	10	.710 .690	18.0 17.6	0.138	3.50	0.38	9.5	0.19	4.8	0.17	0.08
	1/2	15	.875 .855	22.2 21.8	0.161	4.09	0.38	9.5	0.25	6.4	0.30	0.14
	3/4	20	1.085 1.065	27.6 27.2	0.168	4.27	0.50	12.5	0.25	6.4	0.37	0.17
	1	25	1.350 1.330	34.3 33.9	0.196	4.98	0.50	12.5	0.38	9.6	0.60	0.27
	1 1/4	32	1.695 1.675	43.1 42.7	0.208	5.28	0.50	12.5	0.38	9.6	0.96	0.44
	1 1/2	40	1.935 1.915	49.2 48.8	0.218	5.54	0.50	12.5	0.44	11.2	1.20	0.54
	2	50	2.426 2.406	61.7 61.2	0.238	6.04	0.62	16.0	0.50	12.7	2.00	0.91
	2 1/2	65	2.931 2.906	74.4 73.9	0.302	7.67	0.62	16.0	0.62	15.7	2.75	1.25
	3	80	3.560 3.535	90.3 89.8	0.327	8.30	0.62	16.0	0.75	19.0	5.00	2.27
	4	100	4.570 4.545	115.7 115.2	0.368	9.35	0.75	19.0	0.88	22.4	8.25	3.74

Note: When the pipe is seated against the bottom of the socket prior to welding, to prevent possible cracking of the fillet welds, it is recommended that the pipe be withdrawn approximately 1/16 in (1.6mm) away from contact with the bottom of the socket before starting the weld.

Average of socket wall thickness around periphery shall be no less than listed values. The minimum values are permitted in localized areas.

Forged Steel Fittings

Class 6000 Socket Weld


FIGURE 2170 90° Elbows		Size		A <i>Nominal</i>		B <i>Socket Dia.</i>		C <i>Minimum</i>		D <i>Bore Dia.</i>		J <i>Socket Depth Minimum</i>		Unit Weight	
		NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
		1/2	15	0.75	19.0	.875 .855	22.2 21.8	0.204	5.18	.494 .434	12.5 11.0	0.38	9.5	0.90	0.41
		3/4	20	0.88	22.5	1.085 1.065	27.6 27.2	0.238	6.04	.642 .582	16.3 14.8	0.50	12.5	1.50	0.68
		1	25	1.06	27.0	1.350 1.330	34.3 33.9	0.273	6.93	.845 .785	21.5 19.9	0.50	12.5	2.32	1.05
		1 1/4	32	1.25	32.0	1.695 1.675	43.1 42.7	0.273	6.93	1.190 1.130	30.2 28.7	0.50	12.5	3.00	1.36
		1 1/2	40	1.50	38.0	1.935 1.915	49.2 48.8	0.307	7.80	1.368 1.308	34.7 33.2	0.50	12.5	5.50	2.49
		2	50	1.62	41.0	2.426 2.406	61.7 61.2	0.374	9.50	1.717 1.657	43.6 42.1	0.62	16.0	6.50	2.95
		2 1/2	65	2.25	57.1	2.931 2.906	74.4 73.9	0.41	10.41	2.185 2.065	55.5 52.5	0.62	16.0	12.00	5.44
		3	80	2.50	63.5	3.560 3.535	90.3 89.8	0.48	12.19	2.684 2.564	68.2 65.1	0.62	16.0	19.60	8.89
		4	100	2.62	66.5	4.570 4.545	115.7 115.2	0.58	14.73	3.498 3.378	88.8 85.8	0.75	19.0	36.40	16.51

FIGURE 2171 45° Elbows		Size		A		B <i>Socket Dia.</i>		C <i>Minimum</i>		D <i>Bore Dia.</i>		J <i>Socket Depth Minimum</i>		Unit Weight	
		NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
		1/2	15	0.50	12.5	.875 .855	22.2 21.8	0.204	5.18	.494 .434	12.5 11.0	0.38	9.5	0.90	0.41
		3/4	20	0.56	14.0	1.085 1.065	27.6 27.2	0.238	6.04	.642 .582	16.3 14.8	0.50	12.5	1.50	0.68
		1	25	0.69	17.5	1.350 1.330	34.3 33.9	0.273	6.93	.845 .785	21.5 19.9	0.50	12.5	2.32	1.05
		1 1/4	32	0.81	20.5	1.695 1.675	43.1 42.7	0.273	6.93	1.190 1.130	30.2 28.7	0.50	12.5	3.00	1.36
		1 1/2	40	1.00	25.5	1.935 1.915	49.2 48.8	0.307	7.80	1.368 1.308	34.7 33.2	0.50	12.5	5.50	2.49
		2	50	1.12	28.5	2.426 2.406	61.7 61.2	0.374	9.50	1.717 1.657	43.6 42.1	0.62	16.0	6.50	2.95
		2 1/2	65	1.25	31.8	2.931 2.906	74.4 73.9	0.41	10.41	2.185 2.065	55.5 52.5	0.62	16.0	12.00	5.44
		3	80	1.38	35.1	3.560 3.535	90.3 89.8	0.48	12.19	2.684 2.564	68.2 65.1	0.62	16.0	19.60	8.89
		4	100	1.58	40.1	4.570 4.545	115.7 115.2	0.58	14.73	3.498 3.378	88.8 85.8	0.75	19.0	36.40	16.51

Note: When the pipe is seated against the bottom of the socket prior to welding, to prevent possible cracking of the fillet welds, it is recommended that the pipe be withdrawn approximately 1/16 in (1.6mm) away from contact with the bottom of the socket before starting the weld.

Average of socket wall thickness around periphery shall be no less than listed values. The minimum values are permitted in localized areas.

FORGED STEEL FITTINGS

Forged Steel Fittings

Class 6000 Socket Weld


FIGURE 2172 Tees		Size		A		B <i>Socket Dia.</i>		C <i>Minimum</i>		D <i>Bore Dia.</i>		J <i>Socket Depth Minimum</i>		Unit Weight	
		NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
		½	15	0.75	19.0	.875 .855	22.2 21.8	0.204	5.18	.494 .434	12.5 11.0	0.38	9.5	1.16	0.53
		¾	20	0.88	22.5	1.085 1.065	27.6 27.2	0.238	6.04	.642 .582	16.3 14.8	0.50	12.5	2.00	0.91
		1	25	1.06	27.0	1.350 1.330	34.3 33.9	0.273	6.93	.845 .785	21.5 19.9	0.50	12.5	3.16	1.43
		1¼	32	1.25	32.0	1.695 1.675	43.1 42.7	0.273	6.93	1.190 1.130	30.2 28.7	0.50	12.5	3.62	1.64
		1½	40	1.50	38.0	1.935 1.915	49.2 48.8	0.307	7.80	1.368 1.308	34.7 33.2	0.50	12.5	7.10	3.22
		2	50	1.62	41.0	2.426 2.406	61.7 61.2	0.374	9.50	1.717 1.657	43.6 42.1	0.62	16.0	8.90	4.04
		2½	65	2.25	57.1	2.931 2.906	74.4 73.9	0.41	10.41	2.185 2.065	55.5 52.5	0.62	16.0	16.63	7.54
		3	80	2.50	63.5	3.560 3.535	90.3 89.8	0.48	12.19	2.684 2.564	68.2 65.1	0.62	16.0	23.80	10.79
		4	100	2.62	66.5	4.570 4.545	115.7 115.2	0.58	14.73	3.498 3.378	88.8 85.8	0.75	19.0	45.32	20.55



FIGURE 2173 Crosses		Size		A		B <i>Socket Dia.</i>		C <i>Minimum</i>		D <i>Bore Dia.</i>		J <i>Socket Depth Minimum</i>		Unit Weight	
		NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
		½	15	0.75	19.0	.875 .855	22.2 21.8	0.204	5.18	.494 .434	12.5 11.0	0.38	9.5	1.40	0.63
		¾	20	0.88	22.5	1.085 1.065	27.6 27.2	0.238	6.04	.642 .582	16.3 14.8	0.50	12.5	2.30	1.04
		1	25	1.06	27.0	1.350 1.330	34.3 33.9	0.273	6.93	.845 .785	21.5 19.9	0.50	12.5	3.80	1.72
		1¼	32	1.25	32.0	1.695 1.675	43.1 42.7	0.273	6.93	1.190 1.130	30.2 28.7	0.50	12.5	4.70	2.13
		1½	40	1.50	38.0	1.935 1.915	49.2 48.8	0.307	7.80	1.368 1.308	34.7 33.2	0.50	12.5	8.70	3.95
		2	50	1.62	41.0	2.426 2.406	61.7 61.2	0.374	9.50	1.717 1.657	43.6 42.1	0.62	16.0	9.30	4.22

FIGURE 2178 Laterals		Size		B		C		D		K		L		Unit Weight	
		NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
		½	15	1.31	33.27	0.855	21.72	0.375	8.89	2.125	54.66	3.000	76.20	1.00	0.45
		¾	20	1.56	39.62	1.065	27.05	0.500	12.70	2.563	65.10	3.563	90.50	1.50	0.68
		1	25	1.84	46.74	1.330	33.78	0.500	12.70	3.000	76.2	4.125	104.78	2.38	1.07
		1¼	32	2.22	56.39	1.675	41.91	0.500	12.70	3.500	88.90	4.810	122.17	3.75	1.69
		1½	40	2.50	63.50	1.915	49.53	0.500	12.70	3.940	100.08	5.375	135.89	4.13	1.91

Note: When the pipe is seated against the bottom of the socket prior to welding, to prevent possible cracking of the fillet welds, it is recommended that the pipe be withdrawn approximately ¼ in (1.6mm) away from contact with the bottom of the socket before starting the weld.

Average of socket wall thickness around periphery shall be no less than listed values. The minimum values are permitted in localized areas.

Forged Steel Fittings

Class 6000 Socket Weld



FIGURE 2174 Couplings	Size		B Socket Dia.		C Minimum		D Bore Dia.		E		J Socket Depth Minimum		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
	1/2	15	.875 .855	22.2 21.8	0.204 5.18		.494 .434	12.5 11.0	0.38 9.5		0.38 9.5		0.53 0.24	
	3/4	20	1.085 1.065	27.6 27.2	0.238 6.04		.642 .582	16.3 14.8	0.38 9.5		0.50 12.5		0.56 0.25	
	1	25	1.350 1.330	34.3 33.9	0.273 6.93		.845 .785	21.5 19.9	0.50 12.5		0.50 12.5		0.92 0.42	
	1 1/4	32	1.695 1.675	43.1 42.7	0.273 6.93		1.190 1.130	30.2 28.7	0.50 12.5		0.50 12.5		1.16 0.53	
	1 1/2	40	1.935 1.915	49.2 48.8	0.307 7.80		1.368 1.308	34.7 33.2	0.50 12.5		0.50 12.5		2.57 1.17	
	2	50	2.426 2.406	61.7 61.2	0.374 9.50		1.717 1.657	43.6 42.1	0.75 19.0		0.62 16.0		4.75 2.15	
	2 1/2	65	2.931 2.906	74.4 73.9	0.410 10.41		2.185 2.065	55.5 52.5	0.75 19.0		0.62 16.0		— —	
	3	80	3.560 3.535	90.3 89.8	0.480 12.19		2.684 2.564	68.2 65.1	0.75 19.0		0.62 16.0		— —	
	4	100	4.570 4.545	115.7 115.2	0.580 14.73		3.498 3.378	88.8 85.8	0.75 19.0		0.75 19.0		— —	

FIGURE 2175 Half Couplings	Size		B Socket Dia.		D Bore Dia.		F		J Socket Depth Minimum		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
	1/2	15	.875 .855	22.2 21.8	.494 .434	12.5 11.0	0.88 22.5		0.38 9.5		0.56 0.25	
	3/4	20	1.085 1.065	27.6 27.2	.642 .582	16.3 14.8	0.94 24.0		0.50 12.5		0.95 0.43	
	1	25	1.350 1.330	34.3 33.9	.845 .785	21.5 19.9	1.12 28.5		0.50 12.5		1.12 0.51	
	1 1/4	32	1.695 1.675	43.1 42.7	1.190 1.130	30.2 28.7	1.19 30.0		0.50 12.5		1.87 0.85	
	1 1/2	40	1.935 1.915	49.2 48.8	1.368 1.308	34.7 33.2	1.25 32.0		0.50 12.5		2.87 1.30	
	2	50	2.426 2.406	61.7 61.2	1.717 1.657	43.6 42.1	1.62 41.0		0.62 16.0		3.62 1.64	
	2 1/2	65	2.931 2.906	74.4 73.9	2.185 2.065	55.5 52.5	1.69 43.0		0.62 16.0		— —	
	3	80	3.560 3.535	90.3 89.8	2.684 2.564	68.2 65.1	1.75 44.5		0.62 16.0		— —	
	4	100	4.570 4.545	115.7 115.2	3.498 3.378	88.8 85.8	1.88 48.0		0.75 19.0		— —	

Note: When the pipe is seated against the bottom of the socket prior to welding, to prevent possible cracking of the fillet welds, it is recommended that the pipe be withdrawn approximately 1/16 in (1.6mm) away from contact with the bottom of the socket before starting the weld.
Average of socket wall thickness around periphery shall be no less than listed values. The minimum values are permitted in localized areas.

FORGED STEEL FITTINGS

Forged Steel Fittings

Class 6000 Socket Weld


FIGURE 2176 Reducing Couplings	Size				B Socket Dia.		D Bore Dia.		E		J Socket Depth Minimum		Unit Weight	
	Lowest Reduction													
	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
	½	15	¼	8	.875 .855	22.2 21.8	.494 .434	12.5 11.0	0.38	9.5	0.38	9.5	—	—
	¾	20	⅜	10	1.085 1.065	27.6 27.2	.642 .582	16.3 14.8	0.38	9.5	0.50	12.5	0.81	0.37
	1	25	⅜	10	1.350 1.330	34.3 33.9	.845 .785	21.5 19.9	0.50	12.5	0.50	12.5	1.80	0.82
	1¼	32	½	15	1.695 1.675	43.1 42.7	1.190 1.130	30.2 28.7	0.50	12.5	0.50	12.5	2.00	0.91
	1½	40	½	15	1.935 1.915	49.2 48.8	1.368 1.308	34.7 33.2	0.50	12.5	0.50	12.5	3.20	1.45
	2	50	¾	20	2.426 2.406	61.7 61.2	1.717 1.657	43.6 42.1	0.75	19.0	0.62	16.0	5.40	2.45
	2½	65	1¼	32	2.931 2.906	74.4 73.9	2.185 2.065	55.5 52.5	0.75	19.0	0.62	16.0	—	—
	3	80	1½	40	3.560 3.535	90.3 89.8	2.684 2.564	68.2 65.1	0.75	19.0	0.62	16.0	—	—
	4	100	2	50	4.570 4.545	115.7 115.2	3.498 3.378	88.8 85.8	0.75	19.0	0.75	19.0	—	—

FIGURE 2177 Pipe Caps	Size		B Socket Dia.		C Minimum		J Socket Depth Minimum		K Minimum		Unit Weight	
	NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
	1/2	15	.875 .855	22.2 21.8	0.204	5.18	0.38	9.5	0.31	7.9	0.42	0.19
	3/4	20	1.085 1.065	27.6 27.2	0.238	6.04	0.50	12.5	0.31	7.9	0.58	0.26
	1	25	1.350 1.330	34.3 33.9	0.273	6.93	0.50	12.5	0.44	11.2	1.21	0.55
	1 1/4	32	1.695 1.675	43.1 42.7	0.273	6.93	0.50	12.5	0.44	11.2	1.00	0.45
	1 1/2	40	1.935 1.915	49.2 48.8	0.307	7.80	0.50	12.5	0.50	12.7	2.12	0.96
	2	50	2.426 2.406	61.7 61.2	0.374	9.50	0.62	16.0	0.62	15.7	4.87	2.21
	2 1/2	65	2.931 2.906	74.4 73.9	0.41	10.41	0.62	16.0	0.75	19.0	–	–
	3	80	3.560 3.535	90.3 89.8	0.48	12.19	0.62	16.0	0.88	22.4	–	–
	4	100	4.570 4.545	115.7 115.2	0.58	14.73	0.75	19.0	1.12	28.4	–	–

Note: When the pipe is seated against the bottom of the socket prior to welding, to prevent possible cracking of the fillet welds, it is recommended that the pipe be withdrawn approximately 1/16 in (1.6mm) away from contact with the bottom of the socket before starting the weld.

Average of socket wall thickness around periphery shall be no less than listed values. The minimum values are permitted in localized areas.

Forged Steel Fittings

High Pressure Plugs

FIGURE 2122 Square Head Plugs		Size		A		B		C		Unit Weight	
NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
1/8	6	0.38	10	0.25	6	0.28	7	0.02	0.01		
1/4	8	0.44	11	0.25	6	0.38	10	0.03	0.01		
3/8	10	0.50	13	0.31	8	0.44	11	0.06	0.03		
1/2	15	0.56	14	0.38	10	0.56	14	0.10	0.05		
3/4	20	0.62	16	0.44	11	0.62	16	0.18	0.08		
1	25	0.75	19	0.50	13	0.81	21	0.38	0.17		
1 1/4	32	0.81	21	0.56	14	0.94	24	0.62	0.28		
1 1/2	40	0.81	21	0.62	16	1.12	28	0.88	0.40		
2	50	0.88	22	0.69	18	1.31	32	1.40	0.63		
2 1/2	65	1.06	27	0.75	19	1.50	36	2.20	1.00		
3	80	1.12	28	0.81	21	1.69	41	3.40	1.54		
4	100	1.25	32	1.00	25	2.50	65	8.50	3.85		

FIGURE 2142 Hex Head Plugs		Size		A		F <i>Across Flats</i>		H		Unit Weight	
NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
1/8	6	0.38	10	0.44	11	0.25	6	0.03	0.01		
1/4	8	0.44	11	0.62	16	0.25	6	0.05	0.02		
3/8	10	0.50	13	0.69	18	0.31	8	0.09	0.04		
1/2	15	0.56	14	0.88	22	0.31	8	0.13	0.06		
3/4	20	0.62	16	1.06	27	0.38	10	0.27	0.12		
1	25	0.75	19	1.38	36	0.38	10	0.48	0.22		
1 1/4	32	0.81	21	1.75	46	0.56	14	0.94	0.43		
1 1/2	40	0.81	21	2.00	50	0.62	16	1.20	0.54		
2	50	0.88	22	2.50	65	0.69	18	2.40	1.09		
2 1/2	65	1.06	27	3.00	75	0.75	19	3.80	1.72		
3	80	1.12	28	3.50	90	0.81	21	4.80	2.18		
4	100	1.25	32	4.62	115	1.00	25	13.00	5.90		

FIGURE 2121 Round Head Plugs		Size		A		D		E		Unit Weight	
NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
1/8	6	0.38	10	1.38	35	0.41	10	0.05	0.02		
1/4	8	0.44	11	1.62	41	0.53	13	0.10	0.05		
3/8	10	0.50	13	1.62	41	0.69	18	0.16	0.07		
1/2	15	0.56	14	1.75	44	0.84	21	0.28	0.13		
3/4	20	0.62	16	1.75	44	1.06	27	0.42	0.19		
1	25	0.75	19	2.00	51	1.31	33	0.82	0.37		
1 1/4	32	0.81	21	2.00	51	1.69	43	1.20	0.54		
1 1/2	40	0.81	21	2.00	51	1.91	49	1.50	0.68		
2	50	0.88	22	2.50	64	2.38	60	3.20	1.45		
2 1/2	65	1.06	27	2.75	70	2.88	73	—	—		
3	80	1.12	28	2.75	70	3.50	89	—	—		
4	100	1.25	32	3.00	76	4.50	114	—	—		

Note: Plugs and bushings are not identified by Pressure Class. They may be used for ratings up to Pressure Class 6000 (per ASME B16.11)

Forged Steel Fittings

High Pressure Bushings




FIGURE 2139 Hex Head Bushings	Size				A		F		G		Unit Weight	
			Lowest Reduction									
	NPS	DN	NPS	DN	in	mm	in	mm	in	mm	lbs	kg
	¼	8	⅛	6	0.44	11	0.62	16	0.12	3	0.02	0.01
	⅜	10	⅛	6	0.50	13	0.69	18	0.16	4	0.03	0.01
	½	15	⅛	6	0.56	14	0.88	22	0.19	5	0.06	0.03
	¾	20	⅛	6	0.62	16	1.06	27	0.22	6	0.11	0.05
	1	25	⅛	6	0.75	19	1.38	36	0.25	6	0.20	0.09
	1¼	32	⅛	6	0.81	21	1.75	46	0.28	7	0.40	0.18
	1½	40	¼	8	0.81	21	2.00	50	0.31	8	0.50	0.23
	2	50	¼	8	0.88	22	2.50	65	0.34	9	0.85	0.39
	2½	65	½	15	1.06	27	3.00	75	0.38	10	1.20	0.54
	3	80	½	15	1.12	28	3.50	90	0.41	10	2.60	1.18
	4	100	1½	40	1.25	32	4.62	115	0.50	13	7.00	3.17

FIGURE 2140 Flush Bushings	Size				A		Unit Weight	
			Lowest Reduction					
	NPS	DN	NPS	DN	in	mm	lbs	kg
	¼	8	⅛	6	0.44	11	0.03	0.01
	⅜	10	⅛	6	0.50	13	0.03	0.01
	½	15	⅛	6	0.56	14	0.06	0.03
	¾	20	⅛	6	0.62	16	0.09	0.04
	1	25	⅛	6	0.75	19	0.12	0.05
	1¼	32	⅛	6	0.81	21	0.15	0.07
	1½	40	¼	8	0.81	21	0.20	0.09
	2	50	¼	8	0.88	22	0.35	0.16

Note: Plugs and bushings are not identified by Pressure Class. They may be used for ratings up to Pressure Class 6000 (per ASME B16.11)

Forged Steel Fittings

Socket-Weld Reducer Inserts



CLASS 3000

For use with Schedule 40 and 80 Pipe



Reducer inserts comply with MSS standard SP-79. They enable standard socket-weld fittings to be used for making any combination of pipe line reductions quickly and economically. Socket-weld reducer inserts serve SD D the same purpose as threaded reducing bushings with threaded fittings.

Size				Class 3000 – For use with Schedule 40 and 80 Pipe											
				A		D		C Min.		SL		RL Min.		Unit Weight	
NPS	DN	NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
½	15	¼	8	0.81	20.57	0.364	9.25	0.149	3.78	0.62	15.75	–	–	0.18	0.08
		⅜	10	0.81	20.57	0.493	12.52	0.158	4.00	0.62	15.75	–	–		
¾	20	¼	8	0.69	17.53	0.364	9.25	0.149	3.78	–	–	1.06	27	0.25	0.11
		⅜	10	0.62	15.75	0.493	12.52	0.158	4.00	–	–	1.06	27		
		½	15	0.88	22.35	0.622	15.80	0.184	4.67	0.69	17.53	–	–		
1	25	¼	8	0.75	19.05	0.364	9.25	0.149	3.78	–	–	1.12	28	0.35	0.16
		⅜	10	0.69	17.53	0.493	12.52	0.158	4.00	–	–	1.12	28		
		½	15	0.62	15.75	0.622	15.80	0.184	4.67	–	–	1.12	28		
		¾	20	0.94	23.88	0.824	20.93	0.193	4.90	0.75	19.05	–	–		
1¼	32	¼	8	0.88	22.35	0.364	9.25	0.149	3.78	–	–	1.25	32	0.35	0.25
		⅜	10	0.81	20.57	0.493	12.52	0.158	4.00	–	–	1.25	32		
		½	15	0.75	19.05	0.622	15.80	0.184	4.67	–	–	1.25	32		
		¾	20	0.69	17.53	0.824	20.93	0.193	4.90	–	–	1.25	32		
		1	25	1.00	25.40	1.049	26.65	0.224	5.69	0.81	20.57	–	–		
1½	40	⅜	10	0.88	22.35	0.493	12.52	0.158	4.00	–	–	1.31	33	0.62	0.28
		½	15	0.81	20.57	0.622	15.80	0.184	4.67	–	–	1.31	33		
		¾	20	0.75	19.05	0.824	20.93	0.193	4.90	–	–	1.31	33		
		1	25	0.69	17.53	1.049	26.65	0.224	5.69	–	–	1.31	33		
		1¼	32	1.12	28.45	1.380	35.05	0.239	6.00	0.88	22.35	–	–		
2	50	½	15	1.00	25.40	0.622	15.80	0.184	4.67	–	–	1.50	38	1.50	0.68
		¾	20	0.94	23.88	0.824	20.93	0.193	4.90	–	–	1.50	38		
		1	25	0.88	22.35	1.049	26.65	0.224	5.69	–	–	1.50	38		
		1¼	32	0.81	20.57	1.380	35.05	0.239	6.00	–	–	1.50	38		
		1½	40	1.25	31.75	1.610	40.64	0.250	6.35	1.00	25.40	–	–		
2½	65	¾	20	1.56	39.62	0.824	20.93	0.193	4.90	–	–	2.12	54	3.00	1.36
		1	25	1.50	38.10	1.049	26.65	0.224	5.69	–	–	2.12	54		
		1¼	32	1.44	36.58	1.380	35.05	0.239	6.00	–	–	2.12	54		
		1½	40	1.38	35.05	1.610	40.64	0.250	6.35	–	–	2.12	54		
		2	50	1.81	46.00	2.067	52.50	0.273	6.93	1.50	38.10	–	–		
3	80	1	25	1.25	31.75	1.049	26.65	0.224	5.69	–	–	1.87	47	4.40	2.00
		1¼	32	1.19	30.23	1.380	35.05	0.239	6.00	–	–	1.87	47		
		1½	40	1.12	28.45	1.610	40.64	0.250	6.35	–	–	1.87	47		
		2	50	1.00	25.40	2.067	52.50	0.273	6.93	–	–	1.87	47		
		2½	65	1.50	38.10	2.469	62.71	0.345	8.76	1.25	31.75	–	–		

To minimize the possibility of cracking of the fillet welds, it is recommended that the shank portion of the reducer be withdrawn approximately .0625 in. (1.6 mm) away from the contact with the bottom of the socket before starting the weld. Likewise, the pipe is to be kept away from contacting the bottom of the reducer socket before welding.

Forged Steel Fittings

Socket-Weld Reducer Inserts



CLASS 6000

For use with Schedule 160 Pipe


Reducer inserts comply with MSS standard SP-79. They enable standard socket-weld fittings to be used for making any combination of pipe line reductions quickly and economically. Socket-weld reducer inserts serve SD D the same purpose as threaded reducing bushings with threaded fittings.

Size				Class 6000 – For use with Schedule 160 Pipe												
				Type	A		D		C Min.		SL		RL Min.		Unit Weight	
NPS	DN	NPS	DN		in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
¾	20	¼	8	2	0.88	22.35	0.250	6.35	0.181	4.60	–	–	–	32	0.81	0.37
		⅜	10	1	0.88	22.35	0.359	9.12	0.198	5.00	0.75	19.05	1.26	–		
		½	15	1	1.00	25.40	0.464	11.79	0.235	6.00	0.75	19.05	–	–		
1	25	¼	8	2	0.94	23.88	0.250	6.35	0.181	4.60	–	–	1.31	33	1.80	0.82
		⅜	10	2	0.88	22.35	0.359	9.12	0.198	5.00	–	–	1.31	33		
		½	15	1	1.12	28.45	0.464	11.79	0.235	6.00	0.81	20.57	–	–		
		¾	20	1	1.12	28.45	0.612	15.49	0.274	6.96	0.81	20.57	–	–		
1¼	32	¼	8	2	1.00	25.40	0.250	6.35	0.181	4.60	–	–	1.37	35	2.00	0.91
		⅜	10	2	0.94	23.88	0.359	9.12	0.198	5.00	–	–	1.37	35		
		½	15	2	0.88	22.35	0.464	11.79	0.235	6.00	–	–	1.37	35		
		¾	20	2	0.81	20.57	0.612	15.49	0.274	6.96	–	–	1.37	35		
		1	25	1	1.19	30.23	0.815	20.70	0.312	7.92	0.88	22.35	–	–		
1½	40	⅜	10	2	1.12	28.45	0.359	9.12	0.198	5.00	–	–	1.56	40	3.20	1.45
		½	15	2	1.06	26.92	0.464	11.79	0.235	6.00	–	–	1.56	40		
		¾	20	2	1.00	25.40	0.612	15.49	0.274	6.96	–	–	1.56	40		
		1	25	1	1.15	29.21	0.815	20.70	0.312	7.92	1.00	25.40	–	–		
		1¼	32	1	1.38	35.05	1.160	29.46	0.312	7.92	1.00	25.40	–	–		
2	50	½	15	2	1.12	28.45	0.464	11.79	0.235	6.00	–	–	1.62	41	5.40	2.45
		¾	20	2	1.06	26.92	0.612	15.49	0.274	6.96	–	–	1.62	41		
		1	25	2	1.00	25.40	0.815	20.70	0.312	7.92	–	–	1.62	41		
		1¼	32	2	0.94	23.88	1.160	29.46	0.312	7.92	–	–	1.62	41		

To minimize the possibility of cracking of the fillet welds, it is recommended that the shank portion of the reducer be withdrawn approximately .0625 in. (1.6 mm) away from the contact with the bottom of the socket before starting the weld. Likewise, the pipe is to be kept away from contacting the bottom of the reducer socket before welding.

Forged Steel Unions

Class 3000 Threaded & Socket-Weld



Manufactured to MSS standard practice SP83
(Class 6000 by method of MSS SP83)

FIGURE 2125: Threaded Union

Size		A		B		C*		D		E		F		Unit Weight	
NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
1/4	8	1 11/16	43	1 31/64	38	53/64	21	25/32	20	7/16	11	0.555 0.575	14 15	0.30	0.14
3/8	10	1 27/32	47	1 11/16	43	1	25	31/32	25	7/16	11	0.690 0.710	18 18	0.50	0.23
1/2	15	2	51	1 15/16	49	1 3/16	30	1 3/32	28	7/16	11	0.855 0.875	22 22	0.70	0.32
3/4	20	2 5/16	59	2 3/8	60	1 15/32	37	1 5/32	29	9/16	14	1.065 1.085	27 28	1.20	0.54
1	25	2 7/16	62	2 25/32	71	1 25/32	45	1 3/8	35	9/16	14	1.330 1.350	34 34	1.70	0.77
1 1/4	32	2 7/8	73	3 23/64	85	2 7/32	686	1 45/64	43	9/16	14	1.675 1.695	43 43	2.50	1.13
1 1/2	40	3	76	3 23/64	85	2 35/64	65	1 7/8	48	9/16	14	1.915 1.935	49 49	3.30	1.50
2	50	3 1/2	89	4 27/64	112	3 1/16	78	2 1/16	52	1 1/16	17	2.406 2.426	61 62	5.30	2.40
2 1/2	65	4 1/4	108	5 15/64	133	3 9/16	90	2 3/8	60	7/8	22	2.906 2.931	74 74	8.60	3.90
3	80	4 7/16	113	6 5/32	156	4 9/32	109	2 7/16	62	1	25	3.535 3.560	90 90	12.70	5.76


FIGURE 2126: Socket-Weld Union

Size		A		B		C*		D		E		F		Unit Weight	
NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
1/4	8	1 11/16	43	1 31/64	38	53/64	21	25/32	20	7/16	11	0.555 0.575	14 15	0.30	0.14
3/8	10	1 27/32	47	1 11/16	43	1	25	31/32	25	7/16	11	0.690 0.710	18 18	0.50	0.23
1/2	15	2	51	1 15/16	49	1 3/16	30	1 3/32	28	7/16	11	0.855 0.875	22 22	0.70	0.32
3/4	20	2 5/16	59	2 3/8	60	1 15/32	37	1 5/32	29	9/16	14	1.065 1.085	27 28	1.20	0.54
1	25	2 7/16	62	2 25/32	71	1 25/32	45	1 3/8	35	9/16	14	1.330 1.350	34 34	1.70	0.77
1 1/4	32	2 7/8	73	3 23/64	85	2 7/32	686	1 45/64	43	9/16	14	1.675 1.695	43 43	2.50	1.13
1 1/2	40	3	76	3 23/64	85	2 35/64	65	1 7/8	48	9/16	14	1.915 1.935	49 49	3.30	1.50
2	50	3 1/2	89	4 27/64	112	3 1/16	78	2 1/16	52	1 1/16	17	2.406 2.426	61 62	5.30	2.40
2 1/2	65	4 1/4	108	5 15/64	133	3 9/16	90	2 3/8	60	7/8	22	2.906 2.931	74 74	8.60	3.90
3	80	4 7/16	113	6 5/32	156	4 9/32	109	2 7/16	62	1	25	3.535 3.560	90 90	12.70	5.76

**C* dimension measures across octagon corners or across the diameter as applicable. The 2 1/2" NPS (65 DN) and 3" NPS (80 DN) – 3000 and 2" NPS (50 DN) – 6000 sizes have octagonal male and female ends; the other sizes are round.

Forged Steel Unions

Class 6000 Threaded & Socket-Weld



Manufactured to MSS standard practice SP83
(Class 6000 by method of MSS SP83)

FIGURE 2127: Threaded Union

Size		A		B		C*		D		E		F		Unit Weight	
NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
1/4	8	1 ²⁷ / ₃₂	47	1 ¹¹ / ₁₆	43	1	25	3 ¹ / ₃₂	25	7/ ₁₆	11	0.555 0.575	14 15	0.60	0.27
3/8	10	2	51	1 ¹⁵ / ₁₆	49	1 ³ / ₁₆	30	1 ³ / ₃₂	28	7/ ₁₆	11	0.690 0.710	18 18	0.80	0.36
1/2	15	2 ⁵ / ₁₆	59	2 ³ / ₈	60	1 ¹⁵ / ₃₂	37	1 ⁵ / ₃₂	29	9/ ₁₆	14	0.855 0.875	22 22	1.40	0.63
3/4	20	2 ⁷ / ₁₆	62	2 ²⁵ / ₃₂	71	1 ²⁵ / ₃₂	45	1 ³ / ₈	35	9/ ₁₆	14	1.065 1.085	27 28	2.00	0.91
1	25	2 ⁷ / ₈	73	3 ²³ / ₆₄	85	2 ⁷ / ₃₂	686	1 ⁴⁵ / ₆₄	43	9/ ₁₆	14	1.330 1.350	34 34	3.10	1.41
1 ¹ / ₄	32	3	76	3 ²³ / ₃₂	94	2 ³⁵ / ₆₄	65	1 ⁷ / ₈	48	9/ ₁₆	14	1.675 1.695	43 43	5.90	2.68
1 ¹ / ₂	40	3 ¹ / ₂	89	4 ²⁷ / ₆₄	112	3 ¹ / ₁₆	78	2 ¹ / ₁₆	52	1 ¹ / ₁₆	17	1.915 1.935	49 49	6.60	2.99
2	50	4 ¹ / ₈	105	5 ¹⁵ / ₆₄	133	3 ⁹ / ₁₆	90	2 ³ / ₈	60	7/ ₈	22	2.406 2.426	61 62	10.50	4.76

FIGURE 2128: Socket-Weld Union

Size		A		B		C*		D		E		F		Unit Weight	
NPS	DN	in	mm	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
1/4	8	1 ²⁷ / ₃₂	47	1 ¹¹ / ₁₆	43	1	25	3 ¹ / ₃₂	25	7/ ₁₆	11	0.555 0.575	14 15	0.60	0.27
3/8	10	2	51	1 ¹⁵ / ₁₆	49	1 ³ / ₁₆	30	1 ³ / ₃₂	28	7/ ₁₆	11	0.690 0.710	18 18	0.80	0.36
1/2	15	2 ⁵ / ₁₆	59	2 ³ / ₈	60	1 ¹⁵ / ₃₂	37	1 ⁵ / ₃₂	29	9/ ₁₆	14	0.855 0.875	22 22	1.40	0.63
3/4	20	2 ⁷ / ₁₆	62	2 ²⁵ / ₃₂	71	1 ²⁵ / ₃₂	45	1 ³ / ₈	35	9/ ₁₆	14	1.065 1.085	27 28	2.00	0.91
1	25	2 ⁷ / ₈	73	3 ²³ / ₆₄	85	2 ⁷ / ₃₂	686	1 ⁴⁵ / ₆₄	43	9/ ₁₆	14	1.330 1.350	34 34	3.10	1.41
1 ¹ / ₄	32	3	76	3 ²³ / ₃₂	94	2 ³⁵ / ₆₄	65	1 ⁷ / ₈	48	9/ ₁₆	14	1.675 1.695	43 43	5.90	2.68
1 ¹ / ₂	40	3 ¹ / ₂	89	4 ²⁷ / ₆₄	112	3 ¹ / ₁₆	78	2 ¹ / ₁₆	52	1 ¹ / ₁₆	17	1.915 1.935	49 49	6.60	2.99
2	50	4 ¹ / ₈	105	5 ¹⁵ / ₆₄	133	3 ⁹ / ₁₆	90	2 ³ / ₈	60	7/ ₈	22	2.406 2.426	61 62	10.50	4.76

**C* dimension measures across octagon corners or across the diameter as applicable. The 2¹/₂" NPS (65 DN) and 3" NPS (80 DN) – 3000 and 2" NPS (50 DN) – 6000 sizes have octagonal male and female ends; the other sizes are round.

Forged Steel Anvilets

Anvil **Anvilets** provide a strong branch pipe connection, considerably stronger than a welded pipe-to-pipe connection. Consequently, with good welding procedures, Anvil **Anvilets** offer greater resistance to distortion and bursting.

Anvil **Anvilets** readily and economically permit the adding of branch connectors to existing piping installations, eliminating the relatively higher cost of cutting or disassembly and re-assembly required for the installation of tees.

Anvil **Anvilets** of the same outlet size as a header or run pipe size (i.e. "Full Size" **Anvilets**) are so proportioned that the (ellipticallyshaped) hole in the header pipe has the minimum weakening or distortion effect, and yet provides good fluid flow characteristics.

Specifications

Chemical and physical properties are rigidly controlled to ensure consistently high quality. Physical and chemical test reports are available on request. Traceability of individual Anvilets can be established through the heat code of each fitting.

Anvil **Anvilets** meet the requirements of MSS standard SP-97. They are forged from steel which complies with ASTM A105.

Threaded Anvilets - conform with ASME B1.20.1.

Socket-Weld Anvilets - dimensions conform with ASME B16.11.

Buttweld Anvilets - ends conform with ASME B16.25.

Reinforcement Requirements

ASME B31.1 Power Piping Code

ASME B31.3 Refinery Code


Forging Markings

Anvil **Anvilets** are clearly marked with the following:

- Outlet size
- Range of run pipe sizes that the **Anvilet** will fit
- The weight, schedule number, or pressure class
- The material specification
- Steel heat code identification

Installation Note

Anvil **Anvilets** are designed to have no more than a $\frac{1}{16}$ " gap (1.6mm) between the base or skirt of the **Anvilet** when it is seated directly upon the appropriate run pipe. However, it is recommended that the skirt of **Anvilets** be held slightly above the run pipe and tack welded to provide a small continuous root gap between the skirt and run pipe before completing the all-around welding beads or fillet.



Specials

Your local Anvil Branch will be more than happy to assist you with specially machined outlets and those made of alloy material.

Pressure Temperature Ratings



MSS standard Practice SP-97 gives the following correlation between fitting pressure class and pipe schedule number/wall thickness designation for calculation of pressure-temperature ratings:

Branch Connection Type	Pressure Class of Fitting	Branch Connection Size		Pipe Wall for Rating Basis
		NPS	DN	
Buttweld	STD	$\frac{1}{8}$ - 24	6 - 600	STD
	XS/XH	$\frac{1}{8}$ - 24	6 - 600	XS/XH
	SCH 160	$\frac{1}{2}$ - 6	15 - 150	SCH 160
Threaded	3,000	$\frac{1}{4}$ - 4	8 - 100	XS/XH
	6,000	$\frac{1}{2}$ - 2	15 - 50	SCH 160
Socket-Welding	3,000	$\frac{1}{2}$ - 2	15 - 50	XS/XH
	6,000	$\frac{1}{2}$ - 2	15 - 50	SCH 160

The maximum allowable pressure of a fitting is computed in accordance with the applicable piping code or regulation for straight seamless header (run) pipe or for material of equivalent composition and mechanical properties to the fitting. Any corrosion or mechanical allowances and any reduction in allowable stress due to temperature or other service conditions, must be applied to the pipe and fitting alike.

Universal Forged Steel Anvilets

Standard & Extra Strong Butt weld



BUTTWELD Standard



Outlet Size		Dimensions						Unit Weight	
		A		B		C			
NPS	DN	in	mm	in	mm	in	mm	lbs	kg
⅛	6	⅝	16	1	25	0.625	16	0.10	0.05
¼	8	⅝	16	1	25	0.625	16	0.10	0.05
⅜	10	¾	19	1	25	0.493	13	0.10	0.05
½	15	¾	19	1⅞	29	0.622	16	0.12	0.05
¾	20	⅞	22	1½	38	0.824	21	0.22	0.10
1	25	1⅙	27	1⅜	46	1.062	27	0.32	0.15
1¼	32	1¼	32	2¼	57	1.380	35	0.64	0.29
1½	40	1⅙	33	2⅙	65	1.625	41	0.78	0.35
2	50	1½	38	3⅙	84	2.313	59	1.14	0.52
2½	65	1⅞	41	3⅒	93	2.500	64	1.94	0.88
3	80	1¾	44	4⅞	109	3.125	79	2.60	1.18
4	100	2	51	5⅝	137	4.145	105	4.12	1.87
6	150	2⅜	60	7⅒	194	6.112	155	11.00	4.99
8	200	2¾	70	10⅝	264	8.688	221	28.00	12.70
10	250	3⅙	78	12⅙	319	10.813	275	39.00	17.69
12	300	3⅜	86	14⅞	378	12.813	325	65.00	29.48
14	350	3½	89	16⅝	410	14.063	357	70.00	31.75
16	400	3⅙	94	18¼	464	16.063	408	92.00	41.73
18	450	4⅙	103	20¾	527	18.625	473	125.00	56.70
20	500	4⅞	117	23⅙	586	20.063	510	175.00	79.38
24	600	5⅜	137	27⅞	708	25.125	638	280.00	127.01

BUTTWELD Extra Strong



Outlet Size		Dimensions						Unit Weight	
		A		B		C			
NPS	DN	in	mm	in	mm	in	mm	lbs	kg
⅛	6	⅝	16	1	25	0.625	16	0.10	0.05
¼	8	⅝	16	1	25	0.625	16	0.10	0.05
⅜	10	¾	19	1	25	0.423	11	0.10	0.05
½	15	¾	19	1⅛	29	0.546	14	0.12	0.05
¾	20	⅞	22	1½	38	0.742	19	0.18	0.08
1	25	1⅙	27	2⅓⅙	71	1.062	27	0.36	0.16
1¼	32	1¼	32	2¼	57	1.278	32	0.55	0.25
1½	40	1⅙	33	2⅙	65	1.625	41	0.68	0.31
2	50	1½	38	3⅙	84	2.313	59	1.24	0.56
2½	65	1⅞	41	3⅒⅓	93	2.500	64	2.26	1.02
3	80	1¾	44	4⅑	109	3.125	79	2.84	1.29
4	100	2	51	5⅜	137	4.145	105	4.56	2.07
6	150	3⅙	78	7⅒⅓	196	5.800	147	15.00	6.80
8	200	3⅞	98	10⅝	270	8.688	221	32.00	14.51
10	250	3½	89	12⅞	327	10.738	273	46.00	20.87
12	300	3⅙	100	15⅙	386	13.000	330	61.00	27.67
14	350	4⅛	105	16⅙	424	14.313	364	75.00	34.02
16	400	4⅙	113	18⅞	479	16.500	419	115.00	52.16
18	450	4⅙	119	21⅞	537	18.625	473	130.00	58.97
20	500	5	127	23⅜	594	20.813	529	187.00	84.82
24	600	5½	140	27⅞	708	25.125	638	316.00	143.34

Each outlet size listed is available to fit any run curvature. BW Ends per B16.9 and B16.25. Design per MSS-SP-97.

RUN PIPE SIZES Outlet sizes 6" and less fit a number of run pipe sizes, and the fittings are marked accordingly. See page 126 for run pipe size combination table(s).



SCHEDULES Standard Weight Fittings are the same as schedule 40 fittings through 10". A schedule 40 butt-welded Universal Forged Steel Anvil for sizes 12" and larger is available. Dimensions and prices on application. Extra Strong Fittings are the same as schedule 80 fittings through 8". A schedule 80 butt-welded Universal Forged Steel Anvil for sizes 10" and larger is available. Dimensions and prices on application. Pipe schedule numbers and weight designations are in accordance with ASME B36.10.

FLATS Flat butt-welded Universal Forged Steel Anvil fittings for use on welding caps, elliptical heads and flat surfaces is available.

The A,B and C dimensions given for the Branch Connections in the above Table are for reference only and to be used as a guideline. Dimensions B and C are subject to change depending upon the manufacturing process utilized. Although every attempt has been made to insure that the information contained in this table is correct, Anvil reserves the right to change the C dimension as deemed necessary.

Universal Forged Steel Anvilets

XXS, SCH. 160 Butt weld



BUTTWELD XXS, Sch. 160 	Outlet Size		Dimensions						Unit Weight	
			A		B		C			
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg
½	15	1⅝	29	1⅝	35	0.563	14	0.25	0.11	
¾	20	1¼	32	1¾	44	0.750	19	0.70	0.32	
1	25	1½	38	2	51	1.000	25	0.85	0.39	
1¼	32	1¾	44	2⅞	62	1.313	33	1.25	0.57	
1½	40	2	51	2¾	70	1.500	38	1.75	0.79	
2	50	2⅜	56	3⅜	81	1.688	43	2.15	0.98	
2½	65	2⅞	62	3⅝	97	2.125	54	3.40	1.54	
3	80	2⅞	73	4¼	121	2.875	73	6.30	2.86	
4	100	3⅝	84	6	152	3.875	98	4.56	4.76	

Each outlet size listed is available to fit any run curvature. BW Ends per B16.9 and B16.25. Design per MSS-SP-97.

RUN PIPE SIZES Outlet sizes 6" and less fit a number of run pipe sizes, and the fittings are marked accordingly. See page 126 for run pipe size combination table(s).



SCHEDULES Standard Weight Fittings are the same as schedule 40 fittings through 10". A schedule 40 butt-welded Universal Forged Steel Anvilet for sizes 12" and larger is available. Dimensions and prices on application. Extra Strong Fittings are the same as schedule 80 fittings through 8". A schedule 80 butt-welded Universal Forged Steel Anvilet for sizes 10" and larger is available. Dimensions and prices on application. Pipe schedule numbers and weight designations are in accordance with ASME B36.10.

FLATS Flat butt-welded Universal Forged Steel Anvilet fittings for use on welding caps, elliptical heads and flat surfaces is available.

The A,B and C dimensions given for the Branch Connections in the above Table are for reference only and to be used as a guideline. Dimensions B and C are subject to change depending upon the manufacturing process utilized. Although every attempt has been made to insure that the information contained in this table is correct, Anvil reserves the right to change the C dimension as deemed necessary.

Universal Forged Steel Anvilets

Class 3000 & 6000 Threaded



THREADED Class 3000



Outlet Size		Dimensions						Unit Weight	
		A		B		C			
NPS	DN	in	mm	in	mm	in	mm	lbs	kg
1/8	6	3/4	19	1	25	0.625	16	0.10	0.05
1/4	8	3/4	19	1 1/16	27	0.437	11	0.14	0.06
3/8	10	13/16	21	1 1/16	27	0.578	15	0.14	0.06
1/2	15	1	25	1 15/32	37	0.718	18	0.28	0.13
3/4	20	1 1/16	27	1 45/64	43	0.922	23	0.39	0.18
1	25	1 5/16	33	2 3/32	53	1.156	29	0.73	0.33
1 1/4	32	1 5/16	33	2 17/32	64	1.500	38	0.96	0.44
1 1/2	40	1 3/8	35	2 25/32	71	1.734	44	1.12	0.51
2	50	1 1/2	38	3 5/16	84	2.218	56	1.66	0.75
2 1/2	65	1 13/16	46	3 29/32	99	2.625	67	2.73	1.24
3	80	2	51	4 21/32	118	3.250	83	3.88	1.76
4	100	2 1/4	57	5 13/16	148	4.250	108	6.18	2.80

THREADED Class 6000



Outlet Size		Dimensions						Unit Weight	
		A		B		C			
NPS	DN	in	mm	in	mm	in	mm	lbs	kg
½	15	1¼	32	1¾	44	0.718	19	0.28	0.13
¾	20	1⅞	37	2⅛	52	0.922	24	0.39	0.18
1	25	1⅞	40	2⅞	64	1.156	31	0.73	0.33
1¼	32	1⅞	41	2½	64	1.500	40	0.96	0.44
1½	40	1⅞	43	3⅞	84	1.734	46	1.12	0.51
2	50	2⅞	52	3⅞	101	2.218	59	1.66	0.75

Each outlet size listed is available to fit any run curvature. Threaded ends are in accordance with ANSI/ASME B1.20.1. Design per MSS-SP-97.



RUN PIPE SIZES Outlet sizes noted above fit a number of run pipe sizes, and the fittings are marked accordingly. See page 126 for run pipe size combination table(s).

FLATS A flat Threaded Universal Forged Steel Anvil for use on welding caps, elliptical heads and flat surfaces is available.

The A, B and C dimensions given for the Branch Connections in the above Table are for reference only and to be used as a guideline. Dimensions B and C are subject to change depending upon the manufacturing process utilized. Although every attempt has been made to insure that the information contained in this table is correct, Anvil reserves the right to change the C dimension as deemed necessary.

Universal Forged Steel Anvilets

Standard & Extra Strong Socket-Weld



SOCKET-WELD Class 3000



Outlet Size		Dimensions								Unit Weight	
		A		B		C		E			
NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
1/8	6	3/4	19	1	25	0.625	16	9/32	7	0.10	0.05
1/4	8	3/4	19	1	25	0.364	9	3/8	10	0.14	0.06
3/8	10	13/16	21	1 1/16	27	0.493	13	7/16	11	0.14	0.06
1/2	15	1	25	1 15/32	37	0.622	16	9/16	14	0.28	0.13
3/4	20	1 1/16	27	1 45/64	43	0.824	21	9/16	14	0.39	0.18
1	25	1 5/16	33	2 3/32	53	1.049	27	25/32	20	0.73	0.33
1 1/4	32	1 5/16	33	2 17/32	64	1.380	35	23/32	18	0.96	0.44
1 1/2	40	1 3/8	35	2 25/32	71	1.610	41	3/4	19	1.12	0.51
2	50	1 1/2	38	3 5/16	84	2.067	53	13/16	21	1.66	0.75
2 1/2	65	1 13/16	46	3 29/32	99	2.469	63	3/4	19	2.73	1.24
3	80	2	51	4 21/32	118	3.068	78	15/16	24	3.88	1.76
4	100	2 1/4	57	5 13/16	148	4.026	102	1 1/16	27	6.60	2.99

SOCKET-WELD Class 6000



Outlet Size		Dimensions						Unit Weight			
		A		B		C				E	
NPS	DN	in	mm	in	mm	in	mm	in	mm	lbs	kg
½	15	1¼	32	1¾	44	0.464	12	13⁄₁₆	21	0.28	0.13
¾	20	1⅞	37	2⅛	52	0.612	16	15⁄₁₆	24	0.39	0.18
1	25	1⅞	40	2¹⁷⁄₃₂	64	0.815	21	1⅓	26	0.73	0.33
1¼	32	1⅞	41	2½	64	1.160	29	1⅓	26	0.96	0.44
1½	40	1⅞	43	3⅞	84	1.338	34	1⅞	27	1.63	0.74
2	50	2⅞	52	3³¹⁄₃₂	101	1.687	43	1⅞	35	1.66	0.75

Each outlet size listed is available to fit any run curvature. Socket dimensions are in accordance with ASME B16.11. Design per MSS-SP-97.

RUN PIPE SIZES Outlet sizes noted above fit a number of run pipe sizes, and the fittings are marked accordingly. See page 126 for run pipe size combination table(s).

FLATS A flat Socket-welded Universal Forged Steel Anvilet for use on welding caps, elliptical heads and flat surfaces is available.

The A, B and C dimensions given for the Branch Connections in the above Table are for reference only and to be used as a guideline. Dimensions B and C are subject to change depending upon the manufacturing process utilized. Although every attempt has been made to insure that the information contained in this table is correct, Anvil reserves the right to change the C dimension as deemed necessary.

Engineering Specifications

Universal Forged Steel Anvilets Run Size Combinations




Outlet Size (in)												
Butt Weld Standard	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4	6
	1/4	1/2 - 3/8	1 - 1/2	2 - 3/4	1	1 1/4	1 1/2	2	2 1/2	3	4	6
	36 - 3/8	36 - 3/4	36 - 1 1/4	36 - 2 1/2	1 1/2 - 1 1/4	2 - 1 1/2	3 1/2 - 2	3 - 2 1/2	4 - 3	4 - 3 1/2	6 - 5	8
					36 - 2	6 - 2 1/2	36 - 4	6 - 3 1/2	10 - 5	6 - 5	10 - 8	10
						36 - 8		36 - 8	36 - 12	14 - 8	20 - 12	14 - 12
										36 - 16	36 - 22	18 - 16
												24 - 20
												34 - 26
Butt Weld Extra Strong	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4	6
	36 - 1/4	3/8	3/4 - 1/2	1 1/2 - 3/4	1	2 - 1 1/4	1 1/2	2	2 1/2	3	4	6
		36 - 1/2	36 - 1	36 - 2	1 1/2 - 1 1/4	5 - 2 1/2	3 1/2 - 2	3 - 2 1/2	4 - 3	4 - 3 1/2	6 - 5	8
					36 - 2	36 - 6	36 - 4	6 - 3 1/2	10 - 5	6 - 5	10 - 8	10
								36 - 8	36 - 12	14 - 8	20 - 12	14 - 12
										36 - 1	36 - 22	18 - 16
												24 - 20
												34 - 26
												42 - 36

Outlet Size (in)											
Threaded Class 3000	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
	3/8 - 1/4	1 - 3/8	1/2	1 1/4 - 3/4	1	1 1/2 - 1 1/4	1 1/2	2	2 1/2	3	4
	36 - 1/2	36 - 1 1/4	36 - 3/4	36 - 1 1/2	2 1/2 - 1 1/4	3 1/2 - 2	2 1/2 - 2	3 1/2 - 2 1/2	3 1/2 - 3	5 - 3 1/2	6 - 5
					36 - 3	36 - 4	5 - 3	6 - 4	6 - 4	14 - 6	10 - 8
							36 - 6	36 - 8	36 - 8	36 - 16	20 - 12
Threaded Class 6000	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
	3/8 - 1/4	1 - 3/8	1/2	3/4	1	1 1/2 - 1 1/4	1 1/2	2	2 1/2	3	4
	36 - 1/2	36 - 1 1/4	36 - 3/4	1 1/4 - 1	2 1/2 - 1 1/4	3 1/2 - 2	2 1/2 - 2	3 1/2 - 2 1/2	3 1/2 - 3	3 1/2	5
				36 - 1 1/2	36 - 3	8 - 4	5 - 3	6 - 4	5 - 4	4	6
						36 - 10	36 - 6	36 - 8	10 - 6	6 - 5	10 - 8
									26 - 12	12 - 8	18 - 12
									36 - 28	36 - 14	36 - 20

Outlet Size (in)											
Socket-Weld Class 3000	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
	1/4	1/2 - 3/8	1/2	1 1/4 - 3/4	1	1 1/2 - 1 1/4	1 1/2	2	2 1/2	3	4
	36 - 3/8	36 - 3/4	36 - 3/4	36 - 1 1/2	2 1/2 - 1 1/4	3 1/2 - 2	2 1/2 - 2	3 1/2 - 2 1/2	3 1/2 - 3	5 - 3 1/2	6 - 5
					36 - 3	36 - 4	5 - 3	6 - 4	6 - 4	14 - 6	10 - 8
							36 - 6	36 - 8	36 - 8	36 - 16	20 - 12
Socket-Weld Class 6000	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
	36 - 1/4	36 - 3/8	1/2	1 - 3/4	1	1 1/4	1 1/2	2	3 - 2 1/2	3 1/2 - 3	4
			36 - 3/4	36 - 1 1/4	2 1/2 - 1 1/4	4 - 1 1/2	2 1/2 - 2	3 1/2 - 2 1/2	5 - 3 1/2	5 - 4	5
					36 - 3	36 - 5	5 - 3	6 - 4	18 - 6	10 - 6	8 - 6
							36 - 6	36 - 8	36 - 20	26 - 12	14 - 10
										36 - 28	36 - 16

Universal Elbowlet

Class 3000 and 6000 Buttweld, Threaded and Socket-Weld





CLASS 3000 THREADED AND SOCKET-WELD/STANDARD AND XS/XH BUTTWELD									
Outlet Size		Nom. Elbow Size		C		H		Unit Weight	
NPS	DN	NPS	DN	in	mm	in	mm	lbs	kg
1/2	15	36 - 3/4	900 - 32	1 1/2	38	1 19/32	40	0.65	0.29
3/4	20	36 - 1	900 - 32	1 23/32	44	1 7/8	48	0.75	0.34
1	25	36 - 2	900 - 32	2 1/8	54	2 3/16	56	1.10	0.52
1 1/4	32	36 - 2	900 - 32	1 21/32	42	2 3/8	60	1.90	0.86
1 1/2	40	36 - 2	900 - 32	3	76	2 5/8	67	2.60	1.20
2	50	36 - 3	900 - 32	4 1/8	105	3 3/16	81	5.30	2.40
CLASS 6000 THREADED AND SOCKET-WELD									
1/2	15	36 - 3/4	900 - 32	1 23/32	44	1 7/8	48	0.85	0.39
3/4	20	36 - 1	900 - 50	2 1/8	54	2 3/16	56	1.30	0.57
1	25	36 - 2	900 - 50	2 21/32	67	2 3/8	60	2.20	1.00
1 1/4	32	36 - 2	900 - 50	3	76	2 5/8	67	3.90	1.80
1 1/2	40	36 - 2	900 - 50	4 1/8	105	3 3/16	81	6.20	2.80

Universal elbowlets are welded to 90° long radius elbows as branch connections for pipes and fittings. They are also used as pipe hanger or support bosses.


Lateral Anvilets

Class 3000 Butt weld and Threaded

Lateral Anvilets provide a strong, readily attached 45° lateral outlet connection.



BUTT WELD



THREADED

CLASS 3000 STANDARD/XS BUTT WELD

Outlet Size		Nominal Run Pipe Size		H		B		C		Unit Weight	
NPS	DN	NPS	DN	in	mm	in	mm	in	mm	lbs	kg
1/2	15	2 1/2 - 1 1/4 / 12 - 3	65 - 32 / 300 - 80	1 3/8	35	2 5/32	55	1 1/16	37	0.65	0.29
3/4	20	1 1/2 - 1 1/4 / 5 - 2 / 12 - 6	40 - 32 / 125 - 50 / 300 - 150	1 11/16	43	2 17/32	64	1 3/4	44	0.75	0.34
1	25	2 1/2 - 2 / 5 - 3 / 12 - 6	65 - 50 / 125 - 80 / 300 - 150	1 31/32	50	3	76	2 1/8	54	1.10	0.52
1 1/4	32	2 1/2 - 2 / 5 - 3 / 12 - 6	65 - 50 / 125 - 80 / 300 - 150	2 9/32	58	3 19/32	91	2 5/8	67	1.90	0.86
1 1/2	40	2 1/2 - 2 / 5 - 3 / 12 - 6	65 - 50 / 125 - 80 / 300 - 150	2 15/32	63	3 31/32	101	3 1/32	77	2.60	1.20
2	50	5 - 4 / 8 - 6 / 12 - 10	125 - 100 / 200 - 150 / 300 - 150	3 3/16	81	5 1/4	133	4 1/8	105	5.30	2.40


CLASS 3000 THREADED/STANDARD


Outlet Size		Nominal Run Pipe Size		H		B		C		Unit Weight	
NPS	DN	NPS	DN	in	mm	in	mm	in	mm	lbs	kg
1/2	15	2 1/2 - 1 1/4 / 12 - 3	65 - 32 / 300 - 80	1 9/16	40	2 11/32	60	1 1/16	37	0.65	0.29
3/4	20	1 1/2 - 1 1/4 / 5 - 2 / 12 - 6	40 - 32 / 125 - 50 / 300 - 150	1 7/8	48	2 3/4	70	1 3/4	44	0.75	0.34
1	25	2 1/2 - 2 / 5 - 3 / 12 - 6	65 - 50 / 125 - 80 / 300 - 150	2 3/16	56	3 1/4	83	2 1/8	54	1.10	0.52
1 1/4	32	2 1/2 - 2 / 5 - 3 / 12 - 6	65 - 50 / 125 - 80 / 300 - 150	2 1/2	64	3 27/32	98	2 5/8	67	1.90	0.86
1 1/2	40	2 1/2 - 2 / 5 - 3 / 12 - 6	65 - 50 / 125 - 80 / 300 - 150	2 3/4	70	4 7/32	107	3 1/32	77	2.60	1.20
2	50	5 - 4 / 8 - 6 / 12 - 10	125 - 100 / 200 - 150 / 300 - 150	3 3/8	86	5 7/16	138	4 1/8	105	5.30	2.40


Flat Anvilets


Class 3000 Threaded, Buttweld and Socket-Weld

Flat Anvilets are designed to facilitate welding to a flat surface for the installation of branch pipes or fittings.

THREADED Class 3000 Flat Anvilet	Outlet Size		Dimensions				Unit Weight	
			A		B			
	NPS	DN	in	mm	in	mm	lbs	kg
	1/4	8	3/4	19	1	25	0.10	0.05
	3/8	10	13/16	21	1 1/4	32	0.20	0.09
	1/2	15	1	25	1 13/32	36	0.25	0.11
	3/4	20	1 1/16	27	1 23/32	44	0.35	0.16
	1	25	1 5/16	33	2	51	0.60	0.27
	1 1/4	32	1 5/16	33	2 9/16	65	0.90	0.41
	1 1/2	40	1 3/8	35	2 27/32	72	1.00	0.45
	2	50	1 1/2	38	3 15/32	88	1.75	0.79
	2 1/2	65	1 13/16	46	4 1/16	103	3.00	1.36
	3	80	2	51	4 13/16	122	4.35	1.97

BUTTWELD Class 3000 Flat Anvilet	Outlet Size		Dimensions				Unit Weight	
			A		B			
	NPS	DN	in	mm	in	mm	lbs	kg
	1/4	8	5/8	16	1	25	0.10	0.05
	3/8	10	3/4	19	1 1/4	32	0.15	0.07
	1/2	15	3/4	19	1 3/8	35	0.20	0.09
	3/4	20	7/8	22	1 3/4	44	0.30	0.14
	1	25	1 1/16	27	2 1/8	54	0.50	0.23
	1 1/4	32	1 1/4	32	2 9/16	65	0.90	0.41
	1 1/2	40	1 5/16	33	2 7/8	73	1.10	0.50
	2	50	1 1/2	38	3 1/2	89	1.75	0.79
	2 1/2	65	1 5/8	41	4 1/16	103	2.60	1.18
	3	80	1 3/4	44	4 13/16	122	4.10	1.86

SOCKET-WELD Class 3000 Flat Anvilet	Outlet Size		Dimensions						Unit Weight	
			A		B		E			
	NPS	DN	in	mm	in	mm	in	mm	lbs	kg
	1/4	8	3/4	19	1	25	9/32	7	0.10	0.05
	3/8	10	13/16	21	1 1/4	32	7/16	11	0.20	0.09
	1/2	15	1	25	1 13/32	36	9/16	14	0.30	0.14
	3/4	20	1 1/16	27	1 23/32	44	9/16	14	0.35	0.16
	1	25	1 5/16	33	2	51	25/32	20	0.60	0.27
	1 1/4	32	1 5/16	33	2 9/16	65	3/4	19	0.85	0.39
	1 1/2	40	1 3/8	35	2 27/32	72	3/4	19	1.00	0.45
	2	50	1 1/2	38	3 15/32	88	13/16	21	1.60	0.73
	2 1/2	65	1 9/16	40	4 1/16	103	3/4	19	2.75	1.25
	3	80	1 3/4	44	4 13/16	122	15/16	24	3.80	1.72



Material

ASTM A29, A105, A395, A536

Full Traceability:

All Catawissa Oilfield Wing Unions are fully traceable and are available with complete mill certifications upon request.

Interchangeability:

All Catawissa Oilfield Unions are machined to rigid quality standards ensuring that like components of the same size, figure number and pressure rating are fully interchangeable in the field. Catawissa Oilfield Unions are interchangeable with most leading union manufacturers.

Standard Service:

Catawissa Unions are available for Standard Service. Catawissa Oilfield Unions meet or exceed National Association of Corrosion Engineers standard NACE MR-01-75 and API RP-14E, and are made in an ISO 9001-2000 certified facility. (Sour gas unions are available upon request only.)

Full Range of End Connections:

Catawissa Oilfield Wing Unions are also available in threaded ends as well as butt weld and non-pressure seal ends. When you choose Catawissa you receive the utmost in quality, the widest selection and unmatched on-time deliveries.

Malleable Iron

Cast Iron

Small Steel Fittings

Pipe Nipples & Pipe Couplings

Forged Steel Fittings & Unions

Anvilets

Catawissa

J.B. Smith Products

Carton Information

Wing Unions

1,000 psi cwp – 1,500 psi test



FIGURE 100 Threaded Ends Black Nut/Yellow Subs	Size		Item	Unit Weight		A		B		C+		TPI	Material	
	NPS	DN		lbs	kg	in	mm	in	mm	in	mm		Nuts	Subs
	2	50	Union Complete	6.25	2.83	3.940	100.08	2.840	72.14	6.250	158.75	3 MOD	DI	DI
			Nut	3.30	1.50									
			Male Sub	1.30	0.59									
			Female Sub	1.65	0.75									
	2½	65	Union Complete	10.05	4.56	4.490	114.05	3.390	86.11	7.925	201.30	3 MOD	DI	DI
			Nut	5.30	2.40									
			Male Sub	2.25	1.02									
			Female Sub	2.50	1.13									
	3	80	Union Complete	13.65	6.19	5.000	127.00	4.030	102.36	9.000	228.60	3 MOD	DI	DI
			Nut	7.15	3.24									
			Male Sub	3.25	1.47									
			Female Sub	3.25	1.47									
	4	100	Union Complete	22.00	9.98	5.940	150.88	5.230	132.84	10.560	268.22	3 MOD	DI	DI
			Nut	9.80	4.44									
			Male Sub	6.65	3.02									
			Female Sub	5.55	2.52									
	6	150	Union Complete	45.85	20.79	6.800	172.72	7.390	187.71	13.810	350.77	3 STD	DI	DI
			Nut	21.75	9.86									
			Male Sub	11.10	5.03									
			Female Sub	13.00	5.90									
	8	200	Union Complete	66.65	30.23	7.230	183.64	9.700	246.38	16.125	409.58	3 STD	DI	DI
			Nut	27.40	12.43									
			Male Sub	18.10	8.21									
			Female Sub	21.15	9.59									

Low pressure service. Manifold and general service. Female threaded ends. 2" available with 8RD thread. Consult Factory.

FIGURE 100C Threaded Ends Black Nut/Yellow Subs	Size		Item	Unit Weight		A		B		C+		TPI	Material	
	NPS	DN		lbs	kg	in	mm	in	mm	in	mm		Nuts	Subs
	2	50	Lug Union	6.25	3.06	3.940	100.08	2.840	72.14	6.250	158.75	3 MOD	SF	SF

Note: Available in import only. Ideal for low-pressure service. Manifold and general service. Female threaded ends.

- Warnings:** 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
 2. Do not make up or break out Unions in pressurized lines.
 3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.

Wing Unions

2,000 psi cwp – 3,000 psi test



FIGURE 200 Threaded Ends Blue Nut/Gray Subs	Size		Item	Unit Weight		A		B		C+		D	TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm			Nuts	Subs
	1	25	Union Complete	1.75	0.79	2.67	67.82	1.64	41.66	4.07	103.25	▲	6 STD	DI	SF
			Nut	0.95	0.43										
			Male Sub	0.40	0.18										
			Female Sub	0.40	0.18										
	1¼	32	Union Complete	2.25	1.02	2.73	69.34	1.94	49.15	4.64	117.73	▲	6 STD	DI	SF
			Nut	1.20	0.54										
			Male Sub	0.50	0.23										
			Female Sub	0.55	0.25										
	1½	40	Union Complete	2.75	1.25	2.77	70.36	2.25	57.15	4.75	120.65	▲	6 STD	DI	SF
			Nut	1.30	0.59										
			Male Sub	0.70	0.32										
			Female Sub	0.75	0.34										
	† 2	50 (Ductile Iron)	Union Complete	4.75	2.15	3.28	83.19	2.83	71.76	5.90	149.86	▲	4 STD	DI	DI
			Nut	2.20	1.00										
			Male Sub	1.15	0.52										
			Female Sub	1.40	0.63										
	2	50 (Forged Steel)	Union Complete	5.60	2.54	3.28	83.19	2.83	71.76	5.90	149.86	▲	4 STD	DI	SF
			Nut	2.20	1.00										
			Male Sub	1.20	0.54										
			Female Sub	1.60	0.73										
	2½	65	Union Complete	10.70	4.85	4.25	107.95	3.40	86.36	7.90	200.66	▲	4 STD	DI	SF
			Nut	6.40	2.90										
			Male Sub	2.00	0.91										
			Female Sub	2.30	1.04										
	3	80	Union Complete	12.85	5.83	4.66	118.36	4.17	105.92	8.10	205.74	▲	4 STD	DI	SF
			Nut	6.00	2.72										
			Male Sub	3.35	1.52										
			Female Sub	3.50	1.59										
	4	100	Union Complete	18.70	8.48	4.91	124.71	5.08	128.91	9.06	230.12	▲	3 MOD	DI	SF
			Nut	7.40	3.36										
			Male Sub	5.30	2.40										
			Female Sub	6.00	2.72										
	6	150	Union Complete	46.10	20.91	6.61	167.89	7.41	188.21	12.80	325.12	▲	3 STD	DI	SF
			Nut	18.18	8.24										
			Male Sub	12.74	5.78										
			Female Sub	15.18	6.88										

General purpose union. Threaded and butt weld ends available.

- Warnings:** 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
 2. Do not make up or break out Unions in pressurized lines.
 3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.



Wing Unions

2,000 psi cwp – 3,000 psi test



FIGURE 200 Buttweld Ends Schedule 40 Blue Nut/Gray Subs	Size		Item	Unit Weight		A		B		C+		D	TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm			Nuts	Subs
† 2 50			Union Complete	5.50	2.49	3.275	83.19	2.825	71.76	5.900	149.86	▲	4 STD	DI	DI
			Nut	2.20	1.00										
			Male Sub	1.50	0.68										
			Female Sub	1.80	0.82										
3 80			Union Complete	14.50	6.58	4.660	118.36	4.170	105.92	8.100	205.74	▲	4 STD	DI	SF
			Nut	6.00	2.72										
			Male Sub	3.50	1.59										
			Female Sub	4.50	2.04										
4 100			Union Complete	20.90	9.48	4.910	124.71	5.075	128.91	9.060	230.12	▲	3 MOD	DI	SF
			Nut	7.40	3.36										
			Male Sub	6.18	2.80										
			Female Sub	7.38	3.35										

General purpose union. Threaded and butt weld ends available.

FIGURE 200C Threaded Ends Blue Nut/Gray Subs	Size		Item	Unit Weight		A		B		C+		D	TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm			Nuts	Subs
	1	25	Lug Union	1.75	0.79	2.670	67.82	1.640	41.66	4.065	103.25	*	6 STD	SF	SF
	2	50	Lug Union	4.90	2.22	3.275	83.19	2.825	71.76	5.900	149.86	*	4 STD	SF	SF

Note: Available in import only. General purpose union. Available in threaded ends. *Consult Factory.

- Warnings:** 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
 2. Do not make up or break out Unions in pressurized lines.
 3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.

Wing Unions

2,000 psi cwp – 3,000 psi test



FIGURE 206 Threaded Ends Blue Nut/Gray Subs with Seal Ring	Size		Item	Unit Weight		A		B		C+		D	TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm			Nuts	Subs
	1	25	Union Complete	1.75	0.79	2.670	67.82	1.640	41.66	4.065	103.25	▲	6 STD	DI	SF
			Nut	0.95	0.43										
			Male w/O-Ring	0.40	0.18										
			Female Sub	0.40	0.18										
			O-Ring	—	—										
	1¼	32	Union Complete	2.25	1.02	2.730	69.34	1.935	49.15	4.635	117.73	▲	6 STD	DI	SF
			Nut	1.20	0.54										
			Male w/O-Ring	0.50	0.23										
			Female Sub	0.55	0.25										
			O-Ring	—	—										
	1½	40	Union Complete	2.75	1.25	2.770	70.36	2.250	57.15	4.750	120.65	▲	6 STD	DI	SF
			Nut	1.30	0.59										
			Male w/O-Ring	0.70	0.32										
			Female Sub	0.75	0.34										
			O-Ring	—	—										
	† 2	50	Union Complete	4.75	2.15	3.275	83.19	2.825	71.76	5.900	149.86	▲	4 STD	DI	DI
			Nut	2.20	1.00										
			Male w/O-Ring	1.15	0.52										
			Female Sub	1.40	0.63										
			O-Ring	—	—										
	2½	65	Union Complete	10.70	4.85	4.250	107.95	3.400	86.36	7.900	200.66	▲	4 STD	DI	SF
			Nut	6.40	2.90										
			Male w/O-Ring	2.00	0.91										
			Female Sub	2.30	1.04										
			O-Ring	—	—										
	3	80	Union Complete	13.00	5.90	4.660	118.36	4.170	105.92	8.100	205.74	▲	4 STD	DI	SF
			Nut	6.00	2.72										
			Male w/O-Ring	3.35	1.52										
			Female Sub	3.50	1.59										
			O-Ring	—	—										
	4	100	Union Complete	18.70	8.48	4.910	124.71	5.075	128.91	9.060	230.12	▲	3 MOD	DI	SF
			Nut	7.40	3.36										
			Male w/O-Ring	5.30	2.40										
			Female Sub	6.00	2.72										
			O-Ring	—	—										
	6	150	Union Complete	46.10	20.91	6.610	167.89	7.410	188.21	12.800	325.12	▲	3 STD	DI	SF
			Nut	18.18	8.24										
			Male w/O-Ring	12.74	5.78										
			Female Sub	15.18	6.88										
			O-Ring	—	—										

O-Ring in male sub for improved sealing. Available in threaded and butt weld ends.

Warnings: 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
 2. Do not make up or break out Unions in pressurized lines.
 3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.



Wing Unions

2,000 psi cwp – 3,000 psi test

FIGURE 211 Insulating Union Threaded Ends Gray Nut/Light Blue Subs	Size		Item	Unit Weight		A		B		C		TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm		Nuts	Subs
	1	25	Union Complete	2.34	1.06	2.830	71.88	1.560	39.62	4.660	118.36	6 STD	SF	SF
			Nut	1.42	0.64									
			Male Sub	0.40	0.18									
			Female Sub	0.52	0.24									
			Seal Ring Kit	—	—									
	2	50	Union Complete	6.24	2.83	3.510	89.15	2.880	73.15	6.250	158.75	6 STD	SF	SF
			Nut	2.96	1.34									
			Male Sub	1.42	0.64									
			Female Sub	1.86	0.84									
			Seal Ring Kit	—	—									

Laminated rings provide full insulation from electrolytic corrosion. Total of 35 million OHMS resistance. O-Ring in male sub and seal ring in female sub provide primary and secondary seals. All seal rings are field-replaceable. Available in threaded and butt weld ends.

FIGURE 300 Flat-Face Union Gray Nut/Yellow Subs	Size		Item	Unit Weight		A		B		C		Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm	Nuts	Subs
 Straight Away Breakout	1	25	Union Complete	2.21	1.00	2.625	66.68	1.560	39.62	4.250	107.95	DI	SF
			Nut	1.50	0.68								
			Male Sub	0.31	0.14								
			Female Sub w/O-Ring	0.50	0.23								
			Seal Ring	—	—								
	2	50	Union Complete	6.00	2.72	3.750	95.25	2.780	70.61	5.750	146.05	DI	SF
			Nut	3.31	1.50								
			Male Sub	1.25	0.57								
			Female Sub w/O-Ring	1.44	0.65								
			Seal Ring	—	—								
	2½	65	Union Complete	10.88	4.93	4.625	117.48	3.410	86.61	7.000	177.8	DI	SF
			Nut	6.19	2.81								
			Male Sub	2.13	0.97								
			Female Sub w/O-Ring	2.56	1.16								
			Seal Ring	—	—								
	3	80	Union Complete	14.25	6.46	5.000	127.00	4.300	109.22	8.000	203.2	DI	SF
			Nut	6.31	2.86								
			Male Sub	3.50	1.59								
			Female Sub w/O-Ring	4.44	2.01								
			Seal Ring	—	—								
	4	100	Union Complete	20.69	9.38	5.750	146.05	5.110	129.79	8.875	225.43	DI	SF
			Nut	8.31	3.77								
			Male Sub	5.57	2.53								
			Female Sub w/O-Ring	6.63	3.01								
			Seal Ring	—	—								

Flat Face Fig. 300 Unions permit lateral removal of valves and other fittings for easy replacement or inspection. Unions seal equally well in low or high pressure liquid or vapor service.

Wing Unions

3,000 psi cwp – 4,500 psi test



FIGURE 301 Steam Service Union Black Nut/Green Subs	Size		Item	Unit Weight		A		B		C		TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm		Nuts	Subs
	1	25	Union Complete	1.75	0.79	2.670	67.82	1.640	41.66	4.065	103.38	6 STD	SF	SF
			Nut	—	—									
			Male Sub	—	—									
			Female Sub	—	—									
			Seal Ring	—	—									
	2	50	Union Complete	4.90	2.22	3.275	83.31	2.825	71.88	5.900	149.86	3½ STD	SF	SF
			Nut	—	—									
			Male Sub	—	—									
			Female Sub	—	—									
			Seal Ring	—	—									
	3	80	Union Complete	13.25	6.01	4.660	118.36	4.170	105.92	8.100	205.74	4 STD	SF	SF
			Nut	—	—									
			Male Sub	—	—									
			Female Sub	—	—									
			Seal Ring	—	—									

4,000 psi cwp – 6,000 psi test

FIGURE 400 Threaded Ends Black Nut/Red Subs	Size		Item	Unit Weight		A		B		C		TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm		Nuts	Subs
	2	50	Union Complete	11.05	5.01	5.225	132.72	3.000	76.20	7.125	180.98	3 STD	SF	SF
			Nut	5.60	2.54									
			Male Sub	2.65	1.20									
			Female Sub	2.80	1.27									
	3	80	Union Complete	20.00	9.07	6.110	155.19	4.250	107.95	8.750	222.25	3 STD	SF	SF
			Nut	8.50	3.85									
			Male Sub	5.50	2.49									
			Female Sub	6.00	2.72									
	4	100	Union Complete	29.15	13.22	8.200	208.28	5.275	133.99	9.160	232.66	3 STD	SF	SF
			Nut	10.15	4.60									
			Male Sub	8.85	4.01									
			Female Sub	10.15	4.60									

Ideal for manifold and pumping service. Available in threaded and butt weld ends.

- Warnings:** 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
 2. Do not make up or break out Unions in pressurized lines.
 3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.

Wing Unions

4,000 psi cwp – 6,000 psi test

FIGURE 400 Buttweld Ends Schedule 80 Black Nut/Red Subs	Size		Item	Unit Weight		A		B		C		TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm		Nuts	Subs
	2	50	Union Complete	10.75	4.88	5.225	132.72	3.00	76.20	7.125	180.98	3 STD	SF	SF
			Nut	5.60	2.54									
			Male Sub	2.75	1.25									
			Female Sub	3.00	1.36									

Ideal for manifold and pumping service. Available in threaded and butt weld ends.

6,000 psi cwp – 9,000 psi test

FIGURE 600 Threaded Ends Black Nut/Silver Subs 	Size		Item	Unit Weight		A		B		C		TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm		Nuts	Subs
	1	25	Union Complete	3.65	1.66	3.565	90.55	1.750	44.45	4.500	114.3	6 STD	SF	BS
			Nut	1.95	0.88									
			Male Sub	0.65	0.29									
			Female Sub w/Bronze Seat	1.05	0.48									
			Bronze Seat Insert	0.05	0.023									
	1½	40	Union Complete	—	—	*	*	*	*	*	*	4 STD	SF	BS
			Nut	—	—									
			Male Sub	—	—									
			Female Sub w/Bronze Seat	—	—									
			Bronze Seat Insert	—	—									
	2	50	Union Complete	15.64	7.09	6.440	163.58	3.010	76.45	7.160	181.86	2 STD	SF	(F) ST
			Nut	7.08	3.21									(M) SF
			Male Sub	3.22	1.46									
			Female Sub w/Bronze Seat	5.34	2.42									
			Bronze Seat Insert	0.65	0.30									
	3	80	Union Complete	27.25	12.36	8.875	225.43	4.1875	106.36	8.750	222.25	2 STD	SF	SF
			Nut	—	—									
			Male Sub	—	—									
			Female Sub w/Bronze Seat	—	—									
			Bronze Seat Insert	—	—									
4	100	Union Complete	40.00	18.14	10.0625	255.59	5.250	133.35	10.625	269.88	2 STD	SF	SF	
		Nut	14.25	6.48										
		Male Sub	11.00	5.00										
		Female Sub w/Bronze Seat	12.65	5.75										
		Bronze Seat Insert	2.15	0.98										

Features bronze seat for primary seal to prevent rust and corrosion in well servicing and drilling. Available in threaded and butt weld ends. *Consult Factory.


Warnings: 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
 2. Do not make up or break out Unions in pressurized lines.
 3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.

Wing Unions

6,000 psi cwp – 9,000 psi test



FIGURE 602 Threaded Ends Black Nut/Orange Subs	Size		Item	Unit Weight		A		B		C		TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm		Nuts	Subs
	1	25	Union Complete	3.55	1.61	6.625	168.28	1.750	44.45	4.500	114.30	6 STD	SF	SF
			Nut	1.95	0.88									
			Male Sub	0.60	0.27									
			Female Sub w/Ring	1.00	0.45									
			Seat Ring	—	—									
	1½	40	Union Complete	9.54	4.33	4.600	116.84	2.570	65.28	5.520	140.21	4 STD	SF	SF
			Nut	4.98	2.26									
			Male Sub	1.98	0.90									
			Female Sub w/Ring	2.58	1.17									
			Seat Ring	—	—									
	2	50	Union Complete	12.40	5.62	5.300	134.62	2.970	75.44	6.875	174.63	3 MOD	SF	SF
			Nut	6.50	2.95									
			Male Sub	2.85	1.29									
			Female Sub w/Ring	3.05	1.38									
			Seat Ring	—	—									
	3	80	Union Complete	22.30	10.11	6.310	160.27	4.250	107.95	8.875	225.43	3 MOD	SF	SF
			Nut	9.95	4.51									
			Male Sub	5.20	2.36									
			Female Sub w/Ring	7.15	3.24									
			Seat Ring	—	—									
4	100	Union Complete	32.18	14.59	8.300	210.82	5.200	132.08	10.040	255.02	3 MOD	SF	SF	
		Nut	13.30	6.03										
		Male Sub	8.36	3.79										
		Female Sub w/Ring	10.52	4.77										
		Seat Ring	—	—										

Compact design is well-suited for manifold service. Seal ring protects the metal-to-metal seal. Seal design reduces line turbulence.
Available in threaded and butt weld ends.

- Warnings:** 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
2. Do not make up or break out Unions in pressurized lines.
3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.

Wing Unions

6,000 psi cwp – 9,000 psi test

	Size		Item	Unit Weight		A		B		C		TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm		Nuts	Subs
FIGURE 602 Buttweld Ends Schedule 80 Black Nut/Orange Subs	2	50	Union Complete	12.12	5.50	5.300	134.62	2.970	75.44	6.875	174.63	3 MOD	SF	SF
			Nut	6.50	2.95									
			Male Sub	2.76	1.25									
			Female Sub w/Ring	2.82	1.28									
			Seat Ring	—	—									
	3	80	Union Complete	21.25	9.64	6.310	160.27	4.250	107.95	8.875	225.43	3 MOD	SF	SF
			Nut	9.95	4.51									
			Male Sub	5.75	2.61									
			Female Sub w/Ring	6.00	2.72									
			Seat Ring	—	—									
	4	100	Union Complete	28.25	12.81	8.300	210.82	5.200	132.08	10.040	255.02	3 MOD	SF	SF
			Nut	13.30	6.03									
			Male Sub	7.50	3.40									
			Female Sub w/Ring	9.75	4.42									
			Seat Ring	—	—									

FIGURE 607 Well Service Union Threaded Ends Yellow Nut/Silver Subs	Size		Item	Unit Weight		A		B		C		TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm		Nuts	Subs
	1½	40	Union Complete	8.96	4.06	4.15	105.41	2.6	66.04	6.53	165.74	5 STD	SF	SF
			Nut	5.34	2.42									
			Male Sub	1.52	0.69									
			Female Sub w/Ring	2.10	0.95									
			Seat Ring	—	—									
	2	50	Union Complete	14.64	6.64	5.85	148.59	3.08	78.23	7.33	186.18	5 STD	SF	SF
			Nut	7.68	3.48									
			Male Sub	2.82	1.28									
			Female Sub w/Ring	4.14	1.88									
			Seat Ring	—	—									

Ideal for hot oil trucks and any application similar to Figure 602. Extended Subs allow for quick breakout on trucks and manifolds. Metal-to-metal connection.


- Warnings:** 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
 2. Do not make up or break out Unions in pressurized lines.
 3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.

Wing Unions

10,000 psi cwp – 15,000 psi test



FIGURE 1002 Threaded Ends Red Nut/Blue Subs	Size		Item	Unit Weight		A		B		C		TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm		Nuts	Sub
	1	25	Union Complete	3.62	1.64	3.620	91.95	1.750	44.45	4.500	114.30	6	STD	All Alloy Steel Forging
			Nut	2.02	0.92									
			Male Sub	0.70	0.32									
			Female Sub w/Ring	0.90	0.41									
			Seat Ring	—	—									
	1½	40	Union Complete	9.54	4.33	4.600	116.84	2.570	65.28	5.520	140.21	4	STD	
			Nut	4.98	2.26									
			Male Sub	1.98	0.90									
			Female Sub w/Ring	2.58	1.17									
			Seat Ring	—	—									
	2	50	Union Complete	13.00	5.90	5.200	132.08	3.000	76.20	7.375	187.33	3	MOD	
			Nut	7.35	3.33									
			Male Sub	2.65	1.20									
			Female Sub w/Ring	3.00	1.36									
			Seat Ring	—	—									
	3	80	Union Complete	22.40	10.16	6.200	157.48	4.240	107.70	9.320	236.73	4	STD	
			Nut	10.70	4.85									
			Male Sub	5.28	2.39									
			Female Sub w/Ring	6.42	2.91									
			Seat Ring	—	—									
	4	100	Union Complete	33.82	15.34	8.280	210.31	5.250	133.35	10.700	271.78	4	STD	
			Nut	14.70	6.67									
			Male Sub	8.60	3.90									
			Female Sub w/Ring	10.52	4.77									
			Seat Ring	—	—									

Alloy steel forgings in high-pressure manifold and treating iron connections. Field-replaceable seal ring protects the metal-to-metal seal.
Available in threaded and butt weld ends. Unions are used primarily by service companies on applications of cementing, fracturing, and acidizing.

- Warnings:** 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
2. Do not make up or break out Unions in pressurized lines.
3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.

Wing Unions

10,000 psi cwp – 15,000 psi test



FIGURE 1002 Buttweld Ends Schedule 160 Red Nut/Blue Subs	Size	Item	Unit Weight		A		B		C		TPI	Material	
	NPS <i>Dn</i>		lbs <i>kg</i>	in <i>mm</i>	in <i>mm</i>	in <i>mm</i>	Nuts	Subs					
	2 50	Union Complete	14.25	6.46	5.200 132.08	3.000 76.20	7.375 187.33	3 MOD	All Alloy Steel Forging				
		Nut	7.35	3.34									
		Male Sub	3.50	1.59									
		Female Sub w/Ring	3.75	1.70									
		Seat Ring	—	—									
	3 80	Union Complete	21.25	9.64	6.200 157.48	4.240 107.70	9.320 236.73	4 STD					
		Nut	10.70	4.86									
		Male Sub	5.75	2.61									
		Female Sub w/Ring	6.00	2.72									
		Seat Ring	—	—									
	4 100	Union Complete	31.5	14.29	8.280 210.31	5.250 133.35	10.700 271.78	4 STD					
		Nut	14.70	6.68									
		Male Sub	9.00	4.08									
		Female Sub w/Ring	9.50	4.31									
		Seat Ring	—	—									

Alloy steel forgings in high-pressure manifold and treating iron connections. Field-replaceable seal ring protects the metal-to-metal seal. Available in threaded and butt weld ends. Unions are used primarily by service companies on applications of cementing, fracturing, and acidizing.

FIGURE 1002 Buttweld Ends Schedule XXH Red Nut/Blue Subs	Size		Item	Unit Weight		A		B		C		TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm		Nuts	Subs
	2	50	Union Complete	13.16	5.97	5.200	132.08	3.000	76.20	7.375	187.33	3	MOD	All Alloy Steel Forging
			Nut	7.35	3.34									
			Male Sub	3.44	1.56									
			Female Sub w/Ring	3.18	1.44									
			Seat Ring	—	—									
	3	80	Union Complete	25.52	11.57	6.200	157.48	4.240	107.70	9.320	236.73	4	STD	
			Nut	10.70	4.86									
			Male Sub	7.70	3.49									
			Female Sub w/Ring	7.42	3.37									
			Seat Ring	—	—									
	4	100	Union Complete	34.04	15.44	8.280	210.31	5.250	133.35	10.700	271.78	4	STD	
			Nut	14.70	6.68									
			Male Sub	9.36	4.24									
			Female Sub w/Ring	10.34	4.69									
			Seat Ring	—	—									

Alloy steel forgings in high-pressure manifold and treating iron connections. Field-replaceable seal ring protects the metal-to-metal seal. Available in threaded and butt weld ends. Unions are used primarily by service companies on applications of cementing, fracturing, and acidizing.

Warnings: 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
2. Do not make up or break out Unions in pressurized lines.
3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.



Wing Unions

15,000 psi cwp – 22,500 psi test



FIGURE 1502 Threaded Ends Blue Nut/Red Subs	Size		Item	Unit Weight		A		B		C		D	TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm			Nuts	Subs
	2	50	Union Complete	19.46	8.83	7.060	179.32	3.230	82.04	7.860	199.64	▲	3	STD	All Alloy Steel Forging
			Nut	9.78	4.44										
			Male Sub	4.82	2.19										
			Female Sub w/Ring	4.86	2.20										
			Seat Ring	—	—										
	3	80	Union Complete	30.48	13.82	7.630	193.8	4.400	111.76	9.900	251.46	▲	3½	STD	
			Nut	14.18	6.43										
			Male Sub	8.00	3.63										
			Female Sub w/Ring	8.30	3.76										
			Seat Ring	—	—										

Alloy steel forgings in high-pressure manifold and treating iron connections. Field-replaceable seal ring protects the metal-to-metal seal.
Available in threaded and butt weld ends.

FIGURE 1502 Buttweld Ends Schedule XXH Blue Nut/Red Subs	Size		Item	Unit Weight		A		B		C		D	TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm			Nuts	Subs
	2	50	Union Complete	20.58	9.33	7.060	179.32	3.230	82.04	7.860	199.64	▲	3	STD	All Alloy Steel Forging
			Nut	9.78	4.44										
			Male Sub	5.32	2.41										
			Female Sub w/Ring	5.48	2.49										
			Seat Ring	—	—										
	3	80	Union Complete	27.98	12.69	7.630	193.8	4.400	111.76	9.900	251.46	▲	3½	STD	
			Nut	14.18	6.43										
			Male Sub	6.96	3.16										
Female Sub w/Ring			7.76	3.52											
Seat Ring			—	—											

Alloy steel forgings in high-pressure manifold and treating iron connections. Field-replaceable seal ring protects the metal-to-metal seal.
Available in threaded and butt weld ends.

FIGURE 1502 Buttweld Ends Schedule 160 Blue Nut/Red Subs	Size		Item	Unit Weight		A		B		C		D	TPI	Material	
	NPS	Dn		lbs	kg	in	mm	in	mm	in	mm			Nuts	Subs
	2	50	Union Complete	20.06	9.10	7.060	179.32	3.230	82.04	7.860	199.64	▲	3	STD	All Alloy Steel Forging
			Nut	9.78	4.44										
			Male Sub	5.06	2.30										
			Female Sub w/Ring	5.22	2.37										
			Seat Ring	—	—										
	3	80	Union Complete	27.81	12.61	7.630	193.8	4.400	111.76	9.900	251.46	▲	3½	STD	
			Nut	14.18	6.43										
			Male Sub	6.51	2.95										
Female Sub w/Ring			7.12	3.23											
Seat Ring			—	—											

Alloy steel forgings in high-pressure manifold and treating iron connections. Field-replaceable seal ring protects the metal-to-metal seal.
Available in threaded and butt weld ends.

- Warnings:** 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
2. Do not make up or break out Unions in pressurized lines.
3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.



High Speed Unions

3,000 psi cwp — 4,500 psi test

FIGURE S1A High Speed Union 3000# Forged Steel	Size		Unit Weight	
	NPS	Dn	lbs	kg
	1	25	1.50	0.68
	2	50	4.50	2.04
	3	80	12.19	5.53

Female Threaded Ends

FIGURE 3L S1A Tri-Lug High Speed Union 3000# Forged Steel	Size		Unit Weight	
	NPS	Dn	lbs	kg
	1	25	2.15	0.98
	1½	50	3.64	1.65
	2	80	5.85	2.66

Tri-Lug with female threaded ends.

Warnings: 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
 2. Do not make up or break out Unions in pressurized lines.
 3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.



Catawissa Quick Reference Chart



STANDARD SERVICE												
Fig No.	CWP	TEST	API Color Code		Pipe Size (in.)							
			SUB	NUT	1"	1¼"	1½"	2"	2½"	3"	4"	6"
100	1,000	1,500	Yellow	Black								
200	2,000	3,000	Gray	Blue								
206	2,000	3,000	Gray	Blue								
211	2,000	3,000	Light Blue	Gray								
300	2,000	3,000	Yellow	Gray								
301	3,000	4,500	Green	Black								
400	4,000	6,000	Red	Black								
600	6,000	9,000	Silver	Black								
602	6,000	9,000	Orange	Black								
607	6,000	9,000	Silver	Yellow								
1002	10,000	15,000	Blue	Red								
1502	15,000	22,500	Red	Blue								

Warnings: 1. Do not mix Standard Service and Sour Gas Service Unions or parts.
 2. Do not make up or break out Unions in pressurized lines.
 3. Always use good safety practices, including use of safety glasses, when making up or breaking out Unions.

▲ Weld ends – Consult Factory. † Steel Forging Subs available – Consult Factory. TPI = Threads per inch. DI = Ductile Iron. SF = Steel Forging. BS = Bar Stock. ST = Steel Tubing.



J.B. Smith oil country tubular fittings, swages and bull plugs add an important dimension to the industry's leading line of flow control products offered by Anvil. J.B. Smith is a respected name and its products are well known for high quality and consistency.

Full Traceability

All J.B. Smith swages, bull plugs, tubing and casing nipples, and chambers are traceable to the original mill test report. To ensure traceability, all fittings are steel stamped as follows:

Material Specification

- Material Grade WPB (ASTM A234 - Line Pipe)
- Material Grade J-55, K-55, L-80, N-80 (API 5CT - Oil Country Sizes)

Raw Material Code

Each is stamped with unique JBS material code for traceability to material type, details of purchase and mill test report.

Heat Treatment

Items made to specification grades requiring final heat treatment bear an additional two letter code for heat treatment traceability.

All J.B. Smith products conform to the following applicable specifications:

- **API 5B** – Threading Oil Country size
- **API 5CT** – Raw material, Process, End Finish (Oil Country Sizes)
- **ASME B1.20.1** – Threading Line Pipe
- **ASME B16.9** – Weld Bevels
- **MSS SP-95** Swage and Bull Plug
- **ASTM A234 WPB** – Raw material, Process, End Finish (Line Pipe High Temp)
- **ASTM A420 WPL6** – Raw material, Process, End Finish (Line Pipe Low Temp)
- **ASTM B633 Type III Class III** – Zinc Electroplate
- **NACE MR-01-75** – As Applicable

Swage Nipples, Bull Plugs, Oil Country Fittings, Couplings, Stainless Swages



Manufacturing Specification

J.B. Smith manufactures swage nipples and bull plugs in accordance to the applicable specification, API 5CT, ASTM A234, MSS SP-95. Materials include ASTM A106, GR B seamless pipe, A-1000 low to medium carbon, fine grain bar stock, API grades J-55 through N-80 tubing and casing, processed and heat treated to applicable specification requirements. Fitting chemical and physical properties fall within the ranges listed below.

All fittings are manufactured in the U.S.A.

Traceability

All material purchased by J.B. Smith is fully traceable to the mill source. A unique JBS material code appears on all products made since the institution of this program. As a result, mill test reports are now available at any time on products so coded (See EXTRAS for MTR charges.)

Pressure Ratings

Due to the wide variation in service conditions, temperature, vibrations, etc., J.B. Smith Mfg. can make no recommendations as to allowable working pressure of swage nipples and bull plugs. There are a number of working pressure formulas from which the end user may choose to determine the required wall thickness of the piping system. It is our responsibility only to furnish a fitting with end dimensions equal to those of the pipe size and schedule ordered.

Material Certification – Carbon Steel

J.B. Smith certifies that the material used to manufacture line pipe sizes of swage nipples and bull plugs has been processed to comply with the requirements of ASTM A234 grade WPB and the chemical and physical properties of the fittings fall within the ranges listed below.

Marking

All J.B. Smith fittings are permanently marked as follows:

- **Manufacturer's symbol** - 
- **Material Specification or Grade**
WPB (Line Pipe Sizes)
J-55, K-55, L-80, N-80 (Oil Country Sizes)
- **Raw Material Code** - Each part is die stamped with unique JBS material code for traceability to material type, details of purchase and mill test report.
- **Heat Treatment** - Heat treatments are performed to ASTM A234 WPB or API 5CT specification grade requirement as applicable. Fittings bear a two letter code provide traceability to final heat treatment.

Threading

Line Pipe, Tubing and Casing threads conform to ASME B1.20.1 B or API 5B as applicable.

Oil Country Industry Thread Color Code

Industry Color Codes as follows:

8R - Red 10R - Yellow 10V - Blue 11½V - Green LP - Silver

Coatings

- **Zinc Electroplate** - ASTM B633 Type III Class III
- **Paint** (Weld Bevel Ends)

Weld Bevels

Weld bevels are machined per ASME B16.9 specifications.

Chemical and Physical Requirements

API 5CT MATERIAL										
Chemical Requirements										
Grp	Gr	C	Mn	Mo	Cr	Ni	Cu	P	S	Si
1	J55	—	—	—	—	—	—	0.030 Max	0.030 Max	—
1	K55	—	—	—	—	—	—	0.030 Max	0.030 Max	—
1	N80 Type1	—	—	—	—	—	—	0.030 Max	0.030 Max	—
2	L80 Type1	0.43 Max	1.90 Max	—	—	0.25 Max	0.35 Max	0.030 Max	0.030 Max	0.45 Max
Physical Requirements										
Grp	Gr	Total Elongation under load %		Yield Strength ksi		Tensile Strength ksi		Hardness		
1	J55	0.5		55-80		75		—		
1	K55	0.5		55-80		95		—		
1	N80 Type1	0.5		80-110		100		—		
2	L80 Type1	0.5		80-110		95		23 241		

Note:

- Fittings made from bar or plate may have 0.35 Max Carbon.
- Fittings made from forgings may have a 0.35 Max Carbon and 0.35 Max Silicon.
- For each reduction of 0.01% below the specified carbon maximum, an increase of 0.06% manganese above the specified maximum will be permitted, up to a maximum of 1.35%.
- The sum of Copper, Nickel Chromium and Molybdenum shall not exceed 1.00%.
- The sum of Chromium and Molybdenum shall not exceed 0.32%.



Carbon Steel Swage Nipples

Line Pipe Swages

- Nominal Pipe Size range $\frac{1}{8}$ – 8 NPS (6 – 200 DN)
- Manufactured from A106 Gr. B seamless pipe or hex bar and processed in accordance to ASTM A234 Gr. WPB
- Choice of material depends upon size and reduction
- Available in standard, extra heavy, double extra heavy or schedule 160
- End finishes available: NPT, weld beveled, squared cut (for socket weld) or grooved
- Available concentric and eccentric
- 1" (25mm) and smaller are made from hex bar
- $1\frac{1}{4}$ " (32mm) and larger are made from pipe

Concentric Swage Nipples	Size						Length		Standard Weight		XS/XH Weight		XXS/XXH & Sch. 160 Weight	
	Pipe		API or O.D.		Reduced to Size									
	NPS	DN	in	mm	NPS	DN	in	mm	lbs	kg	lbs	kg	lbs	kg
	¼	8	0.540	14	⅛	6	2¼	57	—	—	—	—	0.25	0.11
	⅜	10	0.675	17	⅛	6	2½	64	—	—	0.25	0.11	0.38	0.17
					¼	8	2½	64	—	—	0.25	0.11	0.38	0.17
	½	15	0.840	21	⅛	6	2¾	70	—	—	0.33	0.15	0.50	0.23
					¼ and ⅜	8 and 10	2¾	70	—	—	0.33	0.15	0.50	0.23
	¾	20	1.050	27	⅛	6	3	76	—	—	0.50	0.23	0.75	0.34
					¼ and ⅜	8 and 10	3	76	—	—	0.50	0.23	0.75	0.34
					½	15	3	76	—	—	0.50	0.23	0.75	0.34
	1	25	1.315	33	⅛	6	3½	89	—	—	0.66	0.30	1.00	0.45
					¼ and ⅜	8 and 10	3½	89	—	—	0.66	0.30	1.00	0.45
					½ and ¾	15 and 20	3½	89	—	—	0.66	0.30	1.00	0.45

Note: See page 148 for certification of raw material and marking.

Select sizes of 1 NPS (25 DN) and smaller swages in XS/XH and Schedule 160 weights available in A106.

All sizes on this page have been processed in a manner strictly conforming to the requirements of ASTM A234 from material fully meeting all requirements of that specification. The correct marking for swage nipples to denote conformance with this specification is "WPB".

All sizes 1 NPS (25 DN) and smaller will be made from hex barstock. Most sizes $1\frac{1}{4}$ NPS (32 DN) and larger will be made from pipe, and where pipe is not a practical raw material, round barstock will be used. No sacrifice of properties will result from such practice.

Carbon Steel Swage Nipples




Concentric Swage Nipples	Size				Length		Standard Weight		XS/XH Weight		XXS/XXH & Sch. 160 Weight			
	Pipe	API or O.D.	Reduced to Size											
	NPS	DN	in	mm	NPS	DN	in	mm	lbs	kg	lbs	kg	lbs	kg
	1¼	32	1.660	42	¼ and ¾	8 and 10	4	102	—	—	1.00	0.45	1.5	0.68
					½ and ¾	15 and 20	4	102	—	—	1.00	0.45	1.5	0.68
					1	25	4	102	—	—	1.00	0.45	1.5	0.68
	1½	40	1.900	48	¼ and ¾	8 and 10	4½	114	—	—	1.2	0.53	2.0	0.91
					½ and ¾	15 and 20	4½	114	—	—	1.2	0.53	2.0	0.91
					1	25	4½	114	—	—	1.2	0.53	2.0	0.91
					1¼	32	4½	114	—	—	1.2	0.53	2.0	0.91
	2	50	2¾	60	¼ and ¾	8 and 10	6½	165	—	—	3.0	1.4	4.3	1.9
					½ and ¾	15 and 20	6½	165	—	—	3.0	1.4	4.3	1.9
					1	25	6½	165	2.0	0.91	2.3	1.1	4.3	1.9
					1¼	32	6½	165	2.0	0.91	2.3	1.1	4.3	1.9
					1½	40	6½	165	2.0	0.91	2.3	1.1	4.3	1.9
	2½	65	2¾	73	½ and ¾	15 and 20	7	178	—	—	3.5	1.6	8.0	3.6
					1	25	7	178	3.0	1.4	3.5	1.6	8.0	3.6
					1¼	32	7	178	3.0	1.4	3.5	1.6	8.0	3.6
					1½	40	7	178	3.0	1.4	3.5	1.6	8.0	3.6
					2	50	7	178	3.0	1.4	3.5	1.6	8.0	3.6
	3	80	3½	89	½ and ¾	15 and 20	8	203	—	—	6.0	2.7	11	5.0
					1	25	8	203	4.5	2.0	6.0	2.7	11	5.0
					1¼	32	8	203	4.5	2.0	6.0	2.7	11	5.0
					1½	40	8	203	4.5	2.0	6.0	2.7	11	5.0
					2 and 2½	50 and 65	8	203	4.5	2.0	6.0	2.7	11	5.0
	3½	90	4	100	½ thru 1½	15 thru 40	8	203	5.5	2.5	7.5	3.4	14	6.1
	3½	90	4	100	½ thru 1½	15 thru 40	8	203	5.5	2.5	7.5	3.4	14	6.1
					2 thru 3	50 thru 80	8	203	5.5	2.5	7.5	3.4	14	6.1
					½ and ¾	15 and 20	9	229	—	—	10.0	4.5	18	8.2
	4	100	4½	114	1	25	9	229	7.5	3.4	10.0	4.5	18	8.2
					1¼ and 1½	32 and 40	9	229	7.5	3.4	10.0	4.5	18	8.2
					2	50	9	229	7.5	3.4	10.0	4.5	18	8.2
					2½	65	9	229	7.5	3.4	10.0	4.5	18	8.2
					3 and 3½	80 and 90	9	229	7.5	3.4	10.0	4.5	18	8.2
					1 thru 1½	25 thru 40	11	279	12	5.2	17	7.7	33	15
	5	125	5⅞	140	2 and 2½	50 and 65	11	279	12	5.2	17	7.7	33	15
3 and 3½					80 and 90	11	279	12	5.2	17	7.7	33	15	
4					100	11	279	12	5.2	17	7.7	33	15	
1 thru 1½					25 thru 40	12	305	17	7.7	25	11	46	21	
6	150	6⅝	168	2 and 2½	50 and 65	12	305	17	7.7	25	11	46	21	
				3 and 3½	80 and 90	12	305	17	7.7	25	11	46	21	
				4	100	12	305	17	7.7	25	11	46	21	
				5	125	12	305	17	7.7	25	11	46	21	
				2 thru 3	50 thru 80	13	330	29	13	44	20	78	35	
8	200	8⅝	219	4 and 5	100 and 125	13	330	29	13	44	20	78	35	
				6	150	13	330	29	13	44	20	78	35	

Note: See page 148 for certification of raw material and marking.

Carbon Steel Swage Nipples



Eccentric Swage Nipples	Size						Length	Standard Weight	XS/XH Weight	XXS/XXH & Sch. 160 Weight				
	Pipe		API or O.D.		Reduced to Size									
	NPS	DN	in	mm	NPS	DN	in	mm	lbs	kg	lbs	kg	lbs	kg
	1/4	8	0.540	14	1/8	6	2 1/4	57	—	—	0.16	0.07	0.25	0.11
	3/8	10	0.675	17	1/8	6	2 1/2	64	—	—	0.25	0.11	0.38	0.17
					1/4	8	2 1/2	64	—	—	0.25	0.11	0.38	0.17
	1/2	15	0.840	21	1/4 and 3/8	8 and 10	2 3/4	70	—	—	0.33	0.15	0.50	0.23
	3/4	20	1.050	27	1/4 and 3/8	8 and 10	3	76	—	—	0.50	0.23	0.75	0.34
					1/2	15	3	76	—	—	0.50	0.23	0.75	0.34
	1	25	1.315	33	1/4 and 3/8	8 and 10	3 1/2	89	—	—	0.66	0.30	1.00	0.45
					1/2 and 3/4	15 and 20	3 1/2	89	—	—	0.60	0.27	1.00	0.45
	1 1/4	32	1.660	42	1/2 and 3/4	15 and 20	4	102	—	—	1.00	0.45	1.5	0.68
					1	25	4	102	—	—	1.00	0.45	1.5	0.68
	1 1/2	40	1.900	48	1/2 and 3/4	15 and 20	4 1/2	114	—	—	1.2	0.53	2.0	0.91
					1	25	4 1/2	114	—	—	1.2	0.53	2.0	0.91
					1 1/4	32	4 1/2	114	—	—	1.2	0.53	2.0	0.91
	2	50	2 3/8	60	1/4 and 3/8	8 and 10	6 1/2	165	—	—	3.0	1.4	4.3	1.9
					1/2 and 3/4	15 and 20	6 1/2	165	—	—	3.0	1.4	4.3	1.9
					1	25	6 1/2	165	2.0	0.91	2.3	1.1	4.3	1.9
					1 1/4	32	6 1/2	165	2.0	0.91	2.3	1.1	4.3	1.9
					1 1/2	40	6 1/2	165	2.0	0.91	2.3	1.1	4.3	1.9
	2 1/2	65	2 7/8	73	1	25	7	178	—	—	3.5	1.6	8.0	3.6
					1 1/4	32	7	178	3.0	1.4	3.5	1.6	8.0	3.6
					1 1/2	40	7	178	3.0	1.4	3.5	1.6	8.0	3.6
					2	50	7	178	—	—	3.5	1.6	8.0	3.6
	3	80	3 1/2	89	1/2 and 3/4	15 and 20	8	203	—	—	6.0	2.7	11	5.0
					1	25	8	203	4.5	2.0	6.0	2.7	11	5.0
					1 1/4	32	8	203	4.5	2.0	6.0	2.7	11	5.0
					1 1/2	40	8	203	4.5	2.0	6.0	2.7	11	5.0
					2 and 2 1/2	50 and 65	8	203	4.5	2.0	6.0	2.7	11	5.0
	3 1/2	90	4	102	All reductions	All reductions	8	203	5.5	2.5	7.5	3.4	14	6.1
	4	100	4 1/2	114	1	25	9	229	7.5	3.4	10.0	4.5	18	8.2
					1 1/4 and 1 1/2	32 and 40	9	229	7.5	3.4	10.0	4.5	18	8.2
					2	50	9	229	7.5	3.4	10.0	4.5	18	8.2
					2 1/2	65	9	229	7.5	3.4	10.0	4.5	18	8.2
3 and 3 1/2					80 and 90	9	229	7.5	3.4	10.0	4.5	18	8.2	

Note: See page 148 for certification of raw material and marking. Sizes not shown - P.O.A.

Stainless Steel

Stainless Swages



Stainless & Alloy Steel Swage Nipples	304 Stainless Steel				316 Stainless Steel			
	Size		Length		Size		Length	
	NPS	DN	in	mm	NPS	DN	in	mm
	1/4 x 1/8	8 x 6	2 1/4	57	1/4 x 1/8	8 x 6	2 1/4	57
	3/8 x 1/4	10 x 8	2 1/2	64	3/8 x 1/4	10 x 8	2 1/2	64
	1/2 x 1/4	15 x 8	2 3/4	70	1/2 x 1/4	15 x 8	2 3/4	70
	1/2 x 3/8	15 x 10	2 3/4	70	1/2 x 3/8	15 x 10	2 3/4	70
	3/4 x 1/4	20 x 8	3	76	3/4 x 1/4	20 x 8	3	76
	3/4 x 3/8	20 x 10	3	76	3/4 x 3/8	20 x 10	3	76
	3/4 x 1/2	20 x 15	3	76	3/4 x 1/2	20 x 15	3	76
	1 x 1/4	25 x 8	3 1/2	89	1 x 1/4	25 x 8	3 1/2	89
	1 x 1/2	25 x 15	3 1/2	89	1 x 1/2	25 x 15	3 1/2	89
	1 x 3/4	25 x 20	3 1/2	89	1 x 3/4	25 x 20	3 1/2	89
	1 1/4 x 1/2	32 x 15	4	102	1 1/4 x 1/2	32 x 15	4	102
	1 1/4 x 3/4	32 x 20	4	102	1 1/4 x 3/4	32 x 20	4	102
	1 1/4 x 1	32 x 25	4	102	1 1/4 x 1	32 x 25	4	102
	1 1/2 x 1/2	40 x 15	4 1/2	114	1 1/2 x 1/2	40 x 15	4 1/2	114
	1 1/2 x 3/4	40 x 20	4 1/2	114	1 1/2 x 3/4	40 x 20	4 1/2	114
	1 1/2 x 1	40 x 25	4 1/2	114	1 1/2 x 1	40 x 25	4 1/2	114
	1 1/2 x 1 1/4	40 x 32	4 1/2	114	1 1/2 x 1 1/4	40 x 32	4 1/2	114
	2 x 1/2	50 x 15	6 1/2	165	2 x 1/2	50 x 15	6 1/2	165
	2 x 3/4	50 x 20	6 1/2	165	2 x 3/4	50 x 20	6 1/2	165
	2 x 1	50 x 25	6 1/2	165	2 x 1	50 x 25	6 1/2	165
	2 x 1 1/4	50 x 32	6 1/2	165	2 x 1 1/4	50 x 32	6 1/2	165
	2 x 1 1/2	50 x 40	6 1/2	165	2 x 1 1/2	50 x 40	6 1/2	165
	2 1/2 x 1	65 x 25	7	178	2 1/2 x 1	65 x 25	7	178
	2 1/2 x 1 1/4	65 x 32	7	178	2 1/2 x 1 1/4	65 x 32	7	178
	2 1/2 x 1 1/2	65 x 40	7	178	2 1/2 x 1 1/2	65 x 40	7	178
	2 1/2 x 2	65 x 50	7	178	2 1/2 x 2	65 x 50	7	178
	3 x 1	80 x 25	8	203	3 x 1	80 x 25	8	203
	3 x 1 1/4	80 x 32	8	203	3 x 1 1/4	80 x 32	8	203
	3 x 1 1/2	80 x 40	8	203	3 x 1 1/2	80 x 40	8	203
	3 x 2	80 x 50	8	203	3 x 2	80 x 50	8	203
	3 x 2 1/2	80 x 65	8	203	3 x 2 1/2	80 x 65	8	203
	4 x 1	100 x 25	9	229	4 x 1	100 x 25	9	229
	4 x 1 1/4	100 x 32	9	229	4 x 1 1/4	100 x 32	9	229
	4 x 1 1/2	100 x 40	9	229	4 x 1 1/2	100 x 40	9	229
	4 x 2	100 x 50	9	229	4 x 2	100 x 50	9	229
	4 x 2 1/2	100 x 65	9	229	4 x 2 1/2	100 x 65	9	229
	4 x 3	100 x 80	9	229	4 x 3	100 x 80	9	229
	4 x 3 1/2	100 x 90	9	229	4 x 3 1/2	100 x 90	9	229

Note: See page 148 for certification of raw material and marking. Other types and sizes available on application. For other alloy raw material, Consult factory. Mill test reports furnished upon request only.
Options: E.L.C. Grades of Stainless; Eccentrics; Schedule 10 (no threads) - XXH; Schedule 160 & XXS/XXH; Concentric; Schedule 10, 40, 80, 160 and XXH (Including Eccentric)



Carbon Steel Bull Plugs

Line Pipe Bull Plugs

- Nominal Pipe Size range $\frac{1}{8}$ – 8 NPS (6 – 200 DN)
- Nominal Pipe Size 2 (50 DN) and smaller bull plugs are manufactured from bar which is processed in accordance with ATM A234 Gr. WPB
- Nominal Pipe Size $2\frac{1}{2}$ – 8 (65 – 200 DN) bull plugs are manufactured from A106 Gr. B seamless pipe using J.B. Smith's unique forming process which ensures uniform wall thickness
- Bull Plugs available in standard, extra heavy, double extra heavy, schedule 160 or solid
- All J.B. Smith bull plugs can be tapped
- End finishes available: NPT, weld beveled, squared cut (for socket weld) or grooved

Carbon Steel Bull Plugs	Size				Length	Standard Weight	XS/XH Weight	Solid Weight	XXS/XXH & Sch. 160 Weight					
	Pipe		API or O.D.											
	NPS	DN	in	mm	in	mm	lbs	kg	lbs	kg	lbs	kg		
	⅛	6	0.405	10	2	51	—	—	0.10	0.05	0.20	0.09	0.40	0.18
	¼	8	0.540	14	2	51	—	—	0.11	0.05	0.20	0.09	0.40	0.18
	⅜	10	0.675	17	2¼	57	—	—	0.14	0.06	0.33	0.15	0.28	0.13
	½	15	0.840	21	2½	64	—	—	0.33	0.15	0.50	0.23	0.50	0.23
	¾	20	1.050	27	2¾	70	—	—	0.50	0.23	0.80	0.36	0.75	0.34
	1	25	1.315	33	3	76	—	—	0.66	0.30	1.4	0.63	1.00	0.45
	1¼	32	1.660	42	3¼	83	—	—	1.00	0.45	2.3	1.0	1.5	0.68
	1½	40	1.900	48	3½	89	—	—	1.2	0.53	3.0	1.4	2.0	0.91
	2	50	2⅝	60	4	102	2.3	1.0	2.5	1.1	5.0	2.3	3.5	1.6
	2½	65	2⅞	73	5	127	3.0	1.4	3.5	1.6	—	—	8.0	3.6
	3	80	3½	89	6	152	4.5	2.0	6.0	2.7	—	—	11	5.0
	3½	90	4	102	6½	165	5.5	2.5	7.5	3.4	—	—	14	6.1
	4	100	4½	114	7	178	7.5	3.4	10.0	4.5	—	—	18	8.2
	5	125	5⅞	141	8½	216	13	5.7	17	7.7	—	—	33	15
	6	150	6⅝	168	10	254	17	7.7	25	11	—	—	46	21
8	200	8⅝	219	11	279	29	13	44	20	—	—	78	35	

Solid Refinery Plugs Black (non-plated) Carbon Steel		Size		Length	
		NPS	DN	in	mm
		$\frac{1}{8}$	6	3	76
		$\frac{1}{4}$	8	3	76
		$\frac{3}{8}$	10	3	76
		$\frac{1}{2}$	15	3	76
		$\frac{3}{4}$	20	3	76
		1	25	3	76
		$1\frac{1}{4}$	32	3	76
		$1\frac{1}{2}$	40	3	76
		2	50	3	76

Smith solid black refinery plugs have been especially designed for refinery use. The body length leaves sufficient length for easy wrench application. Material conforms to ASTM-A 234 Grade WPB. Hex Heads $1\frac{1}{4}$ " thru 2" are available.

Adapter Nipples



- J.B. Smith manufactures a full line of adapter nipples in sizes 1" NPS (25 DN) through 12" NPS (300 DN) from seamless A106 pipe.
- Adapter Nipples available in threaded, beveled, grooved and virtually all combinations of these end connections.
- Nipples manufactured in schedule 40, schedule 80, schedule 160 and double extra heavy wall thickness
- Full Traceability and mill certification available upon request at time of order



Adapter Nipples Seamless Schedule 40, 80, 160, XXH			
Size		Weight	
NPS	DN	lbs/ft	kg
¾	20	—	—
1	25	—	—
1¼	32	—	—
1½	40	—	—
2	50	3.6	1.7
2½	65	5.8	2.6
3	80	7.6	3.4
4	100	11	4.9
5	125	15	6.6
6	150	19	8.6
8	200	29	13
10	250	40	18
12	300	50	22

Oil Country Fittings

Current API Thread Standards



Current API Thread Standards					
Size		O.D.		Pipe	Tubing & Casing
NPS	DN	in	mm		
¾	20	1.050	27	14	—
¾ EUE	20	1.050	27	—	10 Rd.
1	25	1.315	33	11½	10 Rd.
1 EUE	25	1.315	33	—	10 Rd.
1¼	32	1.660	42	11½	10 Rd.
1¼ EUE	32	1.660	42	—	10 Rd.
1½	40	1.900	48	11½	10 Rd.
1½ EUE	40	1.900	48	—	10 Rd.
2	50	2⅜	60	11½	10 Rd.
2 EUE	50	2⅜	60	—	8 Rd.
2½	65	2⅞	73	8V	10 Rd.
2½ EUE	65	2⅞	73	—	8 Rd.
3	80	3½	89	8V	10 Rd.
3 EUE	80	3½	89	—	8 Rd.
3½	90	4	102	8V	8 Rd.
3½ EUE	90	4	102	8V	8 Rd.
4	100	4½	114	8V	8 Rd.
4 EUE	100	4½	114	—	8 Rd.
—	—	5	127	—	8 Rd.
—	—	5½	140	—	8 Rd.
5	125	5⅞	141	8V	—
—	—	6	152	—	8 Rd.
6	150	6⅞	168	8V	8 Rd.
—	—	7	178	—	8 Rd.
—	—	7⅞	194	—	8 Rd.
8	200	8⅞	219	8V	8 Rd.
—	—	9⅞	244	—	8 Rd.
10	250	10¾	273	8V	8 Rd.
—	—	11¾	298	—	8 Rd.
12	300	12¾	324	8V	—
—	—	13⅞	340	—	8 Rd.
—	—	14	356	8V	—
—	—	16	406	8V	8 Rd.
—	—	18	457	8V	—
—	—	20	508	8V	8 Rd.

Malleable Iron

Cast Iron

Small Steel Fittings

Pipe Nipples & Pipe Couplings

Forged Steel Fittings & Unions

Anvils

Catawissa

J.B. Smith Products

Carton Information

Oil Country Fittings

Tubing Swages & Casing Swages



- Tubing Nominal Sizes 1 – 4 (25 – 100 DN) upset and non-upset ends are available with any combination of API 5B threads (8Rd, 10Rd, 11 1/2 V, 8V, etc) and are available in grades J-55, K-55, N-80 and L-80 API 5CT material grades
- Wall thicknesses available are standard through double extra heavy
- For different grades of material (stainless, brass, etc.) and different threads, consult factory
- Thread types are color-coded for easy identification. See page 148.

SWAGE NIPPLES – OIL COUNTRY SIZES

Large End Upset Reduced to Regular or Upset	Size		Pipe O.D.		Reduced to Size		Length		Standard Weight		XS/XH Weight		XXS/XXH Weight	
	NPS	DN	in	mm	NPS	DN	in	mm	lbs	kg	lbs	kg	lbs	kg
	1	25	1.315	33	3/4	20	3 1/2	89	0.66	0.30	0.66	0.30	–	–
	1 1/4	32	1.660	42	3/4-1	20-25	4	102	1.00	0.45	1.00	0.45	–	–
	1 1/2	40	1.900	48	3/4-1 1/4	20-32	4 1/2	114	1.3	0.57	1.3	0.57	–	–
	2	50	2 3/8	60	1/4-1/2-3/4	8-15-20	8	203	2.5	1.1	4.0	1.8	6.0	2.7
					1-1 1/4-1 1/2	25-32-40	8	203	2.5	1.1	4.0	1.8	6.0	2.7
					2 1/16 O.D.	52 O.D.	8	203	2.5	1.1	4.0	1.8	6.0	2.7
	2 1/2	65	2 7/8	73	1-1 1/4-1 1/2	25-32-40	8	203	5.0	2.3	6.0	2.7	10.0	4.5
					2	50	8	203	6.0	2.7	6.0	2.7	10.0	4.5
	3	80	3 1/2	89	1-1/4-1 1/2	25-8-40	8	203	7.5	3.4	9.0	4.1	14	6.4
					2-2 1/2	50-65	8	203	7.5	3.4	9.0	4.1	14	6.4
					1-1/4-1 1/2	25-8-40	9	229	11	5.0	14	6.4	23	10
	4	100	4 1/2	114	2-2 1/2	50-65	9	229	11	5.0	14	6.4	23	10
					3-3 1/2	80-90	9	229	11	5.0	14	6.4	23	10

Swage Nipples are made from J-55, K-55, N-80 or the most appropriate material available.

SWAGE NIPPLES – OIL COUNTRY SIZES

Large End Non-Upset Reduced to Upset	Size		Pipe O.D.		Reduced to Size		Length		Standard Weight		XS/XH Weight		XXS/XXH Weight	
	NPS	DN	in	mm	NPS	DN	in	mm	lbs	kg	lbs	kg	lbs	kg
	1	25	1.315	33	3/4	20	3 1/2	89	0.66	0.30	0.66	0.30	–	–
	1 1/4	32	1.660	42	3/4-1	20-25	4	102	1.00	0.45	1.00	0.45	–	–
	1 1/2	40	1.900	48	3/4-1 1/4	20-32	4 1/2	114	1.3	0.57	1.3	0.57	–	–
	2	50	2 3/8	60	3/4	20	6 1/2	165	2.5	1.1	3.5	1.6	5.0	2.3
					1-1 1/4-1 1/2	25-32-40	6 1/2	165	2.5	1.1	3.5	1.6	5.0	2.3
	2 1/2	65	2 7/8	73	1-1 1/4-1 1/2	25-32-40	7	178	4.0	1.8	6.0	2.7	9.0	4.1
					2	50	7	178	4.0	1.8	6.0	2.7	9.0	4.1
	3	80	3 1/2	89	1-1 1/4-1 1/2	25-32-40	8	203	6.0	2.7	9.0	4.1	12	5.4
					2-2 1/2	50-65	8	203	6.0	2.7	9.0	4.1	12	5.4
	4	100	4 1/2	114	1-1 1/4-1 1/2	25-32-40	9	229	8.0	3.6	12	5.4	20	9.1
					2-2 1/2	50-65	9	229	8.0	3.6	12	5.4	20	9.1
					3-3 1/2	80-90	9	229	8.0	3.6	12	5.4	20	9.1
					5 1/2	140	2-3	50	11	5.7	17	7.7	33	15
					7	178	2-3	50	12	7.7	25	11	50	23

Swage Nipples are made from J-55, K-55, N-80 or the most appropriate material available.

Oil Country Fittings

Tubing Swages & Casing Swages



Swage Nipples Oil Country Tubing & Casing non EUE ends	Size						Length	Standard Weight	XS/XH Weight	XXS/XXH Weight				
	Pipe	O.D.	Reduced to											
	NPS	DN	in	mm	NPS	DN	in	mm	lbs	kg	lbs	kg	lbs	kg
	1	25	1.315	33	¼ - ¾	8 - 20	3½	89	0.66	0.30	0.66	0.30	1.00	0.45
	1¼	32	1.660	42	¼ - ½	8 - 15	4	102	1.00	0.45	1.00	0.45	1.5	0.68
					¾ & 1	20 & 25	4	102	1.00	0.45	1.00	0.45	1.5	0.68
	1½	40	1.900	48	¼ - ¾	8 - 20	4½	114	1.2	0.53	—	—	2.0	0.91
					1 & 1¼	25 & 32	4½	114	1.2	0.53	1.00	0.45	2.0	0.91
	2	50	2⅝	60	¼ - ¾	8 - 20	6½	165	2.5	1.1	3.0	1.4	4.3	1.9
					1 - 2 O.D.	25 - 50 O.D.	6½	165	2.0	0.91	2.3	1.1	4.3	1.9
	2½	65	2⅞	73	¼ - ¾	8 - .75	7	178	3.0	1.4	3.5	1.6	8.0	3.6
					1 - 1½	25 - 40	7	178	3.0	1.4	3.5	1.6	8.0	3.6
					2 & 2⅛	50 - 52	7	178	3.0	1.4	3.5	1.6	8.0	3.6
	3	80	3½	89	1 - 1½	25 - 40	8	203	4.5	2.0	6.0	2.7	11	5.0
					2 & 2½	50 - 65	8	203	4.5	2.0	6.0	2.7	11	5.0
	4	100	4½	114	1 - 1½	25 - 40	9	229	7.0	3.2	10.0	4.5	18	8.2
					2 - 4 O.D.	50 - 100 O.D.	9	229	7.5	3.4	10.0	4.5	18	8.2
		5	127	1 - 1½	25 - 40	10	254	9.5	4.3	15	6.8	24	11	
				2 - 4½ O.D.	50 - 100 O.D.	10	254	9.5	4.3	15	6.8	24	11	
		5½	140	1 - 1½	25 - 40	11	279	13	5.7	17	7.7	33	15	
				2 & 2½	50 & 65	11	279	13	5.7	17	7.7	33	15	
				3 - 50.D.	80 - 125 O.D.	11	279	13	5.7	17	7.7	33	15	
		6⅝	168	1 - 1½	25 - 40	12	305	17	7.7	25	11	46	21	
				2 & 2½	50 & 65	12	305	17	7.7	25	11	46	21	
				3 - 4 O.D.	80 - 100 O.D.	12	305	17	7.7	25	11	46	21	
				4 - 6 O.D.	100 - 150 O.D.	12	305	17	7.7	25	11	46	21	
		7	178	1 - 1½	25 - 40	12	305	17	7.7	25	11	—	—	
				2 - 2½	50 - 65	12	305	17	7.7	25	11	—	—	
				3 - 5 O.D.	80 - 125 O.D.	12	305	17	7.7	25	11	—	—	
				5½ O.D. & 6 O.D.	140 O.D. & 150 O.D.	12	305	17	7.7	25	11	—	—	
		7⅝	194	2 - 3	5 - 750	13	330	24	11	32	15	—	—	
				4 O.D. - 6 O.D.	100 O.D. - 150 O.D.	13	330	24	11	32	15	—	—	
				6⅝ O.D. - 7 O.D.	168 O.D. - 175 O.D.	13	330	24	11	32	15	—	—	
		8⅝	219	2 - 3	50 - 75	13	330	29	13	44	20	—	—	
				4 - 6 O.D.	100 - 150 O.D.	13	330	29	13	44	20	—	—	
				6⅝ O.D. & 7⅝ O.D.	168 O.D. - 194 O.D.	13	330	29	13	44	20	—	—	
		9⅝	244	2 - 3	50 - 75	14	356	38	17	48	22	—	—	
				4 - 6 O.D.	100 - 150 O.D.	14	356	38	17	48	22	—	—	
				6⅝ O.D. & 8⅝ O.D.	168 O.D. - 219 O.D.	14	356	38	17	48	22	—	—	
		10¾	273	2 - 3	50 - 75	15	381	48	22	68	31	—	—	
				4 - 6 O.D.	100 - 150 O.D.	15	381	48	22	68	31	—	—	
				6⅝ O.D - 7⅝ O.D.	168 O.D. - 194 O.D.	15	381	48	22	68	31	—	—	
8⅝ O.D. & 9⅝ O.D.				219 O.D. - 245 O.D.	15	381	48	22	68	31	—	—		

All swage nipples on this page are made from J-55, K-55, N-80 or the most appropriate material available. Casing threads (8 Rd.) on one end with any thread or finish (beveled) on the other end. Also includes casing sizes where no thread is specified

Oil Country Fittings

Bull Plugs



Casing Bull Plugs

- 4 1/2" O.D. – 10 3/4" O.D. (114 O.D. – 273 O.D. DN) casing bull plugs available with all current API threads or beveled for welding
- Casing bull plugs available in standard, extra heavy or double extra

Tubing Bull Plugs	Size				Length		Standard Weight		XS/XH Weight		XXS/XXH & Sch. 160 Weight	
	Pipe		API or O.D.									
	NPS	DN	in	mm	in	mm	lbs	kg	lbs	kg	lbs	kg
	¾ EUE	20			3	76	1.5	0.68	0.50	0.23	—	—
	1	25	1.315	33	3	76	1.5	0.68	0.66	0.30	—	—
	1 EUE	25			3	76	1.5	0.68	—	—	—	—
	1¼	32	1.660	42	3¼	83	1.5	0.68	1.00	0.45	—	—
	1¼ EUE	32			3¼	83	1.5	0.68	—	—	—	—
	1½	40	1.900	48	3½	89	1.5	0.68	1.1	0.48	—	—
	1½ EUE	40			3½	89	2.0	0.91	2.3	1.0	—	—
	2	50	2⅜	60	4	102	2.0	0.91	3.0	1.4	4.3	1.9
	2 EUE	50			5	127	3.5	1.6	4.0	1.8	9.0	4.1
	2½	65	2⅞	73	5	127	3.0	1.4	3.5	1.6	8.0	3.6
	2½ EUE	65			5½	140	4.3	1.9	6.0	2.7	14	6.4
	3	80	3½	89	6	152	4.5	2.0	5.0	2.3	11	5.0
3 EUE	80			6½	165	10.0	4.5	15	6.8	25	11	

Note: Also available in solid.

Casing Bull Plugs	API or O.D.		Length		Standard Weight		XS/XH Weight		XXS/XXH & Sch. 160 Weight	
	in	mm	in	mm	lbs	kg	lbs	kg	lbs	kg
	4 1/2	114	7	178	7.5	3.4	10.0	4.5	18	8.2
	5	127	8	203	9.5	4.3	15	6.8	24	11
	5 1/2	140	8 1/2	216	13	5.7	17	7.7	33	15
	6 3/8	168	10	254	17	7.7	25	11	46	21
	7	178	10	254	17	7.7	25	11	50	23
	7 7/8	194	11	279	24	11	32	15	53	24
	8 7/8	219	11	279	29	13	44	20	78	35
	9 7/8	244	12	305	36	16	47	21	76	34
	10 3/4	273	13	330	41	18	56	25	85	39

API Bull Plugs Female	Size				Length	Size				Length		
	Tubing Size		O.D.			Tubing Size		O.D.				
	in	mm	in	mm	in	mm	in	mm	in	mm		
	¾	20	1.313	33	3⅜	81	2	50	2.875	73	4¼	108
	¾ EUE	20	1.660	42	3¼	83	2 EUE	50	3.063	78	4⅞	124
	1	25	1.660	42	3¼	83	2½	65	3.500	89	5⅛	130
	1 EUE	25	1.900	48	3½	89	2½ EUE	65	3.668	93	5¼	133
	1¼	32	2.054	52	3½	89	3	80	4.250	108	5⅝	143
	1¼ EUE	32	2.200	56	3¾	95	3 EUE	80	4.500	114	5¾	146
	1½	40	2.200	56	3¾	95	4	100	5.200	132	6⅞	156
	1½ EUE	40	2.500	64	3⅞	98	4 EUE	100	5.563	141	6¾	159



Oil Country Fittings

Bell Nipples and Tubing Nipples

Bell Nipples

- J.B. Smith manufactures a full line of Bell Nipples in sizes 4½" - 8⅝" NPS from K55 raw materials
- Bell Nipples are 8 RD threaded (short or long) by slip joint end connections.
- Full traceability and mill certification available upon request at time of order.

	O.D. Size		Weight	
	NPS	DN	lbs	kg
	4½	114	4.5	2.0
	5½	140	9.0	4.1
	7	175	13.0	6.0
	8⅝	219	15.0	6.8

Tubing Nipples

- Tubing Nominal Sizes 1 - 4 (25 - 100 DN) upset and non-upset ends
- Lengths are 4" - 18" (102mm-457mm)
- Tubing nipples are available with any combination of API 5B threads (8Rd, 10Rd, 11½ V, 8V, etc) and are available in grades J-55, K-55, N-80 and L-80 API 5CT material grades
- Wall thicknesses available: standard, extra heavy, double extra heavy
- For different grades of material (stainless, brass, etc.) and different threads, consult factory

	Size		End Connection
	NPS	DN	
18" and shorter upset and non-upset	1	25	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)
	1¼	32	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)
	1½	40	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)
	2	50	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)
	2½	65	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)
	3	80	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)
	4	100	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)

	Size		End Connection
	NPS	DN	
18" and shorter upset and non-upset	1	25	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)
	1¼	32	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)
	1½	40	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)
	2	50	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)
	2½	65	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)
	3	80	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)
	4	100	Upset A.P.I. Thds, One or Both Ends
			Non-upset (Regular)

Standard and XH Weight available in standard lengths 4", 6", 8", 10", 12", 14", 16", 18". Also, available in non-standard lengths.

Oil Country Fittings

Casing Nipples



Oil Country Casing Nipples	Size O.D.		Weight Per Foot		API Material Grade
	NPS	DN	lbs	kg	
	4½	114	10.5	4.8	K
			11.6	5.3	K-N-P
	5	125	11.5	5.2	K
			13.0	5.9	K
			15.0	6.8	K-N-P
			18.0	8.2	N-P
	5½	140	14.0	6.4	K
			15.5	7.0	K
			17.0	7.7	K-N-P
			20.0	9.1	N-P
	6¾	168	20.0	9.1	K
			24.0	11	K-N-P
			28.0	13	N-P
	7	175	20.0	9.1	K
			23.0	10	K-N
			26.0	12	K-N-P
			29.0	13	N-P
	7¾	194	26.4	12	K-N
			29.7	13	N-P
	8¾	219	24.0	11	K
			32.0	15	K
			36.0	16	K-N
			44.0	20	N-P
			49.0	22	N-P
	9¾	245	36.0	16	K
			40.0	18	K-N
			43.5	20	N-P
			47.0	21	N-P
	10¾	273	40.5	18	K
			45.5	21	K
			55.5	25	N-P
	11¾	298	60.0	27	K
	13¾	340	54.5	25	K
			61.0	28	K
			68.0	31	K
			72.0	33	K
	16	400	75.0	34	K
			84.0	38	K

Available in standard lengths 8", 10", 12", 18", 24", 36". Also, available in non-standard lengths.
Casing nipples in steel grades other than those noted above are also available.

Oil Country Couplings

Casing Couplings



API Casing Couplings Short Thread	Casing O.D.		Weight/100		Length of Round Thread Coupling	
	NPS	DN	lbs	kg	in	mm
	4½	114	805	365	6¼	159
	5	125	1018	462	6½	165
	5½	140	1144	519	6¾	171
	6⅝	168	1997	906	7¼	184
	7	175	1834	832	7¼	184
	7⅝	194	2693	1222	7½	191
	8⅝	219	3558	1614	7¾	197
	9⅝	244	3951	1792	7¾	197
	10¾	273	4553	2065	8	203
	11¾	298	—	—	8	203
	13⅝	340	5623	2551	8	203
	16	400	7898	3582	9	229
	20	500	9500	4309	9	229

API Casing Couplings Long Thread	Casing O.D.		Weight/100		Length of Coupling	
	NPS	DN	lbs	kg	in	mm
	4½	114	907	411	7	178
	5	125	1256	570	7¾	197
	5½	140	1403	636	8	203
	6⅝	168	1829	830	8¾	222
	7	175	2367	1074	9	229
	7⅝	194	3423	1553	9¼	235
	8⅝	219	4748	2154	10	254
	9⅝	244	5577	2530	10½	267
	10¾	273	6202	2813	10½	267
	13⅝	340	7663	3476	10½	267

Combination Couplings J-55	Size		O.D.
	in		in
	2		2⅝
	2½		2⅝
	3		3
	4		4

Oil Country Couplings

Tubing Couplings




Sub Tubing Couplings J-55	Size		Weight Each
	2 EUE x 2 Reg		5
	2½ Reg x 2 Reg		5
	2½ Reg x 2 EUE		5
	2½ EUE x 2 Reg		8
	2½ EUE x 2 EUE		8
	2½ EUE x 2½ Reg		7
	3 Reg x 2 Reg		11
	3 Reg x 2 EUE		11
	3 Reg x 2½ Reg		10
	3 Reg x 2½ EUE		10
	3 EUE x 2 Reg		15
	3 EUE x 2 EUE		14
	3 EUE x 2½ Reg		16
	3 EUE x 2½ EUE		15
	3 EUE x 3 Reg		13
	4 Reg x 3 Reg		10
	4 Reg x 3 EUE		12
	4 EUE x 3 Reg		11
	4 EUE x 3 EUE		11
	4 EUE x 4 Reg		10

API Tubing Couplings	Size Nominal Inches	Tubing O.D.	Non-Upset			External Upset			
			J-55	N-80	Lbs. Per 100	J-55	N-80	C-75	Lbs. Per 100
	2"	2⅝"	POA	POA	282	POA	POA	POA	342
	2½"	2⅞"	POA	POA	515	POA	POA	POA	529
	3"	3½"	POA	POA	817	POA	POA	POA	902
	3½"	4"	POA	POA	957	POA	POA	POA	1,056
	4"	4½"	POA	POA	1,076	POA	POA	POA	1,331

Special Clearance Tubing Couplings	Size Nominal Inches	Tubing O.D.	External Upset			Lbs. Per 100	Actual O.D. Inches
			J-55	N-80	C-75 L-80		
	2"	2⅝"	POA	POA	POA	240	2.91
	2½"	2⅞"	POA	POA	POA	348	3.46
	3"	3½"	POA	POA	POA	540	4.18



Chambers / Pressure Vessels



- Chambers are available in 2" – 8" inch diameter and up to 2 feet long.
- Material is A106 Grade B seamless, unless otherwise specified.
- Solid, bored, or tapped Ends are available.

Phone: 713-928-5711
Email: webmgr@jbsmith.com

Malleable Iron

Cast Iron

Small Steel
Fittings

Pipe Nipples &
Pipe Couplings

Forged Steel
Fittings & Unions


Anvilets

Catawissa

J.B. Smith Products

Carton Information

Coated Products



Anvil's coated products protect pipes against the corrosive conditions found in oil and gas pipelines. They are effective on all grades of pipe, and can be used to coat malleable, cast iron, forged steel, and ductile metals.

Anvil provides two stock coatings, Scotchkote 134 and Corvel 1660, which are durable, reliable and field-tested. **Scotchkote 134** is a fusion-bonded epoxy coating designed to protect metal surfaces from corrosion. It is resistant to wastewater, corrosive acids, hydrocarbons, harsh chemicals, brine, and saltwater.

Corvel 1660 is specially designed to protect the inside diameter of tubular goods in applications such as fittings, valves, drill pipes, sucker rods, and metering systems. Corvel 1660 is resistant to H₂S, CO₂, harsh chemicals, brine, and salt water.

Anvil also offers a range of specialty coatings, available upon request, including nickel coating, chrome plating, Teflon coating, Nap-Guard coating, and powder coating.

Malleable Iron Class 150 (Standard)

Size		Cartons			Master Container			Pallets			
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight		
NPS	DN		lbs	kg		lbs	kg		lbs	kg	
FIGURE 1101: 90° ELBOW (PAGE 18)											
1/8	B	6	35	2.10	0.95	105	6.30	2.86	18585	1115.10	505.71
1/4	B G	8	25	2.75	1.25	75	8.25	3.74	13275	1460.25	662.24
3/8	B	10	20	3.40	1.54	40	6.80	3.08	7080	1203.60	545.85
1/2	B G	15	50	15.00	6.80	200	60.00	27.21	5400	1620.00	734.69
3/4	B G	20	35	15.75	7.14	140	63.00	28.57	3780	1701.00	771.43
1	B G	25	20	14.60	6.62	80	58.40	26.49	2160	1576.80	715.10
1 1/4	B G	32	12	11.64	5.28	48	46.56	21.12	1296	1257.12	570.12
1 1/2	B G	40	8	10.40	4.72	32	41.60	18.87	864	1123.20	509.39
2	B G	50	10	20.60	9.34	20	41.20	18.68	540	1112.40	504.49
2 1/2		65	5	17.75	8.05	10	35.50	16.10	270	958.50	434.69
3	B	80	4	21.84	9.90	8	43.68	19.81	216	1179.36	534.86
3 1/2		90	3	21.30	9.66	6	42.60	19.32	162	1150.20	521.63
4		100	5	44.75	20.29	5	44.75	20.29	135	1208.25	547.96
FIGURE 1101R: 90° ELBOW, REDUCING (PAGE 18)											
1/4 x 1/8	8 x 6	50	5.00	2.27	100	10.00	4.54	17700	1770.00	802.72	
3/8 x 1/8	10 x 6	25	3.00	1.36	75	9.00	4.08	13275	1593.00	722.45	
3/8 x 1/4	10 x 8	25	3.50	1.59	50	7.00	3.17	8850	1239.00	561.90	
1/2 x 1/4	15 x 8	15	2.85	1.29	30	5.70	2.59	5310	1008.90	457.55	
1/2 x 3/8	15 x 10	75	16.50	7.48	300	66.00	29.93	8100	1782.00	808.16	
3/4 x 1/4	20 x 8	12	3.12	1.41	24	6.24	2.83	4248	1104.48	500.90	
3/4 x 3/8	20 x 10	20	5.80	2.63	160	46.40	21.04	4320	1252.80	568.16	
3/4 x 1/2	B G 20 x 15	45	17.10	7.76	180	68.40	31.02	4860	1846.80	837.55	
1 x 3/8	25 x 10	15	6.15	2.79	120	49.20	22.31	3240	1328.40	602.45	
1 x 1/2	25 x 15	25	11.50	5.22	100	46.00	20.86	2700	1242.00	563.27	
1 x 3/4	B G 25 x 20	20	11.20	5.08	80	44.80	20.32	2160	1209.60	548.57	
1 1/4 x 1/2	B G 32 x 15	20	12.20	5.53	80	48.80	22.13	2160	1317.60	597.55	
1 1/4 x 3/4	32 x 20	15	10.65	4.83	60	42.60	19.32	1620	1150.20	521.63	
1 1/4 x 1	B 32 x 25	15	13.05	5.92	60	52.20	23.67	1620	1409.40	639.18	
1 1/2 x 3/4	40 x 20	12	9.96	4.52	48	39.84	18.07	1296	1075.68	487.84	
1 1/2 x 1	40 x 25	12	12.24	5.55	48	48.96	22.20	1296	1321.92	599.51	
1 1/2 x 1 1/4	40 x 32	8	9.36	4.24	32	37.44	16.98	864	1010.88	458.45	
2 x 3/4	50 x 20	6	7.80	3.54	24	31.20	14.15	648	842.40	382.04	
2 x 1	50 x 25	15	20.25	9.18	30	40.50	18.37	810	1093.50	495.92	
2 x 1 1/4	50 x 32	12	18.36	8.33	24	36.72	16.65	648	991.44	449.63	
2 x 1 1/2	50 x 40	12	21.00	9.52	24	42.00	19.05	648	1134.00	514.29	
2 1/2 x 1 1/2	65 x 40	6	15.00	6.80	12	30.00	13.61	324	810.00	367.35	
2 1/2 x 2	65 x 50	5	14.90	6.76	10	29.80	13.51	270	804.60	364.90	
3 x 2	80 x 50	4	15.00	6.80	8	30.00	13.61	216	810.00	367.35	
3 x 2 1/2	80 x 65	4	17.20	7.80	8	34.40	15.60	216	928.80	421.22	
4 x 3	100 x 80	2	15.74	7.14	4	31.48	14.28	108	849.96	385.47	
FIGURE 1102: 45° ELBOW (PAGE 19)											
1/8		6	50	3.50	1.59	150	10.50	4.76	26550	1858.50	842.86
1/4		8	35	3.85	1.75	70	7.70	3.49	12390	1362.90	618.10
3/8		10	20	3.20	1.45	40	6.40	2.90	7080	1132.80	513.74
1/2	B	15	75	16.50	7.48	300	66.00	29.93	8100	1782.00	808.16
3/4	B	20	40	14.80	6.71	160	59.20	26.85	4320	1598.40	724.90
1	B G	25	25	13.50	6.12	100	54.00	24.49	2700	1458.00	661.22
1 1/4	B	32	15	12.90	5.85	60	51.60	23.40	1620	1393.20	631.84
1 1/2		40	8	9.04	4.10	32	36.16	16.40	864	976.32	442.78
2	B G	50	6	10.74	4.87	24	42.96	19.48	648	1159.92	526.04
2 1/2		65	5	18.00	8.16	10	36.00	16.33	270	972.00	440.82
3		80	4	17.92	8.13	8	35.84	16.25	216	967.68	438.86
4		100	4	29.60	13.42	4	29.60	13.42	108	799.20	362.45

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Malleable Iron Class 150 (Standard)

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 1103: 90° STREET ELBOW (PAGE 19)										
1/8	B	6	40	2.40	1.09	120	7.20	3.27	21240	1274.40 577.96
1/4	B G	8	30	3.00	1.36	90	9.00	4.08	15930	1593.00 722.45
3/8	B	10	20	3.40	1.54	40	6.80	3.08	7080	1203.60 545.85
1/2	B G	15	75	21.00	9.52	300	84.00	38.10	8100	2268.00 1028.57
3/4	B G	20	40	16.40	7.44	160	65.60	29.75	4320	1771.20 803.27
1	B G	25	15	9.30	4.22	60	37.20	16.87	1620	1004.40 455.51
1 1/4	B	32	10	10.90	4.94	40	43.60	19.77	1080	1177.20 533.88
1 1/2	B	40	8	11.52	5.22	32	46.08	20.90	864	1244.16 564.24
2	B	50	10	28.50	12.93	20	57.00	25.85	540	1539.00 697.96
2 1/2		65	4	16.00	7.26	8	32.00	14.51	216	864.00 391.84
3		80	4	24.24	10.99	4	24.24	10.99	108	654.48 296.82
4		100	4	42.12	19.10	4	42.12	19.10	108	1137.24 515.76
FIGURE 1103R: 90° STREET ELBOW, REDUCING (PAGE 19)										
1/2 x 3/8		15 x 10	35	8.05	3.65	280	64.40	29.21	7560	1738.80 788.57
3/4 x 1/2	B	20 x 15	25	8.00	3.63	200	64.00	29.02	5400	1728.00 783.67
1 x 3/4		25 x 20	25	13.50	6.12	100	54.00	24.49	2700	1458.00 661.22
1 1/4 x 1		32 x 25	15	12.90	5.85	60	51.60	23.40	1620	1393.20 631.84
1 1/4 x 3/4		32 x 20	15	11.25	5.10	60	45.00	20.41	1620	1215.00 551.02
1 1/2 x 1 1/4		40 x 32	20	23.60	10.70	40	47.20	21.41	1080	1274.40 577.96
1 1/2 x 1		40 x 25	10	10.80	4.90	40	43.20	19.59	1080	1166.40 528.98
2 x 1 1/2		50 x 40	12	22.20	10.07	24	44.40	20.14	648	1198.80 543.67
FIGURE 1104: 45° STREET ELBOW (PAGE 20)										
1/8		6	50	3.00	1.36	150	9.00	4.08	26550	1593.00 722.45
1/4		8	50	5.00	2.27	100	10.00	4.54	17700	1770.00 802.72
3/8		10	25	3.50	1.59	50	7.00	3.17	8850	1239.00 561.90
1/2		15	75	15.00	6.80	300	60.00	27.21	8100	1620.00 734.69
3/4		20	40	13.20	5.99	160	52.80	23.95	4320	1425.60 646.53
1		25	25	13.00	5.90	100	52.00	23.58	2700	1404.00 636.73
1 1/4		32	15	12.75	5.78	60	51.00	23.13	1620	1377.00 624.49
1 1/2		40	10	12.20	5.53	40	48.80	22.13	1080	1317.60 597.55
2		50	12	23.04	10.45	24	46.08	20.90	648	1244.16 564.24
FIGURE 1105: STRAIGHT TEE (PAGE 20)										
1/8	B	6	25	2.25	1.02	75	6.75	3.06	13275	1194.75 541.84
1/4	B G	8	20	3.00	1.36	40	6.00	2.72	7080	1062.00 481.63
3/8	B	10	15	3.45	1.56	30	6.90	3.13	5310	1221.30 553.88
1/2	B G	15	40	16.40	7.44	160	65.60	29.75	4320	1771.20 803.27
3/4	B G	20	20	12.00	5.44	80	48.00	21.77	2160	1296.00 587.76
1	B G	25	12	10.80	4.90	48	43.20	19.59	1296	1166.40 528.98
1 1/4	B	32	8	10.48	4.75	32	41.92	19.01	864	1131.84 513.31
1 1/2	B G	40	5	8.65	3.92	20	34.60	15.69	540	934.20 423.67
2	B G	50	10	25.20	11.43	20	50.40	22.86	540	1360.80 617.14
2 1/2		65	4	19.60	8.89	8	39.20	17.78	216	1058.40 480.00
3		80	3	21.39	9.70	6	42.78	19.40	162	1155.06 523.84
3 1/2		90	4	36.00	16.33	4	36.00	16.33	108	972.00 440.82
4		100	4	45.28	20.54	4	45.28	20.54	108	1222.56 554.45

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Malleable Iron Class 150 (Standard)

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 1105R: REDUCING TEE (PAGE 21–23)										
1/8 x 1/8 x 1/4	6 x 6 x 8	25	3.00	1.36	50	6.00	2.72	8850	1062.00	481.63
1/4 x 1/4 x 1/8	8 x 8 x 6	25	3.25	1.47	50	6.50	2.95	8850	1150.50	521.77
1/4 x 1/4 x 3/8	8 x 8 x 10	15	2.85	1.29	30	5.70	2.59	5310	1008.90	457.55
3/8 x 1/4 x 1/4	10 x 8 x 8	15	2.85	1.29	30	5.70	2.59	5310	1008.90	457.55
3/8 x 1/4 x 3/8	10 x 8 x 10	15	3.15	1.43	30	6.30	2.86	5310	1115.10	505.71
3/8 x 3/8 x 1/4	10 x 10 x 8	15	3.15	1.43	30	6.30	2.86	5310	1115.10	505.71
3/8 x 3/8 x 1/2	10 x 10 x 15	10	2.70	1.22	20	5.40	2.45	3540	955.80	433.47
1/2 x 1/4 x 1/2	15 x 8 x 15	10	2.90	1.32	20	5.80	2.63	3540	1026.60	465.58
1/2 x 3/8 x 3/8	15 x 10 x 10	10	2.80	1.27	20	5.60	2.54	3540	991.20	449.52
1/2 x 3/8 x 1/2	15 x 10 x 15	10	3.30	1.50	20	6.60	2.99	3540	1168.20	529.80
1/2 x 1/2 x 1/4	15 x 15 x 8	10	2.70	1.22	20	5.40	2.45	3540	955.80	433.47
1/2 x 1/2 x 3/8	15 x 15 x 10	25	7.50	3.40	200	60.00	27.21	5400	1620.00	734.69
1/2 x 1/2 x 3/4	15 x 15 x 20	30	13.50	6.12	120	54.00	24.49	3240	1458.00	661.22
1/2 x 1/2 x 1	15 x 15 x 25	25	13.75	6.24	100	55.00	24.94	2700	1485.00	673.47
3/4 x 1/4 x 3/4	20 x 8 x 20	30	13.50	6.12	120	54.00	24.49	3240	1458.00	661.22
3/4 x 3/8 x 3/8	20 x 10 x 10	35	12.60	5.71	140	50.40	22.86	3780	1360.80	617.14
3/4 x 3/8 x 3/4	20 x 10 x 20	25	11.50	5.22	100	46.00	20.86	2700	1242.00	563.27
3/4 x 1/2 x 1/2	B 20 x 15 x 15	35	15.05	6.83	140	60.20	27.30	3780	1625.40	737.14
3/4 x 1/2 x 3/4	20 x 15 x 20	20	10.20	4.63	80	40.80	18.50	2160	1101.60	499.59
3/4 x 3/4 x 1/4	20 x 20 x 8	35	13.30	6.03	140	53.20	24.13	3780	1436.40	651.43
3/4 x 3/4 x 3/8	20 x 20 x 10	30	12.60	5.71	120	50.40	22.86	3240	1360.80	617.14
3/4 x 3/4 x 1/2	B 20 x 20 x 15	20	9.40	4.26	80	37.60	17.05	2160	1015.20	460.41
3/4 x 3/4 x 1	20 x 20 x 25	15	9.30	4.22	60	37.20	16.87	1620	1004.40	455.51
3/4 x 3/4 x 1 1/4	20 x 20 x 32	10	9.00	4.08	40	36.00	16.33	1080	972.00	440.82
1 x 1/4 x 1	25 x 8 x 25	15	10.35	4.69	60	41.40	18.78	1620	1117.80	506.94
1 x 1/2 x 1/2	B 25 x 15 x 15	25	17.50	7.94	100	70.00	31.75	2700	1890.00	857.14
1 x 1/2 x 3/4	25 x 15 x 20	20	11.20	5.08	80	44.80	20.32	2160	1209.60	548.57
1 x 1/2 x 1	25 x 15 x 25	15	11.40	5.17	60	45.60	20.68	1620	1231.20	558.37
1 x 3/4 x 1/2	25 x 20 x 15	20	11.80	5.35	80	47.20	21.41	2160	1274.40	577.96
1 x 3/4 x 3/4	B 25 x 20 x 20	15	11.10	5.03	60	44.40	20.14	1620	1198.80	543.67
1 x 3/4 x 1	25 x 20 x 25	15	11.70	5.31	60	46.80	21.22	1620	1263.60	573.06
1 x 1 x 1/4	25 x 25 x 8	20	10.60	4.81	80	42.40	19.23	2160	1144.80	519.18
1 x 1 x 3/8	25 x 25 x 10	20	12.00	5.44	80	48.00	21.77	2160	1296.00	587.76
1 x 1 x 1/2	B 25 x 25 x 15	15	10.50	4.76	60	42.00	19.05	1620	1134.00	514.29
1 x 1 x 3/4	B 25 x 25 x 20	15	12.30	5.58	60	49.20	22.31	1620	1328.40	602.45
1 x 1 x 1 1/4	25 x 25 x 32	10	9.20	4.17	40	36.80	16.69	1080	993.60	450.61
1 x 1 x 1 1/2	25 x 25 x 40	8	9.52	4.32	32	38.08	17.27	864	1028.16	466.29
1 x 1 x 2	25 x 25 x 50	12	19.56	8.87	24	39.12	17.74	648	1056.24	479.02
1 1/4 x 1/2 x 1	32 x 15 x 25	10	8.70	3.95	40	34.80	15.78	1080	939.60	426.12
1 1/4 x 1/2 x 1 1/4	32 x 15 x 32	6	6.24	2.83	24	24.96	11.32	648	673.92	305.63
1 1/4 x 3/4 x 3/4	32 x 20 x 20	10	8.60	3.90	40	34.40	15.60	1080	928.80	421.22
1 1/4 x 3/4 x 1	32 x 20 x 25	10	9.10	4.13	40	36.40	16.51	1080	982.80	445.71
1 1/4 x 3/4 x 1 1/4	32 x 20 x 32	6	6.24	2.83	24	24.96	11.32	648	673.92	305.63
1 1/4 x 1 x 1/2	32 x 25 x 15	15	11.40	5.17	60	45.60	20.68	1620	1231.20	558.37
1 1/4 x 1 x 3/4	32 x 25 x 20	10	8.70	3.95	40	34.80	15.78	1080	939.60	426.12
1 1/4 x 1 x 1	32 x 25 x 25	10	11.10	5.03	40	44.40	20.14	1080	1198.80	543.67
1 1/4 x 1 x 1 1/4	32 x 25 x 32	6	6.78	3.07	24	27.12	12.30	648	732.24	332.08
1 1/4 x 1 1/4 x 3/8	32 x 32 x 10	10	8.60	3.90	40	34.40	15.60	1080	928.80	421.22
1 1/4 x 1 1/4 x 1/2	B 32 x 32 x 15	10	9.80	4.44	40	39.20	17.78	1080	1058.40	480.00
1 1/4 x 1 1/4 x 3/4	B 32 x 32 x 20	8	8.56	3.88	32	34.24	15.53	864	924.48	419.27
1 1/4 x 1 1/4 x 1	B 32 x 32 x 25	20	23.60	10.70	40	47.20	21.41	1080	1274.40	577.96
1 1/4 x 1 1/4 x 1 1/2	32 x 32 x 40	15	21.75	9.86	30	43.50	19.73	810	1174.50	532.65
1 1/4 x 1 1/4 x 2	32 x 32 x 50	12	20.40	9.25	24	40.80	18.50	648	1101.60	499.59
1 1/2 x 1/2 x 1 1/2	40 x 15 x 40	15	19.95	9.05	30	39.90	18.10	810	1077.30	488.57

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Malleable Iron Class 150 (Standard)

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 1105R: REDUCING TEE (PAGE 21-23)										
1½ x ¾ x ¾	40 x 20 x 40	10	10.00	4.54	40	40.00	18.14	1080	1080.00	489.80
1½ x ¾ x 1½	40 x 20 x 20	15	21.15	9.59	30	42.30	19.18	810	1142.10	517.96
1½ x 1 x 1	40 x 25 x 40	8	9.12	4.14	32	36.48	16.54	864	984.96	446.69
1½ x 1 x 1¼	40 x 25 x 32	15	19.50	8.84	30	39.00	17.69	810	1053.00	477.55
1½ x 1 x 1½	40 x 25 x 25	15	22.50	10.20	30	45.00	20.41	810	1215.00	551.02
1½ x 1¼ x ½	40 x 32 x 15	10	10.50	4.76	40	42.00	19.05	1080	1134.00	514.29
1½ x 1¼ x ¾	40 x 32 x 20	8	8.64	3.92	32	34.56	15.67	864	933.12	423.18
1½ x 1¼ x 1	40 x 32 x 25	8	10.08	4.57	32	40.32	18.29	864	1088.64	493.71
1½ x 1¼ x 1¼	40 x 32 x 32	12	18.24	8.27	24	36.48	16.54	648	984.96	446.69
1½ x 1¼ x 1½	40 x 32 x 40	12	18.00	8.16	24	36.00	16.33	648	972.00	440.82
1½ x 1½ x ½	40 x 40 x 15	8	9.52	4.32	32	38.08	17.27	864	1028.16	466.29
1½ x 1½ x ¾	40 x 40 x 20	6	9.60	4.35	24	38.40	17.41	648	1036.80	470.20
1½ x 1½ x 1	40 x 40 x 25	6	8.70	3.95	24	34.80	15.78	648	939.60	426.12
1½ x 1½ x 1¼	40 x 40 x 32	6	8.70	3.95	24	34.80	15.78	648	939.60	426.12
1½ x 1½ x 2	40 x 40 x 50	12	22.32	10.12	24	44.64	20.24	648	1205.28	546.61
2 x ½ x 2	50 x 15 x 50	10	21.50	9.75	20	43.00	19.50	540	1161.00	526.53
2 x ¾ x 2	50 x 20 x 50	10	20.00	9.07	20	40.00	18.14	540	1080.00	489.80
2 x 1 x 2	50 x 25 x 50	10	21.40	9.71	20	42.80	19.41	540	1155.60	524.08
2 x 1¼ x 1¼	50 x 32 x 32	10	17.20	7.80	20	34.40	15.60	540	928.80	421.22
2 x 1¼ x 1½	50 x 32 x 40	10	18.50	8.39	20	37.00	16.78	540	999.00	453.06
2 x 1¼ x 2	50 x 32 x 50	10	22.00	9.98	20	44.00	19.95	540	1188.00	538.78
2 x 1½ x 1	50 x 40 x 25	12	18.84	8.54	24	37.68	17.09	648	1017.36	461.39
2 x 1½ x 1¼	50 x 40 x 32	10	17.60	7.98	20	35.20	15.96	540	950.40	431.02
2 x 1½ x 1½	50 x 40 x 40	10	19.50	8.84	20	39.00	17.69	540	1053.00	477.55
2 x 1½ x 2	50 x 40 x 50	8	17.92	8.13	16	35.84	16.25	432	967.68	438.86
2 x 2 x ½	50 x 50 x 15	15	24.75	11.22	30	49.50	22.45	810	1336.50	606.12
2 x 2 x ¾	50 x 50 x 20	12	22.44	10.18	24	44.88	20.35	648	1211.76	549.55
2 x 2 x 1	50 x 50 x 25	12	21.12	9.58	24	42.24	19.16	648	1140.48	517.22
2 x 2 x 1¼	50 x 50 x 32	10	23.50	10.66	20	47.00	21.32	540	1269.00	575.51
2 x 2 x 1½	50 x 50 x 40	10	25.50	11.56	20	51.00	23.13	540	1377.00	624.49
2 x 2 x 2½	50 x 50 x 65	6	21.00	9.52	12	42.00	19.05	324	1134.00	514.29
2½ x 1½ x 2	65 x 40 x 50	6	20.58	9.33	12	41.16	18.67	324	1111.32	504.00
2½ x 1½ x 2½	65 x 40 x 65	6	22.80	10.34	12	45.60	20.68	324	1231.20	558.37
2½ x 2 x 2	65 x 50 x 50	6	19.68	8.93	12	39.36	17.85	324	1062.72	481.96
2½ x 2 x 2½	65 x 50 x 65	4	16.40	7.44	8	32.80	14.88	216	885.60	401.63
2½ x 2½ x ¾	65 x 65 x 20	6	16.32	7.40	12	32.64	14.80	324	881.28	399.67
2½ x 2½ x 1	65 x 65 x 25	6	17.10	7.76	12	34.20	15.51	324	923.40	418.78
2½ x 2½ x 1¼	65 x 65 x 32	6	20.16	9.14	12	40.32	18.29	324	1088.64	493.71
2½ x 2½ x 1½	65 x 65 x 40	6	20.76	9.41	12	41.52	18.83	324	1121.04	508.41
2½ x 2½ x 2	65 x 65 x 50	6	21.90	9.93	12	43.80	19.86	324	1182.60	536.33
2½ x 2½ x 3	65 x 65 x 80	4	23.28	10.56	8	46.56	21.12	216	1257.12	570.12
3 x 2 x 2	80 x 50 x 50	4	18.00	8.16	8	36.00	16.33	216	972.00	440.82
3 x 2 x 3	80 x 50 x 80	4	23.20	10.52	8	46.40	21.04	216	1252.80	568.16
3 x 2½ x 2	80 x 65 x 50	4	19.20	8.71	8	38.40	17.41	216	1036.80	470.20
3 x 2½ x 2½	80 x 65 x 65	4	23.20	10.52	8	46.40	21.04	216	1252.80	568.16
3 x 3 x ¾	80 x 80 x 20	4	16.12	7.31	8	32.24	14.62	216	870.48	394.78
3 x 3 x 1	80 x 80 x 25	4	16.52	7.49	8	33.04	14.98	216	892.08	404.57
3 x 3 x 1¼	80 x 80 x 32	4	18.00	8.16	8	36.00	16.33	216	972.00	440.82
3 x 3 x 1½	80 x 80 x 40	4	20.72	9.40	8	41.44	18.79	216	1118.88	507.43
3 x 3 x 2	80 x 80 x 50	4	22.80	10.34	8	45.60	20.68	216	1231.20	558.37
3 x 3 x 2½	80 x 80 x 65	4	24.36	11.05	8	48.72	22.10	216	1315.44	596.57
4 x 3 x 4	100 x 80 x 100	4	41.60	18.87	4	41.60	18.87	108	1123.20	509.39
4 x 4 x 1½	100 x 100 x 40	4	29.88	13.55	4	29.88	13.55	108	806.76	365.88
4 x 4 x 2	100 x 100 x 50	4	33.56	15.22	4	33.56	15.22	108	906.12	410.94
4 x 4 x 2½	100 x 100 x 65	4	38.40	17.41	4	38.40	17.41	108	1036.80	470.20

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Malleable Iron Class 150 (Standard)

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 1106: STREET OR SERVICE TEE (PAGE 24)										
¼	8	25	3.75	1.70	50	7.50	3.40	8850	1327.50	602.04
⅜	10	12	2.88	1.31	24	5.76	2.61	4248	1019.52	462.37
½	15	15	5.10	2.31	120	40.80	18.50	3240	1101.60	499.59
¾	20	15	9.15	4.15	60	36.60	16.60	1620	988.20	448.16
1	25	10	9.60	4.35	40	38.40	17.41	1080	1036.80	470.20
1¼	32	6	8.34	3.78	24	33.36	15.13	648	900.72	408.49
1½	40	12	23.16	10.50	24	46.32	21.01	648	1250.64	567.18
2	50	8	25.28	11.46	16	50.56	22.93	432	1365.12	619.10
FIGURE 1106: STREET OR SERVICE TEE, REDUCING (PAGE 24)										
1¼ x 1 x 1¼	32 x 25 x 32	8	10.72	4.86	32	42.88	19.45	864	1157.76	525.06
FIGURE 1107: CROSS (PAGE 24)										
⅛	6	25	3.00	1.36	50	6.00	2.72	8850	1062.00	481.63
¼	8	15	2.70	1.22	30	5.40	2.45	5310	955.80	433.47
⅜	10	20	5.60	2.54	160	44.80	20.32	4320	1209.60	548.57
½	15	30	12.60	5.71	120	50.40	22.86	3240	1360.80	617.14
¾	20	15	10.35	4.69	60	41.40	18.78	1620	1117.80	506.94
1	25	10	11.20	5.08	40	44.80	20.32	1080	1209.60	548.57
1¼	32	15	21.60	9.80	30	43.20	19.59	810	1166.40	528.98
1½	40	10	19.80	8.98	20	39.60	17.96	540	1069.20	484.90
2	50	8	26.40	11.97	16	52.80	23.95	432	1425.60	646.53
2½	65	4	23.60	10.70	8	47.20	21.41	216	1274.40	577.96
3	80	4	31.76	14.40	4	31.76	14.40	108	857.52	388.90
FIGURE 1108: 45° Y-BRANCH OR LATERAL (PAGE 24)										
⅜	10	12	3.24	1.47	24	6.48	2.94	4248	1146.96	520.16
½	15	35	12.95	5.87	140	51.80	23.49	3780	1398.60	634.29
¾	20	20	12.40	5.62	80	49.60	22.49	2160	1339.20	607.35
1	25	10	8.60	3.90	40	34.40	15.60	1080	928.80	421.22
1¼	32	6	9.78	4.44	24	39.12	17.74	648	1056.24	479.02
1½	40	10	20.00	9.07	20	40.00	18.14	540	1080.00	489.80
2	50	6	18.30	8.30	12	36.60	16.60	324	988.20	448.16
2½	65	4	23.44	10.63	4	23.44	10.63	108	632.88	287.02
FIGURE 1119: RETURN BENDS OPEN PATTERN, R.H. (PAGE 25)										
½	15	20	7.20	3.27	160	57.60	26.12	4320	1555.20	705.31
¾	20	20	12.80	5.80	80	51.20	23.22	2160	1382.40	626.94
1	25	10	11.00	4.99	40	44.00	19.95	1080	1188.00	538.78
1¼	32	12	21.24	9.63	24	42.48	19.27	648	1146.96	520.16
1½	40	10	25.50	11.56	20	51.00	23.13	540	1377.00	624.49
2	50	6	24.00	10.88	12	48.00	21.77	324	1296.00	587.76
FIGURE 1121: COUPLING RIGHT HAND (PAGE 25)										
⅛	6	40	2.40	1.09	160	9.60	4.35	28320	1699.20	770.61
¼	B 8	35	3.15	1.43	105	9.45	4.29	18585	1672.65	758.57
⅜	10	30	3.90	1.77	60	7.80	3.54	10620	1380.60	626.12
½	B G 15	20	4.00	1.81	40	8.00	3.63	7080	1416.00	642.18
¾	B G 20	60	18.00	8.16	240	72.00	32.65	6480	1944.00	881.63
1	B G 25	25	12.00	5.44	100	48.00	21.77	2700	1296.00	587.76
1¼	B 32	15	11.25	5.10	60	45.00	20.41	1620	1215.00	551.02
1½	B 40	10	10.00	4.54	40	40.00	18.14	1080	1080.00	489.80
2	B 50	5	7.25	3.29	20	29.00	13.15	540	783.00	355.10
2½	65	12	28.80	13.06	24	57.60	26.12	648	1555.20	705.31
3	80	4	13.20	5.99	8	26.40	11.97	216	712.80	323.27
4	100	4	22.88	10.38	8	45.76	20.75	216	1235.52	560.33

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Malleable Iron Class 150 (Standard)

Size		No. Pcs.	Cartons Weight		No. Pcs.	Master Container Weight		No. Pcs.	Pallets Weight		
NPS	DN		lbs	kg		lbs	kg		lbs	kg	
FIGURE 1124: CAP (PAGE 25)											
½	B G	15	75	9.00	4.08	300	36.00	16.33	8100	972.00	440.82
¾	B G	20	60	13.20	5.99	240	52.80	23.95	6480	1425.60	646.53
1	B G	25	35	13.30	6.03	140	53.20	24.13	3780	1436.40	651.43
1¼	B	32	25	14.50	6.58	100	58.00	26.30	2700	1566.00	710.20
1½	B	40	20	14.60	6.62	80	58.40	26.49	2160	1576.80	715.10
2	B	50	12	13.56	6.15	48	54.24	24.60	1296	1464.48	664.16
2½		65	15	26.25	11.90	30	52.50	23.81	810	1417.50	642.86
3		80	12	31.44	14.26	24	62.88	28.52	648	1697.76	769.96
3½		90	8	25.52	11.57	16	51.04	23.15	432	1378.08	624.98
4		100	4	18.16	8.24	8	36.32	16.47	216	980.64	444.73
5		125	4	25.80	11.70	8	51.60	23.40	216	1393.20	631.84
FIGURE 1125: REDUCER (PAGE 26)											
¼ x ¼	B	8 x 6	25	1.75	0.79	100	7.00	3.17	17700	1239.00	561.90
⅜ x ⅜		10 x 6	30	3.30	1.50	90	9.90	4.49	15930	1752.30	794.69
⅜ x ¼	B	10 x 8	25	2.75	1.25	75	8.25	3.74	13275	1460.25	662.24
½ x ⅜		15 x 6	20	2.80	1.27	40	5.60	2.54	7080	991.20	449.52
½ x ¼	B	15 x 8	25	3.75	1.70	50	7.50	3.40	8850	1327.50	602.04
½ x ⅜	B	15 x 10	25	4.25	1.93	50	8.50	3.85	8850	1504.50	682.31
¾ x ⅜		20 x 6	20	4.80	2.18	160	38.40	17.41	4320	1036.80	470.20
¾ x ¼		20 x 8	12	2.64	1.20	24	5.28	2.39	4248	934.56	423.84
¾ x ⅜		20 x 10	50	12.50	5.67	200	50.00	22.68	5400	1350.00	612.24
¾ x ½	B G	20 x 15	60	16.20	7.35	240	64.80	29.39	6480	1749.60	793.47
1 x ¼		25 x 8	20	7.00	3.17	160	56.00	25.40	4320	1512.00	685.71
1 x ⅜		25 x 10	20	7.00	3.17	160	56.00	25.40	4320	1512.00	685.71
1 x ½	B G	25 x 15	45	17.55	7.96	180	70.20	31.84	4860	1895.40	859.59
1 x ¾	B G	25 x 20	35	15.05	6.83	140	60.20	27.30	3780	1625.40	737.14
1¼ x ½		32 x 15	15	9.15	4.15	60	36.60	16.60	1620	988.20	448.16
1¼ x ¾	B	32 x 20	20	12.80	5.80	80	51.20	23.22	2160	1382.40	626.94
1¼ x 1	B	32 x 25	20	13.60	6.17	80	54.40	24.67	2160	1468.80	666.12
1½ x ½		40 x 15	15	11.70	5.31	60	46.80	21.22	1620	1263.60	573.06
1½ x ¾		40 x 20	15	13.20	5.99	60	52.80	23.95	1620	1425.60	646.53
1½ x 1	B	40 x 25	15	13.20	5.99	60	52.80	23.95	1620	1425.60	646.53
1½ x 1¼	B	40 x 32	10	9.00	4.08	40	36.00	16.33	1080	972.00	440.82
2 x ½		50 x 15	10	13.00	5.90	40	52.00	23.58	1080	1404.00	636.73
2 x ¾		50 x 20	5	6.70	3.04	20	26.80	12.15	540	723.60	328.16
2 x 1	B	50 x 25	5	7.00	3.17	20	28.00	12.70	540	756.00	342.86
2 x 1¼		50 x 32	5	7.65	3.47	20	30.60	13.88	540	826.20	374.69
2 x 1½	B	50 x 40	5	7.75	3.51	20	31.00	14.06	540	837.00	379.59
2½ x 1		65 x 25	10	21.20	9.61	20	42.40	19.23	540	1144.80	519.18
2½ x 1¼		65 x 32	10	20.90	9.48	20	41.80	18.96	540	1128.60	511.84
2½ x 1½		65 x 40	7	14.63	6.63	14	29.26	13.27	378	790.02	358.29
2½ x 2		65 x 50	8	20.08	9.11	16	40.16	18.21	432	1084.32	491.76
3 x 1		80 x 25	5	15.80	7.17	10	31.60	14.33	270	853.20	386.94
3 x 1¼		80 x 32	4	11.96	5.42	8	23.92	10.85	216	645.84	292.90
3 x 1½		80 x 40	4	13.20	5.99	8	26.40	11.97	216	712.80	323.27
3 x 2		80 x 50	5	16.25	7.37	10	32.50	14.74	270	877.50	397.96
3 x 2½		80 x 65	5	16.55	7.51	10	33.10	15.01	270	893.70	405.31
3½ x 2		90 x 50	4	17.28	7.84	8	34.56	15.67	216	933.12	423.18
3½ x 2½		90 x 65	4	18.88	8.56	8	37.76	17.12	—	—	—
3½ x 3		90 x 80	4	19.96	9.05	8	39.92	18.10	216	1077.84	488.82
4 x 1½		100 x 40	4	19.60	8.89	4	19.60	8.89	108	529.20	240.00
4 x 2		100 x 50	4	20.40	9.25	4	20.40	9.25	108	550.80	249.80
4 x 2½		100 x 65	4	23.72	10.76	4	23.72	10.76	108	640.44	290.45
4 x 3		100 x 80	4	26.20	11.88	4	26.20	11.88	108	707.40	320.82
4 x 3½		100 x 90	4	25.20	11.43	4	25.20	11.43	108	680.40	308.57

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Malleable Iron Class 150 (Standard)

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 1134: HEX LOCKNUT (PAGE 27)										
1/8	6	50	2.00	0.91	200	8.00	3.63	35400	1416.00	642.18
1/4	8	50	1.00	0.45	200	4.00	1.81	35400	708.00	321.09
3/8	10	50	2.00	0.91	200	8.00	3.63	35400	1416.00	642.18
1/2	15	50	3.00	1.36	150	9.00	4.08	26550	1593.00	722.45
3/4	20	50	4.00	1.81	100	8.00	3.63	17700	1416.00	642.18
1	25	25	3.50	1.59	50	7.00	3.17	8850	1239.00	561.90
1 1/4	32	25	5.25	2.38	200	42.00	19.05	5400	1134.00	514.29
1 1/2	40	15	3.60	1.63	120	28.80	13.06	3240	777.60	352.65
2	50	25	1—	4.54	100	4—	18.14	2700	108—	489.80
FIGURE 1190: FLOOR FLANGE – DUCTILE IRON (PAGE 27)										
1/4	8	—	—	—	200	78.00	35.37	—	—	—
3/8	10	—	—	—	200	86.00	39.00	—	—	—
1/2	15	30	16.80	7.62	120	67.20	30.48	3240	1814.40	822.86
3/4	20	20	12.00	5.44	80	48.00	21.77	2160	1296.00	587.76
1	25	15	12.60	5.71	60	50.40	22.86	1620	1360.80	617.14
1 1/4	32	25	22.50	10.20	50	45.00	20.41	1350	1215.00	551.02
1 1/2	40	10	12.00	5.44	40	48.00	21.77	1080	1296.00	587.76
2	50	15	30.45	13.81	30	60.90	27.62	810	1644.30	745.71
FIGURE 1133: WASTE NUT (PAGE 27)										
1/2	15	50	6.00	2.72	100	12.00	5.44	17700	2124.00	963.27
3/4	20	25	3.75	1.70	50	7.50	3.40	8850	1327.50	602.04
FIGURE 1138: EXTENSION PIECE (PAGE 27)										
1/2	15	20	3.80	1.72	40	7.60	3.45	7080	1345.20	610.07
3/4	20	60	21.00	9.52	240	84.00	38.10	6480	2268.00	1028.57
1	25	30	14.40	6.53	120	57.60	26.12	3240	1555.20	705.31

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Malleable Iron

Class 300 (XS / XH)

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
			lbs	kg		lbs	kg		lbs	kg
NPS	DN									
FIGURE 1161: 90° ELBOW (PAGE 28)										
1/4	8	20	4.00	1.81	40	8.00	3.63	7080	1416.00	642.18
3/8	10	15	4.35	1.97	30	8.70	3.95	5310	1539.90	698.37
1/2	B 15	40	18.80	8.53	160	75.20	34.10	4320	2030.40	920.82
3/4	B 20	20	13.20	5.99	80	52.80	23.95	2160	1425.60	646.53
1	B 25	15	17.25	7.82	60	69.00	31.29	1620	1863.00	844.90
1 1/4	32	13	24.44	11.08	26	48.88	22.17	702	1319.76	598.53
1 1/2	B 40	10	24.70	11.20	20	49.40	22.40	540	1333.80	604.90
2	B 50	6	23.10	10.48	12	46.20	20.95	324	1247.40	565.71
2 1/2	65	3	17.40	7.89	6	34.80	15.78	162	939.60	426.12
3	80	2	19.90	9.02	4	39.80	18.05	108	1074.60	487.35
FIGURE 1161R: 90° ELBOW, REDUCING (PAGE 28)										
3/8 x 1/4	10 x 8	25	6.50	2.95	50	13.00	5.90	1350	351.00	159.18
1/2 x 3/8	15 x 10	25	10.25	4.65	50	20.50	9.30	1350	553.50	251.02
3/4 x 1/2	20 x 15	20	12.40	5.62	40	24.80	11.25	1080	669.60	303.67
1 x 1/2	25 x 15	20	17.40	7.89	40	34.80	15.78	1080	939.60	426.12
1 x 3/4	25 x 20	20	20.00	9.07	40	40.00	18.14	1080	1080.00	489.80
1 1/4 x 3/4	32 x 20	15	21.15	9.59	30	42.30	19.18	810	1142.10	517.96
1 1/4 x 1	32 x 25	15	24.00	10.88	30	48.00	21.77	810	1296.00	587.76
1 1/2 x 1	40 x 25	10	18.90	8.57	20	37.80	17.14	540	1020.60	462.86
1 1/2 x 1 1/4	40 x 32	10	21.50	9.75	20	43.00	19.50	540	1161.00	526.53
2 x 1 1/4	50 x 32	5	15.60	7.07	10	31.20	14.15	270	842.40	382.04
2 x 1 1/2	50 x 40	5	16.50	7.48	10	33.00	14.97	270	891.00	404.08
FIGURE 1160: 45° STREET ELBOW (PAGE 28)										
1/2	15	12	4.32	1.96	24	8.64	3.92	4248	1529.28	693.55
3/4	20	30	16.20	7.35	120	64.80	29.39	3240	1749.60	793.47
1	25	15	12.75	5.78	60	51.00	23.13	1620	1377.00	624.49
1 1/4	32	10	15.00	6.80	40	60.00	27.21	1080	1620.00	734.69
1 1/2	40	6	12.36	5.61	24	49.44	22.42	648	1334.88	605.39
2	50	8	26.72	12.12	16	53.44	24.24	432	1442.88	654.37
FIGURE 1162: 45° ELBOW (PAGE 29)										
1/4	8	25	4.75	2.15	50	9.50	4.31	8850	1681.50	762.59
3/8	10	15	4.20	1.90	30	8.40	3.81	5310	1486.80	674.29
1/2	15	10	4.30	1.95	20	8.60	3.90	3540	1522.20	690.34
3/4	20	12	7.92	3.59	96	63.36	28.73	2592	1710.72	775.84
1	25	15	15.00	6.80	60	60.00	27.21	1620	1620.00	734.69
1 1/4	32	15	25.05	11.36	30	50.10	22.72	810	1352.70	613.47
1 1/2	40	11	23.65	10.73	22	47.30	21.45	594	1277.10	579.18
2	50	6	20.40	9.25	12	40.80	18.50	324	1101.60	499.59
2 1/2	65	4	22.04	10.00	8	44.08	19.99	216	1190.16	539.76
3	80	3	24.30	11.02	6	48.60	22.04	162	1312.20	595.10
4	100	3	40.23	18.24	3	40.23	18.24	81	1086.21	492.61
FIGURE 1170: 90° STREET ELBOW (PAGE 29)										
1/4	8	30	5.10	2.31	60	10.20	4.63	10620	1805.40	818.78
3/8	10	15	3.90	1.77	30	7.80	3.54	5310	1380.60	626.12
1/2	15	20	8.00	3.63	160	64.00	29.02	4320	1728.00	783.67
3/4	20	25	17.00	7.71	100	68.00	30.84	2700	1836.00	832.65
1	25	15	15.60	7.07	60	62.40	28.30	1620	1684.80	764.08
1 1/4	32	15	24.00	10.88	30	48.00	21.77	810	1296.00	587.76
1 1/2	40	10	22.00	9.98	20	44.00	19.95	540	1188.00	538.78
2	50	4	14.36	6.51	8	28.72	13.02	216	775.44	351.67
3	80	2	19.10	8.66	4	38.20	17.32	108	1031.40	467.76

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Malleable Iron Class 300 (XS / XH)

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 1164: STRAIGHT TEE (PAGE 29)										
¼	8	15	4.05	1.84	30	8.10	3.67	5310	1433.70	650.20
⅝	10	10	4.20	1.90	20	8.40	3.81	3540	1486.80	674.29
½	15	25	16.25	7.37	100	65.00	29.48	2700	1755.00	795.92
¾	20	15	16.05	7.28	60	64.20	29.12	1620	1733.40	786.12
1	25	10	16.20	7.35	40	64.80	29.39	1080	1749.60	793.47
1¼	32	10	24.90	11.29	20	49.80	22.59	540	1344.60	609.80
1½	40	7	23.80	10.79	14	47.60	21.59	378	1285.20	582.86
2	50	5	26.00	11.79	10	52.00	23.58	270	1404.00	636.73
2½	65	4	31.48	14.28	4	31.48	14.28	108	849.96	385.47
3	80	4	49.84	22.60	4	49.84	22.60	108	1345.68	610.29
FIGURE 1164R: REDUCING TEE (PAGE 30)										
⅝x⅝x¼	10 x 10 x 8	30	11.10	5.03	120	44.40	20.14	3240	1198.80	543.67
½x½x¼	15 x 15 x 8	52	24.96	11.32	104	49.92	22.64	2808	1347.84	611.27
½x½x¾	15 x 15 x 20	13	10.40	4.72	52	41.60	18.87	1404	1123.20	509.39
¾x½x¾	20 x 15 x 20	13	12.09	5.48	52	48.36	21.93	1404	1305.72	592.16
¾x¾x¼	20 x 20 x 8	15	11.40	5.17	60	45.60	20.68	1620	1231.20	558.37
¾x¾x⅝	20 x 20 x 10	13	10.40	4.72	52	41.60	18.87	1404	1123.20	509.39
¾x¾x½	20 x 20 x 15	13	11.70	5.31	52	46.80	21.22	1404	1263.60	573.06
1 x ½x1	25 x 15 x 25	18	24.48	11.10	36	48.96	22.20	972	1321.92	599.51
1 x ¾x¾	25 x 20 x 20	10	12.70	5.76	40	50.80	23.04	1080	1371.60	622.04
1 x ¾x1	25 x 20 x 25	9	12.42	5.63	36	49.68	22.53	972	1341.36	608.33
1 x 1 x ¼	25 x 25 x 8	9	9.81	4.45	36	39.24	17.80	972	1059.48	480.49
1 x 1 x ½	25 x 25 x 15	10	12.60	5.71	40	50.40	22.86	1080	1360.80	617.14
1 x 1 x ¾	25 x 25 x 20	10	13.30	6.03	40	53.20	24.13	1080	1436.40	651.43
1¼x 1 x 1	32 x 25 x 25	14	26.88	12.19	28	53.76	24.38	756	1451.52	658.29
1¼x 1¼x ½	32 x 32 x 15	15	25.50	11.56	30	51.00	23.13	810	1377.00	624.49
1¼x 1¼x ¾	32 x 32 x 20	12	22.80	10.34	24	45.60	20.68	648	1231.20	558.37
1¼x 1¼x 1	32 x 32 x 25	6	12.60	5.71	24	50.40	22.86	648	1360.80	617.14
1½x 1½x ½	40 x 40 x 15	10	22.70	10.29	20	45.40	20.59	540	1225.80	555.92
1½x 1½x ¾	40 x 40 x 20	10	24.60	11.16	20	49.20	22.31	540	1328.40	602.45
1½x 1½x 1	40 x 40 x 25	9	23.40	10.61	18	46.80	21.22	486	1263.60	573.06
1½x 1½x 1¼	40 x 40 x 32	9	27.45	12.45	18	54.90	24.90	486	1482.30	672.24
2 x 1½x 2	50 x 40 x 50	5	22.50	10.20	10	45.00	20.41	270	1215.00	551.02
2 x 2 x ½	50 x 50 x 15	5	16.75	7.60	10	33.50	15.19	270	904.50	410.20
2 x 2 x ¾	50 x 50 x 20	8	28.48	12.92	16	56.96	25.83	432	1537.92	697.47
2 x 2 x 1	50 x 50 x 25	6	22.20	10.07	12	44.40	20.14	324	1198.80	543.67
2 x 2 x 1¼	50 x 50 x 32	6	25.32	11.48	12	50.64	22.97	324	1367.28	620.08
2 x 2 x 1½	50 x 50 x 40	5	23.00	10.43	10	46.00	20.86	270	1242.00	563.27
2½x 2½x 1½	65 x 65 x 40	4	25.40	11.52	8	50.80	23.04	216	1371.60	622.04
3 x 3 x 2	80 x 80 x 50	4	38.40	17.41	4	38.40	17.41	108	1036.80	470.20
FIGURE 1165: CROSS (PAGE 30)										
¼	8	60	21.00	9.52	120	42.00	19.05	—	—	—
¾	20	25	31.25	14.17	50	62.50	28.34	1350	1687.50	765.31
1	25	13	24.70	11.20	26	49.40	22.40	702	1333.80	604.90
1¼	32	8	25.84	11.72	16	51.68	23.44	432	1395.36	632.82
1½	40	6	25.20	11.43	12	50.40	22.86	324	1360.80	617.14
2	50	3	19.47	8.83	6	38.94	17.66	162	1051.38	476.82

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Malleable Iron

Class 300 (XS / XH)

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
			lbs	kg		lbs	kg		lbs	kg
NPS	DN									
FIGURE 1166: COUPLING (PAGE 31)										
¼	8	30	5.10	2.31	60	10.20	4.63	10620	1805.40	818.78
¾	10	10	2.60	1.18	20	5.20	2.36	3540	920.40	417.41
½	15	10	4.00	1.81	20	8.00	3.63	3540	1416.00	642.18
¾	20	12	7.80	3.54	96	62.40	28.30	2592	1684.80	764.08
1	25	8	7.92	3.59	64	63.36	28.73	1728	1710.72	775.84
1¼	32	15	24.90	11.29	30	49.80	22.59	810	1344.60	609.80
1½	40	12	24.36	11.05	24	48.72	22.10	648	1315.44	596.57
2	50	8	25.92	11.76	16	51.84	23.51	432	1399.68	634.78
2½	65	5	27.25	12.36	10	54.50	24.72	270	1471.50	667.35
3	80	3	21.90	9.93	6	43.80	19.86	162	1182.60	536.33
FIGURE 1167: REDUCER (PAGE 31)										
¾ x ¼	10 x 8	24	5.04	2.29	48	10.08	4.57	8496	1784.16	809.14
½ x ¼	15 x 8	12	3.72	1.69	24	7.44	3.37	4248	1316.88	597.22
½ x ¾	15 x 10	12	4.08	1.85	24	8.16	3.70	4248	1444.32	655.02
¾ x ¼	20 x 8	45	20.70	9.39	90	41.40	18.78	2430	1117.80	506.94
¾ x ¾	20 x 10	45	21.15	9.59	90	42.30	19.18	2430	1142.10	517.96
¾ x ½	20 x 15	45	22.50	10.20	90	45.00	20.41	2430	1215.00	551.02
1 x ¼	25 x 8	15	9.90	4.49	60	39.60	17.96	1620	1069.20	484.90
1 x ¾	25 x 10	20	14.20	6.44	80	56.80	25.76	2160	1533.60	695.51
1 x ½	25 x 15	20	14.20	6.44	80	56.80	25.76	2160	1533.60	695.51
1 x ¾	25 x 20	30	23.10	10.48	60	46.20	20.95	1620	1247.40	565.71
1¼ x ½	32 x 15	22	24.64	11.17	44	49.28	22.35	1188	1330.56	603.43
1¼ x ¾	32 x 20	12	13.92	6.31	48	55.68	25.25	1296	1503.36	681.80
1¼ x 1	32 x 25	12	15.24	6.91	48	60.96	27.65	1296	1645.92	746.45
1½ x ½	40 x 15	16	24.16	10.96	32	48.32	21.91	864	1304.64	591.67
1½ x ¾	40 x 20	10	15.70	7.12	40	62.80	28.48	1080	1695.60	768.98
1½ x 1	40 x 25	8	12.96	5.88	32	51.84	23.51	864	1399.68	634.78
1½ x 1¼	40 x 32	8	14.24	6.46	32	56.96	25.83	864	1537.92	697.47
2 x ½	50 x 15	12	28.68	13.01	24	57.36	26.01	648	1548.72	702.37
2 x ¾	50 x 20	10	24.40	11.07	20	48.80	22.13	540	1317.60	597.55
2 x 1	50 x 25	9	22.86	10.37	18	45.72	20.73	486	1234.44	559.84
2 x 1¼	50 x 32	6	15.96	7.24	12	31.92	14.48	324	861.84	390.86
2 x 1½	50 x 40	10	27.20	12.34	20	54.40	24.67	540	1468.80	666.12
2½ x 1½	65 x 40	4	16.36	7.42	8	32.72	14.84	216	883.44	400.65
2½ x 2	65 x 50	5	21.60	9.80	10	43.20	19.59	270	1166.40	528.98
3 x 1½	80 x 40	4	23.16	10.50	8	46.32	21.01	216	1250.64	567.18
3 x 2	80 x 50	4	23.32	10.58	8	46.64	21.15	216	1259.28	571.10
3 x 2½	80 x 65	4	25.80	11.70	8	51.60	23.40	216	1393.20	631.84
4 x 2	100 x 50	4	38.00	17.23	4	38.00	17.23	108	1026.00	465.31
4 x 3	100 x 80	4	40.00	18.14	4	40.00	18.14	108	1080.00	489.80
FIGURE 1163: CAP (PAGE 32)										
¼	8	40	4.00	1.81	120	12.00	5.44	21240	2124.00	963.27
¾	10	25	3.75	1.70	75	11.25	5.10	13275	1991.25	903.06
½	15	15	3.45	1.56	30	6.90	3.13	5310	1221.30	553.88
¾	20	12	4.20	1.90	24	8.40	3.81	4248	1486.80	674.29
1	25	15	8.70	3.95	120	69.60	31.56	3240	1879.20	852.24
1¼	32	10	10.00	4.54	80	80.00	36.28	2160	2160.00	979.59
1½	40	5	5.90	2.68	40	47.20	21.41	1080	1274.40	577.96
2	50	8	15.52	7.04	32	62.08	28.15	864	1676.16	760.16
2½	65	10	33.20	15.06	20	66.40	30.11	540	1792.80	813.06
3	80	8	37.68	17.09	16	75.36	34.18	432	2034.72	922.78
FIGURE 390: SQUARE COUNTERSUNK PLUGS (PAGE 32)										
½	15	100	5.00	2.27	200	10.00	4.54	35400	1770.00	802.72
¾	20	50	5.50	2.49	100	11.00	4.99	17700	1947.00	882.99

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

All Iron Unions

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
			lbs	kg		lbs	kg		lbs	kg
NPS	DN									
FIGURE J-3300: ALL IRON UNION CLASS 300 (PAGE 32)										
1/4	8	100	27.00	12.24	—	—	—	—	—	—
3/8	10	100	37.00	16.78	—	—	—	—	—	—
1/2	15	60	30.60	13.88	—	—	—	—	—	—
3/4	20	50	38.00	17.23	—	—	—	—	—	—
1	25	25	30.00	13.61	—	—	—	—	—	—
1 1/4	32	20	37.40	16.96	—	—	—	—	—	—
1 1/2	40	15	37.65	17.07	—	—	—	—	—	—
2	50	10	43.00	19.50	—	—	—	—	—	—
2 1/2	65	8	48.16	21.84	—	—	—	—	—	—
3	80	4	31.84	14.44	—	—	—	—	—	—

Malleable Iron Unions

Class 150; 250; 300

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
			lbs	kg		lbs	kg		lbs	kg
NPS	DN									
FIGURE 463: CLASS 150 UNION (PAGE 33)										
1/8	6	25	3.75	1.70	75	11.25	5.10	13275	1991.25	903.06
1/4	8	40	18.00	8.16	160	72.00	32.65	4320	1944.00	881.63
3/8	B 10	40	16.80	7.62	160	67.20	30.48	4320	1814.40	822.86
1/2	B G 15	40	17.60	7.98	160	70.40	31.93	4320	1900.80	862.04
3/4	B G 20	30	18.00	8.16	120	72.00	32.65	3240	1944.00	881.63
3/4 x 1/2	20 x 15	30	16.50	7.48	120	66.00	29.93	3240	1782.00	808.16
1	B G 25	15	13.65	6.19	60	54.60	24.76	1620	1474.20	668.57
1 1/4	B 32	8	11.60	5.26	32	46.40	21.04	864	1252.80	568.16
1 1/2	B G 40	15	25.35	11.50	30	50.70	22.99	810	1368.90	620.82
2	B G 50	12	29.52	13.39	24	59.04	26.78	648	1594.08	722.94
FIGURE 554: CLASS 250 UNION (PAGE 33)										
1/8	6	25	3.50	1.59	75	10.50	4.76	13275	1858.50	842.86
1/4	8	40	18.00	8.16	160	72.00	32.65	4320	1944.00	881.63
3/8	10	25	9.25	4.20	200	74.00	33.56	5400	1998.00	906.12
1/2	15	30	15.90	7.21	120	63.60	28.84	3240	1717.20	778.78
3/4	20	20	16.00	7.26	80	64.00	29.02	2160	1728.00	783.67
1	25	20	25.60	11.61	40	51.20	23.22	1080	1382.40	626.94
1 1/4	32	15	24.45	11.09	30	48.90	22.18	810	1320.30	598.78
1 1/2	40	15	30.90	14.01	30	61.80	28.03	810	1668.60	756.73
2	50	9	31.32	14.20	9	31.32	14.20	540	1879.20	852.24
FIGURE 459: CLASS 300 UNION (PAGE 33)										
1/8	6	25	3.50	1.59	75	10.50	4.76	13275	1858.50	842.86
1/4	8	40	18.00	8.16	160	72.00	32.65	4320	1944.00	881.63
3/8	10	25	10.75	4.88	200	86.00	39.00	5400	2322.00	1053.06
1/2	15	15	7.95	3.61	120	63.60	28.84	3240	1717.20	778.78
3/4	B 20	20	16.00	7.26	80	64.00	29.02	2160	1728.00	783.67
1	B 25	10	12.80	5.80	40	51.20	23.22	1080	1382.40	626.94
1 1/4	32	20	32.60	14.78	40	65.20	29.57	1080	1760.40	798.37
1 1/2	40	12	25.56	11.59	24	51.12	23.18	648	1380.24	625.96
2	50	9	31.14	14.12	18	62.28	28.24	486	1681.56	762.61

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Malleable Iron Unions

Class 150; 250; 300

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 832: DART UNION BRONZE TO BRONZE SEAT UNION (PAGE 34)										
3/8	10	20	8.20	3.72	160	65.60	29.75	4320	1771.20	803.27
1/2	15	15	8.70	3.95	120	69.60	31.56	3240	1879.20	852.24
3/4	20	30	24.60	11.16	60	49.20	22.31	1620	1328.40	602.45
1	25	10	13.10	5.94	40	52.40	23.76	1080	1414.80	641.63
1 1/4	32	12	22.80	10.34	24	45.60	20.68	648	1231.20	558.37
1 1/2	40	12	27.84	12.63	24	55.68	25.25	648	1503.36	681.80
2	50	7	28.00	12.70	14	56.00	25.40	378	1512.00	685.71

Malleable Hex and Face Bushing

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 383: HEX BUSHING (PAGE 35)										
3/4 x 1/8	10 x 6	40	4.80	2.18	80	9.60	4.35	14160	1699.20	770.61
3/4 x 1/4	10 x 8	25	3.50	1.59	75	10.50	4.76	13275	1858.50	842.86
3/4 x 3/8	10 x 10	25	2.75	1.25	75	8.25	3.74	13275	1460.25	662.24
3/4 x 1/2	10 x 15	25	2.25	1.02	75	6.75	3.06	13275	1194.75	541.84
1 x 1/8	25 x 6	25	6.00	2.72	50	12.00	5.44	8850	2124.00	963.27
1 x 1/4	25 x 8	25	4.50	2.04	50	9.00	4.08	8850	1593.00	722.45
1 x 3/8	25 x 10	25	4.50	2.04	50	9.00	4.08	8850	1593.00	722.45
1 x 1/2	25 x 15	50	10.00	4.54	200	40.00	18.14	5400	1080.00	489.80
1 x 3/4	25 x 20	50	8.00	3.63	200	32.00	14.51	5400	864.00	391.84
1 1/4 x 1/4	32 x 8	20	6.60	2.99	160	52.80	23.95	4320	1425.60	646.53
1 1/4 x 3/8	32 x 10	25	6.75	3.06	200	54.00	24.49	5400	1458.00	661.22
1 1/4 x 1/2	32 x 15	35	11.90	5.40	140	47.60	21.59	3780	1285.20	582.86
1 1/4 x 3/4	32 x 20	35	13.65	6.19	140	54.60	24.76	3780	1474.20	668.57
1 1/4 x 1	32 x 25	50	15.00	6.80	200	60.00	27.21	5400	1620.00	734.69
1 1/2 x 1 1/4	40 x 32	30	9.00	4.08	120	36.00	16.33	3240	972.00	440.82
2 x 1 1/2	50 x 40	20	12.80	5.80	80	51.20	23.22	2160	1382.40	626.94
2 1/2 x 2	65 x 50	10	10.20	4.63	40	40.80	18.50	1080	1101.60	499.59
FIGURE 385: FACE BUSHING (PAGE 35)										
3/4 x 3/8	20 x 10	100	8.00	3.63	800	64.00	29.02	21600	1728.00	783.67
3/4 x 1/2	20 x 15	100	6.00	2.72	800	48.00	21.77	21600	1296.00	587.76
1 x 1/2	25 x 15	50	8.00	3.63	400	64.00	29.02	10800	1728.00	783.67
1 x 3/4	25 x 20	50	5.00	2.27	400	40.00	18.14	10800	1080.00	489.80
1 1/4 x 1/2	32 x 15	30	9.00	4.08	240	72.00	32.65	6480	1944.00	881.63
1 1/4 x 3/4	32 x 20	30	8.10	3.67	240	64.80	29.39	6480	1749.60	793.47
1 1/4 x 1	32 x 25	35	6.65	3.02	280	53.20	24.13	7560	1436.40	651.43
1 1/2 x 1/2	40 x 15	20	8.00	3.63	160	64.00	29.02	4320	1728.00	783.67
1 1/2 x 3/4	40 x 20	20	7.80	3.54	160	62.40	28.30	4320	1684.80	764.08
1 1/2 x 1	40 x 25	25	8.25	3.74	200	66.00	29.93	5400	1782.00	808.16
1 1/2 x 1 1/4	40 x 32	50	8.00	3.63	200	32.00	14.51	5400	864.00	391.84
2 x 1	50 x 25	25	16.25	7.37	100	65.00	29.48	2700	1755.00	795.92
2 x 1 1/4	50 x 32	25	13.25	6.01	100	53.00	24.04	2700	1431.00	648.98
2 x 1 1/2	50 x 40	30	12.00	5.44	120	48.00	21.77	3240	1296.00	587.76
2 1/2 x 1 1/4	65 x 32	15	16.50	7.48	60	66.00	29.93	1620	1782.00	808.16
2 1/2 x 1 1/2	65 x 40	15	13.95	6.33	60	55.80	25.31	1620	1506.60	683.27
2 1/2 x 2	65 x 50	15	6.00	2.72	60	24.00	10.88	1620	648.00	293.88
3 x 2 1/2	80 x 65	20	19.80	8.98	40	39.60	17.96	1080	1069.20	484.90

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Cast Iron Threaded Fittings

Class 125 (Standard)

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 351: 90° ELBOW (PAGE 38)										
¼	8	80	12.80	5.80	160	25.60	11.61	7680	1228.80	557.28
⅜	10	40	10.00	4.54	80	20.00	9.07	3840	960.00	435.37
½	15	150	60.00	27.21	—	—	—	5850	2340.00	1061.22
¾	B 20	100	60.00	27.21	—	—	—	3900	2340.00	1061.22
1	B 25	45	41.40	18.78	—	—	—	1755	1614.60	732.24
1¼	B 32	25	36.00	16.33	—	—	—	975	1404.00	636.73
1½	B 40	15	29.25	13.27	—	—	—	585	1140.75	517.35
2	B 50	20	62.60	28.39	—	—	—	400	1252.00	567.80
2½	65	—	—	—	—	—	—	400	1976.00	896.15
4	100	—	—	—	—	—	—	200	2434.00	1103.85
FIGURE 356: 45° ELBOW (PAGE 39)										
½	15	150	55.50	25.17	—	—	—	5850	2164.50	981.63
¾	20	100	55.00	24.94	—	—	—	3900	2145.00	972.79
1	25	60	49.80	22.59	—	—	—	2340	1942.20	880.82
1¼	32	35	46.55	21.11	35	46.55	21.11	1365	1815.45	823.33
1½	40	25	44.75	20.29	—	—	—	975	1745.25	791.50
2	50	20	57.80	26.21	—	—	—	400	1156.00	524.26
2½	65	10	42.90	19.46	—	—	—	390	1673.10	758.78
FIGURE 352: 90° ELBOW, REDUCING (PAGE 40)										
¾ x ½	20 x 15	120	61.20	27.76	—	—	—	4680	2386.80	1082.45
1 x ½	B 25 x 15	70	46.90	21.27	—	—	—	2730	1829.10	829.52
1 x ¾	B 25 x 20	70	53.20	24.13	—	—	—	2730	2074.80	940.95
1¼ x ½	32 x 15	55	58.85	26.69	—	—	—	2145	2295.15	1040.88
1¼ x ¾	32 x 20	50	51.00	23.13	—	—	—	1950	1989.00	902.04
1¼ x 1	B 32 x 25	40	48.40	21.95	—	—	—	1560	1887.60	856.05
1½ x ½	40 x 15	—	—	—	—	—	—	975	1491.75	676.53
1½ x ¾	40 x 20	—	—	—	—	—	—	975	1511.25	685.37
1½ x 1	B 40 x 25	30	43.20	19.59	—	—	—	1170	1684.80	764.08
1½ x 1¼	40 x 32	25	43.50	19.73	—	—	—	975	1696.50	769.39
2 x ½	50 x 15	15	33.30	15.10	—	—	—	585	1298.70	588.98
2 x ¾	50 x 20	15	33.00	14.97	—	—	—	585	1287.00	583.67
2 x 1	50 x 25	15	31.20	14.15	—	—	—	585	1216.80	551.84
2 x 1¼	50 x 32	25	58.25	26.42	—	—	—	500	1165.00	528.34
2 x 1½	50 x 40	25	64.75	29.37	—	—	—	500	1295.00	587.30
FIGURE 358: TEE (PAGE 41)										
½	15	100	56.00	25.40	—	—	—	3900	2184.00	990.48
¾	20	60	50.40	22.86	—	—	—	2340	1965.60	891.43
1	B 25	30	37.50	17.01	—	—	—	1170	1462.50	663.27
1¼	B 32	20	40.60	18.41	—	—	—	780	1583.40	718.10
1½	40	20	54.00	24.49	—	—	—	400	1080.00	489.80
2	B 50	10	42.30	19.18	—	—	—	200	846.00	383.67

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Cast Iron Threaded Fittings Class 125 (Standard)

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 359: TEE REDUCING (PAGE 41–45)										
¾ x ¾ x ½	20 x 20 x 15	70	53.20	24.13	—	—	—	2730	2074.80	940.95
1 x ½ x 1	 25 x 15 x 25	45	48.60	22.04	—	—	—	1755	1895.40	859.59
1 x ¾ x ¾	25 x 20 x 20	50	50.00	22.68	—	—	—	1950	1950.00	884.35
1 x ¾ x 1	25 x 20 x 25	45	50.85	23.06	—	—	—	900	1017.00	461.22
1 x 1 x ½	 25 x 25 x 15	50	50.50	22.90	—	—	—	1950	1969.50	893.20
1 x 1 x ¾	25 x 25 x 20	45	49.95	22.65	—	—	—	900	999.00	453.06
1 x 1 x 1¼	25 x 25 x 32	20	29.80	13.51	—	—	—	780	1162.20	527.07
1¼ x ½ x 1¼	32 x 15 x 32	25	41.00	18.59	—	—	—	975	1599.00	725.17
1¼ x ¾ x 1¼	32 x 20 x 32	25	43.25	19.61	—	—	—	975	1686.75	764.97
1¼ x 1 x ½	 32 x 25 x 15	35	44.45	20.16	—	—	—	1365	1733.55	786.19
1¼ x 1 x ¾	32 x 25 x 20	30	40.80	18.50	—	—	—	600	816.00	370.07
1¼ x 1 x 1	 32 x 25 x 25	20	30.60	13.88	—	—	—	780	1193.40	541.22
1¼ x 1 x 1¼	32 x 25 x 32	20	35.80	16.24	—	—	—	780	1396.20	633.20
1¼ x 1 x 1½	32 x 25 x 40	25	51.75	23.47	—	—	—	500	1035.00	469.39
1¼ x 1¼ x ½	 32 x 32 x 15	30	44.10	20.00	—	—	—	1170	1719.90	780.00
1¼ x 1¼ x ¾	32 x 32 x 20	25	39.25	17.80	—	—	—	500	785.00	356.01
1¼ x 1¼ x 1	 32 x 32 x 25	20	34.60	15.69	—	—	—	780	1349.40	611.97
1¼ x 1¼ x 1½	32 x 32 x 40	20	45.80	20.77	—	—	—	780	1786.20	810.07
1½ x ½ x 1½	40 x 15 x 40	20	42.80	19.41	—	—	—	400	856.00	388.21
1½ x 1 x ¾	40 x 25 x 20	25	42.50	19.27	—	—	—	975	1657.50	751.70
1½ x 1 x 1	40 x 25 x 25	20	34.40	15.60	—	—	—	780	1341.60	608.44
1½ x 1 x 1¼	40 x 25 x 32	25	52.00	23.58	—	—	—	500	1040.00	471.66
1½ x 1 x 1½	40 x 25 x 40	25	57.25	25.96	—	—	—	500	1145.00	519.27
1½ x 1¼ x ½	 40 x 32 x 15	25	41.75	18.93	—	—	—	975	1628.25	738.44
1½ x 1¼ x ¾	40 x 32 x 20	20	35.80	16.24	—	—	—	400	716.00	324.72
1½ x 1¼ x 1	 40 x 32 x 25	20	39.40	17.87	—	—	—	780	1536.60	696.87
1½ x 1¼ x 1¼	40 x 32 x 32	20	45.60	20.68	—	—	—	400	912.00	413.61
1½ x 1¼ x 1½	40 x 32 x 40	10	25.00	11.34	—	—	—	390	975.00	442.18
1½ x 1¼ x 2	40 x 32 x 50	15	46.05	20.88	—	—	—	300	921.00	417.69
1½ x 1½ x ½	 40 x 40 x 15	20	36.80	16.69	—	—	—	780	1435.20	650.88
1½ x 1½ x ¾	 40 x 40 x 20	20	39.00	17.69	—	—	—	780	1521.00	689.80
1½ x 1½ x 1	 40 x 40 x 25	30	63.90	28.98	—	—	—	600	1278.00	579.59
1½ x 1½ x 1¼	40 x 40 x 32	25	61.00	27.66	—	—	—	500	1220.00	553.29
1½ x 1½ x 2	40 x 40 x 50	10	32.30	14.65	—	—	—	390	1259.70	571.29
2 x ½ x 2	50 x 15 x 50	10	33.00	14.97	—	—	—	200	660.00	299.32
2 x ¾ x 2	50 x 20 x 50	15	49.65	22.52	—	—	—	300	993.00	450.34
2 x 1 x 1	50 x 25 x 25	15	40.50	18.37	—	—	—	—	—	—
2 x 1 x 2	50 x 25 x 50	15	51.90	23.54	—	—	—	300	1038.00	470.75
2 x 1¼ x 1	50 x 32 x 25	15	40.95	18.57	—	—	—	300	819.00	371.43
2 x 1¼ x 1¼	50 x 32 x 32	15	43.50	19.73	—	—	—	300	870.00	394.56
2 x 1¼ x 2	50 x 32 x 50	15	55.65	25.24	—	—	—	300	1113.00	504.76
2 x 1½ x ½	50 x 40 x 15	25	58.50	26.53	—	—	—	500	1170.00	530.61
2 x 1½ x ¾	50 x 40 x 20	20	49.20	22.31	—	—	—	400	984.00	446.26
2 x 1½ x 1	50 x 40 x 25	20	53.20	24.13	—	—	—	400	1064.00	482.54
2 x 1½ x 1¼	50 x 40 x 32	15	44.70	20.27	—	—	—	300	894.00	405.44
2 x 1½ x 1½	50 x 40 x 40	15	48.60	22.04	—	—	—	300	972.00	440.82
2 x 1½ x 2	50 x 40 x 50	15	55.50	25.17	—	—	—	300	1110.00	503.40
2 x 2 x ½	50 x 50 x 15	20	54.80	24.85	—	—	—	400	1096.00	497.05
2 x 2 x ¾	50 x 50 x 20	20	57.20	25.94	—	—	—	400	1144.00	518.82
2 x 2 x 1	 50 x 50 x 25	15	45.75	20.75	—	—	—	300	915.00	414.97
2 x 2 x 1¼	50 x 50 x 32	15	50.70	22.99	—	—	—	300	1014.00	459.86
2 x 2 x 1½	50 x 50 x 40	15	53.85	24.42	—	—	—	300	1077.00	488.44
2 x 2 x 2½	50 x 50 x 65	—	—	—	—	—	—	100	517.00	234.47

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Cast Iron Threaded Fittings

Class 125 (Standard)

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 366: SCREWED HEX COUPLING (PAGE 47)										
1	25	60	49.20	22.31	—	—	—	2340	1918.80	870.20
FIGURE 367: CONCENTRIC REDUCER (PAGE 48)										
1 x ½ (Hex)	B 25 x 15	80	43.20	19.59	—	—	—	3120	1684.80	764.08
1 x ¾ (Hex)	B 25 x 20	70	44.10	20.00	—	—	—	2730	1719.90	780.00
1¼ x ¾	32 x 20	—	—	—	—	—	—	2000	1800.00	816.33
2 x 1	50 x 25	—	—	—	—	—	—	390	713.70	323.67
FIGURE 383: HEX BUSHING (PAGE 50–51)										
1½ x ¼	40 x 8	25	11.75	5.33	50	23.50	10.66	2400	1128.00	511.56
1½ x ⅝	40 x 10	25	11.75	5.33	50	23.50	10.66	2400	1128.00	511.56
1½ x ½	40 x 15	25	10.50	4.76	50	21.00	9.52	2400	1008.00	457.14
1½ x ¾	B 40 x 20	25	11.75	5.33	50	23.50	10.66	2400	1128.00	511.56
1½ x 1	B 40 x 25	25	12.50	5.67	50	25.00	11.34	2400	1200.00	544.22
2 x ¼	50 x 8	15	11.25	5.10	30	22.50	10.20	1440	1080.00	489.80
2 x ⅝	50 x 10	15	11.25	5.10	30	22.50	10.20	1440	1080.00	489.80
2 x ½	50 x 15	15	10.50	4.76	30	21.00	9.52	1440	1008.00	457.14
2 x ¾	50 x 20	15	10.65	4.83	30	21.30	9.66	1440	1022.40	463.67
2 x 1	B 50 x 25	15	10.95	4.97	30	21.90	9.93	1440	1051.20	476.73
2 x 1¼	B 50 x 32	15	12.15	5.51	30	24.30	11.02	1440	1166.40	528.98
2½ x 1¼	65 x 32	20	24.80	11.25	—	—	—	400	496.00	224.94
3 x 2	80 x 50	—	—	—	—	—	—	200	380.00	172.34
4 x 2	100 x 50	20	62.20	28.21	—	—	—	400	1244.00	564.17
FIGURE 387: SQUARE HEAD PLUGS, CORED (PAGE 52)										
¾	20	120	15.60	7.07	240	31.20	14.15	11520	1497.60	679.18
1	B G 25	60	15.00	6.80	120	30.00	13.61	5760	1440.00	653.06
1¼	B G 32	30	11.70	5.31	60	23.40	10.61	2880	1123.20	509.39
1½	B 40	25	12.50	5.67	50	25.00	11.34	2400	1200.00	544.22
2	B G 50	15	12.30	5.58	30	24.60	11.16	1440	1180.80	535.51
2½	65	10	13.20	5.99	20	26.40	11.97	960	1267.20	574.69
3	80	—	—	—	—	—	—	600	1122.00	508.84
4	100	—	—	—	—	—	—	100	400.00	181.41
FIGURE 388: SQUARE HEAD PLUGS, SOLID (PAGE 52)										
½	15	150	15.00	6.80	300	30.00	13.61	14400	1440.00	653.06
¾	20	120	20.40	9.25	240	40.80	18.50	11520	1958.40	888.16
1	B 25	60	19.20	8.71	120	38.40	17.41	5760	1843.20	835.92
1¼	32	30	15.90	7.21	60	31.80	14.42	2880	1526.40	692.24
1½	40	25	19.00	8.62	50	38.00	17.23	2400	1824.00	827.21
2	50	15	18.45	8.37	30	36.90	16.73	1440	1771.20	803.27
2½	65	10	20.00	9.07	20	40.00	18.14	200	400.00	181.41
FIGURE 390: COUNTER SUNK PLUGS (PAGE 52)										
1	25	60	12.00	5.44	120	24.00	10.88	5760	1152.00	522.45
1¼	32	30	9.60	4.35	60	19.20	8.71	2880	921.60	417.96
1½	40	25	11.75	5.33	50	23.50	10.66	2400	1128.00	511.56
2	50	15	12.60	5.71	30	25.20	11.43	1440	1209.60	548.57
2½	65	10	14.00	6.35	—	—	—	200	280.00	126.98

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Cast Iron Drainage Fittings

Size		Cartons		Master Container		Pallets		
		No. Pcs.	Weight	No. Pcs.	Weight	No. Pcs.	Weight	
NPS	DN		lbs		kg		lbs	kg
FIGURE 701: 90° SHORT TURN ELBOW (PAGE 56)								
1½	40	—	—	—	—	780	1489.80	675.65
2	50	—	—	—	—	400	1216.00	551.47
FIGURE 701R: 90° REDUCING SHORT TURN ELBOW (PAGE 56)								
1½ x 1¼	40 x 32	—	—	—	—	975	1647.75	747.28
FIGURE 702: 90° LONG TURN ELBOW (PAGE 56)								
1½	40	—	—	—	—	400	896.00	406.35
2	50	—	—	—	—	300	1083.00	491.16
4	100	20	328.00	148.75	—	—	—	—
FIGURE 703: 60° SHORT TURN ELBOW (PAGE 56)								
1½	40	—	—	—	—	780	1825.20	827.76
FIGURE 705: 45° SHORT TURN ELBOW (PAGE 57)								
1½	40	—	—	—	—	975	1667.25	756.12
2	50	—	—	—	—	400	1116.00	506.12
FIGURE 707: 22 1/2° ELBOW (PAGE 57)								
1½	40	—	—	—	—	975	1608.75	729.59
FIGURE 726: 90° SHORT TURN Y-BRANCH TEE PATTERN (PAGE 60)								
1½	40	—	—	—	—	300	927.00	420.41
2	50	—	—	—	—	200	1016.00	460.77
FIGURE 727: 90° REDUCING SHORT TURN Y-BRANCH TEE PATTERN (PAGE 60)								
2 x 2 x 1½	50 x 50 x 40	—	—	—	—	200	832.00	377.32
FIGURE 734: 45° Y-BRANCH (PAGE 61)								
1½	40	—	—	—	—	300	1209.00	548.30
FIGURE 754: BATH P-TRAP (PAGE 62)								
1½	40	—	—	—	—	200	774.00	351.02

Cast Iron Flanged Fittings

Class 125 (Standard)

Size		Cartons		Master Container		Pallets		
		No. Pcs.	Weight	No. Pcs.	Weight	No. Pcs.	Weight	
NPS	DN		lbs		kg		lbs	kg
FIGURE 801: 90° FLANGED ELBOW (PAGE 64)								
3	80	—	—	—	—	70	1680.00	761.90
4	100	—	—	—	—	40	1640.00	743.76
6	150	—	—	—	—	20	1360.00	616.78
FIGURE 811: FLANGED TEE (PAGE 67)								
4	100	—	—	—	—	27	1728.00	783.67
6	150	—	—	—	—	13	1365.00	619.05
8	200	—	—	—	—	7	1155.00	523.81

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Iron Flanges

Class 125 (Standard)

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 1011: COMPANION FLANGE (PAGE 73)										
2 x 6	50 x 152	—	—	—	—	—	—	700	2800.00	1269.84
3 x 7½	80 x 191	—	—	—	—	—	—	400	3052.00	1384.13
4 x 9	100 x 229	—	—	—	—	—	—	250	2937.50	1332.20

High Hub Flanges for C.I. Pipe

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 1010T: CAST IRON FLANGES FOR CAST IRON PIPE (PAGE 76)										
4	100	10	130.00	58.96	—	—	—	—	—	—
6	150	10	172.00	78.00	—	—	—	—	—	—
8	200	10	290.00	131.52	—	—	—	—	—	—

Steel Pipe Bushings, Plugs & Caps

Merchant Steel

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
HEX BUSHINGS (PAGE 81)										
¼ x ⅝	8 x 6	100	2.00	0.91	—	—	—	24000	480.00	217.69
⅜ x ⅝	10 x 6	100	5.00	2.27	—	—	—	32400	1620.00	734.69
⅜ x ¾	10 x 8	100	3.00	1.36	—	—	—	32400	972.00	440.82
½ x ⅝	15 x 6	100	11.00	4.99	—	—	—	20000	2200.00	997.73
½ x ¾	15 x 8	100	5.00	2.27	—	—	—	24000	1200.00	544.22
½ x ⅜	15 x 10	100	6.00	2.72	—	—	—	24000	1440.00	653.06
¾ x ⅝	20 x 6	100	21.00	9.52	—	—	—	12000	2520.00	1142.86
¾ x ¾	20 x 8	100	18.00	8.16	—	—	—	12000	2160.00	979.59
¾ x ⅜	20 x 10	100	15.00	6.80	—	—	—	15000	2250.00	1020.41
¾ x ½	20 x 15	100	10.00	4.54	—	—	—	18000	1800.00	816.33
COUNTERSUNK PLUGS: SQUARE SOCKET (PAGE 81)										
⅝	6	100	2.00	0.91	—	—	—	—	—	—
¾	8	100	4.00	1.81	—	—	—	10400	416.00	188.66
⅝	10	100	6.00	2.72	—	—	—	10400	624.00	282.99
½	15	100	12.00	5.44	—	—	—	10400	1248.00	565.99
¾	20	50	9.50	4.31	—	—	—	5200	988.00	448.07
1	25	75	16.50	7.48	—	—	—	—	—	—
1¼	32	25	9.25	4.20	—	—	—	—	—	—
1½	40	25	11.75	5.33	—	—	—	—	—	—
2	50	20	16.80	7.62	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Steel Pipe Bushings, Plugs & Caps

Merchant Steel

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
COUNTERSUNK PLUGS: HEX SOCKET (PAGE 81)										
1/8	6	100	2.00	0.91	—	—	—	10400	208.00	94.33
1/4	8	100	4.00	1.81	—	—	—	10400	416.00	188.66
3/8	10	100	6.00	2.72	—	—	—	10400	624.00	282.99
1/2	15	100	12.00	5.44	—	—	—	10400	1248.00	565.99
3/4	20	100	19.00	8.62	—	—	—	5200	988.00	448.07
1	25	75	15.75	7.14	150	31.50	14.29	—	—	—
1 1/4	32	25	9.50	4.31	—	—	—	—	—	—
1 1/2	40	25	11.00	4.99	—	—	—	—	—	—
2	50	20	17.00	7.71	—	—	—	—	—	—
FLUSH BUSHINGS (PAGE 82)										
1/4 x 1/8	8 x 6	100	1.00	0.45	—	—	—	10400	104.00	47.17
3/8 x 1/8	10 x 6	100	3.00	1.36	—	—	—	10400	312.00	141.50
3/8 x 1/4	10 x 8	100	2.00	0.91	—	—	—	10400	208.00	94.33
1/2 x 1/4	15 x 8	100	5.00	2.27	—	—	—	10400	520.00	235.83
1/2 x 3/8	15 x 10	100	3.00	1.36	—	—	—	10400	312.00	141.50
CAPS (PAGE 82)										
1/8	6	100	2.00	0.91	—	—	—	32400	648.00	293.88
1/8	8	100	3.00	1.36	—	—	—	8000	240.00	108.84
3/8	10	100	6.00	2.72	—	—	—	20000	1200.00	544.22
1/2	15	100	11.00	4.99	—	—	—	12000	1320.00	598.64
3/4	20	100	14.00	6.35	—	—	—	5200	728.00	330.16

Steel Pipe Plugs & Hose Fittings

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
SOLID SQUARE HEAD PLUGS (PAGE 82)										
1/8	6	100	2.00	0.91	—	—	—	10400	208.00	94.33
1/4	8	100	4.00	1.81	—	—	—	10400	416.00	188.66
3/8	10	100	6.00	2.72	—	—	—	10400	624.00	282.99
1/2	15	100	12.00	5.44	—	—	—	10400	1248.00	565.99
3/4	20	50	9.50	4.31	—	—	—	5200	988.00	448.07
1	25	50	17.00	7.71	—	—	—	—	—	—
1 1/4	32	25	13.75	6.24	—	—	—	—	—	—
1 1/2	40	25	20.50	9.30	—	—	—	—	—	—
2	50	10	13.50	6.12	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Steel Pipe Couplings

Merchant Couplings, Standard

Size		Cartons				Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight		
NPS	DN		lbs	kg		lbs	kg		lbs	kg	
FIGURE 336: FULL, STRAIGHT TAPPED (PAGE 90)											
1/8	B G	6	100	3.00	1.36	—	—	—	36000	1080.00	489.80
1/4	B G	8	100	7.00	3.17	—	—	—	21000	1470.00	666.67
3/8	B	10	100	10.00	4.54	—	—	—	16800	1680.00	761.90
1/2	B G	15	100	18.00	8.16	—	—	—	10000	1800.00	816.33
3/4	B G	20	50	13.00	5.90	—	—	—	5000	1300.00	589.57
1	B G	25	30	12.60	5.71	—	—	—	3000	1260.00	571.43
1 1/4	B	32	25	12.50	5.67	—	—	—	2500	1250.00	566.89
1 1/2	B	40	25	16.75	7.60	—	—	—	1500	1005.00	455.78
2	B	50	20	20.60	9.34	—	—	—	1200	1236.00	560.54
FIGURE 336: FULL, TAPER TAPERED (PAGE 90)											
1/8	B G	6	100	3.00	1.36	—	—	—	—	—	—
1/4	B G	8	100	7.00	3.17	—	—	—	—	—	—
3/8	B	10	100	10.00	4.54	—	—	—	—	—	—
1/2	B G	15	100	18.00	8.16	—	—	—	—	—	—
3/4	B G	20	50	13.00	5.90	—	—	—	—	—	—
1	B G	25	30	12.60	5.71	—	—	—	—	—	—
1 1/4	B	32	25	12.50	5.67	—	—	—	—	—	—
1 1/2	B	40	25	16.75	7.60	—	—	—	—	—	—
2	B	50	20	20.60	9.34	—	—	—	—	—	—
2 1/2		65	—	—	—	—	—	—	1080	2322.00	1053.06
3		80	—	—	—	—	—	—	680	2352.80	1067.03
4		100	—	—	—	—	—	—	392	1909.04	865.78
FIGURE 336: HALF, STRAIGHT TAPPED (PAGE 90)											
1/8		6	200	2.00	—,91	—	—	—	—	—	—
1/4	B	8	200	6.00	2.72	—	—	—	—	—	—
3/8		10	200	10.00	4.54	—	—	—	—	—	—
1/2	B	15	200	16.00	7.26	—	—	—	—	—	—
3/4	B	20	200	24.00	10.88	—	—	—	—	—	—
1		25	100	18.00	8.16	—	—	—	—	—	—
1 1/4		32	50	11.50	5.22	—	—	—	—	—	—
1 1/2		40	50	16.00	7.26	—	—	—	—	—	—
2		50	25	11.75	5.33	—	—	—	—	—	—
2 1/2		65	15	14.40	6.53	—	—	—	—	—	—
3		80	150	240.00	108.84	—	—	—	—	—	—
FIGURE 336: HALF, TAPER TAPPED (PAGE 90)											
1/8		6	100	1.00	—,45	—	—	—	—	—	—
1/4	B	8	100	3.00	1.36	—	—	—	—	—	—
3/8		10	100	5.00	2.27	—	—	—	—	—	—
1/2	B	15	100	8.00	3.63	—	—	—	—	—	—
3/4	B	20	100	12.00	5.44	—	—	—	—	—	—
1		25	100	18.00	8.16	—	—	—	—	—	—
1 1/4		32	50	11.50	5.22	—	—	—	—	—	—
1 1/2		40	50	16.00	7.26	—	—	—	—	—	—
2		50	25	11.75	5.33	—	—	—	—	—	—
2 1/2		65	15	14.40	6.53	—	—	—	—	—	—
3		80	150	240.00	108.84	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Steel Pipe Couplings

Merchant Couplings

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 337: EXTRA STRONG (XS), FULL (PAGE 91)										
1/8	6	100	4.00	1.81	—	—	—	—	—	—
1/4	8	100	10.00	4.54	—	—	—	—	—	—
3/8	10	100	15.00	6.80	—	—	—	—	—	—
1/2	15	100	27.00	12.24	—	—	—	—	—	—
3/4	20	50	19.50	8.84	—	—	—	—	—	—
1	25	25	20.50	9.30	—	—	—	—	—	—
1 1/4	32	25	27.00	12.24	—	—	—	—	—	—
1 1/2	40	20	19.60	8.89	—	—	—	—	—	—
2	B 50	15	29.25	13.27	—	—	—	—	—	—
FIGURE 337: EXTRA STRONG (XS), HALF (PAGE 91)										
1/8	6	200	4.00	1.81	—	—	—	—	—	—
1/4	8	200	10.00	4.54	—	—	—	—	—	—
3/8	10	200	14.00	6.35	—	—	—	—	—	—
1/2	15	200	26.00	11.79	—	—	—	—	—	—
3/4	20	100	19.00	8.62	—	—	—	—	—	—
1	25	50	21.00	9.52	—	—	—	—	—	—
1 1/4	32	50	29.00	13.15	—	—	—	—	—	—
1 1/2	40	50	25.00	11.34	—	—	—	—	—	—
2	50	30	32.10	14.56	—	—	—	—	—	—
FIGURE 346: STANDARD, RIGHT & LEFT (PAGE 92)										
1/8	6	100	3.00	1.36	—	—	—	—	—	—
1/4	8	100	7.00	3.17	—	—	—	—	—	—
3/8	10	100	9.00	4.08	—	—	—	—	—	—
1/2	15	100	17.00	7.71	—	—	—	—	—	—
3/4	20	50	13.00	5.90	—	—	—	—	—	—
1	25	30	12.00	5.44	—	—	—	—	—	—
1 1/4	32	25	12.00	5.44	—	—	—	—	—	—
1 1/2	40	25	16.75	7.60	—	—	—	—	—	—
2	50	20	21.00	9.52	—	—	—	—	—	—
FIGURE 347: EXTRA STRONG (XS), RIGHT & LEFT (PAGE 92)										
1/4	8	100	9.00	4.08	—	—	—	—	—	—
3/8	10	100	140.00	63.49	—	—	—	—	—	—
1/2	15	100	25.00	11.34	—	—	—	—	—	—
3/4	20	50	18.00	8.16	—	—	—	—	—	—
1 1/4	32	25	27.00	12.24	—	—	—	—	—	—
1 1/2	40	25	23.75	10.77	—	—	—	—	—	—
2	50	15	30.15	13.67	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Steel Pipe Couplings

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 348: API LINE PIPE COUPLINGS (PAGE 93)										
⅛	6	100	4.00	1.81	—	—	—	—	—	—
¼	8	100	10.00	4.54	—	—	—	—	—	—
⅜	10	100	13.00	5.90	—	—	—	—	—	—
½	15	100	24.00	10.88	—	—	—	—	—	—
¾	20	50	17.50	7.94	—	—	—	—	—	—
1	25	25	13.00	5.90	—	—	—	—	—	—
1¼	32	25	25.00	11.34	—	—	—	—	—	—
1½	40	20	17.60	7.98	—	—	—	—	—	—
2	50	15	27.45	12.45	—	—	—	—	—	—
FIGURE 379: SHALLOW WELL COUPLINGS (PAGE 94)										
1¼	32	25	25.75	11.68	—	—	—	—	—	—
1½	40	20	18.00	8.16	—	—	—	—	—	—
2	50	15	27.90	12.65	—	—	—	—	—	—
FIGURE 380: WATER WELL REAMED & DRIFTED COUPLINGS (PAGE 94)										
1¼	32	25	15.00	6.80	—	—	—	—	—	—
1½	40	25	21.00	9.52	—	—	—	—	—	—
2	50	15	23.70	10.75	—	—	—	—	—	—
FIGURE 381: #9 DRIVE COUPLINGS (PAGE 94)										
1¼	32	25	25.00	11.34	—	—	—	—	—	—
1½	40	25	21.00	9.52	—	—	—	—	—	—
2	50	15	32.10	14.56	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Forged Steel Fittings

Class 2000 Threaded

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
			lbs	kg		lbs	kg		lbs	kg
NPS	DN									
FIGURE 2101: 90° ELBOWS (PAGE 96)										
1/4	8	25	4.50	2.04	—	—	—	9600	1728.00	783.67
3/8	10	25	7.00	3.17	—	—	—	9600	2688.00	1219.05
1/2	B 15	25	13.75	6.24	—	—	—	4500	2475.00	1122.45
3/4	20	25	18.00	8.16	—	—	—	2500	1800.00	816.33
1	B 25	25	30.50	13.83	—	—	—	1500	1830.00	829.93
1 1/4	32	10	16.50	7.48	—	—	—	800	1320.00	598.64
1 1/2	40	5	10.60	4.81	—	—	—	500	1060.00	480.73
2	B 50	5	18.90	8.57	—	—	—	420	1587.60	720.00
2 1/2	65	—	—	—	—	—	—	180	1170.00	530.61
3	80	—	—	—	—	—	—	128	1420.80	644.35
4	100	—	—	—	—	—	—	48	1070.40	485.44
FIGURE 2102: 45° ELBOWS (PAGE 96)										
1/4	8	25	4.00	1.81	—	—	—	9600	1536.00	696.60
3/8	10	25	6.25	2.83	—	—	—	9600	2400.00	1088.44
1/2	15	25	12.00	5.44	—	—	—	4500	2160.00	979.59
3/4	20	25	14.25	6.46	—	—	—	2500	1425.00	646.26
1	25	25	22.00	9.98	—	—	—	2100	1848.00	838.10
1 1/4	32	10	13.20	5.99	—	—	—	500	660.00	299.32
1 1/2	40	5	8.10	3.67	—	—	—	900	1458.00	661.22
2	50	5	14.15	6.42	—	—	—	420	1188.60	539.05
2 1/2	65	—	—	—	—	—	—	180	1386.00	628.57
3	80	—	—	—	—	—	—	128	1536.00	696.60
FIGURE 2103: TEES (PAGE 97)										
1/4	8	25	6.25	2.83	—	—	—	4500	1125.00	510.20
3/8	10	25	9.25	4.20	—	—	—	4500	1665.00	755.10
1/2	B 15	25	15.50	7.03	—	—	—	2500	1550.00	702.95
3/4	20	25	10.75	4.88	—	—	—	2000	860.00	390.02
1	B 25	25	33.25	15.08	—	—	—	1500	1995.00	904.76
1 1/4	32	10	21.00	9.52	—	—	—	840	1764.00	800.00
1 1/2	40	5	14.00	6.35	—	—	—	400	1120.00	507.94
2	B 50	5	22.50	10.20	—	—	—	300	1350.00	612.24
2 1/2	65	—	—	—	—	—	—	192	1747.20	792.38
3	80	—	—	—	—	—	—	128	1728.00	783.67
4	100	—	—	—	—	—	—	48	1536.00	696.60
FIGURE 2104: CROSSES (PAGE 97)										
1/4	8	25	12.50	5.67	—	—	—	9600	4800.00	2176.87
3/8	10	25	10.00	4.54	—	—	—	4500	1800.00	816.33
1/2	15	25	21.25	9.64	—	—	—	2500	2125.00	963.72
3/4	20	10	11.00	4.99	—	—	—	1000	1100.00	498.87
1	25	10	17.00	7.71	—	—	—	1000	1700.00	770.98
1 1/4	32	10	24.00	10.88	—	—	—	500	1200.00	544.22
1 1/2	40	5	16.00	7.26	—	—	—	400	1280.00	580.50
2	50	5	26.00	11.79	—	—	—	420	2184.00	990.48

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Forged Steel Fittings

Class 3000 Threaded

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 2111: 90° ELBOWS (PAGE 98)										
1/8	6	25	5.75	2.61	—	—	—	9600	2208.00	1001.36
1/4	8	25	8.75	3.97	—	—	—	9600	3360.00	1523.81
3/8	10	25	16.50	7.48	—	—	—	4500	2970.00	1346.94
1/2	15	25	23.25	10.54	—	—	—	2000	1860.00	843.54
3/4	20	10	14.80	6.71	—	—	—	1200	1776.00	805.44
1	B	25	23.00	10.43	—	—	—	800	1840.00	834.47
1 1/4	32	5	13.40	6.08	—	—	—	500	1340.00	607.71
1 1/2	40	5	26.50	12.02	—	—	—	360	1908.00	865.31
2	50	5	29.25	13.27	—	—	—	360	2106.00	955.10
2 1/2	65	—	—	—	—	—	—	180	1800.00	816.33
3	80	—	—	—	—	—	—	128	2201.60	998.46
4	100	—	—	—	—	—	—	48	1406.40	637.82
FIGURE 2112: 45° ELBOWS (PAGE 98)										
1/8	6	25	4.50	2.04	—	—	—	9600	1728.00	783.67
1/4	8	25	6.25	2.83	—	—	—	9600	2400.00	1088.44
3/8	10	25	13.25	6.01	—	—	—	4500	2385.00	1081.63
1/2	15	25	19.50	8.84	—	—	—	2000	1560.00	707.48
3/4	20	10	12.00	5.44	—	—	—	4500	5400.00	2448.98
1	25	10	19.00	8.62	—	—	—	1000	1900.00	861.68
1 1/4	32	10	23.00	10.43	—	—	—	900	2070.00	938.78
1 1/2	40	5	20.80	9.43	—	—	—	400	1664.00	754.65
2	50	5	25.60	11.61	—	—	—	420	2150.40	975.24
2 1/2	65	—	—	—	—	—	—	180	1386.00	628.57
3	80	—	—	—	—	—	—	128	1536.00	696.60
4	100	—	—	—	—	—	—	48	945.60	428.84
FIGURE 2114: TEES (PAGE 98)										
1/8	6	25	7.75	3.51	—	—	—	4800	1488.00	674.83
1/4	8	25	10.50	4.76	—	—	—	4500	1890.00	857.14
3/8	10	25	23.25	10.54	—	—	—	2500	2325.00	1054.42
1/2	15	25	30.00	13.61	—	—	—	2000	2400.00	1088.44
3/4	20	10	18.40	8.34	—	—	—	800	1472.00	667.57
1	25	10	30.50	13.83	—	—	—	720	2196.00	995.92
1 1/4	32	5	18.10	8.21	—	—	—	500	1810.00	820.86
1 1/2	40	5	33.25	15.08	—	—	—	300	1995.00	904.76
2	50	5	35.75	16.21	—	—	—	300	2145.00	972.79
2 1/2	65	—	—	—	—	—	—	192	2630.40	1192.93
3	80	—	—	—	—	—	—	128	2688.00	1219.05
4	100	—	—	—	—	—	—	48	1824.00	827.21
FIGURE 2115: CROSSES (PAGE 99)										
1/2	15	25	35.00	15.87	—	—	—	1500	2100.00	952.38
3/4	20	10	21.00	9.52	—	—	—	1000	2100.00	952.38
1	25	5	17.50	7.94	—	—	—	500	1750.00	793.65
1 1/4	32	5	21.50	9.75	—	—	—	400	1720.00	780.05
1 1/2	40	5	41.00	18.59	—	—	—	300	2460.00	1115.65
2	50	5	42.00	19.05	—	—	—	300	2520.00	1142.86
2 1/2	65	—	—	—	—	—	—	—	—	—
3	80	—	—	—	—	—	—	—	—	—
4	100	—	—	—	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Forged Steel Fittings

Class 3000 Threaded

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
			lbs	kg		lbs	kg		lbs	kg
NPS	DN									
FIGURE 2113: 90° STREET ELBOWS (PAGE 99)										
1/4	8	25	5.75	2.61	—	—	—	9600	2208.00	1001.36
3/8	10	25	9.50	4.31	—	—	—	4500	1710.00	775.51
1/2	15	25	13.25	6.01	—	—	—	4500	2385.00	1081.63
3/4	20	25	22.00	9.98	—	—	—	2000	1760.00	798.19
1	25	10	14.00	6.35	—	—	—	1000	1400.00	634.92
1 1/4	32	5	12.00	5.44	—	—	—	900	2160.00	979.59
1 1/2	40	5	14.50	6.58	—	—	—	500	1450.00	657.60
2	50	5	25.00	11.34	—	—	—	300	1500.00	680.27
FIGURE 2117: COUPLINGS (PAGE 100)										
1/8	6	50	7.00	3.17	—	—	—	—	—	—
1/4	B 8	50	5.00	2.27	—	—	—	16200	1620.00	734.69
3/8	10	50	6.50	2.95	—	—	—	12000	1560.00	707.48
1/2	B 15	50	14.00	6.35	—	—	—	6000	1680.00	761.90
3/4	B 20	50	22.00	9.98	—	—	—	4000	1760.00	798.19
1	B 25	25	27.00	12.24	—	—	—	2000	2160.00	979.59
1 1/4	32	10	16.80	7.62	—	—	—	1200	2016.00	914.29
1 1/2	40	12	26.04	11.81	—	—	—	960	2083.20	944.76
2	B 50	10	32.00	14.51	—	—	—	480	1536.00	696.60
2 1/2	65	5	23.50	10.66	—	—	—	300	1410.00	639.46
3	80	—	—	—	—	—	—	200	1360.00	616.78
4	100	—	—	—	—	—	—	96	1180.80	535.51
FIGURE 2119: HALF COUPLINGS (PAGE 100)										
1/8	6	100	5.00	2.27	—	—	—	—	—	—
1/4	B 8	100	4.00	1.81	—	—	—	32400	1296.00	587.76
3/8	10	100	6.00	2.72	—	—	—	24000	1440.00	653.06
1/2	B 15	50	6.00	2.72	—	—	—	12000	1440.00	653.06
3/4	20	100	21.00	9.52	—	—	—	8000	1680.00	761.90
1	B 25	25	10.75	4.88	—	—	—	4500	1935.00	877.55
1 1/4	32	20	15.20	6.89	—	—	—	—	—	—
1 1/2	40	20	22.80	10.34	—	—	—	1600	1824.00	827.21
2	B 50	10	15.00	6.80	—	—	—	1200	1800.00	816.33
2 1/2	65	10	24.00	10.88	—	—	—	—	—	—
3	80	8	26.00	11.79	—	—	—	288	936.00	424.49
4	100	4	25.00	11.34	—	—	—	—	—	—
FIGURE 2120: PIPE CAPS (PAGE 101)										
1/8	6	100	7.00	3.17	—	—	—	—	—	—
1/4	8	100	8.00	3.63	—	—	—	—	—	—
3/8	10	50	5.50	2.49	—	—	—	—	—	—
1/2	15	20	4.60	2.09	—	—	—	—	—	—
3/4	20	20	8.00	3.63	—	—	—	—	—	—
1	25	25	19.75	8.96	—	—	—	2500	1975.00	895.69
1 1/4	32	10	12.10	5.49	—	—	—	1800	2178.00	987.76
1 1/2	40	10	17.50	7.94	—	—	—	1800	3150.00	1428.57
2	50	25	61.50	27.89	—	—	—	—	—	—
2 1/2	65	6	26.22	11.89	—	—	—	480	2097.60	951.29
3	80	—	—	—	—	—	—	300	1950.00	884.35
4	100	—	—	—	—	—	—	192	2169.60	983.95

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Forged Steel Fittings

Class 3000 Threaded

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
			lbs	kg		lbs	kg		lbs	kg
NPS	DN									
FIGURE 2118: REDUCING COUPLINGS (PAGE 101)										
1/4 x 1/8	8 x 6	25	2.50	1.13	—	—	—	—	—	—
3/8 x 1/8	10 x 6	25	3.75	1.70	—	—	—	—	—	—
3/8 x 1/4	10 x 8	50	7.50	3.40	—	—	—	—	—	—
1/2 x 1/8	15 x 6	50	17.50	7.94	—	—	—	5000	1750.00	793.65
1/2 x 1/4	15 x 8	50	17.50	7.94	—	—	—	6000	2100.00	952.38
1/2 x 3/8	15 x 10	50	17.50	7.94	—	—	—	—	—	—
3/4 x 1/8	20 x 6	25	13.00	5.90	—	—	—	3000	1560.00	707.48
3/4 x 1/4	20 x 8	25	13.00	5.90	—	—	—	3750	1950.00	884.35
3/4 x 3/8	20 x 10	25	13.00	5.90	—	—	—	3750	1950.00	884.35
3/4 x 1/2	20 x 15	25	13.00	5.90	—	—	—	3750	1950.00	884.35
1 x 1/8	25 x 6	25	27.50	12.47	—	—	—	—	—	—
1 x 1/4	25 x 8	25	27.50	12.47	—	—	—	2000	2200.00	997.73
1 x 3/8	25 x 10	25	27.50	12.47	—	—	—	2000	2200.00	997.73
1 x 1/2	25 x 15	25	27.50	12.47	—	—	—	2000	2200.00	997.73
1 x 3/4	25 x 20	25	27.50	12.47	—	—	—	2000	2200.00	997.73
1 1/4 x 1/8	32 x 6	20	41.60	18.87	—	—	—	—	—	—
1 1/4 x 1/4	32 x 8	20	41.60	18.87	—	—	—	—	—	—
1 1/4 x 3/8	32 x 10	20	41.60	18.87	—	—	—	—	—	—
1 1/4 x 1/2	32 x 15	10	20.80	9.43	—	—	—	—	—	—
1 1/4 x 3/4	32 x 20	20	41.60	18.87	—	—	—	—	—	—
1 1/4 x 1	32 x 25	10	20.80	9.43	—	—	—	1000	2080.00	943.31
1 1/2 x 1/8	40 x 6	10	29.30	13.29	—	—	—	—	—	—
1 1/2 x 1/4	40 x 8	10	29.30	13.29	—	—	—	—	—	—
1 1/2 x 3/8	40 x 10	10	29.30	13.29	—	—	—	—	—	—
1 1/2 x 1/2	40 x 15	10	29.30	13.29	—	—	—	800	2344.00	1063.04
1 1/2 x 3/4	40 x 20	10	29.30	13.29	—	—	—	800	2344.00	1063.04
1 1/2 x 1	40 x 25	10	29.30	13.29	—	—	—	800	2344.00	1063.04
1 1/2 x 1 1/4	40 x 32	10	29.30	13.29	—	—	—	800	2344.00	1063.04
2 x 1/8	50 x 6	5	22.00	9.98	—	—	—	—	—	—
2 x 1/4	50 x 8	5	22.00	9.98	—	—	—	—	—	—
2 x 3/8	50 x 10	5	22.00	9.98	—	—	—	—	—	—
2 x 1/2	50 x 15	5	22.00	9.98	—	—	—	—	—	—
2 x 3/4	50 x 20	5	22.00	9.98	—	—	—	—	—	—
2 x 1	50 x 25	8	35.20	15.96	—	—	—	—	—	—
2 x 1 1/4	50 x 32	8	35.20	15.96	—	—	—	—	—	—
2 x 1 1/2	50 x 40	8	35.20	15.96	—	—	—	—	—	—
2 1/2 x 2	65 x 50	6	45.00	20.41	—	—	—	—	—	—
3 x 2	80 x 50	4	44.00	19.95	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Forged Steel Fittings

Class 6000 Threaded

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
			lbs	kg		lbs	kg		lbs	kg
NPS	DN									
FIGURE 2131: 90° ELBOWS (PAGE 102)										
1/2	15	25	37.50	17.01	—	—	—	1500	2250.00	1020.41
3/4	20	15	39.00	17.69	—	—	—	900	2340.00	1061.22
1	25	5	17.50	7.94	—	—	—	500	1750.00	793.65
1 1/4	32	5	30.00	13.61	—	—	—	420	2520.00	1142.86
1 1/2	40	5	40.00	18.14	—	—	—	360	2880.00	1306.12
2	50	2	26.00	11.79	—	—	—	120	1560.00	707.48
FIGURE 2132: 45° ELBOWS (PAGE 102)										
1/2	15	25	56.25	25.51	—	—	—	—	—	—
3/4	20	25	57.50	26.08	—	—	—	—	—	—
1	25	5	13.45	6.10	—	—	—	—	—	—
1 1/4	32	5	23.45	10.63	—	—	—	—	—	—
1 1/2	40	4	22.40	10.16	—	—	—	—	—	—
2	50	2	19.00	8.62	—	—	—	200	1900.00	861.68
FIGURE 2134: TEES (PAGE 102)										
1/2	15	20	42.00	19.05	—	—	—	1200	2520.00	1142.86
3/4	20	10	33.70	15.28	—	—	—	840	2830.80	1283.81
1	25	5	22.50	10.20	—	—	—	400	1800.00	816.33
1 1/4	32	5	37.50	17.01	—	—	—	300	2250.00	1020.41
1 1/2	40	3	31.50	14.29	—	—	—	240	2520.00	1142.86
2	50	2	34.80	15.78	—	—	—	120	2088.00	946.94
FIGURE 2135: CROSSES (PAGE 103)										
1/2	15	15	39.00	17.69	—	—	—	—	—	—
3/4	20	5	21.50	9.75	—	—	—	—	—	—
1	25	5	28.50	12.93	—	—	—	—	—	—
1 1/4	32	5	48.00	21.77	—	—	—	—	—	—
1 1/2	40	4	45.60	20.68	—	—	—	—	—	—
2	50	2	42.80	19.41	—	—	—	—	—	—
FIGURE 2137: COUPLINGS (PAGE 104)										
1/4	8	20	6.00	2.72	—	—	—	—	—	—
3/8	10	50	22.50	10.20	—	—	—	—	—	—
1/2	15	25	17.50	7.94	—	—	—	3000	2100.00	952.38
3/4	20	20	23.00	10.43	—	—	—	—	—	—
1	25	10	18.30	8.30	—	—	—	—	—	—
1 1/4	32	10	20.80	9.43	—	—	—	800	1664.00	754.65
1 1/2	40	8	31.60	14.33	—	—	—	—	—	—
2	50	4	26.00	11.79	—	—	—	—	—	—
FIGURE 2141: HALF COUPLINGS (PAGE 104)										
1/4	8	50	6.50	2.95	—	—	—	—	—	—
3/8	10	50	11.00	4.99	—	—	—	—	—	—
1/2	15	50	17.50	7.94	—	—	—	—	—	—
3/4	20	50	23.00	10.43	—	—	—	—	—	—
1	25	10	9.50	4.31	—	—	—	2000	1900.00	861.68
1 1/4	32	25	27.50	12.47	—	—	—	—	—	—
1 1/2	40	20	42.40	19.23	—	—	—	—	—	—
2	50	10	30.00	13.61	—	—	—	—	—	—
FIGURE 2143: PIPE CAPS (PAGE 105)										
1/2	15	20	8.20	3.72	—	—	—	—	—	—
3/4	20	20	11.40	5.17	—	—	—	—	—	—
1	25	10	11.70	5.31	—	—	—	—	—	—
1 1/4	32	5	7.10	3.22	—	—	—	—	—	—
1 1/2	40	5	10.85	4.92	—	—	—	—	—	—
2	50	5	18.30	8.30	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Forged Steel Fittings

Class 3000 Socket Weld

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 2150: 90° ELBOWS (PAGE 106)										
1/8	6	25	6.25	2.83	—	—	—	—	—	—
1/4	8	25	7.75	3.51	—	—	—	9600	2976.00	1349.66
3/8	10	25	7.75	3.51	—	—	—	9600	2976.00	1349.66
1/2	15	25	13.25	6.01	—	—	—	4500	2385.00	1081.63
3/4	B 20	25	16.00	7.26	—	—	—	2500	1600.00	725.62
1	B 25	25	23.75	10.77	—	—	—	1500	1425.00	646.26
1 1/4	32	10	16.00	7.26	—	—	—	1000	1600.00	725.62
1 1/2	40	5	10.60	4.81	—	—	—	500	1060.00	480.73
2	B 50	5	18.30	8.30	—	—	—	420	1537.20	697.14
2 1/2	65	—	—	—	—	—	—	180	1098.00	497.96
3	80	—	—	—	—	—	—	128	1241.60	563.08
4	100	—	—	—	—	—	—	48	1104.00	500.68
FIGURE 2151: 45° ELBOWS (PAGE 106)										
1/8	6	25	4.50	2.04	—	—	—	—	—	—
1/4	8	25	4.00	1.81	—	—	—	9600	1536.00	696.60
3/8	10	25	4.50	2.04	—	—	—	9600	1728.00	783.67
1/2	15	25	10.75	4.88	—	—	—	4500	1935.00	877.55
3/4	20	25	14.50	6.58	—	—	—	4500	2610.00	1183.67
1	25	25	22.50	10.20	—	—	—	2000	1800.00	816.33
1 1/4	32	10	13.00	5.90	—	—	—	1000	1300.00	589.57
1 1/2	40	5	7.85	3.56	—	—	—	900	1413.00	640.82
2	50	5	13.65	6.19	—	—	—	420	1146.60	520.00
2 1/2	65	—	—	—	—	—	—	180	1350.00	612.24
4	100	—	—	—	—	—	—	128	2534.40	1149.39
FIGURE 2152: TEES (PAGE 107)										
1/8	6	20	5.60	2.54	—	—	—	—	—	—
1/4	8	20	4.80	2.18	—	—	—	9600	2304.00	1044.90
3/8	10	20	7.60	3.45	—	—	—	4500	1710.00	775.51
1/2	15	25	16.25	7.37	—	—	—	2500	1625.00	736.96
3/4	20	25	21.50	9.75	—	—	—	2000	1720.00	780.05
1	25	25	34.25	15.53	—	—	—	1500	2055.00	931.97
1 1/4	32	10	20.00	9.07	—	—	—	840	1680.00	761.90
1 1/2	40	5	14.00	6.35	—	—	—	500	1400.00	634.92
2	50	5	19.25	8.73	—	—	—	300	1155.00	523.81
2 1/2	65	—	—	—	—	—	—	192	1574.40	714.01
3	80	—	—	—	—	—	—	128	1536.00	696.60
FIGURE 2153: CROSSES (PAGE 107)										
1/8	6	25	11.25	5.10	—	—	—	—	—	—
1/4	8	25	9.50	4.31	—	—	—	—	—	—
3/8	10	25	8.00	3.63	—	—	—	—	—	—
1/2	15	25	20.25	9.18	—	—	—	4500	3645.00	1653.06
3/4	20	10	11.00	4.99	—	—	—	1500	1650.00	748.30
1	25	10	15.60	7.07	—	—	—	—	—	—
1 1/4	32	5	12.20	5.53	—	—	—	—	—	—
1 1/2	40	5	16.25	7.37	—	—	—	—	—	—
2	50	5	26.00	11.79	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Forged Steel Fittings

Class 3000 Socket Weld

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 2154: COUPLINGS (PAGE 108)										
1/8	6	50	4.00	1.81	—	—	—	18000	1440.00	653.06
1/4	8	50	5.00	2.27	—	—	—	—	—	—
3/8	10	25	4.00	1.81	—	—	—	—	—	—
1/2	15	50	10.50	4.76	—	—	—	7500	1575.00	714.29
3/4	20	40	16.00	7.26	—	—	—	4800	1920.00	870.75
1	B 25	20	11.00	4.99	—	—	—	2400	1320.00	598.64
1 1/4	B 32	25	18.75	8.50	—	—	—	2000	1500.00	680.27
1 1/2	40	20	22.00	9.98	—	—	—	1600	1760.00	798.19
2	50	10	16.50	7.48	—	—	—	800	1320.00	598.64
2 1/2	65	10	32.50	14.74	—	—	—	—	—	—
3	80	5	25.50	11.56	—	—	—	400	2040.00	925.17
4	100	4	30.00	13.61	—	—	—	—	—	—
FIGURE 2155: HALF COUPLINGS (PAGE 109)										
1/8	6	50	4.50	2.04	—	—	—	—	—	—
1/4	8	50	6.00	2.72	—	—	—	—	—	—
3/8	10	25	5.75	2.61	—	—	—	—	—	—
1/2	15	25	7.00	3.17	—	—	—	—	—	—
3/4	20	30	12.90	5.85	—	—	—	4500	1935.00	877.55
1	25	20	13.20	5.99	—	—	—	—	—	—
1 1/4	32	10	11.00	4.99	—	—	—	—	—	—
1 1/2	40	10	10.60	4.81	—	—	—	—	—	—
2	50	10	21.50	9.75	—	—	—	—	—	—
FIGURE 2156: REDUCING COUPLINGS (PAGE 109)										
1/2 x 1/4	15 x 8	25	8.75	3.97	—	—	—	6000	2100.00	952.38
1/2 x 3/8	15 x 10	25	8.75	3.97	—	—	—	6000	2100.00	952.38
3/4 x 1/2	20 x 15	30	17.40	7.89	—	—	—	4500	2610.00	1183.67
1 x 1/2	25 x 15	20	22.00	9.98	—	—	—	2000	2200.00	997.73
1 x 3/4	25 x 20	20	22.00	9.98	—	—	—	—	—	—
1 1/4 x 1/2	32 x 15	10	14.60	6.62	—	—	—	1200	1752.00	794.56
1 1/4 x 1	32 x 25	10	14.60	6.62	—	—	—	—	—	—
1 1/2 x 1/2	40 x 15	10	19.80	8.98	—	—	—	1200	2376.00	1077.55
1 1/2 x 3/4	40 x 20	10	19.80	8.98	—	—	—	—	—	—
1 1/2 x 1	40 x 25	10	19.80	8.98	—	—	—	—	—	—
1 1/2 x 1 1/4	40 x 32	10	19.80	8.98	—	—	—	—	—	—
2 x 1/2	50 x 15	10	35.00	15.87	—	—	—	600	2100.00	952.38
2 x 1	50 x 25	10	35.00	15.87	—	—	—	—	—	—
2 x 1 1/4	50 x 32	10	35.00	15.87	—	—	—	—	—	—
2 x 1 1/2	50 x 40	10	35.00	15.87	—	—	—	—	—	—
FIGURE 2157: PIPE CAPS (PAGE 110)										
1	25	25	15.00	6.80	—	—	—	—	—	—
1 1/4	32	10	9.60	4.35	—	—	—	1800	1728.00	783.67
1 1/2	40	10	12.00	5.44	—	—	—	—	—	—
2	50	25	50.00	22.68	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Forged Steel Fittings

Class 6000 Socket Weld

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 2170: 90° ELBOWS (PAGE 111)										
1/2	15	20	18.00	8.16	—	—	—	2000	1800.00	816.33
3/4	20	15	22.50	10.20	—	—	—	—	—	—
1	25	5	11.60	5.26	—	—	—	800	1856.00	841.72
1 1/4	32	5	15.00	6.80	—	—	—	—	—	—
1 1/2	40	5	27.50	12.47	—	—	—	240	1320.00	598.64
2	50	2	13.00	5.90	—	—	—	—	—	—
FIGURE 2171: 45° ELBOWS (PAGE 111)										
1/2	15	25	19.00	8.62	—	—	—	—	—	—
3/4	20	15	18.00	8.16	—	—	—	—	—	—
1	25	5	10.00	4.54	—	—	—	—	—	—
1 1/4	32	5	11.75	5.33	—	—	—	—	—	—
1 1/2	40	5	21.00	9.52	—	—	—	540	2268.00	1028.57
2	50	2	11.70	5.31	—	—	—	—	—	—
FIGURE 2172: TEES (PAGE 112)										
1/2	15	20	23.20	10.52	—	—	—	2000	2320.00	1052.15
3/4	20	10	20.00	9.07	—	—	—	1000	2000.00	907.03
1	25	5	15.80	7.17	—	—	—	—	—	—
1 1/4	32	5	18.10	8.21	—	—	—	—	—	—
1 1/2	40	3	21.30	9.66	—	—	—	—	—	—
2	50	2	17.80	8.07	—	—	—	—	—	—
FIGURE 2173: CROSSES (PAGE 112)										
1/2	15	15	21.00	9.52	—	—	—	—	—	—
3/4	20	5	11.50	5.22	—	—	—	—	—	—
1	25	5	19.00	8.62	—	—	—	—	—	—
1 1/4	32	5	23.50	10.66	—	—	—	—	—	—
1 1/2	40	3	26.10	11.84	—	—	—	—	—	—
FIGURE 2174: COUPLINGS (PAGE 113)										
1/2	15	25	13.25	6.01	—	—	—	—	—	—
3/4	20	25	14.00	6.35	—	—	—	—	—	—
1	25	10	9.20	4.17	—	—	—	—	—	—
1 1/4	32	10	11.60	5.26	—	—	—	—	—	—
1 1/2	40	5	12.85	5.83	—	—	—	—	—	—
2	50	6	28.50	12.93	—	—	—	480	2280.00	1034.01
FIGURE 2175: HALF COUPLINGS (PAGE 113)										
1/2	15	25	14.00	6.35	—	—	—	—	—	—
3/4	20	25	23.75	10.77	—	—	—	—	—	—
1	25	25	28.00	12.70	—	—	—	—	—	—
1 1/4	32	25	46.75	21.20	—	—	—	—	—	—
1 1/2	40	10	28.70	13.02	—	—	—	—	—	—
2	50	5	18.10	8.21	—	—	—	—	—	—
FIGURE 2177: PIPE CAPS (PAGE 114)										
1/2	15	25	10.50	4.76	—	—	—	—	—	—
3/4	20	15	8.70	3.95	—	—	—	—	—	—
1	25	10	12.10	5.49	—	—	—	—	—	—
1 1/4	32	15	15.00	6.80	—	—	—	—	—	—
1 1/2	40	5	10.60	4.81	—	—	—	—	—	—
2	50	5	24.35	11.04	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Forged Steel Fittings

High Pressure Plugs

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 2122: SQUARE HEAD PLUGS (PAGE 115)										
1/8	6	100	2.00	0.91	—	—	—	—	—	—
1/4	8	100	3.00	1.36	—	—	—	—	—	—
3/8	10	100	6.00	2.72	—	—	—	—	—	—
1/2	15	100	10.00	4.54	—	—	—	20000	2000.00	907.03
3/4	B 20	50	9.00	4.08	—	—	—	10000	1800.00	816.33
1	B 25	25	9.50	4.31	—	—	—	5000	1900.00	861.68
1 1/4	32	25	15.50	7.03	—	—	—	3000	1860.00	843.54
1 1/2	40	10	8.80	3.99	—	—	—	2400	2112.00	957.82
2	50	15	21.00	9.52	—	—	—	—	—	—
2 1/2	65	10	22.00	9.98	—	—	—	—	—	—
3	80	10	34.00	15.42	—	—	—	—	—	—
FIGURE 2142: HEX HEAD PLUGS (PAGE 115)										
1/8	6	100	3.00	1.36	—	—	—	—	—	—
1/4	B 8	100	5.00	2.27	—	—	—	32400	1620.00	734.69
3/8	10	100	9.00	4.08	—	—	—	—	—	—
1/2	B 15	100	13.00	5.90	—	—	—	12000	1560.00	707.48
3/4	B 20	50	13.50	6.12	—	—	—	8000	2160.00	979.59
1	B 25	25	12.00	5.44	—	—	—	4000	1920.00	870.75
1 1/4	32	20	18.80	8.53	—	—	—	2400	2256.00	1023.13
1 1/2	40	10	12.00	5.44	—	—	—	—	—	—
2	B 50	10	24.00	10.88	—	—	—	—	—	—
3	80	5	24.00	10.88	—	—	—	—	—	—
FIGURE 2121: ROUND HEAD PLUGS (PAGE 115)										
1/8	6	100	5.00	2.27	—	—	—	—	—	—
1/4	8	100	10.00	4.54	—	—	—	—	—	—
3/8	10	50	8.00	3.63	—	—	—	—	—	—
1/2	15	50	14.00	6.35	—	—	—	—	—	—
3/4	20	25	10.50	4.76	—	—	—	—	—	—
1	25	15	12.30	5.58	—	—	—	—	—	—
1 1/4	32	15	18.00	8.16	—	—	—	—	—	—
1 1/2	40	15	22.50	10.20	—	—	—	—	—	—
2	50	8	25.60	11.61	—	—	—	—	—	—

Forged Steel Fittings

High Pressure Bushings

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 2140: FLUSH BUSHINGS (PAGE 116)										
1/2 x 3/8	15 x 10	50	3.00	1.36	—	—	—	16200	972.00	440.82
3/4 x 3/8	20 x 10	50	4.50	2.04	—	—	—	16200	1458.00	661.22
3/4 x 1/2	20 x 15	50	4.50	2.04	—	—	—	16200	1458.00	661.22
1 x 1/2	25 x 15	50	6.00	2.72	—	—	—	12000	1440.00	653.06
1 x 3/4	25 x 20	50	6.00	2.72	—	—	—	12000	1440.00	653.06
1 1/4 x 3/4	32 x 20	—	—	—	—	—	—	3750	562.50	255.10
1 1/4 x 1	32 x 25	50	7.50	3.40	—	—	—	9000	1350.00	612.24
2 x 3/4	50 x 20	—	—	—	—	—	—	2250	787.50	357.14
2 x 1 1/2	50 x 40	20	7.00	3.17	—	—	—	3600	1260.00	571.43

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Forged Steel Fittings

High Pressure Bushings

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 2139: HEX HEAD BUSHINGS (PAGE 116)										
1/4 x 1/8	8 x 6	100	2.00	0.91	—	—	—	32400	648.00	293.88
3/8 x 1/8	10 x 6	100	3.00	1.36	—	—	—	—	—	—
3/8 x 1/4	10 x 8	100	3.00	1.36	—	—	—	32400	972.00	440.82
1/2 x 1/8	15 x 6	100	6.00	2.72	—	—	—	20000	1200.00	544.22
1/2 x 1/4	15 x 8	100	6.00	2.72	—	—	—	24000	1440.00	653.06
1/2 x 3/8	15 x 10	100	6.00	2.72	—	—	—	24000	1440.00	653.06
3/4 x 1/8	20 x 6	50	5.50	2.49	—	—	—	10000	1100.00	498.87
3/4 x 1/4	20 x 8	50	5.50	2.49	—	—	—	12000	1320.00	598.64
3/4 x 3/8	20 x 10	50	5.50	2.49	—	—	—	12000	1320.00	598.64
3/4 x 1/2	20 x 15	50	5.50	2.49	—	—	—	12000	1320.00	598.64
1 x 1/8	25 x 6	50	10.00	4.54	—	—	—	4500	900.00	408.16
1 x 1/4	25 x 8	50	10.00	4.54	—	—	—	4500	900.00	408.16
1 x 3/8	25 x 10	50	10.00	4.54	—	—	—	6000	1200.00	544.22
1 x 1/2	25 x 15	50	10.00	4.54	—	—	—	7500	1500.00	680.27
1 x 3/4	25 x 20	50	10.00	4.54	—	—	—	9000	1800.00	816.33
1 1/4 x 1/8	32 x 6	25	10.00	4.54	—	—	—	—	—	—
1 1/4 x 1/4	32 x 8	25	10.00	4.54	—	—	—	—	—	—
1 1/4 x 3/8	32 x 10	25	10.00	4.54	—	—	—	—	—	—
1 1/4 x 1/2	32 x 15	25	10.00	4.54	—	—	—	—	—	—
1 1/4 x 3/4	32 x 20	25	10.00	4.54	—	—	—	—	—	—
1 1/4 x 1	32 x 25	25	10.00	4.54	—	—	—	4500	1800.00	816.33
1 1/2 x 1/8	40 x 6	20	10.00	4.54	—	—	—	1800	900.00	408.16
1 1/2 x 1/4	40 x 8	20	10.00	4.54	—	—	—	2400	1200.00	544.22
1 1/2 x 3/8	40 x 10	20	10.00	4.54	—	—	—	2400	1200.00	544.22
1 1/2 x 1/2	40 x 15	20	10.00	4.54	—	—	—	—	—	—
1 1/2 x 3/4	40 x 20	20	10.00	4.54	—	—	—	—	—	—
1 1/2 x 1	40 x 25	20	10.00	4.54	—	—	—	3600	1800.00	816.33
1 1/2 x 1 1/4	40 x 32	20	10.00	4.54	—	—	—	3600	1800.00	816.33
2 x 1/8	50 x 6	12	10.20	4.63	—	—	—	—	—	—
2 x 1/4	50 x 8	12	10.20	4.63	—	—	—	—	—	—
2 x 3/8	50 x 10	12	10.20	4.63	—	—	—	—	—	—
2 x 1/2	50 x 15	12	10.20	4.63	—	—	—	1440	1224.00	555.10
2 x 3/4	50 x 20	12	10.20	4.63	—	—	—	1440	1224.00	555.10
2 x 1	50 x 25	12	10.20	4.63	—	—	—	1440	1224.00	555.10
2 x 1 1/4	50 x 32	12	10.20	4.63	—	—	—	2160	1836.00	832.65
2 x 1 1/2	50 x 40	12	10.20	4.63	—	—	—	2160	1836.00	832.65
2 1/2 x 1 1/4	65 x 32	10	12.00	5.44	—	—	—	—	—	—
2 1/2 x 1 1/2	65 x 40	10	12.00	5.44	—	—	—	—	—	—
3 x 3/4	80 x 20	5	13.00	5.90	—	—	—	—	—	—
3 x 1 1/4	80 x 32	5	13.00	5.90	—	—	—	—	—	—
3 x 2	80 x 50	12	31.20	14.15	—	—	—	—	—	—
4 x 3	100 x 80	5	35.00	15.87	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Forged Steel Fittings

Socket-Weld Reducer Inserts

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
SOCKET-WELD REDUCER INSERTS: CLASS 3000 (PAGE 117)										
½ x ¼	15 x 8	50	9.00	4.08	—	—	—	—	—	—
½ x ⅜	15 x 10	50	9.00	4.08	—	—	—	—	—	—
¾ x ¼	20 x 8	50	12.50	5.67	—	—	—	8000	2000.00	907.03
¾ x ⅜	20 x 10	50	12.50	5.67	—	—	—	10000	2500.00	1133.79
¾ x ½	20 x 15	50	12.50	5.67	—	—	—	—	—	—
1 x ½	25 x 15	50	17.50	7.94	—	—	—	6000	2100.00	952.38
1 x ¾	25 x 20	50	17.50	7.94	—	—	—	5000	1750.00	793.65
1¼ x ⅜	32 x 10	25	14.00	6.35	—	—	—	3750	2100.00	952.38
1¼ x ½	32 x 15	25	14.00	6.35	—	—	—	3000	1680.00	761.90
1¼ x ¾	32 x 20	25	14.00	6.35	—	—	—	3750	2100.00	952.38
1¼ x 1	32 x 25	25	14.00	6.35	—	—	—	3000	1680.00	761.90
1½ x ½	40 x 15	10	6.20	2.81	—	—	—	1800	1116.00	506.12
1½ x ¾	40 x 20	20	12.40	5.62	—	—	—	1800	1116.00	506.12
1½ x 1	40 x 25	12	7.44	3.37	—	—	—	—	—	—
1½ x 1¼	40 x 32	12	7.44	3.37	—	—	—	—	—	—
2 x ½	50 x 15	10	15.00	6.80	—	—	—	—	—	—
2 x ¾	50 x 20	10	15.00	6.80	—	—	—	—	—	—
2 x 1	50 x 25	10	15.00	6.80	—	—	—	—	—	—
2 x 1¼	50 x 32	10	15.00	6.80	—	—	—	—	—	—
2 x 1½	50 x 40	10	15.00	6.80	—	—	—	—	—	—
2½ x 2	65 x 50	10	30.00	13.61	—	—	—	—	—	—

Forged Steel Unions

Class 3000 Threaded & Socket-Weld

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 2125: THREADED UNION (PAGE 119)										
¼	8	25	7.50	3.40	—	—	—	—	—	
⅜	10	25	12.50	5.67	—	—	—	—	—	
½	B 15	25	17.50	7.94	—	—	—	—	—	
¾	20	25	30.00	13.61	—	—	—	—	—	
1	B 25	10	17.00	7.71	—	—	—	—	—	
1¼	32	10	25.00	11.34	—	—	—	—	—	
1½	40	5	16.50	7.48	—	—	—	—	—	
2	50	5	26.50	12.02	—	—	—	—	—	
2½	65	5	43.00	19.50	—	—	—	—	—	
3	80	4	50.80	23.04	—	—	—	—	—	
FIGURE 2126: SOCKET-WELD UNION (PAGE 119)										
¼	8	25	7.50	3.40	—	—	—	—	—	
⅜	10	25	12.50	5.67	—	—	—	—	—	
½	15	25	17.50	7.94	—	—	—	—	—	
¾	20	25	30.00	13.61	—	—	—	—	—	
1	25	10	17.00	7.71	—	—	—	—	—	
1¼	32	10	25.00	11.34	—	—	—	—	—	
1½	40	5	16.50	7.48	—	—	—	—	—	
2	50	5	26.50	12.02	—	—	—	—	—	

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Forged Steel Unions

Class 6000 Threaded & Socket-Weld

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 2127: THREADED UNION (PAGE 120)										
¼	8	25	15.00	6.80	—	—	—	—	—	—
½	15	10	14.00	6.35	—	—	—	—	—	—
¾	20	10	20.00	9.07	—	—	—	—	—	—
1	25	10	31.00	14.06	—	—	—	—	—	—
1¼	32	5	29.50	13.38	—	—	—	—	—	—
1½	40	10	66.00	29.93	—	—	—	—	—	—
2	50	5	52.50	23.81	—	—	—	—	—	—
FIGURE 2128: SOCKET-WELD UNION (PAGE 120)										
½	15	25	35.00	15.87	—	—	—	—	—	—

Catawissa

Wing Unions

Size		Cartons			Master Container			Pallets			
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight		
NPS	DN		lbs	kg		lbs	kg		lbs	kg	
FIGURE 100: LUG UNION (PAGE 132)											
2	B	50	12	75.00	34.01	—	—	—	336	2100.00	952.38
2½		65	8	80.40	36.46	—	—	—	224	2251.20	1020.95
3		80	6	81.90	37.14	—	—	—	168	2293.20	1040.00
4		100	2	44.00	19.95	—	—	—	56	1232.00	558.73
6		150	—	—	—	—	—	—	28	1283.80	582.22
8		200	—	—	—	—	—	—	28	1866.20	846.35
FIGURE 100C: LUG UNION (PAGE 132)											
2	B	50	12	81.00	36.73	—	—	—	336	2268.00	1028.57
FIGURE 200: LUG UNION (PAGE 133)											
1	B	25	36	63.00	28.57	—	—	—	1008	1764.00	800.00
1¼		32	25	56.25	25.51	—	—	—	700	1575.00	714.29
1½		40	24	66.00	29.93	—	—	—	672	1848.00	838.10
2		50	14	78.40	35.56	—	—	—	392	2195.20	995.56
2 (Ductile Iron)	B	50	14	66.50	30.16	—	—	—	392	1862.00	844.44
2½		65	8	85.60	38.82	—	—	—	224	2396.80	1086.98
3		80	6	77.10	34.97	—	—	—	168	2158.80	979.05
4		100	4	74.80	33.92	—	—	—	112	2094.40	949.84
FIGURE 200: BUTTWELD ENDS, SCHEDULE 40, UNION (PAGE 134)											
2		50	14	77.00	34.92	—	—	—	—	—	—
3		80	6	87.00	39.46	—	—	—	—	—	—
4		100	4	83.60	37.91	—	—	—	—	—	—
FIGURE 200C: LUG UNION (PAGE 134)											
1	B	25	36	68.40	31.02	—	—	—	1008	1915.20	868.57
2	B	50	6	34.50	15.65	—	—	—	300	1725.00	782.31

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Catawissa Wing Unions

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
			lbs	kg		lbs	kg		lbs	kg
NPS	DN									
FIGURE 206: LUG UNION (PAGE 135)										
1	25	25	56.25	25.51	—	—	—	700	1575.00	714.29
1¼	32	24	66.00	29.93	—	—	—	672	1848.00	838.10
1½	40	36	63.00	28.57	—	—	—	1008	1764.00	800.00
2	50	14	66.50	30.16	—	—	—	392	1862.00	844.44
2½	65	8	85.60	38.82	—	—	—	—	—	—
3	80	6	78.00	35.37	—	—	—	168	2184.00	990.48
4	100	4	74.80	33.92	—	—	—	112	2094.40	949.84
6	150	—	—	—	—	—	—	28	1290.80	585.40
FIGURE 206: BUTTWELD ENDS, SCHEDULE 40, UNION (PAGE 136)										
2	50	14	84.00	38.10	—	—	—	—	—	—
3	80	6	87.00	39.46	—	—	—	—	—	—
4	100	4	83.60	37.91	—	—	—	—	—	—
FIGURE 211: INSULATING UNION (PAGE 137)										
1	25	30	70.20	31.84	—	—	—	840	1965.60	891.43
2	50	12	74.88	33.96	—	—	—	336	2096.64	950.86
FIGURE 300: LUG UNION (PAGE 137)										
1	25	30	66.30	30.07	—	—	—	840	1856.40	841.90
2	50	12	72.00	32.65	—	—	—	336	2016.00	914.29
2½	65	8	87.04	39.47	—	—	—	224	2437.12	1105.27
3	80	6	85.50	38.78	—	—	—	168	2394.00	1085.71
4	100	4	82.76	37.53	—	—	—	112	2317.28	1050.92
FIGURE 400: LUG UNION (PAGE 138)										
2	50	6	66.30	30.07	—	—	—	168	1856.40	841.90
3	80	3	60.00	27.21	—	—	—	84	1680.00	761.90
4	100	2	58.30	26.44	—	—	—	56	1632.40	740.32
FIGURE 400: BUTTWELD ENDS, SCHEDULE 80, UNION (PAGE 139)										
2	50	6	64.50	29.25	—	—	—	—	—	—
FIGURE 600: LUG UNION (PAGE 139)										
1	25	25	91.25	41.38	—	—	—	700	2555.00	1158.73
1½	40	7	0.07	0.03	—	—	—	—	—	—
2	50	4	62.56	28.37	—	—	—	112	1751.68	794.41
3	80	3	0.03	0.01	—	—	—	—	—	—
4	100	2	0.02	0.01	—	—	—	—	—	—
FIGURE 602: LUG UNION (PAGE 140)										
1	25	25	88.75	40.25	—	—	—	700	2485.00	1126.98
1½	40	7	66.78	30.29	—	—	—	196	1869.84	848.00
2	50	6	74.40	33.74	—	—	—	168	2083.20	944.76
3	80	3	66.90	30.34	—	—	—	84	1873.20	849.52
4	100	2	64.36	29.19	—	—	—	56	1802.08	817.27
FIGURE 602: BUTTWELD ENDS, SCHEDULE 80, UNION (PAGE 141)										
2	50	6	72.72	32.98	—	—	—	—	—	—
3	80	3	63.75	28.91	—	—	—	—	—	—
4	100	2	56.50	25.62	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Catawissa Wing Unions

Size		Cartons			Master Container			Pallets		
		No. Pcs.	Weight		No. Pcs.	Weight		No. Pcs.	Weight	
NPS	DN		lbs	kg		lbs	kg		lbs	kg
FIGURE 607: LUG UNION (PAGE 141)										
1½	40	7	62.72	28.44	—	—	—	196	1756.16	796.44
2	50	4	58.56	26.56	—	—	—	112	1639.68	743.62
FIGURE 1002: LUG UNION (PAGE 142)										
1	25	25	90.50	41.04	—	—	—	700	2534.00	1149.21
1½	40	7	66.78	30.29	—	—	—	—	—	—
2	50	6	78.00	35.37	—	—	—	168	2184.00	990.48
3	80	3	67.20	30.48	—	—	—	84	1881.60	853.33
4	100	3	101.46	46.01	—	—	—	84	2840.88	1288.38
FIGURE 1002: BUTTWELDED ENDS, SCHEDULE 160, UNION (PAGE 143)										
2	50	6	85.50	38.78	—	—	—	—	—	—
3	80	3	63.75	28.91	—	—	—	—	—	—
4	100	2	63.00	28.57	—	—	—	—	—	—
FIGURE 1002: BUTTWELDED ENDS, SCHEDULE XXH, UNION (PAGE 143)										
2	50	6	78.96	35.81	—	—	—	—	—	—
3	80	3	76.56	34.72	—	—	—	—	—	—
4	100	2	68.08	30.88	—	—	—	—	—	—
FIGURE 1502: LUG UNION (PAGE 144)										
1½	40	7	108.22	49.08	—	—	—	—	—	—
2	50	4	77.84	35.30	—	—	—	112	2179.52	988.44
3	80	2	60.96	27.65	—	—	—	56	1706.88	774.10
FIGURE 1502: BUTTWELDED ENDS, SCHEDULE XXH, UNION (PAGE 144)										
1½	40	7	110.25	50.00	—	—	—	—	—	—
2	50	4	82.32	37.33	—	—	—	112	2304.96	1045.33
3	80	2	55.96	25.38	—	—	—	56	1566.88	710.60
FIGURE S1A: HIGH SPEED UNION (PAGE 145)										
1	25	36	54.00	24.49	—	—	—	—	—	—
2	50	19	85.50	38.78	—	—	—	—	—	—

Weights are for black fittings. **B** Sold in box only, black. **G** Sold in box only, galvanized.

Standards and Specifications

	Dimensions	Material	Galvanizing****	Thread	Pressure Rating	Federal/Other
MALLEABLE IRON FITTINGS						
Class 150/PN 20	ASME B16.3•	ASTM A-197	ASTM A-153	ASME B1 20.1+	ASME B16.3•	ASME B16.3**
Class 300/PN 50	ASME B16.3•	ASTM A-197	ASTM A-153	ASME B1 20.1+	ASME B16.3•	
MALLEABLE IRON UNIONS						
Class 150/PN 20	ASME B16.39•	ASTM A-197	ASTM A-153	ASME B1 20.1+	ASME B16.39•	ASME B16.39***
Class 250	ASME B16.39•	ASTM A-197	ASTM A-153	ASME B1 20.1+	ASME B16.39•	
Class 300/PN 50	ASME B16.39•	ASTM A-197	ASTM A-153	ASME B1 20.1+	ASME B16.39•	
CAST IRON THREADED FITTINGS						
Class 125	ASME B16.4•	ASTM A-126 (A)	ASTM A-153	ASME B1.20.1+	ASME B16.4•	ASME B16.4■
Class 250	ASME B16.4•	ASTM A-126 (A)	ASTM A-153	ASME B1.20.1+	ASME B16.4•	ASME B16.4■
CAST IRON PLUGS AND BUSHINGS						
	ASME B16.14•	ASTM A- 126 (A)	ASTM A-153	ASME B1.20.1+	ASME B16.14•	WW-P-471
CAST IRON DRAINAGE THREADED FITTINGS						
	ASME B16.12•	ASTM A-126 (A)	ASTM A-153	ASME B1.20.1+	ASME B16.12•	
CAST IRON FLANGES AND FLANGED FITTINGS						
Class 125 (1"-12")	ASME B16.1•	ASTM A- 126 (A) or (B)	ASTM A-153	ASME B1.20.1+	ASME B16.1	ASME B16.1•
Class 125 (14"-up)	ASME B16.1•	ASTM A-126 (B)	ASTM A-153	ASME B1.20.1+	ASME B16.1	ASME B16.1•
Class 250 (1"-12")	ASME B16.1•	ASTM A- 126 (A) or (B)	ASTM A-153	ASME B1.20.1+	ASME B16.1	ASME B16.1•
Class 250 (14"-up)	ASME B16.1•	ASTM A-126 (B)	ASTM A-153	ASME B1.20.1+	ASME B16.1	ASME B16.1•
FORGED STEEL THREADED FITTINGS						
Class 2000, 3000, 6000	ASME B16.11•	ASTM A105, ASTM A182, ASTM A350		ASME B1.20.1+	ASME B16.11•	
PIPE NIPPLES						
Steel Pipe - Welded	ASTM A733	ASTM A53 Type F or Type E		ASME B1.20.1+		WWN 351
Steel Pipe - Seamless (High Temp.)	ASTM A733	ASTM A106 Gr. B		ASME B1.20.1+		WWN 351
Brass		ASTM B43		ASME B1.20.1+		WWN 351

*The standard
•an American National standard (ANSI)

+ASME B1.20.1 was ANSI B2.1
■Formerly WW-P-501

**Formerly WW-P-521
***Formerly WW-U-531

****ASTM B 633. Type I, SC 4, may be supplied as alternate zinc coating per applicable ASME B16 product standard.

Conditions and Terms of Sale

1. **CONTROLLING PROVISIONS:** These terms and conditions shall control with respect to any purchase order or sale of Seller's products. No waiver, alteration or modification of these terms and conditions whether on Buyer's purchase order or otherwise shall be valid unless the waiver, alteration or modification is specifically accepted in writing and signed by an authorized representative of Seller.
2. **DELIVERY:** Seller will make every effort to complete delivery of products as indicated on Seller's acceptance of an order, but Seller assumes no responsibility or liability, and will accept no back-charge, for loss or damage due to delay or inability to deliver caused by acts of God, war, labor difficulties, accident, delays of carriers, by contractors or suppliers, inability to obtain materials, shortages of fuel and energy, or any other causes of any kind whatever beyond the control of Seller. Seller may terminate any contract of sale of its products without liability of any nature, by written notice to Buyer, in the event that the delay in delivery or performance resulting from any of the aforesaid causes shall continue for a period of sixty (60) days. Under no circumstances shall Seller be liable for any special or consequential damages or for loss, damage, or expense (whether or not based on negligence) directly or indirectly arising from delays or failure to give notice of delay.
3. **WARRANTY:** Seller warrants for one year from the date of shipment Seller's manufactured products to the extent that Seller will replace those having defects in materials or workmanship when used for the purpose and in the manner which Seller recommends. If Seller's examination shall disclose to its satisfaction that the products are defective, and an adjustment is required, the amount of such adjustment shall not exceed the net sales price of the defective products only and no allowance will be made for labor or expense of repairing or replacing defective products or workmanship or damage resulting from the same. Seller warrants the products which it sells of other manufacturers to the extent of the warranties of their respective makers. Where engineering design or fabrication work is supplied, buyer's acceptance of Seller's design or of delivery of work shall relieve Seller of all further obligation, other than as expressed in Seller's product warranty. THIS IS SELLER'S SOLE WARRANTY. SELLER MAKES NO OTHER WARRANTY OF ANY KIND, EXPRESSED OR IMPLIED; and ALL IMPLIED WARRANTIES OF MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE WHICH EXCEED SELLER'S AFORE STATED OBLIGATION ARE HEREBY DISCLAIMED BY SELLER and EXCLUDED FROM THIS WARRANTY. Seller neither assumes, nor authorizes any person to assume for it, any other obligation in connection with the sale of its engineering designs or products. This warranty shall not apply to any products or parts of products which (a) have been repaired or altered outside of Seller's factory, in any manner; or (b) have been subjected to misuse, negligence or accidents; or (c) have been used in a manner contrary to Seller's instructions or recommendations. Seller shall not be responsible for design errors due to inaccurate or incomplete information supplied by Buyer or its representatives.
4. **SELLER'S LIABILITY:** Seller will not be liable for any loss, damage, cost of repairs, incidental or consequential damages of any kind, whether based upon warranty (except for the obligation accepted by Seller under "Warranty" above), contract or negligence arising in connection with the design, manufacture, sale, use or repair of the products or of the engineering designs supplied to Buyer.
5. **RETURNS:** Seller cannot accept return of any products unless its written permission has been first obtained, in which case same will be credited subject to the following: (a) All material returned must, on its arrival at Seller's plant, be found to be in first-class condition; if not, cost of putting in saleable condition will be deducted from credit memoranda. (b) A handling charge deduction of twenty percent (20%) will be made from all credit memoranda issued for material returned. (c) Transportation charges, if not prepaid, will be deducted from credit memoranda.
6. **SHIPMENTS:** All products sent out will be carefully examined, counted and packed. The cost of any special packing or special handling caused by Buyer's requirements or requests shall be added to the amount of the order. No claim for shortages will be allowed unless made in writing within ten (10) days of receipt of a shipment. Claims for products damaged or lost in transit should be made on the carrier, as Seller's responsibility ceases, and title passes, on delivery to the carrier.
7. **SPECIAL PRODUCTS:** Orders covering special or non-standard products are not subject to cancellation except on such terms as Seller may specify on application.
8. **PRICES and DESIGNS:** Prices and designs are subject to change without notice. All prices are F.O.B. Point of Shipment, unless otherwise stated.
9. **TAXES:** The amount of any sales, excise or other taxes, if any, applicable to the products covered by this order, shall be added to the purchase price and shall be paid by Buyer unless Buyer provides Seller with an exemption certificate acceptable to the taxing authorities.
10. **NUCLEAR PLANTS:** Where the products, engineering design or fabrication is for nuclear plant applications, Buyer agrees: (a) to take all necessary steps to add Seller as an insured under the American Nuclear Insurers' (ANI) pool and under the Mutual Atomic Energy Reinsurance Pool (MAERP) for property damage and liability insurance and if necessary steps could have been taken, but are not taken, Buyer shall hold Seller harmless against all such losses which could have been thus covered, (b) to hold Seller harmless with respect to any personal injury (or death), property damage or other loss in a nuclear incident which is caused directly or indirectly by defective design, material, or workmanship furnished by Seller and which is covered by insurance maintained by Buyer (or which could be so covered but with respect to which Buyer has elected to self-insure), and further agrees to waive subrogation by its carriers of such insurance against Seller, and (c) as to nuclear hazards for which Buyer cannot obtain insurance coverage, the liability of Seller for any personal injury (or death), property damage or other loss directly caused by defective design, material, or workmanship furnished by Seller shall not exceed the value of the material furnished by Seller at the time of the loss occurrence.
11. **MINIMUM INVOICE:** \$25.00 plus transportation.
12. **TERMS:** Cash, net 30 days unless otherwise specified.

General Assembly of Threaded Fittings

- 1) Inspect both male and female components prior to assembly.
 - Threads should be free from mechanical damage, dirt, chips and excess cutting oil.
 - Clean or replace components as necessary.
- 2) Application of pipe dope
 - Use a pipe dope that is fast drying, sets-up to a semi hard condition and is vibration resistant. Alternately, an anaerobic sealant may be utilized.
 - Thoroughly mix the thread sealant prior to application.
 - Apply a thick even coat to the male threads only. Best application is achieved with a brush stiff enough to force sealant down to the root of the threads.
- 3) Joint Makeup
 - For sizes up to and including 1½" pipe, wrench tight makeup is considered three full turns past handtight. Handtight engagement for ½" through 2" thread varies from 4½ turns to 5 turns.
 - For 2½" through 4" sizes, wrench tight makeup is considered two full turns past handtight. Handtight engagement for 2½" through 4" thread varies from 5½ turns to 6¾ turns.

Engineering Information

15.3

MULTIPLY	BY	TO OBTAIN
Atmosphere	0.001316	Torrs
Atmospheres	76	Cms. of mercury
"	29.92	Inches of mercury
"	33.9	Feet of water
"	14.7	Lbs./sq. inch
Barrels—Oil	42	Gallons
Barrels—Cement	376	Lbs.—cement
Bags or Sacks—Cement	94	Lbs.—cement
Board—feet	144 sq. in. x 1 in	Cubic in.
British Thermal Units	777.5	Foot lbs.
" " "	0.0003927	Horsepower—hrs.
" " "	0.0002928	Kilowatt—hrs.
" " "	0.00001	Therms
B.T.U./min	12.96	Foot lbs./sec
"	0.02356	Horsepower
"	0.01757	Kilowatts
"	17.57	Watts
Centimeters	0.3937	Inches
Cubic centimeters	0.00003531	Cubic ft.
"	0.06102	Cubic inches
"	0.000001308	Cubic yards
"	0.0002642	Gallons
"	0.03381	Ounces (Fluid)
Cubic Cm./min	0.002118	Cu. ft./hr.
" " / "	0.0002641	Gal./min.
Cubic feet	1728	Cubic in.
"	7.48052	Gallons
Cubic inches	0.0005787	Cubic feet
"	0.00002143	Cubic yards
"	0.004329	Gallons
Cubic meters	35.31	Cu. ft.
"	61.023	Cu. in.
"	1.308	Cu. yds.
"	264.2	Gallons
Cubic yards	27	Cu. ft.
Degrees (angle)	60	Minutes
"	0.01745	Radians
"	3600	Seconds
Degrees/sec	0.01745	Radians/sec.
"	0.1667	Revolutions/min.
" / "	0.002778	Revolutions/sec.
English Viscosity Units	14.88	Poises
Feet	30.48	Centimeters
"	12	Inches
"	0.3048	Meters
Feet of water	0.0295	Atmosphere
" " "	0.8826	In. of mercury
"	62.43	Lbs./sq. ft.
" " "	0.4335	Lbs./sq. in.
Feet/sec	0.6818	Miles/hr.
Foot lbs	0.001286	Br. Thermal Units
"	0.00000505	Horsepower hrs.
"	3.766E-07	Kilowatt hrs.
Foot lbs./min	0.001286	B.T.U./min.
" " / "	0.01667	Ft. lbs./sec.
" " / "	0.0000303	Horsepower
" " / "	0.0000266	Kilowatts
Foot lbs./sec	0.0717	B.T.U./min.
" " / "	0.001818	Horsepower
" " / "	0.001356	Kilowatts
Gallons	3785	Cubic centimeters
"	0.1337	Cubic feet
"	231	Cubic inches
Gallons (Imperial)	1.20095	U.S. gallons
" (U.S.)	0.83267	Imperial gallons
Gallons water	8.3453	Pounds of water
Gallons/min	0.002228	Cu. ft./sec.
" / "	8.0208	Cu. ft./hr.
Grams	0.03527	Ounces
"	0.002205	Pounds
Grams/cu. cm	62.43	Pounds/cu. ft.
" / " "	0.03613	Pounds/cu. in.
Horsepower	42.44	B.T.U./min.
"	33000	Ft. lbs./min.
"	0.55	Ft. lbs./sec.
"	0.7457	Kilowatts
Horsepower (boiler)	33,479	B.T.U./hr.
"	9.803	Kilowatts

MULTIPLY	BY	TO OBTAIN
Horsepower hours	0.2547	British Thermal Units
" " "	7457	Kilowatt hours
Inches	2.54	Centimeters
Inches of mercury	0.03342	Atmospheres
" " "	1.133	Ft. of water
" " "	70.73	Lbs./sq. ft.
" " "	0.4912	Lbs./sq. in.
Inches of water	0.002458	Atmospheres
" " "	0.07355	Inches of mercury
" " "	5.202	Lbs./sq. ft.
" " "	0.03613	Lbs./sq. in.
" " "	0.5781	Ounces/sq.in.
Kilograms	2.205	Lbs.
Kgs./meter	0.672	Lbs./ft.
Kgs./sq. meter	0.003281	Feet of water
" / " "	0.2048	Lbs./sq. ft.
" / " "	0.001422	Lbs./sq. in.
Kilometers	3281	Feet
"	0.6214	Miles
"	0.1094	Yards
Kilometers/hr	27.78	Centimeters/sec.
" / "	54.68	Feet/min.
" / "	0.9113	Feet/sec.
" / "	0.6214	Miles/hr.
Kilowatts	56.92	B.T.Units/min.
"	44250	Ft. lbs./min.
"	737.6	Ft. lbs./sec.
"	1.341	Horsepower
"	0.1	Watts
Kilowatt hrs	0.3415	B.T.U.
" " "	0.000002655	Ft. lbs.
" " "	1.341	Horsepower-hrs.
Liters	0.03531	Cu. ft.
"	61.02	Cu. in.
"	0.2642	Gallons
Meters	100	Centimeters
"	3.281	Feet
"	39.37	Inches
"	1.094	Yards
Meters/sec	196.8	Ft./min.
Millimeters	0.1	Centimeters
"	0.03937	Inches
Ounces	437.5	Grains
"	28.349527	Grams
"	0.0625	Pounds
Pounds	16	Ounces
"	7	Grains
"	453.5924	Grams
Pounds of water	0.01602	Cu. ft.
" " "	27.68	Cu. in.
" " "	0.1198	Gallons
Pounds/cu. ft	0.0005787	Lbs./cu. in.
Pounds/cu. in	1728	Lbs./cu. ft.
Radians	57.3	Degrees
"	0.3438	Minutes
"	0.637	Quadrants
Radians / sec	57.3	Degrees/sec.
" / "	0.1592	Revolutions/sec.
" / "	9.549	Revolutions/min.
Revolutions	360	Degrees
"	4	Quadrants
"	6.283	Radians
Revolutions/min	6	Degrees/sec
" / "	0.1047	Radians/sec.
" / "	0.01667	Revolutions/sec.
Temp. (°C) +273	1	Abs. temp. Co
" +17.78	1.8	Temp. (°F)
Temp. (°F) +460	1	Abs. temp. (°F)
" -32	39942	Temp. (°C)
Torr	760	Atmospheres
Torr	1	mm Hg
Watts	0.05692	B.T. Units/min.
"	44.26	Ft. lbs./min.
"	0.001341	Horsepower
"	0.01	Kilowatts
Yards	91.44	Centimeters
"	3	Feet
"	36	Inches
"	0.9144	Meters

Figure Number Index

FIGURE NO.	PAGE
3L S1A	145
100/100C	132
200/200C	133-134
206	135-136
202	136
211	137
300	137
301	138
336	90
337	91
346	92
347	92
348	93
351	38
352	40
356/356A/356R	39
358	41
359	41-45
360	46
361	46
366	47
367	48
368	49
370	53
371	38
379	94
380	52, 94
381	52, 94
383	35, 50-51
385	35, 51
387	52
388	52
389	52
390	32, 52
400	138-139
421	53
424	53
425	54
426	54
459	33
463	33
551	33
552	34
554	33
600	139

FIGURE NO.	PAGE
602	140-141
607	141
701/701R	56
702/702A	56
703	56
705	57
706	57
707	57
708	57
718	59
719	59
722	59
723	59
726	60
727	60
729	60
730	60
731	61
734	61
735	61
736	61
744	62
752	62
753	62
754	62
801	64
802	64
803	65
804/804R	65
805	66
808	66
811	68
821	69
823	69
825	70
826	70
831	72
832	34
841	72
842	72
855	73
1002	142-143
1010T	76
1011	73
1016	74

FIGURE NO.	PAGE
1018	75
1021	76
1025	75
1030	76
1101/1101R	18
1102	19
1103	19
1104	20
1105	20
1105R	21-23
1106	24
1107	24
1108	24
1119	25
1121	25
1124	25
1125	26
1133	27
1134	27
1138	27
1160	28
1161/1161R	28
1162	29
1163	32
1164/1164R	29-30
1165	30
1166	31
1167	31
1170	29
1190	27
1502	144
1538	77
2101	96
2102	96
2103	97
2104	97
2111	98
2112	98
2113	99
2114	98
2115	99
2116	99
2117	100
2118	101
2119	100

FIGURE NO.	PAGE
2120	101
2121	115
2122	115
2125	119
2126	119
2127	120
2128	120
2131	102
2132	102
2133	103
2134	102
2135	103
2136	103
2137	104
2138	105
2139	116
2140	116
2141	104
2142	115
2143	105
2150	104
2151	106
2152	107
2153	107
2158	108
2154	108
2155	109
2156	109
2157	110
2159	117-118
2170	111
2171	111
2172	112
2173	112
2174	113
2175	113
2176	114
2177	114
2178	112
2179	117-118
J-3300	32
S1A	145

Today Anvil® International is the largest and most complete fitting and hanger manufacturer in the world.

2004 Anvil® International acquires Star Pipe Products, Building and Construction Divisions (SPF) and forms AnvilStar™ Fire Products Division.

2001 Anvil® International acquires Merit® Manufacturing and Beck Manufacturing.

2000 The industry's trusted manufacturer of pipe fittings, hangers and grooved fittings is renamed Anvil® International, Inc.

1999 Tyco sells the distribution and manufacturing operations known up to this point as "Grinnell Supply Sales", but keeps the Grinnell® trademark.

1994 J.B. Smith™ and Catawissa™ join the Grinnell Supply Sales and Manufacturing division.

1969 Grinnell Co. acquired by International Telephone and Telegraph. Two years later, ITT divests the Fire Protection Division, but keeps the manufacturing and sales divisions that will become known as Anvil® International.

1960 Gruvlok® line of grooved fittings is introduced.

1919 General Fire Extinguisher Co. becomes Grinnell Co.

1909 Frederick Grinnell opens a foundry in Cranston, RI. Companies express interest in buying its piping products, laying the groundwork for what would become the Grinnell Supply Sales Division. It would be these manufacturing and sales operations that eventually become Anvil® International.

1850 Providence Steam & Gas Pipe Co. is formed, and Frederick Grinnell purchases a controlling interest.

Grinnell® is a registered trademark of Grinnell Corporation, a Tyco International Ltd. company.

TRUSTED FOR 150 YEARS

We built our reputation from the ground up.

Anvil's history stretches back to the mid 1800s, when a company named Grinnell® began providing its customers with the finest quality pipe products. Since 2000, those quality products and services—and the people who provide them—have been known as Anvil® International. Anvil® customers receive the quality and integrity that have been building strong connections in both products and business relationships for over 150 years.

Focused Product Line:

Anvil® Malleable and Cast Iron Fittings

Anvil® Hangers, Supports and Struts

Beck Welded Pipe Nipples

Anvil® Seamless Pipe Nipples

Anvil® Steel Pipe Couplings and Small Steel Fittings

Merit® Tee-Lets and Drop Nipples

Gruvlok® Couplings, Fittings and Valves

SPF™ Malleable and Cast and Ductile Iron Fittings

SPF™ Grooved Fittings and O'lets

J.B. Smith Swage Nipples and Bull Plugs

Catawissa® Wing Unions and Check Valves



BUILDING CONNECTIONS THAT LAST



ANVIL
BRANDS:







ANVIL[®]
INTERNATIONAL

Building Connections That Last

www.anvilintl.com



PIPE HANGERS & SUPPORT CATALOG
ORDER DOCUMENT #165




PIPE FITTINGS CATALOG
ORDER DOCUMENT #010



**ANVIL-STRUT METAL FRAMING
PRODUCT & ENGINEERING CATALOG**
ORDER DOCUMENT #125



PIPE FITTERS HANDBOOK
ORDER DOCUMENT #030



**GRUVLOK MECHANICAL
PIPING PRODUCTS CATALOG**
ORDER DOCUMENT #040

BRANDS OF ANVIL INTERNATIONAL



Anvil® product lines include malleable and cast iron fittings, unions and flanges; seamless steel pipe nipples; steel pipe couplings; universal anvilets; forged steel fittings and unions; pipe hangers and supports; threaded rod; and engineered hangers.



The Gruvlok® product line consists of couplings for grooved and plain-end fittings, butterfly valves and check valves; flanges; pump protection components; pipe grooving tools; as well as copper and stainless steel system components.



Anvil-Strut™ products include a complete line of channel in stock lengths of 10 and 20 feet, with custom lengths available upon request. A variety of fittings and accessories are also offered. All products can be ordered in an assortment of finishes and material choices including SupR-Green™, Zinc Trivalent Chromium, pre-galvanized, hot-dipped galvanized, electro-galvanized, aluminum, plain, and stainless steel.



JB Smith™ is the leading manufacturer of oil country tubular fittings, swages and bull plugs – all meeting API specifications. Offering tubing nipples, casing nipples as well as a full line of traditional line pipe and oil country threads in every schedule, JB Smith is the resource for all your oilfield needs.



Catawissa™ NACE and API approved wing unions for Standard Service are offered in non-pressure seal ends as well as threaded and butt weld, and are interchangeable with most leading union manufacturers. Fully traceable and available with complete mill certifications, Catawissa's oilfield wing union product line includes the standard ball-and-cone design plus our unique Figure 300 Flat Face design, where space and pipe line separation are a consideration.



The SPF/Anvil™ product line includes a variety of internationally sourced products such as grooved couplings, fittings and flanges, cast iron, malleable iron and ductile iron threaded fittings, steel pipe nipples, as well as o'lets.



The Merit® product line includes a variety of tee-lets, drop nipples, and steel welding flanges for fire protection applications. Most Merit products are UL/ULC Listed, FM Approved, and rated from 175 to 300 psi.



Steel pipe nipples and steel pipe couplings are manufactured in accordance with the ASTM A733 Standard Specification for Welded and Seamless Carbon Steel and Stainless Steel Pipe Nipples. Steel pipe couplings are manufactured in accordance with the ASTM A865 Standard Specification for Threaded Couplings, Steel, Black or Zinc-Coated (Galvanized) Welded or Seamless, for Use in Steel Pipe Joints. API couplings are manufactured in accordance with the API Specification for line pipe.



Canvil® manufactures low pressure hexagon reducer bushings, as well as plugs and hex caps up to 1" in diameter in various finishes including Oil Treat, Phosphate and Electro Galvanized. In addition, Canvil manufactures A105 hex or round material in class 3000 and 6000 pound, forged steel couplings and bar stock products offered as either as normalized (A105N) or non-normalized (A105) that are fully traceable for mechanicals and chemistry through our MTR program.



Anvil EPS-Engineered Pipe Supports are products used to support piping systems under thermal, seismic, and other dynamic loading conditions. The product line encompasses variable spring hangers, constant supports, sway struts and snubbers as well as standard and special design clamps. Anvil EPS brings the highest quality products and innovative engineering solutions to common and uncommon piping system problems.



Corporate Offices

110 Corporate Drive, Suite 10
P.O. Box 3180
Portsmouth, NH 03801-3180
Tel: 603-422-8000
Fax: 603-422-8033
E-mail: webmaster@anvilintl.com

U.S. REGIONAL SERVICE CENTERS

Northern Region

Regional Distribution & Customer Service Center

750 Central Avenue
University Park, IL 60484
Tel: 708-885-3000
Fax: 708-534-5441
Toll Free: 1-800-301-2701

Southern Region

Regional Distribution & Customer Service Center

1401 Valley View Lane, Suite 150
Irving, TX 75061
Tel: 972-871-1206
Fax: 972-641-8946
Toll Free: 1-800-451-4414

CANADA SERVICE CENTER

Anvil International Canada Customer Service Center

390 Second Avenue
P.O. Box 40
Simcoe, Ontario N3Y 4K9
Tel: 519-426-4551
Fax: 519-426-5509

INTERNATIONAL SALES

Europe and Middle East Region

Rick van Meesen, *Sales Director*
The Netherlands
rvanmeesen@anvilintl.com
Tel: +31-53-5725570
Fax: +31-53-5725579
International Customer Service
Tel: +1-708-885-3000
Fax: +1-708-534-5441

Mexico, Puerto Rico and Latin America

Abraham Quijada, *Sales Manager*
aquijada@anvilintl.com
Tel: +1-281-590-4600
International Customer Service
Tel: +1-708-885-3000
Fax: +1-708-534-5441

BUILDING CONNECTIONS THAT LAST

