

# Liberty Pumps®

## Model 101



### Cast Iron Pedestal Sump Pump

**1/3 hp  
1-1/4" Discharge**

#### **Features:**

- 1/3 hp Motor with automatic thermal overload protection, 8 ft 3-wire power cord, and ground plug.
- Adjustable level control for most efficient pumping operation.
  - Double inlet screening to prevent clogging.
  - High-strength cast impeller for impact and abrasion resistance.
- Extra large base for added stability.
  - Exclusive shaft seal to isolate bearing from impeller cavity.
  - Flexible shaft coupling for quiet, vibration-free performance.

innovate. evolve.

# Model 101 Cast Iron

## Pedestal Sump Pump

**Motor:**

1/3 hp, continuous-duty, 1725 rpm, PSC.

**Switch:**

Specially designed dual-contact, top-mounted, float and rod activated.

**Housing:**

Durable heavy duty cast iron, enamel coated.

**Column:**

Corrosion-resistant zinc-coated steel.

**Bearing:**

Oil impregnated bronze with oil retaining felt reservoir.

**Impeller:**

Cast iron, large, open non-clog design.

**Discharge:**

1-1/4" FPT.

### High - Temp Pedestal Pump

**Model 101H: Cast Iron**

For use in water up to 200° F. The H-option incorporates a stainless steel impeller shaft, copper float and metal rod guide.

### Performance:

Capacity	TDH	5'	10'	15'	18' MAX HEAD
	GPH	3150	2380	1260	0

All models are tested and rated in accordance with SSPMA standards.



Dual Safety certification for the United States and Canada.

Specifications subject to change without notice.

Liberty Pumps • 7000 Apple Tree Avenue • Bergen, New York 14416 • Phone 800-543-2550 Fax (585) 494-1839

[www.libertypumps.com](http://www.libertypumps.com)

Copyright © Liberty Pumps, Inc. 2010  
All rights reserved. LLIT 3500 R2/10